

Package ‘SelfControlledCohort’

May 27, 2026

Type Package

Title Population-Level Estimation Method That Estimates Incidence Rate Comparison of Exposed/Unexposed Time Within an Exposed Cohort

Version 2.0.0

Date 2026-05-27

Maintainer Jamie Gilbert <jpg@azimov.co.uk>

Description Estimates risk by comparing time exposed with time unexposed among an exposed cohort using self-controlled cohort methodology. Provides comprehensive diagnostics including power analysis (MDRR), pre-exposure gain detection, and event-dependent observation checks.

URL <https://github.com/OHDSI/SelfControlledCohort>

BugReports <https://github.com/OHDSI/SelfControlledCohort/issues>

Language en-US

Depends DatabaseConnector (>= 5.0.0),
R (>= 4.1.0)

Imports SqlRender (>= 1.4.3),
ParallelLogger,
rateratio.test,
checkmate,
dplyr,
EmpiricalCalibration,
ResultModelManager,
Andromeda,
readr,
rlang,
cli,
stats

Suggests withr,
testthat,
knitr,
rmarkdown,
Eunomia,
duckdb,
DiagrammeR,
tidyr,
R.utils,

jsonlite,
DT,
ggplot2,
shiny,
shinycssloaders,
plotly,
reactable,
shinyWidgets

License Apache License 2.0

RoxygenNote 7.3.3

VignetteBuilder knitr

Encoding UTF-8

Contents

computeEase	3
computeMdrForRateRatio	4
createExposureOutcome	5
createResultsDataModel	6
createRunSelfControlledCohortArgs	7
createSccAnalysis	8
createSelfControlledCohortModuleSpecifications	10
execute	11
getDataMigrator	12
getDefaultDiagnosticThresholds	13
getDefaultExportManager	14
getDiagnosticsSummary	14
getModuleInfo	15
getResultsDataModelSpecifications	15
getResultsFolders	16
getSccRiskWindowStats	16
loadExposureOutcomeList	18
loadSccAnalysisList	19
migrateDataModel	19
runSccAnalyses	20
runSccDiagnostics	22
runSccRiskWindows	23
runSelfControlledCohort	25
saveExposureOutcomeList	29
saveSccAnalysisList	30
uploadResults	30

Index	32
--------------	-----------

computeEase	<i>Compute Expected Absolute Systematic Error (EASE)</i>
-------------	--

Description

Computes the expected absolute systematic error from the null distribution fitted on negative control estimates. EASE summarizes both bias (mean of null) and imprecision (spread of null) into a single metric.

Usage

```
computeEase(negatives)
```

Arguments

<code>negatives</code>	Data frame of negative control results with columns 'rr' and 'seLogRr'
------------------------	--

Details

EASE is computed by fitting a null distribution to the negative control log rate ratios using `EmpiricalCalibration::fit` then calling `EmpiricalCalibration::computeExpectedAbsoluteSystematicError()`.

Lower values indicate less systematic error. A value of 0 means no detectable bias. The default threshold of 0.25 is aligned with SCCS package conventions.

Value

Numeric EASE value, or NA if the null distribution could not be fitted.

References

Schuemie MJ, Hripcsak G, Ryan PB, Madigan D, Suchard MA. Empirical confidence interval calibration for population-level effect estimation studies in observational healthcare data. PNAS. 2018;115(11):2571-2577.

Examples

```
# Compute EASE from negative control results
negativeControls <- data.frame(
  rr = c(0.95, 1.02, 0.98, 1.05),
  seLogRr = c(0.2, 0.18, 0.22, 0.19)
)
ease <- computeEase(negativeControls)
```

computeMdrForRateRatio

Compute Minimum Detectable Relative Risk (MDRR) for rate ratio

Description

Calculates the minimum detectable relative risk for a two-sample Poisson rate comparison using the Signed Root Likelihood (SRL1) method described by Musonda et al. (2006). This diagnostic assesses whether the study has adequate statistical power to detect clinically meaningful effects in a self-controlled design.

Usage

```
computeMdrForRateRatio(
  exposedPersonTime,
  unexposedPersonTime,
  exposedEvents,
  unexposedEvents,
  alpha = 0.05,
  power = 0.8
)
```

Arguments

exposedPersonTime	Total person-time in exposed window (in days)
unexposedPersonTime	Total person-time in unexposed window (in days)
exposedEvents	Number of outcome events in exposed window
unexposedEvents	Number of outcome events in unexposed window
alpha	Significance level (default: 0.05)
power	Desired power (default: 0.80)

Details

The MDRR is the minimum incidence rate ratio that can be detected with the given sample size, alpha, and power. This implementation uses the SRL1 method from Musonda (2006), which is more accurate for self-controlled studies than standard binomial approximations.

Value

Numeric value representing the MDRR. Values > 10.0 typically indicate low power.

References

Musonda P, Farrington CP, Whitaker HJ (2006) Samples sizes for self-controlled case series studies, *Statistics in Medicine*, 15;25(15):2618-31

Examples

```
# Calculate MDRR for a study with 100 exposed person-years and 200 unexposed person-years
mdrr <- computeMdrForRateRatio(
  exposedPersonTime = 36500, # 100 person-years in days
  unexposedPersonTime = 73000, # 200 person-years in days
  exposedEvents = 10,
  unexposedEvents = 15
)
```

createExposureOutcome *Create exposure-outcome combinations.*

Description

Create exposure-outcome combinations.

Usage

```
createExposureOutcome(exposureId, outcomeId, trueEffectSize = NA)
```

Arguments

exposureId	A concept ID indentifying the drug of interest in the exposure table. If multiple strategies for picking the exposure will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the exposureType parameter in the createSccAnalysis function.
outcomeId	A concept ID indentifying the outcome of interest in the outcome table. If multiple strategies for picking the outcome will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the #' outcomeType parameter in the createSccAnalysis function.
trueEffectSize	Should this be set to 1 this will be considered a negative control

Details

Create a hypothesis of interest, to be used with the [runSccAnalyses](#) function.

Value

An object of class exposureOutcome specifying an exposure-outcome pair for analysis.

Examples

```
# Create a simple exposure-outcome pair
eo1 <- createExposureOutcome(exposureId = 1124300,
                             outcomeId = 444382)

# Create a negative control (true effect size = 1)
eo2 <- createExposureOutcome(exposureId = 1124300,
                             outcomeId = 444382,
                             trueEffectSize = 1)
```

```
createResultsDataModel
```

Create the results data model tables on a database server.

Description

Create the results data model tables on a database server.

Usage

```
createResultsDataModel(  
  connectionDetails = NULL,  
  databaseSchema,  
  tablePrefix = ""  
)
```

Arguments

connectionDetails

DatabaseConnector connectionDetails instance @seealso[DatabaseConnector::createConnectionDetails]

databaseSchema The schema on the server where the tables will be created.

tablePrefix (Optional) string to insert before table names for database table names

Details

Only PostgreSQL and SQLite servers are supported.

Value

Invisibly returns NULL. Creates database tables for results storage as a side effect.

Examples

```
## Not run:  
connectionDetails <- DatabaseConnector::createConnectionDetails(  
  dbms = "postgresql",  
  server = "localhost/ohdsi",  
  user = "joe",  
  password = "secret"  
)  
  
createResultsDataModel(  
  connectionDetails = connectionDetails,  
  databaseSchema = "results"  
)  
  
## End(Not run)
```

```
createRunSelfControlledCohortArgs
```

Create a parameter object for the function runSelfControlledCohort

Description

Create a parameter object for the function runSelfControlledCohort

Usage

```
createRunSelfControlledCohortArgs(  
  firstExposureOnly = TRUE,  
  firstOutcomeOnly = TRUE,  
  minAge = "",  
  maxAge = "",  
  studyStartDate = "",  
  studyEndDate = "",  
  addLengthOfExposureExposed = TRUE,  
  riskWindowStartExposed = 1,  
  riskWindowEndExposed = 30,  
  addLengthOfExposureUnexposed = TRUE,  
  riskWindowEndUnexposed = -1,  
  riskWindowStartUnexposed = -30,  
  hasFullTimeAtRisk = FALSE,  
  washoutPeriod = 0,  
  followupPeriod = 0  
)
```

Arguments

firstExposureOnly	If TRUE, only use first occurrence of each drug concept id for each person
firstOutcomeOnly	If TRUE, only use first occurrence of each condition conceptid for each person.
minAge	Integer for minimum allowable age.
maxAge	Integer for maximum allowable age.
studyStartDate	Date for minimum allowable data for index exposure. Dateformat is 'yyym-mdd'.
studyEndDate	Date for maximum allowable data for index exposure. Dateformat is 'yyym-mdd'.
addLengthOfExposureExposed	If TRUE, use the duration from drugEraStart -> drugEraEnd as part of timeAtRisk.
riskWindowStartExposed	Integer of days to add to drugEraStart for start of timeAtRisk (0 to include index date, 1 to start the day after).
riskWindowEndExposed	Additional window to add to end of exposure period (if addLengthOfExposureExposed = TRUE, then add to exposure end date, else add to exposure start date).

addLengthOfExposureUnexposed
If TRUE, use the duration from exposure start -> exposureend as part of timeAtRisk looking back before exposurestart.

riskWindowEndUnexposed
Integer of days to add to exposure start for end of timeAtRisk (0 to include index date, -1 to end the daybefore).

riskWindowStartUnexposed
Additional window to add to start of exposure period (if addLengthOfExposureUnexposed = TRUE, then add to exposureend date, else add to exposure start date).

hasFullTimeAtRisk
If TRUE, restrict to people who have full time-at-risk exposed and unexposed.

washoutPeriod Integer to define required time observed before exposurestart.

followupPeriod Integer to define required time observed after exposurestart. absolute time between treatment and outcome. Note, may add significant computation time on some database engines. If set true in one analysis will default to true for all others.

Details

Create an object defining the parameter values.

Value

A parameter object of class `args` for use with `runSelfControlledCohort`.

Examples

```
# Create default parameters
args1 <- createRunSelfControlledCohortArgs()

# Custom risk window settings
args2 <- createRunSelfControlledCohortArgs(
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 60,
  hasFullTimeAtRisk = TRUE
)
```

<code>createSccAnalysis</code>	<i>Create a SelfControlledCohort analysis specification</i>
--------------------------------	---

Description

Create a SelfControlledCohort analysis specification

Usage

```
createSccAnalysis(
  analysisId = 1,
  description = "",
  exposureType = NULL,
  outcomeType = NULL,
  runSelfControlledCohortArgs,
  controlType = "outcome",
  runDiagnostics = TRUE,
  diagnostics = c("all"),
  diagnosticThresholds = getDefaultDiagnosticThresholds()
)
```

Arguments

analysisId	An integer that will be used later to refer to this specific set of analysis choices.
description	A short description of the analysis.
exposureType	If more than one exposure is provided for each exposureOutcome, this field should be used to select the specific exposure to use in this analysis.
outcomeType	If more than one outcome is provided for each exposureOutcome, this field should be used to select the specific outcome to use in this analysis.
runSelfControlledCohortArgs	An object representing the arguments to be used when calling the runSelfControlledCohort function.
controlType	Character string specifying the type of control. Options are "outcome" or "exposure". Default is "outcome".
runDiagnostics	Logical indicating whether to run diagnostic tests on the results. Default is TRUE.
diagnostics	Character vector specifying which diagnostics to run. Options: "all", "counts", "event_dependent", "pre_exposure", "window_balance", "cohort_stability". Default is "all".
diagnosticThresholds	Named list of diagnostic thresholds. See getDefaultDiagnosticThresholds() for defaults.

Details

Create a set of analysis choices, to be used with the [runSccAnalyses](#) function.

Value

An object of class `sccAnalysis` containing the analysis specifications.

Examples

```
# Create SCC analysis with default risk window settings
sccArgs <- createRunSelfControlledCohortArgs(riskWindowStartExposed = 1,
                                             riskWindowEndExposed = 30)

analysis1 <- createSccAnalysis(analysisId = 1,
                              description = "30-day exposed risk window",
                              runSelfControlledCohortArgs = sccArgs)
```

```
createSelfControlledCohortModuleSpecifications
```

Create Self-Controlled Cohort Module Specifications

Description

Creates a specifications object for the Self-Controlled Cohort module to be used within the OHDSI Strategus framework.

Usage

```
createSelfControlledCohortModuleSpecifications(
  analysisSettings,
  exposureOutcomeList,
  computeThreads = parallel::detectCores() - 1
)
```

Arguments

`analysisSettings`

A list of analysis settings containing the analysis configuration and parameters for self-controlled cohort analyses.

`exposureOutcomeList`

A list of objects of type `exposureOutcome` as created using the [createExposureOutcome](#) function. Each object defines an exposure-outcome pair with `exposureId`, `outcomeId`, and optionally `trueEffectSize` (set to 1 for negative controls).

`computeThreads` Integer specifying the number of threads to use for parallel computation. Default is the number of available cores minus 1.

Value

A list object of class `'SelfControlledCohortModuleSpecifications'` and `'ModuleSpecifications'` containing the module name, version, repository information, and analysis settings.

Examples

```
## Not run:
eo1 <- createExposureOutcome(exposureId = 1124300, outcomeId = 444382)
analysis1 <- createSccAnalysis(analysisId = 1,
                             description = "Main",
                             runSelfControlledCohortArgs = createRunSelfControlledCohortArgs())

moduleSpec <- createSelfControlledCohortModuleSpecifications(
  analysisSettings = list(analysis1),
  exposureOutcomeList = list(eo1)
)

## End(Not run)
```

`execute`*Execute Self-Controlled Cohort Analyses for Strategus*

Description

Executes Self-Controlled Cohort analyses within the OHDSI Strategus framework using the provided analysis specifications and settings.

Usage

```
execute(  
  connectionDetails,  
  executionSettings,  
  analysisSpecifications,  
  databaseId,  
  exportFolder  
)
```

Arguments

<code>connectionDetails</code>	An object containing the details required to connect to the database.
<code>executionSettings</code>	A list of settings for execution, including database schemas and cohort table names.
<code>analysisSpecifications</code>	A list containing analysis settings, exposure-outcome pairs, and compute thread count.
<code>databaseId</code>	A string identifier for the target database.
<code>exportFolder</code>	Path to the folder where results and exports will be written.

Details

This function validates the input specifications, extracts unique exposure and outcome cohort IDs, identifies negative control pairs, and iterates over each analysis setting to run the Self-Controlled Cohort analysis. Results are exported to the specified folder. Diagnostic settings are handled per-analysis, and warnings are issued if no negative controls are found.

Value

No return value. Results are written to the specified export folder as a side effect.

Examples

```
## Not run:  
execute(  
  connectionDetails = connectionDetails,  
  executionSettings = list(  
    databaseSchema = "main",  
    cohortTable = "cohort",  
    cdmDatabaseSchema = "main"
```

```

    ),
    analysisSpecifications = moduleSpec,
    databaseId = "MyDatabase",
    exportFolder = "./strategus_results"
  )

  ## End(Not run)

```

getDataMigrator

Get database migrations instance

Description

Returns ResultModelManager DataMigrationsManager instance.

Usage

```
getDataMigrator(connectionDetails, databaseSchema, tablePrefix = "")
```

Arguments

connectionDetails DatabaseConnector connection details object

databaseSchema String schema where database schema lives

tablePrefix (Optional) Use if a table prefix is used before table names (e.g. "cd_")

Value

Instance of ResultModelManager::DataMigrationManager that has interface for converting existing data models

See Also

[ResultModelManager::DataMigrationManager] which this function is a utility for.

Examples

```

## Not run:
migrator <- getDataMigrator(
  connectionDetails = connectionDetails,
  databaseSchema = "results"
)

## End(Not run)

```

`getDefaultDiagnosticThresholds`*Get default diagnostic thresholds*

Description

Returns default thresholds for diagnostic tests following SCCS standards. Version 2.1.0+ uses revised diagnostics that align with SelfControlledCaseSeries package.

Usage

```
getDefaultDiagnosticThresholds()
```

Details

Thresholds:

- `mdrrMaxAcceptable` - Maximum acceptable MDRR (default: 10.0). Higher values indicate low power.
- `maxPreExposureProportion` - Maximum proportion of persons with pre-exposure outcomes (default: 0.05)
- `preExposurePThreshold` - Significance threshold for pre-exposure gain test (default: 0.05)
- `maxEventDependentCensoring` - Maximum proportion censored within 30 days of outcome (default: 0.25)
- `minEventsPerWindow` - Minimum events required in each window (default: 3)
- `easeMaxAcceptable` - Maximum acceptable EASE (default: 0.25). Requires negative controls.

Value

A list of diagnostic thresholds

Examples

```
# Get default thresholds
thresholds <- getDefaultDiagnosticThresholds()

# Modify specific thresholds
customThresholds <- getDefaultDiagnosticThresholds()
customThresholds$mdrrMaxAcceptable <- 5.0
```

```
getDefaultExportManager
```

Get Default export manager

Description

Returns the default export manager class for writing csv file results

Usage

```
getDefaultExportManager(resultExportPath, databaseId)
```

Arguments

resultExportPath

Folder where result files are exported

databaseId

Unique identifier for database - required

Value

An instance of `ResultModelManager::ResultExportManager` configured for `SelfControlledCohort` results.

Examples

```
## Not run:
exportManager <- getDefaultExportManager(
  resultExportPath = "../results",
  databaseId = "CCAE"
)

## End(Not run)
```

```
getDiagnosticsSummary
```

Get diagnostics summary

Description

Returns a summary of diagnostic results for each target-outcome pair, including blinding status.

Usage

```
getDiagnosticsSummary(diagnosticResults)
```

Arguments

diagnosticResults

Data frame of diagnostic results as returned by `runScdDiagnostics`

Value

A data frame with blinding status per target-outcome pair

Examples

```
## Not run:
diagnosticResults <- runScdDiagnostics(...)
summary <- getDiagnosticsSummary(diagnosticResults)

## End(Not run)
```

getModuleInfo	<i>Get module information</i>
---------------	-------------------------------

Description

Get module information

Usage

```
getModuleInfo()
```

Value

A list with module metadata

Examples

```
moduleInfo <- getModuleInfo()
```

getResultsDataModelSpecifications	<i>Get specifications for CohortMethod results data model</i>
-----------------------------------	---

Description

Get specifications for CohortMethod results data model

Usage

```
getResultsDataModelSpecifications()
```

Value

A data frame object with specifications

Examples

```
specs <- getResultsDataModelSpecifications()
```

getResultsFolders	<i>Get results folders for an analysis specification</i>
-------------------	--

Description

Get results folders for an analysis specification

Usage

```
getResultsFolders(analysisSpecification, exportFolder)
```

Arguments

analysisSpecification	An analysis specification object containing analysis settings and exposure-outcome pairs.
exportFolder	The base folder where results are exported. Individual analysis results will be in subfolders named A_analysisId.

Value

A character vector of paths to results folders for each analysis setting.

Examples

```
## Not run:
resultsFolders <- getResultsFolders(analysisSpec, "./results")

## End(Not run)
```

getSccRiskWindowStats	<i>Get Self-Controlled Cohort Risk Window Statistics</i>
-----------------------	--

Description

Compute statistics from risk windows.

Usage

```
getSccRiskWindowStats(
  connection,
  outcomeDatabaseSchema,
  databaseId,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  outcomeIds = NULL,
  outcomeTable = "condition_era",
  firstOutcomeOnly = TRUE,
  resultsDatabaseSchema = NULL,
  riskWindowsTable = "#risk_windows",
  resultExportPath = "scc_result",
```

```

    analysisId = 1,
    resultExportManager = ResultModelManager::createResultExportManager(tableSpecification
    = getResultsDataModelSpecifications(), exportDir = resultExportPath, databaseId =
    databaseId)
)

```

Arguments

connection	DatabaseConnector connection instance
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If exposureTable = CONDITION_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
databaseId	Unique identifier for database - required
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
outcomeIds	The condition_concept_ids or cohort_definition_ids of the outcomes of interest. If empty, all the outcomes in the outcome table will be included.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable <> CONDITION_OCCURRENCE, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
firstOutcomeOnly	If TRUE, only use first occurrence of each condition concept id for each person.
resultsDatabaseSchema	Schema to output results to. Ignored if resultsTable and riskWindowsTable are temporary.
riskWindowsTable	String: optionally store the risk windows in a (non-temporary) table.
resultExportPath	Folder where result files are exported
analysisId	An integer unique to this analysis
resultExportManager	ResultModelManager::ResultExportManager instance - customize this to implement an alternative mechanism for exporting results

Details

Requires a risk window table to be created first with 'runSccRiskWindows'

Value

list containing data frames: treatmentTimeDistribution, timeToOutcomeDistribution, timeToOutcomeDistributionExposed, timeToOutcomeDistributionUnexposed

Examples

```
## Not run:
# First, create the risk windows table
connectionDetails <- Eunomia::getEunomiaConnectionDetails()
connection <- DatabaseConnector::connect(connectionDetails)
riskWindowsTable <- "computed_risk_windows"
runSccRiskWindows(connection,
  cdmDatabaseSchema = "main",
  exposureIds = c(1102527, 1125315),
  resultsDatabaseSchema = "main",
  riskWindowsTable = riskWindowsTable,
  exposureTable = "drug_era")
# Get stats based on outcomes of interest
tarStats <- getSccRiskWindowStats(connection,
  outcomeDatabaseSchema = "main",
  resultsDatabaseSchema = "main",
  riskWindowsTable = riskWindowsTable,
  outcomeTable = "condition_era",
  outcomeIds = 192671)

## End(Not run)
```

loadExposureOutcomeList

Load a list of exposureOutcome from file

Description

Load a list of objects of type exposureOutcome from file. The file is in JSON format.

Usage

```
loadExposureOutcomeList(file)
```

Arguments

file	The name of the file
------	----------------------

Value

A list of objects of type exposureOutcome.

Examples

```
## Not run:
eoList <- loadExposureOutcomeList("exposureOutcomes.json")

## End(Not run)
```

loadSccAnalysisList	<i>Load a list of sccAnalysis from file</i>
---------------------	---

Description

Load a list of objects of type sccAnalysis from file. The file is in JSON format.

Usage

```
loadSccAnalysisList(file)
```

Arguments

file	The name of the file
------	----------------------

Value

A list of objects of type sccAnalysis.

Examples

```
## Not run:  
analysisList <- loadSccAnalysisList("analyses.json")  
  
## End(Not run)
```

migrateDataModel	<i>Migrate Data model</i>
------------------	---------------------------

Description

Migrate data from current state to next state

It is strongly advised that you have a backup of all data (either sqlite files, a backup database (in the case you are using a postgres backend) or have kept the csv/zip files from your data generation.

Usage

```
migrateDataModel(connectionDetails, databaseSchema, tablePrefix = "")
```

Arguments

connectionDetails	DatabaseConnector connection details object
databaseSchema	String schema where database schema lives
tablePrefix	(Optional) Use if a table prefix is used before table names (e.g. "cd_")

Value

Invisibly returns NULL. Migrates the database schema as a side effect.

Examples

```
## Not run:
migrateDataModel(
  connectionDetails = connectionDetails,
  databaseSchema = "results"
)

## End(Not run)
```

runSccAnalyses	<i>Run a list of analyses</i>
----------------	-------------------------------

Description

Run a list of analyses

Usage

```
runSccAnalyses(
  connectionDetails,
  cdmDatabaseSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema,
  outcomeTable = "condition_occurrence",
  resultsFolder = "./SelfControlledCohortOutput",
  sccAnalysisList,
  exposureOutcomeList,
  databaseId,
  controlType = "outcome",
  analysisThreads = 1,
  computeThreads = 1
)
```

Arguments

- connectionDetails**
An R object of type `connectionDetails` created using the function `createConnectionDetails` in the `DatabaseConnector` package.
- cdmDatabaseSchema**
Name of database schema that contains the OMOP CDM and vocabulary.
- tempEmulationSchema**
Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
- exposureDatabaseSchema**
The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If `exposureTable = DRUG_ERA`, `exposureDatabaseSchema` is not used by assumed to be `cdmSchema`. Requires read permissions to this database.

exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If exposureTable = CONDITION_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable <> CONDITION_OCCURRENCE, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
resultsFolder	Name of the folder where all the outputs will written to.
sccAnalysisList	A list of objects of type sccAnalysis as created using the createSccAnalysis function.
exposureOutcomeList	A list of objects of type exposureOutcome as created using the createExposureOutcome function.
databaseId	Unique identifier for database - required
controlType	Calibrate effect estimates with outcome (default) or exposure controls
analysisThreads	The number of parallel threads to use to execute the analyses.
computeThreads	Number of parallel threads for computing IRRs with exact confidence intervals.

Details

Run a list of analyses for the drug-comparator-outcomes of interest. This function will run all specified analyses against all hypotheses of interest, meaning that the total number of outcome models is `length(cmAnalysisList) * length(drugComparatorOutcomesList)`.

Value

Invisibly returns a data frame containing a reference table for all exposure-outcome-analysis combinations executed.

Examples

```
## Not run:
connectionDetails <- Eunomia::getEunomiaConnectionDetails()

eo1 <- createExposureOutcome(exposureId = 1124300, outcomeId = 444382)
analysis1 <- createSccAnalysis(analysisId = 1,
                              description = "Main analysis",
                              runSelfControlledCohortArgs = createRunSelfControlledCohortArgs())

results <- runSccAnalyses(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = "main",
  exposureOutcomeList = list(eo1),
  sccAnalysisList = list(analysis1),
  databaseId = "Eunomia",
```

```

    resultsFolder = "../results"
  )

  ## End(Not run)

```

runSccDiagnostics

Run Self-Controlled Cohort Diagnostics

Description

Runs a suite of diagnostic tests to assess the validity of SCC analysis assumptions. Version 1.6.0+ implements diagnostics aligned with SelfControlledCaseSeries package standards.

Usage

```

runSccDiagnostics(
  connection,
  cdmDatabaseSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  resultsTable,
  riskWindowsTable,
  outcomeTable = "condition_era",
  outcomeDatabaseSchema = cdmDatabaseSchema,
  analysisId,
  databaseId,
  estimates = NULL,
  diagnostics = c("all"),
  thresholds = getDefaultDiagnosticThresholds(),
  resultExportManager
)

```

Arguments

connection	DatabaseConnector connection instance
cdmDatabaseSchema	Name of database schema that contains OMOP CDM
tempEmulationSchema	Schema for temp table emulation (Oracle, Impala)
resultsTable	Name of the results table (contains counts)
riskWindowsTable	Name of the risk windows table
outcomeTable	Name of outcome table (e.g., "condition_era", "cohort")
outcomeDatabaseSchema	Schema containing outcome table
analysisId	Analysis identifier
databaseId	Database identifier for results export
estimates	Data frame of raw SCC results (including rr and se_log_rr)
diagnostics	Character vector of diagnostics to run. Options: "all", "mdrr", "pre_exposure_gain", "event_dependent", "ease"
thresholds	Named list of diagnostic thresholds (see getDefaultDiagnosticThresholds)
resultExportManager	ResultModelManager::ResultExportManager instance

Value

Invisible data frame of diagnostic results

Examples

```
## Not run:
connection <- DatabaseConnector::connect(connectionDetails)

diagnostics <- runScDiagnostics(
  connection = connection,
  cdmDatabaseSchema = "main",
  resultsTable = "#scc_results",
  riskWindowsTable = "#risk_windows",
  analysisId = 1,
  databaseId = "Eunomia",
  estimates = resultsData,
  diagnostics = "all",
  thresholds = getDefaultDiagnosticThresholds()
)

DatabaseConnector::disconnect(connection)

## End(Not run)
```

runScRiskWindows	<i>Run Self-Controlled Cohort Risk Windows</i>
------------------	--

Description

Compute time at risk exposed and time at risk unexposed for risk window parameters. See ‘getScRiskWindowStats’ for example usage.

Usage

```
runScRiskWindows(
  connection,
  cdmDatabaseSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  exposureIds = NULL,
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  firstExposureOnly = TRUE,
  minAge = "",
  maxAge = "",
  studyStartDate = "",
  studyEndDate = "",
  addLengthOfExposureExposed = TRUE,
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 30,
  addLengthOfExposureUnexposed = TRUE,
  riskWindowEndUnexposed = -1,
  riskWindowStartUnexposed = -30,
```

```

    hasFullTimeAtRisk = FALSE,
    washoutPeriod = 0,
    followupPeriod = 0,
    riskWindowsTable = "#risk_windows",
    keepResultsTables = TRUE,
    analysisId = 1,
    resultsDatabaseSchema = NULL
)

```

Arguments

connection	DatabaseConnector connection instance
cdmDatabaseSchema	Name of database schema that contains the OMOP CDM and vocabulary.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
exposureIds	A vector containing the drug_concept_ids or cohort_definition_ids of the exposures of interest. If empty, all exposures in the exposure table will be included.
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
firstExposureOnly	If TRUE, only use first occurrence of each drug concept id for each person
minAge	Integer for minimum allowable age.
maxAge	Integer for maximum allowable age.
studyStartDate	Date for minimum allowable data for index exposure. Date format is 'yyyymmdd'.
studyEndDate	Date for maximum allowable data for index exposure. Date format is 'yyyymmdd'.
addLengthOfExposureExposed	If TRUE, use the duration from drugEraStart -> drugEraEnd as part of timeAtRisk.
riskWindowStartExposed	Integer of days to add to drugEraStart for start of timeAtRisk (0 to include index date, 1 to start the day after).
riskWindowEndExposed	Additional window to add to end of exposure period (if addLengthOfExposureExposed = TRUE, then add to exposure end date, else add to exposure start date).
addLengthOfExposureUnexposed	If TRUE, use the duration from exposure start -> exposure end as part of timeAtRisk looking back before exposure start.

riskWindowEndUnexposed
 Integer of days to add to exposure start for end of timeAtRisk (0 to include index date, -1 to end the day before).

riskWindowStartUnexposed
 Additional window to add to start of exposure period (if addLengthOfExposureUnexposed = TRUE, then add to exposure end date, else add to exposure start date).

hasFullTimeAtRisk
 If TRUE, restrict to people who have full time-at-risk exposed and unexposed.

washoutPeriod Integer to define required time observed before exposure start.

followupPeriod Integer to define required time observed after exposure start.

riskWindowsTable
 String: optionally store the risk windows in a (non-temporary) table.

keepResultsTables
 Keep the results tables in place if they exist. This allows the data set to be added to with additional targets and outcomes. (ignored if temporary tables are used, default)

analysisId An integer unique to this analysis

resultsDatabaseSchema
 Schema to output results to. Ignored if resultsTable and riskWindowsTable are temporary.

Value

Invisibly returns NULL. Creates the risk windows table in the database as a side effect.

Examples

```
## Not run:
connection <- DatabaseConnector::connect(connectionDetails)

runScRiskWindows(
  connection = connection,
  cdmDatabaseSchema = "main",
  exposureIds = c(1124300),
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 30,
  riskWindowsTable = "#risk_windows"
)

DatabaseConnector::disconnect(connection)

## End(Not run)
```

runSelfControlledCohort

Run self-controlled cohort

Description

runSelfControlledCohort generates population-level estimation by comparing exposed and unexposed time among exposed cohort.

Usage

```

runSelfControlledCohort(
  connectionDetails = NULL,
  cdmDatabaseSchema,
  connection = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  exposureIds = NULL,
  outcomeIds = NULL,
  negativeControlPairs = NULL,
  controlType = "outcome",
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema,
  outcomeTable = "condition_era",
  firstExposureOnly = TRUE,
  firstOutcomeOnly = TRUE,
  minAge = "",
  maxAge = "",
  studyStartDate = "",
  studyEndDate = "",
  addLengthOfExposureExposed = TRUE,
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 30,
  addLengthOfExposureUnexposed = TRUE,
  riskWindowEndUnexposed = -1,
  riskWindowStartUnexposed = -30,
  hasFullTimeAtRisk = FALSE,
  washoutPeriod = 0,
  followupPeriod = 0,
  computeThreads = getOption("strategus.SelfControlledCohort.computeThreads", default =
    parallel::detectCores() - 1),
  riskWindowsTable = "#risk_windows",
  resultsTable = "#results",
  keepResultsTables = TRUE,
  extractResults = TRUE,
  resultsDatabaseSchema = NULL,
  resultExportPath = "scc_result",
  databaseId,
  analysisId = 1,
  analysisDescription = paste("SCC analysis", analysisId),
  resultExportManager = getDefaultExportManager(resultExportPath, databaseId),
  runDiagnostics = TRUE,
  diagnostics = c("all"),
  diagnosticThresholds = getDefaultDiagnosticThresholds()
)

```

Arguments

`connectionDetails`

An R object of type `connectionDetails` created using the function `createConnectionDetails` in the `DatabaseConnector` package.

cdmDatabaseSchema	Name of database schema that contains the OMOP CDM and vocabulary.
connection	DatabaseConnector connection instance
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
exposureIds	A vector containing the drug_concept_ids or cohort_definition_ids of the exposures of interest. If empty, all exposures in the exposure table will be included.
outcomeIds	The condition_concept_ids or cohort_definition_ids of the outcomes of interest. If empty, all the outcomes in the outcome table will be included.
negativeControlPairs	A list of vectors for pairs of negative control
controlType	Calibrate effect estimates with outcome (default) or exposure controls
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If exposureTable = CONDITION_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable <> CONDITION_OCCURRENCE, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
firstExposureOnly	If TRUE, only use first occurrence of each drug concept id for each person
firstOutcomeOnly	If TRUE, only use first occurrence of each condition concept id for each person.
minAge	Integer for minimum allowable age.
maxAge	Integer for maximum allowable age.
studyStartDate	Date for minimum allowable data for index exposure. Date format is 'yyyymmdd'.
studyEndDate	Date for maximum allowable data for index exposure. Date format is 'yyyymmdd'.
addLengthOfExposureExposed	If TRUE, use the duration from drugEraStart -> drugEraEnd as part of timeAtRisk.
riskWindowStartExposed	Integer of days to add to drugEraStart for start of timeAtRisk (0 to include index date, 1 to start the day after).
riskWindowEndExposed	Additional window to add to end of exposure period (if addLengthOfExposureExposed = TRUE, then add to exposure end date, else add to exposure start date).

`addLengthOfExposureUnexposed`
 If TRUE, use the duration from exposure start -> exposure end as part of timeAtRisk looking back before exposure start.

`riskWindowEndUnexposed`
 Integer of days to add to exposure start for end of timeAtRisk (0 to include index date, -1 to end the day before).

`riskWindowStartUnexposed`
 Additional window to add to start of exposure period (if `addLengthOfExposureUnexposed = TRUE`, then add to exposure end date, else add to exposure start date).

`hasFullTimeAtRisk`
 If TRUE, restrict to people who have full time-at-risk exposed and unexposed.

`washoutPeriod` Integer to define required time observed before exposure start.

`followupPeriod` Integer to define required time observed after exposure start.

`computeThreads` Number of parallel threads for computing IRRs with exact confidence intervals.

`riskWindowsTable`
 String: optionally store the risk windows in a (non-temporary) table.

`resultsTable` String: optionally store the summary results (number exposed/ unexposed patients per outcome-exposure pair) in a (non-temporary) table. Note that this table does not store the rate ratios, only the values required to calculate rate ratios.

`keepResultsTables`
 Keep the results tables in place if they exist. This allows the data set to be added to with additional targets and outcomes. (ignored if temporary tables are used, default)

`extractResults` Export results to disk. In the case of very large exposure/outcome set pairs it is often more ideal to create a permanent results table with the `@resultsTable` parameter and extract and calibrate small subsets on demand. Performing calibration across the full set of outcome/exposure pairs can take a significant amount of time. If set to false, no relative risk ratios will be produced.

`resultsDatabaseSchema`
 Schema to output results to. Ignored if `resultsTable` and `riskWindowsTable` are temporary.

`resultExportPath`
 Folder where result files are exported

`databaseId` Unique identifier for database - required

`analysisId` An integer unique to this analysis

`analysisDescription`
 A string description of the analysis (optional)

`resultExportManager`
`ResultModelManager::ResultExportManager` instance - customize this to implement an alternative mechanism for exporting results

`runDiagnostics` If TRUE, run diagnostic tests on the results

`diagnostics` Character vector specifying which diagnostics to run. Options: "all", "counts", "event_dependent", "pre_exposure", "window_balance", "cohort_stability". Default is "all".

`diagnosticThresholds`
 Named list of diagnostic thresholds. See `getDefaultDiagnosticThresholds()`

Details

Population-level estimation method that estimates incidence rate comparison of exposed/unexposed time within an exposed cohort. If multiple exposureIds and outcomeIds are provided, estimates will be generated for every combination of exposure and outcome.

Value

An object of type sccResults containing the results of the analysis.

References

Ryan PB, Schuemie MJ, Madigan D. Empirical performance of a self-controlled cohort method: lessons for developing a risk identification and analysis system. Drug Safety 36 Suppl1:S95-106, 2013

Examples

```
## Not run:
# Use Eunomia synthetic database for demonstration
connectionDetails <- Eunomia::getEunomiaConnectionDetails()

result <- runSelfControlledCohort(
  connectionDetails = connectionDetails,
  cdmDatabaseSchema = "main",
  exposureIds = c(1124300),
  outcomeIds = 444382,
  outcomeTable = "condition_era",
  databaseId = "Eunomia"
)

## End(Not run)
```

```
saveExposureOutcomeList
```

Save a list of exposureOutcome to file

Description

Write a list of objects of type exposureOutcome to file. The file is in JSON format.

Usage

```
saveExposureOutcomeList(exposureOutcomeList, file)
```

Arguments

```
exposureOutcomeList
```

The exposureOutcome list to be written to file

```
file
```

The name of the file where the results will be written

Value

Invisibly returns NULL. Saves the exposure-outcome list to file as a side effect.

Examples

```
## Not run:
eo1 <- createExposureOutcome(exposureId = 1124300, outcomeId = 444382)
saveExposureOutcomeList(list(eo1), "exposureOutcomes.json")

## End(Not run)
```

saveSccAnalysisList	<i>Save a list of sccAnalysis to file</i>
---------------------	---

Description

Write a list of objects of type sccAnalysis to file. The file is in JSON format.

Usage

```
saveSccAnalysisList(sccAnalysisList, file)
```

Arguments

sccAnalysisList	The sccAnalysis list to be written to file
file	The name of the file where the results will be written

Value

Invisibly returns NULL. Saves the analysis list to file as a side effect.

Examples

```
## Not run:
analysis1 <- createSccAnalysis(analysisId = 1,
                             description = "30-day risk window",
                             runSelfControlledCohortArgs = createRunSelfControlledCohortArgs())
saveSccAnalysisList(list(analysis1), "analyses.json")

## End(Not run)
```

uploadResults	<i>Upload results to the database server.</i>
---------------	---

Description

Requires the results data model tables have been created using the [createResultsDataModel](#) function.

Usage

```
uploadResults(
  connectionDetails,
  schema,
  resultsFolder,
  forceOverWriteOfSpecifications = FALSE,
  purgeSiteDataBeforeUploading = FALSE,
  tablePrefix = "",
  ...
)
```

Arguments

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package.
schema	The schema on the server where the tables have been created.
resultsFolder	Path to result files
forceOverWriteOfSpecifications	If TRUE, specifications of the phenotypes, cohort definitions, and analysis will be overwritten if they already exist on the database. Only use this if these specifications have changed since the last upload.
purgeSiteDataBeforeUploading	If TRUE, before inserting data for a specific databaseId all the data for that site will be dropped. This assumes the input zip file contains the full data for that data site.
tablePrefix	(Optional) string to insert before table names for database table names
...	See ResultModelManager::uploadResults

Value

Invisibly returns NULL. Uploads results to the database as a side effect.

Examples

```
## Not run:
uploadResults(
  connectionDetails = connectionDetails,
  schema = "results",
  resultsFolder = "../output"
)

## End(Not run)
```

Index

computeEase, [3](#)
computeMdrForRateRatio, [4](#)
createConnectionDetails, [31](#)
createExposureOutcome, [5](#), [10](#), [21](#)
createResultsDataModel, [6](#), [30](#)
createRunSelfControlledCohortArgs, [7](#)
createSccAnalysis, [5](#), [8](#), [21](#)
createSelfControlledCohortModuleSpecifications,
[10](#)

execute, [11](#)

getDataMigrator, [12](#)
getDefaultDiagnosticThresholds, [13](#)
getDefaultExportManager, [14](#)
getDiagnosticsSummary, [14](#)
getModuleInfo, [15](#)
getResultsDataModelSpecifications, [15](#)
getResultsFolders, [16](#)
getSccRiskWindowStats, [16](#)

loadExposureOutcomeList, [18](#)
loadSccAnalysisList, [19](#)

migrateDataModel, [19](#)

runSccAnalyses, [5](#), [9](#), [20](#)
runSccDiagnostics, [22](#)
runSccRiskWindows, [23](#)
runSelfControlledCohort, [8](#), [9](#), [25](#)

saveExposureOutcomeList, [29](#)
saveSccAnalysisList, [30](#)

uploadResults, [30](#)