

Package ‘SelfControlledCohort’

April 29, 2025

Type Package

Title Population-Level Estimation Method that Estimates Incidence Rate Comparison of Exposed/Unexposed Time Within an Exposed Cohort

Version 2.0.0

Date 2024-09-01

Maintainer Jamie Gilbert <jpg@azimov.co.uk>

Description A method to estimate risk by comparing time exposed with time unexposed among the exposed cohort.

URL <https://github.com/OHDSI/SelfControlledCohort>

BugReports <https://github.com/OHDSI/SelfControlledCohort/issues>

Language en-US

Depends DatabaseConnector (>= 5.0.0),
R (>= 4.0.0)

Imports SqlRender (>= 1.4.3),
ParallelLogger,
rateratio.test,
checkmate,
dplyr,
EmpiricalCalibration,
ResultModelManager,
Andromeda,
readr

Suggests withr,
testthat,
knitr,
rmarkdown,
Eunomia,
duckdb,
DiagrammeR,
tidyr,
R.utils,
jsonlite

Remotes OHDSI/ResultModelManager@fix-finalize

License Apache License 2.0

RoxygenNote 7.3.2

VignetteBuilder knitr

Encoding UTF-8

Contents

createExposureOutcome	2
createResultsDataModel	3
createRunSelfControlledCohortArgs	3
createSccAnalysis	5
getDataMigrator	5
getResultsDataModelSpecifications	6
getSccRiskWindowStats	6
loadExposureOutcomeList	8
loadSccAnalysisList	8
migrateDataModel	9
runSccAnalyses	9
runSccRiskWindows	11
runSelfControlledCohort	12
saveExposureOutcomeList	16
saveSccAnalysisList	16
uploadResults	17
Index	18

createExposureOutcome *Create exposure-outcome combinations.*

Description

Create exposure-outcome combinations.

Usage

```
createExposureOutcome(exposureId, outcomeId, trueEffectSize = NA)
```

Arguments

- | | |
|----------------|---|
| exposureId | A concept ID indentifying the drug of interest in the exposure table. If multiple strategies for picking the exposure will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the exposureType parameter in the createSccAnalysis function. |
| outcomeId | A concept ID indentifying the outcome of interest in the outcome table. If multiple strategies for picking the outcome will be tested in the analysis, a named list of numbers can be provided instead. In the analysis, the name of the number to be used can be specified using the #' outcomeType parameter in the createSccAnalysis function. |
| trueEffectSize | Should this be set to 1 this will be considered a negative control |

Details

Create a hypothesis of interest, to be used with the [runSccAnalyses](#) function.

```
createResultsDataModel
```

Create the results data model tables on a database server.

Description

Create the results data model tables on a database server.

Usage

```
createResultsDataModel(
  connectionDetails = NULL,
  databaseSchema,
  tablePrefix = ""
)
```

Arguments

connectionDetails

DatabaseConnector connectionDetails instance @seealso[DatabaseConnector::createConnectionDetails]

databaseSchema The schema on the server where the tables will be created.

tablePrefix (Optional) string to insert before table names for database table names

Details

Only PostgreSQL and SQLite servers are supported.

```
createRunSelfControlledCohortArgs
```

Create a parameter object for the function runSelfControlledCohort

Description

Create a parameter object for the function runSelfControlledCohort

Usage

```
createRunSelfControlledCohortArgs(
  firstExposureOnly = TRUE,
  firstOutcomeOnly = TRUE,
  minAge = "",
  maxAge = "",
  studyStartDate = "",
  studyEndDate = "",
  addLengthOfExposureExposed = TRUE,
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 30,
  addLengthOfExposureUnexposed = TRUE,
  riskWindowEndUnexposed = -1,
```

```

    riskWindowStartUnexposed = -30,
    hasFullTimeAtRisk = FALSE,
    washoutPeriod = 0,
    followupPeriod = 0
  )

```

Arguments

firstExposureOnly If TRUE, only use first occurrence of each drug concept id for each person

firstOutcomeOnly If TRUE, only use first occurrence of each condition concept id for each person.

minAge Integer for minimum allowable age.

maxAge Integer for maximum allowable age.

studyStartDate Date for minimum allowable data for index exposure. Dateformat is 'yyyymmdd'.

studyEndDate Date for maximum allowable data for index exposure. Dateformat is 'yyyymmdd'.

addLengthOfExposureExposed If TRUE, use the duration from drugEraStart -> drugEraEnd as part of timeAtRisk.

riskWindowStartExposed Integer of days to add to drugEraStart for start of timeAtRisk (0 to include index date, 1 to start the day after).

riskWindowEndExposed Additional window to add to end of exposure period (if addLengthOfExposureExposed = TRUE, then add to exposure end date, else add to exposure start date).

addLengthOfExposureUnexposed If TRUE, use the duration from exposure start -> exposure end as part of timeAtRisk looking back before exposure start.

riskWindowEndUnexposed Integer of days to add to exposure start for end of timeAtRisk (0 to include index date, -1 to end the day before).

riskWindowStartUnexposed Additional window to add to start of exposure period (if addLengthOfExposureUnexposed = TRUE, then add to exposure end date, else add to exposure start date).

hasFullTimeAtRisk If TRUE, restrict to people who have full time-at-risk exposed and unexposed.

washoutPeriod Integer to define required time observed before exposure start.

followupPeriod Integer to define required time observed after exposure start. absolute time between treatment and outcome. Note, may add significant computation time on some database engines. If set true in one analysis will default to true for all others.

Details

Create an object defining the parameter values.

createSccAnalysis	Create a SelfControlledCohort analysis specification
-------------------	--

Description

Create a SelfControlledCohort analysis specification

Usage

```
createSccAnalysis(  
  analysisId = 1,  
  description = "",  
  exposureType = NULL,  
  outcomeType = NULL,  
  runSelfControlledCohortArgs  
)
```

Arguments

analysisId	An integer that will be used later to refer to this specific set of analysis choices.
description	A short description of the analysis.
exposureType	If more than one exposure is provided for each exposureOutcome, this field should be used to select the specific exposure to use in this analysis.
outcomeType	If more than one outcome is provided for each exposureOutcome, this field should be used to select the specific outcome to use in this analysis.
runSelfControlledCohortArgs	An object representing the arguments to be used when calling the runSelfControlledCohort function.

Details

Create a set of analysis choices, to be used with the [runSccAnalyses](#) function.

getDataMigrator	Get database migrations instance
-----------------	----------------------------------

Description

Returns ResultModelManager DataMigrationsManager instance.

Usage

```
getDataMigrator(connectionDetails, databaseSchema, tablePrefix = "")
```

Arguments

connectionDetails	DatabaseConnector connection details object
databaseSchema	String schema where database schema lives
tablePrefix	(Optional) Use if a table prefix is used before table names (e.g. "cd_")

Value

Instance of ResultModelManager::DataMigrationManager that has interface for converting existing data models

See Also

[ResultModelManager::DataMigrationManager] which this function is a utility for.

getResultsDataModelSpecifications

Get specifications for CohortMethod results data model

Description

Get specifications for CohortMethod results data model

Usage

```
getResultsDataModelSpecifications()
```

Value

A data frame object with specifications

getSccRiskWindowStats *Get Self-Controlled Cohort Risk Window Statistics*

Description

Compute statistics from risk windows.

Usage

```
getSccRiskWindowStats(
  connection,
  outcomeDatabaseSchema,
  databaseId,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  outcomeIds = NULL,
  outcomeTable = "condition_era",
  firstOutcomeOnly = TRUE,
  resultsDatabaseSchema = NULL,
  riskWindowsTable = "#risk_windows",
  resultExportPath = "scc_result",
  analysisId = 1,
  resultExportManager = ResultModelManager::createResultExportManager(tableSpecification
    = getResultsDataModelSpecifications(), exportDir = resultExportPath, databaseId =
    databaseId)
)
```

Arguments

connection	DatabaseConnector connection instance
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If exposureTable = CONDITION_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
databaseId	Unique identifier for database - required
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
outcomeIds	The condition_concept_ids or cohort_definition_ids of the outcomes of interest. If empty, all the outcomes in the outcome table will be included.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable <> CONDITION_OCCURRENCE, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
firstOutcomeOnly	If TRUE, only use first occurrence of each condition concept id for each person.
resultsDatabaseSchema	Schema to output results to. Ignored if resultsTable and riskWindowsTable are temporary.
riskWindowsTable	String: optionally store the risk windows in a (non-temporary) table.
resultExportPath	Folder where result files are exported
analysisId	An integer unique to this analysis
resultExportManager	ResultModelManager::ResultExportManager instance - customize this to implement an alternative mechanism for exporting results

Details

Requires a risk window table to be created first with 'runSccRiskWindows'

Value

list containing data frames: treatmentTimeDistribution, timeToOutcomeDistribution, timeToOutcomeDistributionExposed, timeToOutcomeDistributionUnexposed

Examples

```
## Not run:
# First, create the risk windows table
connectionDetails <- Eunomia::getEunomiaConnectionDetails()
connection <- DatabaseConnector::connect(connectionDetails)
riskWindowsTable <- "computed_risk_windows"
runSccRiskWindows(connection,
  cdmDatabaseSchema = "main",
  exposureIds = c(1102527, 1125315),
```

```

        resultsDatabaseSchema = "main",
        riskWindowsTable = riskWindowsTable,
        exposureTable = "drug_era")
# Get stats based on outcomes of interest
tarStats <- getSccRiskWindowStats(connection,
                                   outcomeDatabaseSchema = "main",
                                   resultsDatabaseSchema = "main",
                                   riskWindowsTable = riskWindowsTable,
                                   outcomeTable = "condition_era",
                                   outcomeIds = 192671)

## End(Not run)

```

loadExposureOutcomeList

Load a list of exposureOutcome from file

Description

Load a list of objects of type exposureOutcome from file. The file is in JSON format.

Usage

```
loadExposureOutcomeList(file)
```

Arguments

file The name of the file

Value

A list of objects of type exposureOutcome.

loadSccAnalysisList

Load a list of sccAnalysis from file

Description

Load a list of objects of type sccAnalysis from file. The file is in JSON format.

Usage

```
loadSccAnalysisList(file)
```

Arguments

file The name of the file

Value

A list of objects of type sccAnalysis.

migrateDataModel	<i>Migrate Data model</i>
------------------	---------------------------

Description

Migrate data from current state to next state

It is strongly advised that you have a backup of all data (either sqlite files, a backup database (in the case you are using a postgres backend) or have kept the csv/zip files from your data generation.

Usage

```
migrateDataModel(connectionDetails, databaseSchema, tablePrefix = "")
```

Arguments

connectionDetails	DatabaseConnector connection details object
databaseSchema	String schema where database schema lives
tablePrefix	(Optional) Use if a table prefix is used before table names (e.g. "cd_")

runSccAnalyses	<i>Run a list of analyses</i>
----------------	-------------------------------

Description

Run a list of analyses

Usage

```
runSccAnalyses(
  connectionDetails,
  cdmDatabaseSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema,
  outcomeTable = "condition_occurrence",
  resultsFolder = "./SelfControlledCohortOutput",
  sccAnalysisList,
  exposureOutcomeList,
  databaseId,
  controlType = "outcome",
  analysisThreads = 1,
  computeThreads = 1
)
```

Arguments

connectionDetails	An R object of type connectionDetails created using the function createConnectionDetails in the DatabaseConnector package.
cdmDatabaseSchema	Name of database schema that contains the OMOP CDM and vocabulary.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If exposureTable = CONDITION_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable <> CONDITION_OCCURRENCE, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
resultsFolder	Name of the folder where all the outputs will written to.
sccAnalysisList	A list of objects of type sccAnalysis as created using the createSccAnalysis function.
exposureOutcomeList	A list of objects of type exposureOutcome as created using the createExposureOutcome function.
databaseId	Unique identifier for database - required
controlType	Calibrate effect estimates with outcome (default) or exposure controls
analysisThreads	The number of parallel threads to use to execute the analyses.
computeThreads	Number of parallel threads for computing IRRs with exact confidence intervals.

Details

Run a list of analyses for the drug-comparator-outcomes of interest. This function will run all specified analyses against all hypotheses of interest, meaning that the total number of outcome models is `'length(cmAnalysisList) * length(drugComparatorOutcomesList)'`.

runSccRiskWindows	<i>Run Self-Controlled Cohort Risk Windows</i>
-------------------	--

Description

Compute time at risk exposed and time at risk unexposed for risk window parameters. See ‘getSccRiskWindowStats’ for example usage.

Usage

```
runSccRiskWindows(
  connection,
  cdmDatabaseSchema,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  exposureIds = NULL,
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  firstExposureOnly = TRUE,
  minAge = "",
  maxAge = "",
  studyStartDate = "",
  studyEndDate = "",
  addLengthOfExposureExposed = TRUE,
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 30,
  addLengthOfExposureUnexposed = TRUE,
  riskWindowEndUnexposed = -1,
  riskWindowStartUnexposed = -30,
  hasFullTimeAtRisk = FALSE,
  washoutPeriod = 0,
  followupPeriod = 0,
  riskWindowsTable = "#risk_windows",
  resultsDatabaseSchema = NULL
)
```

Arguments

connection	DatabaseConnector connection instance
cdmDatabaseSchema	Name of database schema that contains the OMOP CDM and vocabulary.
tempEmulationSchema	Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
exposureIds	A vector containing the drug_concept_ids or cohort_definition_ids of the exposures of interest. If empty, all exposures in the exposure table will be included.
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.

exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
firstExposureOnly	If TRUE, only use first occurrence of each drug concept id for each person
minAge	Integer for minimum allowable age.
maxAge	Integer for maximum allowable age.
studyStartDate	Date for minimum allowable data for index exposure. Date format is 'yyyymmdd'.
studyEndDate	Date for maximum allowable data for index exposure. Date format is 'yyyymmdd'.
addLengthOfExposureExposed	If TRUE, use the duration from drugEraStart -> drugEraEnd as part of timeAtRisk.
riskWindowStartExposed	Integer of days to add to drugEraStart for start of timeAtRisk (0 to include index date, 1 to start the day after).
riskWindowEndExposed	Additional window to add to end of exposure period (if addLengthOfExposureExposed = TRUE, then add to exposure end date, else add to exposure start date).
addLengthOfExposureUnexposed	If TRUE, use the duration from exposure start -> exposure end as part of timeAtRisk looking back before exposure start.
riskWindowEndUnexposed	Integer of days to add to exposure start for end of timeAtRisk (0 to include index date, -1 to end the day before).
riskWindowStartUnexposed	Additional window to add to start of exposure period (if addLengthOfExposureUnexposed = TRUE, then add to exposure end date, else add to exposure start date).
hasFullTimeAtRisk	If TRUE, restrict to people who have full time-at-risk exposed and unexposed.
washoutPeriod	Integer to define required time observed before exposure start.
followupPeriod	Integer to define required time observed after exposure start.
riskWindowsTable	String: optionally store the risk windows in a (non-temporary) table.
resultsDatabaseSchema	Schema to output results to. Ignored if resultsTable and riskWindowsTable are temporary.

runSelfControlledCohort

Run self-controlled cohort

Description

runSelfControlledCohort generates population-level estimation by comparing exposed and unexposed time among exposed cohort.

Usage

```

runSelfControlledCohort(
  connectionDetails = NULL,
  cdmDatabaseSchema,
  connection = NULL,
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  exposureIds = NULL,
  outcomeIds = NULL,
  negativeControlPairs = NULL,
  controlType = "outcome",
  exposureDatabaseSchema = cdmDatabaseSchema,
  exposureTable = "drug_era",
  outcomeDatabaseSchema = cdmDatabaseSchema,
  outcomeTable = "condition_era",
  firstExposureOnly = TRUE,
  firstOutcomeOnly = TRUE,
  minAge = "",
  maxAge = "",
  studyStartDate = "",
  studyEndDate = "",
  addLengthOfExposureExposed = TRUE,
  riskWindowStartExposed = 1,
  riskWindowEndExposed = 30,
  addLengthOfExposureUnexposed = TRUE,
  riskWindowEndUnexposed = -1,
  riskWindowStartUnexposed = -30,
  hasFullTimeAtRisk = FALSE,
  washoutPeriod = 0,
  followupPeriod = 0,
  computeThreads = 1,
  riskWindowsTable = "#risk_windows",
  resultsTable = "#results",
  resultsDatabaseSchema = NULL,
  resultExportPath = "scc_result",
  outputFolder = "scc_work",
  databaseId,
  analysisId = 1,
  resultExportManager = ResultModelManager::createResultExportManager(tableSpecification
    = getResultsDataModelSpecifications(), exportDir = resultExportPath, databaseId =
      databaseId)
)

```

Arguments

connectionDetails

An R object of type connectionDetails created using the function createConnectionDetails in the DatabaseConnector package.

cdmDatabaseSchema

Name of database schema that contains the OMOP CDM and vocabulary.

connection

DatabaseConnector connection instance

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp ta-

	bles. To emulate temp tables, provide a schema with write privileges where temp tables can be created.
exposureIds	A vector containing the drug_concept_ids or cohort_definition_ids of the exposures of interest. If empty, all exposures in the exposure table will be included.
outcomeIds	The condition_concept_ids or cohort_definition_ids of the outcomes of interest. If empty, all the outcomes in the outcome table will be included.
negativeControlPairs	A list of vectors for pairs of negative control
controlType	Calibrate effect estimates with outcome (default) or exposure controls
exposureDatabaseSchema	The name of the database schema that is the location where the exposure data used to define the exposure cohorts is available. If exposureTable = DRUG_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
exposureTable	The tablename that contains the exposure cohorts. If exposureTable <> DRUG_ERA, then expectation is exposureTable has format of COHORT table: cohort_concept_id, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
outcomeDatabaseSchema	The name of the database schema that is the location where the data used to define the outcome cohorts is available. If exposureTable = CONDITION_ERA, exposureDatabaseSchema is not used by assumed to be cdmSchema. Requires read permissions to this database.
outcomeTable	The tablename that contains the outcome cohorts. If outcomeTable <> CONDITION_OCCURRENCE, then expectation is outcomeTable has format of COHORT table: COHORT_DEFINITION_ID, SUBJECT_ID, COHORT_START_DATE, COHORT_END_DATE.
firstExposureOnly	If TRUE, only use first occurrence of each drug concept id for each person
firstOutcomeOnly	If TRUE, only use first occurrence of each condition concept id for each person.
minAge	Integer for minimum allowable age.
maxAge	Integer for maximum allowable age.
studyStartDate	Date for minimum allowable data for index exposure. Date format is 'yyyymmdd'.
studyEndDate	Date for maximum allowable data for index exposure. Date format is 'yyyymmdd'.
addLengthOfExposureExposed	If TRUE, use the duration from drugEraStart -> drugEraEnd as part of timeAtRisk.
riskWindowStartExposed	Integer of days to add to drugEraStart for start of timeAtRisk (0 to include index date, 1 to start the day after).
riskWindowEndExposed	Additional window to add to end of exposure period (if addLengthOfExposureExposed = TRUE, then add to exposure end date, else add to exposure start date).
addLengthOfExposureUnexposed	If TRUE, use the duration from exposure start -> exposure end as part of timeAtRisk looking back before exposure start.

riskWindowEndUnexposed	Integer of days to add to exposure start for end of timeAtRisk (0 to include index date, -1 to end the day before).
riskWindowStartUnexposed	Additional window to add to start of exposure period (if addLengthOfExposureUnexposed = TRUE, then add to exposure end date, else add to exposure start date).
hasFullTimeAtRisk	If TRUE, restrict to people who have full time-at-risk exposed and unexposed.
washoutPeriod	Integer to define required time observed before exposure start.
followupPeriod	Integer to define required time observed after exposure start.
computeThreads	Number of parallel threads for computing IRRs with exact confidence intervals.
riskWindowsTable	String: optionally store the risk windows in a (non-temporary) table.
resultsTable	String: optionally store the summary results (number exposed/ unexposed patients per outcome-exposure pair) in a (non-temporary) table. Note that this table does not store the rate ratios, only the values required to calculate rate ratios.
resultsDatabaseSchema	Schema to output results to. Ignored if resultsTable and riskWindowsTable are temporary.
resultExportPath	Folder where result files are exported
outputFolder	Folder where intermediate files are stored
databaseId	Unique identifier for database - required
analysisId	An integer unique to this analysis
resultExportManager	ResultModelManager::ResultExportManager instance - customize this to implement an alternative mechanism for exporting results

Details

Population-level estimation method that estimates incidence rate comparison of exposed/unexposed time within an exposed cohort. If multiple exposureIds and outcomeIds are provided, estimates will be generated for every combination of exposure and outcome.

Value

An object of type `sccResults` containing the results of the analysis.

References

Ryan PB, Schuemie MJ, Madigan D. Empirical performance of a self-controlled cohort method: lessons for developing a risk identification and analysis system. *Drug Safety* 36 Suppl1:S95-106, 2013

Examples

```
## Not run:
connectionDetails <- createConnectionDetails(dbms = "sql server",
                                             server = "RNDUSRDHIT07.jnj.com")
sccResult <- runSelfControlledCohort(connectionDetails,
```

```

                                cdmDatabaseSchema = "cdm_truven_mdcrcr.dbo",
                                exposureIds = c(767410, 1314924, 907879),
                                outcomeIds = 444382,
                                outcomeTable = "condition_era")
runSelfControlledCohort(connectionDetails,
                        cdmDatabaseSchema = "cdm_truven_mdcrcr.dbo",
                        exposureIds = c(767410, 1314924, 907879),
                        outcomeIds = 444382,
                        outcomeTable = "condition_era",
                        returnEstimates = FALSE)

## End(Not run)

```

saveExposureOutcomeList

Save a list of exposureOutcome to file

Description

Write a list of objects of type exposureOutcome to file. The file is in JSON format.

Usage

```
saveExposureOutcomeList(exposureOutcomeList, file)
```

Arguments

exposureOutcomeList	The exposureOutcome list to be written to file
file	The name of the file where the results will be written

saveSccAnalysisList *Save a list of sccAnalysis to file*

Description

Write a list of objects of type sccAnalysis to file. The file is in JSON format.

Usage

```
saveSccAnalysisList(sccAnalysisList, file)
```

Arguments

sccAnalysisList	The sccAnalysis list to be written to file
file	The name of the file where the results will be written

uploadResults	<i>Upload results to the database server.</i>
---------------	---

Description

Requires the results data model tables have been created using the [createResultsDataModel](#) function.

Usage

```
uploadResults(
  connectionDetails,
  schema,
  resultsFolder,
  forceOverWriteOfSpecifications = FALSE,
  purgeSiteDataBeforeUploading = TRUE,
  tablePrefix = "",
  ...
)
```

Arguments

connectionDetails	An object of type connectionDetails as created using the createConnectionDetails function in the DatabaseConnector package.
schema	The schema on the server where the tables have been created.
resultsFolder	Path to result files
forceOverWriteOfSpecifications	If TRUE, specifications of the phenotypes, cohort definitions, and analysis will be overwritten if they already exist on the database. Only use this if these specifications have changed since the last upload.
purgeSiteDataBeforeUploading	If TRUE, before inserting data for a specific databaseId all the data for that site will be dropped. This assumes the input zip file contains the full data for that data site.
tablePrefix	(Optional) string to insert before table names for database table names
...	See ResultModelManager::uploadResults

Index

createConnectionDetails, [17](#)
createExposureOutcome, [2](#), [10](#)
createResultsDataModel, [3](#), [17](#)
createRunSelfControlledCohortArgs, [3](#)
createSccAnalysis, [2](#), [5](#), [10](#)

getDataMigrator, [5](#)
getResultsDataModelSpecifications, [6](#)
getSccRiskWindowStats, [6](#)

loadExposureOutcomeList, [8](#)
loadSccAnalysisList, [8](#)

migrateDataModel, [9](#)

runSccAnalyses, [2](#), [5](#), [9](#)
runSccRiskWindows, [11](#)
runSelfControlledCohort, [5](#), [12](#)

saveExposureOutcomeList, [16](#)
saveSccAnalysisList, [16](#)

uploadResults, [17](#)