

Package ‘SkeletonCohortDiagnosticsStudy’

November 28, 2022

Type Package

Title A Study Package for Generating Cohort Diagnostics

Version 0.0.1

Author Gowtham Rao [aut, cre]

Date 2022-11-07

Maintainer Gowtham Rao <rao@ohdsi.org>

Description

A package that generates cohort diagnostics for cohort definitions included in the package.

Depends R (>= 4.1.0)

Imports CohortDiagnostics (>= 3.1.0),
CohortGenerator (>= 0.7.0),
ParallelLogger (>= 3.0.0),
DatabaseConnector (>= 5.0.0),
OhdsiSharing,
keyring,
jsonlite

Suggests ROhdsiWebApi

License Apache License (>= 2)

LazyData TRUE

RoxygenNote 7.2.1

Encoding UTF-8

Language en-US

R topics documented:

execute	2
uploadResults	3

Index	4
-------	---

execute

*Execute the cohort diagnostics***Description**

Execute the cohort diagnostics

Usage

```
execute(
  connectionDetails,
  cdmDatabaseSchema,
  vocabularyDatabaseSchema = cdmDatabaseSchema,
  cohortDatabaseSchema = cdmDatabaseSchema,
  cohortTable = "cohort",
  tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
  verifyDependencies = TRUE,
  outputFolder,
  incrementalFolder = file.path(outputFolder, "incrementalFolder"),
  databaseId = "Unknown",
  databaseName = databaseId,
  databaseDescription = databaseId,
  extraLog = NULL
)
```

Arguments

connectionDetails

An object of type connectionDetails as created using the [createConnectionDetails](#) function in the DatabaseConnector package.

cdmDatabaseSchema

Schema name where your patient-level data in OMOP CDM format resides. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.

vocabularyDatabaseSchema

Schema name where your OMOP vocabulary data resides. This is commonly the same as cdmDatabaseSchema. Note that for SQL Server, this should include both the database and schema name, for example 'vocabulary.dbo'.

cohortDatabaseSchema

Schema name where intermediate data can be stored. You will need to have write privileges in this schema. Note that for SQL Server, this should include both the database and schema name, for example 'cdm_data.dbo'.

cohortTable

The name of the table that will be created in the work database schema. This table will hold the exposure and outcome cohorts used in this study.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

verifyDependencies

Check whether correct package versions are installed?

outputFolder	Name of local folder to place results; make sure to use forward slashes (/). Do not use a folder on a network drive since this greatly impacts performance.
incrementalFolder	Name of local folder to hold the logs for incremental run; make sure to use forward slashes (/). Do not use a folder on a network drive since this greatly impacts performance.
databaseId	A short string for identifying the database (e.g. 'Synpuf').
databaseName	The full name of the database (e.g. 'Medicare Claims Synthetic Public Use Files (SynPUFs)').
databaseDescription	A short description (several sentences) of the database.
extraLog	Do you want to add anything extra into the log?

Details

This function executes the cohort diagnostics.

uploadResults	<i>Upload results to OHDSI server</i>
---------------	---------------------------------------

Description

Upload results to OHDSI server

Usage

```
uploadResults(outputFolder, privateKeyFileName, userName)
```

Arguments

outputFolder	Name of local folder where the results were generated; make sure to use forward slashes (/). Do not use a folder on a network drive since this greatly impacts performance.
privateKeyFileName	A character string denoting the path to the RSA private key provided by the study coordinator.
userName	A character string containing the user name provided by the study coordinator.

Details

This function uploads the 'Results_<databaseId>.zip' to the OHDSI SFTP server. Before sending, you can inspect the zip file, which contains (zipped) CSV files. You can send the zip file from a different computer than the one on which it was created.

Index

`createConnectionDetails`, [2](#)

`execute`, [2](#)

`uploadResults`, [3](#)