

Package ‘Strategus’

September 25, 2026

Type Package

Title Coordinate and Execute OHDSI HADES Modules

Version 1.6.0

Date 2026-09-25

Maintainer Anthony Sena <sena@ohdsi.org>

Description Coordinate and execute large scale analytics using OHDSI Health Analytics Data-to-Evidence Suite (HADES) (<<https://ohdsi.github.io/Hades/>>) modules.

Depends R (>= 4.2.0),
CohortGenerator (>= 1.0.0),
DatabaseConnector (>= 6.2.3),
R6

Imports checkmate,
cli,
digest,
dplyr,
methods,
stats,
ParallelLogger (>= 3.1.0),
purrr,
ResultModelManager (>= 0.5.8),
rlang,
SqlRender (>= 1.18.0)

Suggests Characterization (>= 4.0.0),
CirceR,
CohortDiagnostics (>= 3.4.0),
CohortIncidence (>= 4.2.0),
CohortMethod (>= 6.0.0),
Cyclops (>= 3.6.0),
Eunomia,
EvidenceSynthesis (>= 1.1.0),
meta,
metafor,
FeatureExtraction,
fs,
knitr,
PatientLevelPrediction (>= 6.5.0),
PheValuator,

readr,
 rmarkdown,
 RSQLite,
 SelfControlledCaseSeries ($\geq 6.0.0$),
 testthat ($\geq 3.0.0$),
 TreatmentPatterns ($\geq 3.1.0$),
 withr
Remotes ohdsi/CohortDiagnostics,
 ohdsi/PheValuator
License Apache License 2.0
VignetteBuilder knitr
URL <https://ohdsi.github.io/Strategus>, <https://github.com/OHDSI/Strategus>
BugReports <https://github.com/OHDSI/Strategus/issues>
NeedsCompilation no
Roxygen list(markdown = TRUE)
Encoding UTF-8
Language en-US
Config/testthat/edition 3
Config/roxygen2/version 8.0.0

Contents

addCharacterizationModuleSpecifications	3
addCohortDiagnosticsModuleSpecifications	4
addCohortGeneratorModuleSpecifications	4
addCohortIncidenceModuleSpecifications	5
addCohortMethodeModuleSpecifications	5
addEvidenceSynthesisModuleSpecifications	6
addModuleSpecifications	7
addPatientLevelPredictionModuleSpecifications	7
addPatientLevelPredictionValidationModuleSpecifications	8
addPheValuatorModuleSpecifications	8
addSelfControlledCaseSeriesModuleSpecifications	9
addSharedResources	9
addTreatmentPatternsModuleSpecifications	10
CharacterizationModule	10
CohortDiagnosticsModule	14
CohortGeneratorModule	17
CohortIncidenceModule	20
CohortMethodModule	23
createCdmExecutionSettings	26
createEmptyAnalysisSpecifications	27
createEmptyAnalysisSpecifiications	27
createResultDataModel	28
createResultsDataModelSettings	28
createResultsExecutionSettings	29
EvidenceSynthesisModule	30
execute	35

```
addCohortDiagnosticsModuleSpecifications
```

Add Cohort Diagnostics module specifications to analysis specifications

Description

Add Cohort Diagnostics module specifications to analysis specifications

Usage

```
addCohortDiagnosticsModuleSpecifications(
  analysisSpecifications,
  moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

moduleSpecifications

Created by the [CohortDiagnosticsModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

```
addCohortGeneratorModuleSpecifications
```

Add Cohort Generator module specifications to analysis specifications

Description

Add Cohort Generator module specifications to analysis specifications

Usage

```
addCohortGeneratorModuleSpecifications(
  analysisSpecifications,
  moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

moduleSpecifications

Created by the [CohortGeneratorModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

`addCohortIncidenceModuleSpecifications`

Add Cohort Incidence module specifications to analysis specifications

Description

Add Cohort Incidence module specifications to analysis specifications

Usage

```
addCohortIncidenceModuleSpecifications(  
  analysisSpecifications,  
  moduleSpecifications  
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

moduleSpecifications

Created by the `CohortIncidenceModule$createModuleSpecifications()` function.

Value

Returns the analysisSpecifications object with the module specifications added.

`addCohortMethodModuleSpecifications`

Add Cohort Method module specifications to analysis specifications

Description

Add Cohort Method module specifications to analysis specifications

Usage

```
addCohortMethodModuleSpecifications(  
  analysisSpecifications,  
  moduleSpecifications  
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications](#)

moduleSpecifications

Created by the [CohortMethodModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

addEvidenceSynthesisModuleSpecifications

Add Evidence Synthesis module specifications to analysis specifications

Description

Add Evidence Synthesis module specifications to analysis specifications

Usage

```
addEvidenceSynthesisModuleSpecifications(
  analysisSpecifications,
  moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications](#)

moduleSpecifications

Created by the [EvidenceSynthesisModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

`addModuleSpecifications`*Add generic module specifications to analysis specifications*

Description

Add generic module specifications to analysis specifications

Usage

```
addModuleSpecifications(analysisSpecifications, moduleSpecifications)
```

Arguments

`analysisSpecifications`

An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpecifications`

`moduleSpecifications`

An object of type `ModuleSpecifications`

Value

Returns the `analysisSpecifications` object with the module specifications added.

`addPatientLevelPredictionModuleSpecifications`*Add Patient Level Prediction module specifications to analysis specifications*

Description

Add Patient Level Prediction module specifications to analysis specifications

Usage

```
addPatientLevelPredictionModuleSpecifications(  
  analysisSpecifications,  
  moduleSpecifications  
)
```

Arguments

`analysisSpecifications`

An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpecifications`

`moduleSpecifications`

Created by the `PatientLevelPredictionModule$createModuleSpecifications()` function.

Value

Returns the `analysisSpecifications` object with the module specifications added.

```
addPatientLevelPredictionValidationModuleSpecifications
```

Add Patient Level Prediction Validation Module module specifications to analysis specifications

Description

Add Patient Level Prediction Validation Module module specifications to analysis specifications

Usage

```
addPatientLevelPredictionValidationModuleSpecifications(
  analysisSpecifications,
  moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

moduleSpecifications

Created by the [PatientLevelPredictionValidationModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

```
addPheValuatorModuleSpecifications
```

Add PheValuator Module specifications to analysis specifications

Description

Add PheValuator Module specifications to analysis specifications

Usage

```
addPheValuatorModuleSpecifications(
  analysisSpecifications,
  moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

moduleSpecifications

Created by the [PheValuatorModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

```
addSelfControlledCaseSeriesModuleSpecifications
    Add Self Controlled Case Series Module module specifications to anal-
    ysis specifications
```

Description

Add Self Controlled Case Series Module module specifications to analysis specifications

Usage

```
addSelfControlledCaseSeriesModuleSpecifications(
    analysisSpecifications,
    moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications](#)

moduleSpecifications

Created by the [SelfControlledCaseSeriesModule\\$createModuleSpecifications\(\)](#) function.

Value

Returns the analysisSpecifications object with the module specifications added.

```
addSharedResources    Add shared resources (i.e. cohorts) to analysis specifications
```

Description

Add shared resources (i.e. cohorts) to analysis specifications

Usage

```
addSharedResources(analysisSpecifications, sharedResources)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications](#)

sharedResources

An object of type SharedResources.

Value

Returns the analysisSpecifications object with the module specifications added.

```
addTreatmentPatternsModuleSpecifications
```

Add Treatment Patterns Module specifications to analysis specifications

Description

Add Treatment Patterns Module specifications to analysis specifications

Usage

```
addTreatmentPatternsModuleSpecifications(
  analysisSpecifications,
  moduleSpecifications
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

moduleSpecifications

Created by the `TreatmentPatternsModule$createModuleSpecifications()`

Value

Returns the analysisSpecifications object with the module specifications added

```
CharacterizationModule
```

Characterize cohorts with the R [href=https://ohdsi.github.io/Characterization/HADES](https://ohdsi.github.io/Characterization/HADES) Characterization Package

Description

Computes cohort characterization information against the OMOP Common Data Model

Super class

[StrategusModule](#) -> CharacterizationModule

Public fields

tablePrefix The table prefix to append to the results tables

Methods

Public methods:

- [CharacterizationModule\\$new\(\)](#)
- [CharacterizationModule\\$execute\(\)](#)
- [CharacterizationModule\\$createResultsDataModel\(\)](#)
- [CharacterizationModule\\$getResultsDataModelSpecification\(\)](#)
- [CharacterizationModule\\$uploadResults\(\)](#)
- [CharacterizationModule\\$createModuleSpecifications\(\)](#)
- [CharacterizationModule\\$clone\(\)](#)

`CharacterizationModule$new()`: Initialize the module

Usage:

```
CharacterizationModule$new()
```

`CharacterizationModule$execute()`: Execute characterization

Usage:

```
CharacterizationModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

`connectionDetails` An object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`executionSettings` An object of type `ExecutionSettings` as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

`CharacterizationModule$createResultsDataModel()`: Create the results data model for the module

Usage:

```
CharacterizationModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = self$tablePrefix
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsDatabaseSchema` The schema in the results database that holds the results data model.

`tablePrefix` A prefix to apply to the database table names (optional).

`tablePrefix` A prefix to apply to the database table names (optional).

`CharacterizationModule$getResultsDataModelSpecification()`: Get the results data model specification for the module

Usage:

```
CharacterizationModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

`tablePrefix` A prefix to apply to the database table names (optional).

`tablePrefix` A prefix to apply to the database table names (optional).

`CharacterizationModule$uploadResults()`: Upload the results for the module

Usage:

```
CharacterizationModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

`resultsDataModelSettings` The results data model settings as created using `createResultsDataModelSettings`

`CharacterizationModule$createModuleSpecifications()`: Creates the Characterization-Module Specifications

Usage:

```
CharacterizationModule$createModuleSpecifications(
  characterizationSettings = NULL,
  targetIds = NULL,
  limitToFirstInNDays = NULL,
  minPriorObservation = NULL,
  outcomeIds = NULL,
  outcomeWashoutDays = NULL,
  riskWindowStart = NULL,
  startAnchor = NULL,
  riskWindowEnd = NULL,
  endAnchor = NULL,
  dechallengeStopInterval = NULL,
  dechallengeEvaluationWindow = NULL,
  covariateSettings = NULL,
  caseCovariateSettings = NULL,
  casePreTargetDuration = NULL,
  casePostOutcomeDuration = NULL,
  includeTimeToEvent = NULL,
  includeDechallengeRechallenge = NULL,
  includeTargetBaseline = NULL,
```

```

    includeRiskFactors = NULL,
    includeCaseSeries = NULL,
    mode = "CohortIncidence",
    minSMD = 0,
    minCharacterizationMean = 0,
    minCovariateCount = 0,
    minTargetSize = 0,
    minCaseSize = 0,
    outputTable = "characterization_cohorts"
)

```

Arguments:

characterizationSettings The settings defined using `Characterization::createCharacterizationSettings`

targetIds Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

limitToFirstInNDays Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

minPriorObservation Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

outcomeIds Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

outcomeWashoutDays Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

riskWindowStart Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

startAnchor Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

riskWindowEnd Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

endAnchor Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

dechallengeStopInterval Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

dechallengeEvaluationWindow Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

covariateSettings Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

caseCovariateSettings Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

casePreTargetDuration Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

casePostOutcomeDuration Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

includeTimeToEvent Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

includeDechallengeRechallenge Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

includeTargetBaseline Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

includeRiskFactors Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

includeCaseSeries Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

mode Pick one of 'CohortIncidence'/'Efficient'/'PatientLevelPrediction' to specify how the non-cases are defined

minSMD The minimum standardized mean difference for the risk factors analysis

minCharacterizationMean The minimum fraction patients in the target have a covariate for it to be included

minCovariateCount The minimum number of patients in the analysis to have a covariate for it to be included

minTargetSize Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

minCaseSize Deprecated. Use Characterization v4 settings objects via `characterizationSettings`.

outputTable The table used by characterization to create the cohorts used in characterization (included targets, cases, non-cases, etc.). The spec hash and database hash are added to this name to make it unique per run.

CharacterizationModule\$clone(): The objects of this class are cloneable with this method.

Usage:

```
CharacterizationModule$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

CohortDiagnosticsModule

Evaluate phenotypes with the R
CohortDiagnostics Package

Description

Development and evaluation of phenotype algorithms against the OMOP Common Data Model.

Super class

[StrategusModule](#) -> CohortDiagnosticsModule

Public fields

tablePrefix The table prefix to append to results tables

Methods**Public methods:**

- [CohortDiagnosticsModule\\$new\(\)](#)
- [CohortDiagnosticsModule\\$execute\(\)](#)
- [CohortDiagnosticsModule\\$createResultsDataModel\(\)](#)
- [CohortDiagnosticsModule\\$getResultsDataModelSpecification\(\)](#)
- [CohortDiagnosticsModule\\$uploadResults\(\)](#)
- [CohortDiagnosticsModule\\$createModuleSpecifications\(\)](#)
- [CohortDiagnosticsModule\\$validateModuleSpecifications\(\)](#)
- [CohortDiagnosticsModule\\$clone\(\)](#)

CohortDiagnosticsModule\$new(): Initialize the module

Usage:

```
CohortDiagnosticsModule$new()
```

CohortDiagnosticsModule\$execute(): Executes the CohortDiagnostics package

Usage:

```
CohortDiagnosticsModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)
 analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)
 executionSettings An object of type ExecutionSettings as created by [createCdmExecutionSettings\(\)](#)
 or [createResultsExecutionSettings\(\)](#).

CohortDiagnosticsModule\$createResultsDataModel(): Create the results data model for the module

Usage:

```
CohortDiagnosticsModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = self$tablePrefix
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.
 resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.
 resultsDatabaseSchema The schema in the results database that holds the results data model.
 tablePrefix A prefix to apply to the database table names (optional).
 tablePrefix A prefix to apply to the database table names (optional).

CohortDiagnosticsModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
CohortDiagnosticsModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).
 tablePrefix A prefix to apply to the database table names (optional).

CohortDiagnosticsModule\$uploadResults(): Upload the results for the module

Usage:

```
CohortDiagnosticsModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.
 resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.
 analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)
 analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)

resultsDataModelSettings The results data model settings as created using [createResultsDataModelSettings](#)

CohortDiagnosticsModule\$createModuleSpecifications(): Creates the CohortDiagnostics Module Specifications

Usage:

```
CohortDiagnosticsModule$createModuleSpecifications(
  cohortIds = NULL,
  runInclusionStatistics = TRUE,
  runIncludedSourceConcepts = TRUE,
  runOrphanConcepts = TRUE,
  runTimeSeries = FALSE,
  runVisitContext = TRUE,
  runBreakdownIndexEvents = TRUE,
  runIncidenceRate = TRUE,
  runCohortRelationship = TRUE,
  runTemporalCohortCharacterization = TRUE,
  temporalCovariateSettings = private$.getDefaultCovariateSettings(),
  minCharacterizationMean = 0.01,
  irWashoutPeriod = 0
)
```

Arguments:

cohortIds A list of cohort IDs to use when running the CohortDiagnostics. Default is NULL which will use all cohorts present in the cohort definition set in the analysis specification

runInclusionStatistics Generate and export statistic on the cohort inclusion rules?

runIncludedSourceConcepts Generate and export the source concepts included in the cohorts?

runOrphanConcepts Generate and export potential orphan concepts?

runTimeSeries Generate and export the time series diagnostics?

runVisitContext Generate and export index-date visit context?

runBreakdownIndexEvents Generate and export the breakdown of index events?

runIncidenceRate Generate and export the cohort incidence rates?

runCohortRelationship Generate and export the cohort relationship? Cohort relationship checks the temporal relationship between two or more cohorts.

runTemporalCohortCharacterization Generate and export the temporal cohort characterization? Only records with values greater than 0.001 are returned.

temporalCovariateSettings Either an object of type covariateSettings as created using one of the createTemporalCovariateSettings function in the FeatureExtraction package, or a list of such objects.

minCharacterizationMean The minimum mean value for characterization output. Values below this will be cut off from output. This will help reduce the file size of the characterization output, but will remove information on covariates that have very low values. The default is 0.001 (i.e. 0.1 percent)

irWashoutPeriod Number of days washout to include in calculation of incidence rates - default is 0

CohortDiagnosticsModule\$validateModuleSpecifications(): Validate the module specifications

Usage:

```
CohortDiagnosticsModule$validateModuleSpecifications(moduleSpecifications)
```

Arguments:

moduleSpecifications The CohortIncidence module specifications

CohortDiagnosticsModule\$clone(): The objects of this class are cloneable with this method.

Usage:

CohortDiagnosticsModule\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

CohortGeneratorModule *Generate cohorts with the R*[hrefhttps://ohdsi.github.io/CohortGenerator/HADES](https://ohdsi.github.io/CohortGenerator/HADES)
CohortGenerator Package

Description

Generates cohorts against the OMOP Common Data Model

Super class

[StrategusModule](#) -> CohortGeneratorModule

Public fields

cohortDefinitionSharedResourcesClassName A constant for the name of the cohort definition
shared resources section of the analysis specification

negativeControlOutcomeSharedResourcesClassName A constant for the name of the negative
control outcome shared resources section of the analysis specification

Methods**Public methods:**

- [CohortGeneratorModule\\$new\(\)](#)
- [CohortGeneratorModule\\$execute\(\)](#)
- [CohortGeneratorModule\\$createResultsDataModel\(\)](#)
- [CohortGeneratorModule\\$getResultsDataModelSpecification\(\)](#)
- [CohortGeneratorModule\\$uploadResults\(\)](#)
- [CohortGeneratorModule\\$createModuleSpecifications\(\)](#)
- [CohortGeneratorModule\\$createCohortSharedResourceSpecifications\(\)](#)
- [CohortGeneratorModule\\$createNegativeControlOutcomeCohortSharedResourceSpecifications\(\)](#)
- [CohortGeneratorModule\\$validateModuleSpecifications\(\)](#)
- [CohortGeneratorModule\\$validateCohortSharedResourceSpecifications\(\)](#)
- [CohortGeneratorModule\\$validateNegativeControlOutcomeCohortSharedResourceSpecifications\(\)](#)
- [CohortGeneratorModule\\$clone\(\)](#)

CohortGeneratorModule\$new(): Initialize the module

Usage:

CohortGeneratorModule\$new()

CohortGeneratorModule\$execute(): Generates the cohorts

Usage:

```
CohortGeneratorModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

executionSettings An object of type ExecutionSettings as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

CohortGeneratorModule\$createResultsDataModel(): Create the results data model for the module

Usage:

```
CohortGeneratorModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = ""
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsDatabaseSchema The schema in the results database that holds the results data model.

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

CohortGeneratorModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
CohortGeneratorModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

CohortGeneratorModule\$uploadResults(): Upload the results for the module

Usage:

```
CohortGeneratorModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpec`

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpec`

resultsDataModelSettings The results data model settings as created using `createResultsDataModelSettings`

`CohortGeneratorModule$createModuleSpecifications()`: Creates the CohortGenerator Module Specifications

Usage:

```
CohortGeneratorModule$createModuleSpecifications(generateStats = TRUE)
```

Arguments:

generateStats When TRUE, the Circe cohort definition SQL will include steps to compute inclusion rule statistics.

`CohortGeneratorModule$createCohortSharedResourceSpecifications()`: Create shared specifications for the cohort definition set

Usage:

```
CohortGeneratorModule$createCohortSharedResourceSpecifications(
  cohortDefinitionSet
)
```

Arguments:

cohortDefinitionSet The cohort definition set to include in the specification. See the CohortGenerator package for details on how to build this object.

`CohortGeneratorModule$createNegativeControlOutcomeCohortSharedResourceSpecifications()`: Create shared specifications for the negative control outcomes cohort set

Usage:

```
CohortGeneratorModule$createNegativeControlOutcomeCohortSharedResourceSpecifications(
  negativeControlOutcomeCohortSet,
  occurrenceType,
  detectOnDescendants
)
```

Arguments:

negativeControlOutcomeCohortSet The negative control outcome cohort definition set defines the concepts to use to construct negative control outcome cohorts. See the CohortGenerator package for more details.

occurrenceType Either "first" or "all"

detectOnDescendants When TRUE, the concept ID for the negative control will use the concept_ancestor table and will detect descendant concepts when constructing the cohort.

`CohortGeneratorModule$validateModuleSpecifications()`: Validate the module specifications

Usage:

CohortGeneratorModule\$validateModuleSpecifications(moduleSpecifications)

Arguments:

moduleSpecifications The CohortGenerator module specifications

CohortGeneratorModule\$validateCohortSharedResourceSpecifications(): Validate the cohort shared resource specifications

Usage:

```
CohortGeneratorModule$validateCohortSharedResourceSpecifications(
  cohortSharedResourceSpecifications
)
```

Arguments:

cohortSharedResourceSpecifications The cohort shared resource specifications

CohortGeneratorModule\$validateNegativeControlOutcomeCohortSharedResourceSpecifications(): Validate the cohort shared resource specifications

Usage:

```
CohortGeneratorModule$validateNegativeControlOutcomeCohortSharedResourceSpecifications(
  negativeControlOutcomeCohortSharedResourceSpecifications
)
```

Arguments:

negativeControlOutcomeCohortSharedResourceSpecifications The cohort shared resource specifications

CohortGeneratorModule\$clone(): The objects of this class are cloneable with this method.

Usage:

```
CohortGeneratorModule$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

CohortIncidenceModule *Compute incidence with the R*
[hrefhttps://ohdsi.github.io/CohortIncidence/HADES](https://ohdsi.github.io/CohortIncidence/HADES)
CohortIncidence Package

Description

Computes incidence rates for cohorts against the OMOP Common Data Model

Super class

[StrategusModule](#) -> CohortIncidenceModule

Public fields

tablePrefix The table prefix to append to results tables

Methods

Public methods:

- [CohortIncidenceModule\\$new\(\)](#)
- [CohortIncidenceModule\\$execute\(\)](#)
- [CohortIncidenceModule\\$createResultsDataModel\(\)](#)
- [CohortIncidenceModule\\$getResultsDataModelSpecification\(\)](#)
- [CohortIncidenceModule\\$uploadResults\(\)](#)
- [CohortIncidenceModule\\$createModuleSpecifications\(\)](#)
- [CohortIncidenceModule\\$validateModuleSpecifications\(\)](#)
- [CohortIncidenceModule\\$clone\(\)](#)

[CohortIncidenceModule\\$new\(\)](#): Initialize the module

Usage:

```
CohortIncidenceModule$new()
```

[CohortIncidenceModule\\$execute\(\)](#): Execute the CohortIncidence package

Usage:

```
CohortIncidenceModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

`connectionDetails` An object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`executionSettings` An object of type `ExecutionSettings` as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

[CohortIncidenceModule\\$createResultsDataModel\(\)](#): Create the results data model for the module

Usage:

```
CohortIncidenceModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = ""
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsDatabaseSchema` The schema in the results database that holds the results data model.

`tablePrefix` A prefix to apply to the database table names (optional).

`tablePrefix` A prefix to apply to the database table names (optional).

`CohortIncidenceModule$getResultsDataModelSpecification()`: Get the results data model specification for the module

Usage:

```
CohortIncidenceModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

`tablePrefix` A prefix to apply to the database table names (optional).

`tablePrefix` A prefix to apply to the database table names (optional).

`CohortIncidenceModule$uploadResults()`: Upload the results for the module

Usage:

```
CohortIncidenceModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

`resultsDataModelSettings` The results data model settings as created using `createResultsDataModelSettings`

`CohortIncidenceModule$createModuleSpecifications()`: Creates the CohortIncidence Module Specifications

Usage:

```
CohortIncidenceModule$createModuleSpecifications(irDesign = NULL)
```

Arguments:

`irDesign` The incidence rate design created from the CohortIncidence package

`CohortIncidenceModule$validateModuleSpecifications()`: Validate the module specifications

Usage:

```
CohortIncidenceModule$validateModuleSpecifications(moduleSpecifications)
```

Arguments:

`moduleSpecifications` The CohortIncidence module specifications

`CohortIncidenceModule$clone()`: The objects of this class are cloneable with this method.

Usage:

```
CohortIncidenceModule$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

CohortMethodModule	<i>New-user</i>	<i>cohort</i>	<i>studies</i>	<i>with</i>	<i>the</i>
	Rhrefhttps://ohdsi.github.io/CohortMethod/HADES				<i>CohortMethod</i>
	<i>Package</i>				

Description

Module for performing new-user cohort studies against the OMOP Common Data Model

Super class

[StrategusModule](#) -> CohortMethodModule

Methods

Public methods:

- [CohortMethodModule\\$new\(\)](#)
- [CohortMethodModule\\$execute\(\)](#)
- [CohortMethodModule\\$createResultsDataModel\(\)](#)
- [CohortMethodModule\\$getResultsDataModelSpecification\(\)](#)
- [CohortMethodModule\\$uploadResults\(\)](#)
- [CohortMethodModule\\$createModuleSpecifications\(\)](#)
- [CohortMethodModule\\$validateModuleSpecifications\(\)](#)
- [CohortMethodModule\\$clone\(\)](#)

[CohortMethodModule\\$new\(\)](#): Initialize the module

Usage:

```
CohortMethodModule$new()
```

[CohortMethodModule\\$execute\(\)](#): Executes the CohortMethod package

Usage:

```
CohortMethodModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

`connectionDetails` An object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`analysisSpecifications` The analysis specifications for the study

`executionSettings` An object of type `ExecutionSettings` as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

[CohortMethodModule\\$createResultsDataModel\(\)](#): Create the results data model for the module

Usage:

```

CohortMethodModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = ""
)

```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsDatabaseSchema The schema in the results database that holds the results data model.

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

CohortMethodModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```

CohortMethodModule$getResultsDataModelSpecification(tablePrefix = "")

```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

CohortMethodModule\$uploadResults(): Upload the results for the module

Usage:

```

CohortMethodModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)

```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

analysisSpecifications An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

resultsDataModelSettings The results data model settings as created using `createResultsDataModelSettings`

CohortMethodModule\$createModuleSpecifications(): Creates the CohortMethod Module Specifications

Usage:

```

CohortMethodModule$createModuleSpecifications(
  cmAnalysesSpecifications,
  cmAnalysisList = NULL,
  targetComparatorOutcomesList = NULL,

```

```

    analysesToExclude = NULL,
    refitPsForEveryOutcome = NULL,
    refitPsForEveryStudyPopulation = NULL,
    cmDiagnosticThresholds = NULL
  )

```

Arguments:

`cmAnalysesSpecifications` An R6 class created by `CohortMethod::createCmAnalysesSpecifications`

`cmAnalysisList` Deprecated with CohortMethod v6 - please use the `cmAnalysesSpecifications` parameter instead.

`targetComparatorOutcomesList` Deprecated with CohortMethod v6 - please use the `cmAnalysesSpecifications` parameter instead.

`analysesToExclude` Deprecated with CohortMethod v6 - please use the `cmAnalysesSpecifications` parameter instead.

`refitPsForEveryOutcome` Deprecated with CohortMethod v6 - please use the `cmAnalysesSpecifications` parameter instead.

`refitPsForEveryStudyPopulation` Deprecated with CohortMethod v6 - please use the `cmAnalysesSpecifications` parameter instead.

`cmDiagnosticThresholds` Deprecated with CohortMethod v6 - please use the `cmAnalysesSpecifications` parameter instead.

Details: Run a list of analyses for the target-comparator-outcomes of interest. This function will run all specified analyses against all hypotheses of interest, meaning that the total number of outcome models is `length(cmAnalysisList) * length(targetComparatorOutcomesList)` (if all analyses specify an outcome model should be fitted). When you provide several analyses it will determine whether any of the analyses have anything in common, and will take advantage of this fact. For example, if we specify several analyses that only differ in the way the outcome model is fitted, then this function will extract the data and fit the propensity model only once, and re-use this in all the analysis.

After completion, a tibble containing references to all generated files can be obtained using the `CohortMethod::getFileReference()` function. A summary of the analysis results can be obtained using the `CohortMethod::getResultsSummary()` function.

Analyses to Exclude:

Normally, `runCmAnalyses` will run all combinations of target-comparator-outcome-analyses settings. However, sometimes we may not need all those combinations. Using the `analysesToExclude` argument, we can remove certain items from the full matrix. This argument should be a data frame with at least one of the following columns:

`CohortMethodModule$validateModuleSpecifications()`: Validate the module specifications

Usage:

```
CohortMethodModule$validateModuleSpecifications(moduleSpecifications)
```

Arguments:

`moduleSpecifications` The CohortMethod module specifications

`CohortMethodModule$clone()`: The objects of this class are cloneable with this method.

Usage:

```
CohortMethodModule$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

```
createCdmExecutionSettings
    Create CDM execution settings
```

Description

Create CDM execution settings

Usage

```
createCdmExecutionSettings(
    workDatabaseSchema,
    cdmDatabaseSchema,
    cohortTableNames = CohortGenerator::getCohortTableNames(cohortTable = "cohort"),
    tempEmulationSchema = getOption("sqlRenderTempEmulationSchema"),
    workFolder,
    resultsFolder,
    logFileName = file.path(resultsFolder, "strategus-log.txt"),
    minCellCount = 5,
    incremental = TRUE,
    maxCores = parallel::detectCores(),
    modulesToExecute = c(),
    skipCompletedTasks = FALSE
)
```

Arguments

workDatabaseSchema

A database schema where intermediate data can be stored. The user (as identified in the connection details) will need to have write access to this database schema.

cdmDatabaseSchema

The database schema containing the data in CDM format. The user (as identified in the connection details) will need to have read access to this database schema.

cohortTableNames

An object identifying the various cohort table names that will be created in the workDatabaseSchema. This object can be created using the [CohortGenerator::getCohortTableNames](#) function.

tempEmulationSchema

Some database platforms like Oracle and Impala do not truly support temp tables. To emulate temp tables, provide a schema with write privileges where temp tables can be created.

workFolder

A folder in the local file system where intermediate results can be written.

resultsFolder

The root folder holding the study results.

logFileName

Logging information from Strategus and all modules will be located in this file. Individual modules will continue to have their own module-specific logs. By default this will be written to the root of the resultsFolder

minCellCount

The minimum number of subjects contributing to a count before it can be included in results.

incremental	This value will be passed to each module that supports execution in an incremental manner. Modules and their underlying packages may use the workFolder contents to determine their state of execution and attempt to pick up where they left off when this value is set to TRUE.
maxCores	The maximum number of processing cores to use for execution. The default is to use all available cores on the machine.
modulesToExecute	(Optional) A vector with the list of modules to execute. When an empty vector/NULL is supplied (default), all modules in the analysis specification are executed.
skipCompletedTasks	When TRUE, modules with a matching completed execution_status.json record in the results folder are skipped. Execution status is persisted regardless of this value.

Value

An object of type ExecutionSettings.

```
createEmptyAnalysisSpecifications
```

Create an empty analysis specifications object.

Description

Create an empty analysis specifications object.

Usage

```
createEmptyAnalysisSpecifications()
```

Value

An object of type AnalysisSpecifications. The object records the installed Strategus version and an renv-compatible hash of the package DESCRIPTION.

```
createEmptyAnalysisSpecifications
```

DEPRECATED DUE TO MISSPELLING

Description

DEPRECATED DUE TO MISSPELLING

Usage

```
createEmptyAnalysisSpecifications()
```

See Also

[createEmptyAnalysisSpecifications\(\)](#)

```
createResultDataModel Create Result Data Model
```

Description

This function creates the results data model in the specified schema within the results database. The results data model is used to hold the study results and must be created before using [uploadResults\(\)](#).

Usage

```
createResultDataModel(
  analysisSpecifications,
  resultsDataModelSettings,
  resultsConnectionDetails
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#).

resultsDataModelSettings

The results data model settings as created using [createResultsDataModelSettings\(\)](#).

resultsConnectionDetails

The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

```
createResultsDataModelSettings
```

Create Results Data Model Settings

Description

The results data model settings are used to create the results data model and to upload results.

Usage

```
createResultsDataModelSettings(
  resultsDatabaseSchema,
  resultsFolder,
  logFileName = file.path(resultsFolder, "strategus-results-data-model-log.txt"),
  modulesToExecute = c(),
  skipCompletedUploads = FALSE
)
```

Arguments

resultsDatabaseSchema	The schema in the results database that holds the results data model.
resultsFolder	The root folder holding the study results.
logFileName	Log location for data model operations
modulesToExecute	(Optional) A vector with the list of modules to execute. When an empty vector/NULL is supplied (default), all modules in the analysis specification are executed.
skipCompletedUploads	When TRUE, module uploads with a matching completed upload_status.json record are skipped. Upload status is persisted regardless of this value.

Value

An object of type ResultsDataModelSettings

```
createResultsExecutionSettings
```

Create Results execution settings

Description

Create Results execution settings

Usage

```
createResultsExecutionSettings(
  resultsDatabaseSchema,
  workFolder,
  resultsFolder,
  logFileName = file.path(resultsFolder, "strategus-log.txt"),
  minCellCount = 5,
  maxCores = parallel::detectCores(),
  modulesToExecute = c(),
  skipCompletedTasks = FALSE
)
```

Arguments

resultsDatabaseSchema	The schema in the results database that holds the results data model.
workFolder	A folder in the local file system where intermediate results can be written.
resultsFolder	The root folder holding the study results.
logFileName	Logging information from Strategus and all modules will be located in this file. Individual modules will continue to have their own module-specific logs. By default this will be written to the root of the resultsFolder
minCellCount	The minimum number of subjects contributing to a count before it can be included in results.

maxCores	The maximum number of processing cores to use for execution. The default is to use all available cores on the machine.
modulesToExecute	(Optional) A vector with the list of modules to execute. When an empty vector/NULL is supplied (default), all modules in the analysis specification are executed.
skipCompletedTasks	When TRUE, modules with a matching completed execution_status.json record in the results folder are skipped. Execution status is persisted regardless of this value.

Value

An object of type ExecutionSettings.

EvidenceSynthesisModule

Meta-analysis with the R
EvidenceSynthesis Package

Description

Module for for combining causal effect estimates and study diagnostics across multiple data sites in a distributed study. This includes functions for performing meta-analysis and forest plots

Super class

[StrategusModule](#) -> EvidenceSynthesisModule

Methods**Public methods:**

- [EvidenceSynthesisModule\\$new\(\)](#)
- [EvidenceSynthesisModule\\$execute\(\)](#)
- [EvidenceSynthesisModule\\$createResultsDataModel\(\)](#)
- [EvidenceSynthesisModule\\$getResultsDataModelSpecification\(\)](#)
- [EvidenceSynthesisModule\\$uploadResults\(\)](#)
- [EvidenceSynthesisModule\\$validateModuleSpecifications\(\)](#)
- [EvidenceSynthesisModule\\$createEvidenceSynthesisSource\(\)](#)
- [EvidenceSynthesisModule\\$createRandomEffectsMetaAnalysis\(\)](#)
- [EvidenceSynthesisModule\\$createFixedEffectsMetaAnalysis\(\)](#)
- [EvidenceSynthesisModule\\$createBayesianMetaAnalysis\(\)](#)
- [EvidenceSynthesisModule\\$createEsDiagnosticThresholds\(\)](#)
- [EvidenceSynthesisModule\\$createModuleSpecifications\(\)](#)
- [EvidenceSynthesisModule\\$clone\(\)](#)

`EvidenceSynthesisModule$new()`: Initialize the module

Usage:

`EvidenceSynthesisModule$new()`

EvidenceSynthesisModule\$execute(): Executes the EvidenceSynthesis package

Usage:

```
EvidenceSynthesisModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

executionSettings An object of type ExecutionSettings as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

EvidenceSynthesisModule\$createResultsDataModel(): Create the results data model for the module

Usage:

```
EvidenceSynthesisModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = ""
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsDatabaseSchema The schema in the results database that holds the results data model.

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

EvidenceSynthesisModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
EvidenceSynthesisModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

EvidenceSynthesisModule\$uploadResults(): Upload the results for the module

Usage:

```
EvidenceSynthesisModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpec`

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpec`

resultsDataModelSettings The results data model settings as created using `createResultsDataModelSettings`

`EvidenceSynthesisModule$validateModuleSpecifications()`: Validate the module specifications

Usage:

```
EvidenceSynthesisModule$validateModuleSpecifications(moduleSpecifications)
```

Arguments:

moduleSpecifications The EvidenceSynthesis module specifications Create an evidence synthesis source

`EvidenceSynthesisModule$createEvidenceSynthesisSource()`:

Usage:

```
EvidenceSynthesisModule$createEvidenceSynthesisSource(
  sourceMethod = "CohortMethod",
  databaseIds = NULL,
  analysisIds = NULL,
  likelihoodApproximation = "grid with gradients"
)
```

Arguments:

sourceMethod The source method generating the estimates to synthesize. Can be "Cohort-Method" or "SelfControlledCaseSeries"

databaseIds The database IDs to include. Use databaseIds = NULL to include all database IDs.

analysisIds The source method analysis IDs to include. Use analysisIds = NULL to include all analysis IDs.

likelihoodApproximation The type of likelihood approximation. Can be "adaptive grid", "normal", or "grid with gradients".

Returns: An object of type EvidenceSynthesisSource. Create parameters for a random-effects meta-analysis

`EvidenceSynthesisModule$createRandomEffectsMetaAnalysis()`:

Usage:

```
EvidenceSynthesisModule$createRandomEffectsMetaAnalysis(
  alpha = 0.05,
  evidenceSynthesisAnalysisId = 1,
  evidenceSynthesisDescription = "Random-effects",
  evidenceSynthesisSource = NULL,
  controlType = "outcome"
)
```

Arguments:

alpha The alpha (expected type I error) used for the confidence intervals.
evidenceSynthesisAnalysisId description
evidenceSynthesisDescription description
evidenceSynthesisSource description
controlType description Create a parameter object for the function computeFixedEffectMeta-Analysis

Details: Use DerSimonian-Laird meta-analysis

EvidenceSynthesisModule\$createFixedEffectsMetaAnalysis():

Usage:

```
EvidenceSynthesisModule$createFixedEffectsMetaAnalysis(
  alpha = 0.05,
  evidenceSynthesisAnalysisId = 1,
  evidenceSynthesisDescription = "Fixed-effects",
  evidenceSynthesisSource = NULL,
  controlType = "outcome"
)
```

Arguments:

alpha The alpha (expected type I error) used for the confidence intervals.
evidenceSynthesisAnalysisId description
evidenceSynthesisDescription description
evidenceSynthesisSource description
controlType description Create a parameter object for the function computeBayesianMeta-Analysis

Details: Create an object defining the parameter values.

EvidenceSynthesisModule\$createBayesianMetaAnalysis():

Usage:

```
EvidenceSynthesisModule$createBayesianMetaAnalysis(
  chainLength = 1100000,
  burnIn = 1e+05,
  subSampleFrequency = 100,
  priorSd = c(2, 0.5),
  alpha = 0.05,
  robust = FALSE,
  df = 4,
  seed = 1,
  evidenceSynthesisAnalysisId = 1,
  evidenceSynthesisDescription = "Bayesian random-effects",
  evidenceSynthesisSource = NULL,
  controlType = "outcome"
)
```

Arguments:

chainLength Number of MCMC iterations.
burnIn Number of MCMC iterations to consider as burn in.
subSampleFrequency Subsample frequency for the MCMC.

priorSd A two-dimensional vector with the standard deviation of the prior for mu and tau, respectively.

alpha The alpha (expected type I error) used for the credible intervals.

robust Whether or not to use a t-distribution model; default: FALSE.

df Degrees of freedom for the t-model, only used if robust is TRUE.

seed The seed for the random number generator.

evidenceSynthesisAnalysisId description

evidenceSynthesisDescription description

evidenceSynthesisSource description

controlType description Create EvidenceSynthesis diagnostics thresholds

Details: Create an object defining the parameter values.

`EvidenceSynthesisModule$createEsDiagnosticThresholds()`: Threshold used to determine if we pass or fail diagnostics.

Usage:

```
EvidenceSynthesisModule$createEsDiagnosticThresholds(
  mdrThreshold = 10,
  easeThreshold = 0.25,
  i2Threshold = 0.4,
  tauThreshold = log(2),
  sdmThreshold = NULL,
  sdmAlpha = NULL
)
```

Arguments:

mdrThreshold What is the maximum allowed minimum detectable relative risk (MDRR)?

easeThreshold What is the maximum allowed expected absolute systematic error (EASE).

i2Threshold What is the maximum allowed I^2 (measure of between-database heterogeneity in random-effects models)?

tauThreshold What is the maximum allowed tau (measure of between-database heterogeneity in Bayesian random-effects models)?

sdmThreshold What is the maximum allowed standardized difference of mean (SDM) in a meta-analysis of balance statistics? If any covariate has a meta-analysis SDM exceeding this threshold, the diagnostic will fail. If set to NULL, this diagnostic will be ignored.

sdmAlpha What is the alpha for testing whether the absolute SDM exceeds sdmThreshold? If not provided, no significance testing will be performed and any absolute SDM greater than the threshold will be considered imbalance. Note that a Bonferroni adjustment will automatically be applied to adjust for the number of tests performed.

Returns: An object of type `EsDiagnosticThresholds`.

`EvidenceSynthesisModule$createModuleSpecifications()`: Creates the module Specifications

Usage:

```
EvidenceSynthesisModule$createModuleSpecifications(
  evidenceSynthesisAnalysisList,
  esDiagnosticThresholds = self$createEsDiagnosticThresholds()
)
```

Arguments:

`evidenceSynthesisAnalysisList` A list of objects of type `EvidenceSynthesisAnalysis` as generated by either the `EvidenceSynthesisModule#createFixedEffectsMetaAnalysis()` or `EvidenceSynthesisModule#createBayesianMetaAnalysis()` function.

`esDiagnosticThresholds` An object of type `EsDiagnosticThresholds` as generated by the `EvidenceSynthesisModule#createEsDiagnosticThresholds()` function.

`EvidenceSynthesisModule$clone()`: The objects of this class are cloneable with this method.

Usage:

```
EvidenceSynthesisModule$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

execute

Execute analysis specifications.

Description

Execute analysis specifications.

Usage

```
execute(analysisSpecifications, executionSettings, connectionDetails)
```

Arguments

`analysisSpecifications`

An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpecifications()`

`executionSettings`

An object of type `ExecutionSettings` as created by `createCdmExecutionSettings()` or `createResultsExecutionSettings()`.

`connectionDetails`

An object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

Value

Returns a list of lists that contains

- `moduleName`: The name of the module executed
- `result`: The result of the execution. See `purrr::safely` for details on this result.
- `executionTime`: The time for the module to execute

```
getCdmDatabaseMetaData
```

Gets the metadata for your OMOP CDM Database

Description

This function is used to gather metadata about your OMOP CDM and inspect for informational purposes. This information will be saved with your results when executing an analysis specification.

Usage

```
getCdmDatabaseMetaData(cdmExecutionSettings, connectionDetails)
```

Arguments

cdmExecutionSettings

An object of type CdmExecutionSettings as created [createCdmExecutionSettings\(\)](#).

connectionDetails

An object of class connectionDetails as created by the [DatabaseConnector::createConnection](#) function.

```
getExecutionStatus
```

Inspect execution status

Description

Inspects module execution status without executing the analysis or connecting to a database.

Usage

```
getExecutionStatus(analysisSpecifications, resultsFolder, modules = NULL)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications](#)

resultsFolder

The root folder holding the study results.

modules

Optional character vector selecting modules from the analysis specification. Matching is case-insensitive.

Value

An OperationStatus object.

getUploadStatus	<i>Inspect upload status</i>
-----------------	------------------------------

Description

Inspects destination-specific module upload status without connecting to the results database.

Usage

```
getUploadStatus(
  analysisSpecifications,
  resultsDataModelSettings,
  resultsConnectionDetails,
  modules = NULL
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#).

resultsDataModelSettings

The results data model settings as created using [createResultsDataModelSettings\(\)](#).

resultsConnectionDetails

The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

modules

Optional character vector selecting modules from the analysis specification. Matching is case-insensitive.

Value

An OperationStatus object.

PatientLevelPredictionModule

Patient-level prediction with the R[hrefhttps://ohdsi.github.io/PatientLevelPrediction/HADES](https://ohdsi.github.io/PatientLevelPrediction/HADES)
PatientLevelPrediction Package

Description

Module for performing patient-level prediction in an observational database in the OMOP Common Data Model.

Super class

[StrategusModule](#) -> PatientLevelPredictionModule

Public fields

tablePrefix The table prefix to append to the results tables

Methods

Public methods:

- [PatientLevelPredictionModule\\$new\(\)](#)
- [PatientLevelPredictionModule\\$execute\(\)](#)
- [PatientLevelPredictionModule\\$createResultsDataModel\(\)](#)
- [PatientLevelPredictionModule\\$getResultsDataModelSpecification\(\)](#)
- [PatientLevelPredictionModule\\$uploadResults\(\)](#)
- [PatientLevelPredictionModule\\$createModuleSpecifications\(\)](#)
- [PatientLevelPredictionModule\\$validateModuleSpecifications\(\)](#)
- [PatientLevelPredictionModule\\$clone\(\)](#)

[PatientLevelPredictionModule\\$new\(\)](#): Initialize the module

Usage:

```
PatientLevelPredictionModule$new()
```

[PatientLevelPredictionModule\\$execute\(\)](#): Executes the PatientLevelPrediction package

Usage:

```
PatientLevelPredictionModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

`connectionDetails` An object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`executionSettings` An object of type `ExecutionSettings` as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

[PatientLevelPredictionModule\\$createResultsDataModel\(\)](#): Create the results data model for the module

Usage:

```
PatientLevelPredictionModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = self$tablePrefix
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsDatabaseSchema` The schema in the results database that holds the results data model.

`tablePrefix` A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

PatientLevelPredictionModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
PatientLevelPredictionModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

PatientLevelPredictionModule\$uploadResults(): Upload the results for the module

Usage:

```
PatientLevelPredictionModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)

resultsDataModelSettings The results data model settings as created using [createResultsDataModelSettings](#)

PatientLevelPredictionModule\$createModuleSpecifications(): Creates the PatientLevel-Prediction Module Specifications

Usage:

```
PatientLevelPredictionModule$createModuleSpecifications(
  modelDesignList,
  skipDiagnostics = FALSE
)
```

Arguments:

modelDesignList A list of model designs created using PatientLevelPrediction::createModelDesign()

skipDiagnostics Whether to run the diagnostics based on PROBAST before model development

PatientLevelPredictionModule\$validateModuleSpecifications(): Validate the module specifications

Usage:

```
PatientLevelPredictionModule$validateModuleSpecifications(moduleSpecifications)
```

Arguments:

moduleSpecifications The PatientLevelPrediction module specifications

PatientLevelPredictionModule\$clone(): The objects of this class are cloneable with this method.

Usage:

```
PatientLevelPredictionModule$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

PatientLevelPredictionValidationModule

Validation of patient-level prediction models with the
[Rhrefhttps://ohdsi.github.io/PatientLevelPrediction/HADES](https://ohdsi.github.io/PatientLevelPrediction/HADES) Pa-
tientLevelPrediction Package

Description

Module for performing patient-level prediction model validation for models built using the PatientLevelPrediction package.

Super class

[StrategusModule](#) -> PatientLevelPredictionValidationModule

Public fields

tablePrefix The table prefix to append to the results tables

Methods**Public methods:**

- [PatientLevelPredictionValidationModule\\$new\(\)](#)
- [PatientLevelPredictionValidationModule\\$execute\(\)](#)
- [PatientLevelPredictionValidationModule\\$createResultsDataModel\(\)](#)
- [PatientLevelPredictionValidationModule\\$uploadResults\(\)](#)
- [PatientLevelPredictionValidationModule\\$createModuleSpecifications\(\)](#)
- [PatientLevelPredictionValidationModule\\$validateModuleSpecifications\(\)](#)
- [PatientLevelPredictionValidationModule\\$clone\(\)](#)

[PatientLevelPredictionValidationModule\\$new\(\)](#): Initialize the module

Usage:

```
PatientLevelPredictionValidationModule$new()
```

[PatientLevelPredictionValidationModule\\$execute\(\)](#): Executes the PatientLevelPrediction package to validate a PLP model

Usage:

```
PatientLevelPredictionValidationModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpecifications()`

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpecifications()`

executionSettings An object of type ExecutionSettings as created by `createCdmExecutionSettings()` or `createResultsExecutionSettings()`.

`PatientLevelPredictionValidationModule$createResultsDataModel()`: Create the results data model for the module

Usage:

```
PatientLevelPredictionValidationModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = self$tablePrefix
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsDatabaseSchema The schema in the results database that holds the results data model.

tablePrefix A prefix to apply to the database table names (optional).

`PatientLevelPredictionValidationModule$uploadResults()`: Upload the results for the module

Usage:

```
PatientLevelPredictionValidationModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the `DatabaseConnector::createConnectionDetails()` function.

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpecifications()`

analysisSpecifications An object of type AnalysisSpecifications as created by `createEmptyAnalysisSpecifications()`

resultsDataModelSettings The results data model settings as created using `createResultsDataModelSettings()`

`PatientLevelPredictionValidationModule$createModuleSpecifications()`: Creates the PatientLevelPredictionValidation Module Specifications

Usage:

```

PatientLevelPredictionValidationModule$createModuleSpecifications(
  validationList = list(PatientLevelPrediction::createValidationDesign(plpModelList =
    list(file.path("location_to_model")), targetId = 1, outcomeId = 3,
    restrictPlpDataSettings = PatientLevelPrediction::createRestrictPlpDataSettings(),
    populationSettings = NULL, recalibrate = "weakRecalibration", runCovariateSummary =
    TRUE), PatientLevelPrediction::createValidationDesign(plpModelList =
    list(file.path("location_to_model")), targetId = 4, outcomeId = 3,
    restrictPlpDataSettings = PatientLevelPrediction::createRestrictPlpDataSettings(),
    populationSettings = NULL, recalibrate = "weakRecalibration", runCovariateSummary
    = TRUE)),
  logLevel = "INFO"
)

```

Arguments:

validationList A list of validation designs from PatientLevelPrediction::createValidationDesign
logLevel The logging level while executing the model validation.

PatientLevelPredictionValidationModule\$validateModuleSpecifications(): Validate the module specifications

Usage:

```

PatientLevelPredictionValidationModule$validateModuleSpecifications(
  moduleSpecifications
)

```

Arguments:

moduleSpecifications The PatientLevelPredictionValidation module specifications

PatientLevelPredictionValidationModule\$clone(): The objects of this class are cloneable with this method.

Usage:

```

PatientLevelPredictionValidationModule$clone(deep = FALSE)

```

Arguments:

deep Whether to make a deep clone.

PheValuatorModule	<i>Evaluate phenotype algorithms with the</i>
	<i>Rhrefhttps://ohdsi.github.io/PheValuator/HADES PheValuator</i>
	<i>Package</i>

Description

Evaluates phenotype algorithms using the PheValuator method against the OMOP Common Data Model.

Super class

[StrategusModule](#) -> PheValuatorModule

Public fields

tablePrefix The table prefix to append to the results tables

Methods**Public methods:**

- [PheValuatorModule\\$new\(\)](#)
- [PheValuatorModule\\$execute\(\)](#)
- [PheValuatorModule\\$createResultsDataModel\(\)](#)
- [PheValuatorModule\\$getResultsDataModelSpecification\(\)](#)
- [PheValuatorModule\\$uploadResults\(\)](#)
- [PheValuatorModule\\$createModuleSpecifications\(\)](#)
- [PheValuatorModule\\$validateModuleSpecifications\(\)](#)
- [PheValuatorModule\\$clone\(\)](#)

PheValuatorModule\$new(): Initialize the module

Usage:

```
PheValuatorModule$new()
```

PheValuatorModule\$execute(): Execute PheValuator

Usage:

```
PheValuatorModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

executionSettings An object of type ExecutionSettings as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

PheValuatorModule\$createResultsDataModel(): Create the results data model for the module

Usage:

```
PheValuatorModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = self$tablePrefix
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsDatabaseSchema The schema in the results database that holds the results data model.
 tablePrefix A prefix to apply to the database table names (optional).
 tablePrefix A prefix to apply to the database table names (optional).

PheValuatorModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
PheValuatorModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).
 tablePrefix A prefix to apply to the database table names (optional).

PheValuatorModule\$uploadResults(): Upload the results for PheValuator

Usage:

```
PheValuatorModule$uploadResults(  
  resultsConnectionDetails,  
  analysisSpecifications,  
  resultsDataModelSettings  
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.
 resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.
 analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)
 analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)
 resultsDataModelSettings The results data model settings as created using [createResultsDataModelSettings](#)

PheValuatorModule\$createModuleSpecifications(): Creates the PheValuator Module Specifications

Usage:

```
PheValuatorModule$createModuleSpecifications(  
  analysisName = "Main",  
  pheValuatorAnalysisList  
)
```

Arguments:

analysisName A short name for the analysis (default: "Main").
 pheValuatorAnalysisList A list of analysis specification objects. Each element is a list with two named fields:
 phenotype A short file-system-safe name for the phenotype (e.g. "bladderCancer").
 cohortsToEvaluate A list of evaluation parameters:
 phenotypeCohortId Cohort ID(s) of the phenotype to evaluate.
 washoutPeriod Minimum prior observation days (should match cohort definition).
 xSpecCohortId Cohort ID for the extremely-specific (xSpec) cohort.
 daysFromxSpec Days from xSpec cohort start to index visit.

`xSensCohortId` Cohort ID for the extremely-sensitive (xSens) cohort.
`prevalenceCohortId` Cohort ID used to estimate prevalence.
`excludedCovariateConceptIds` Integer vector of concept IDs to exclude from covariates.
`covariateSettingsType` One of "chronic" or "acute" (default "chronic").

`PheValuatorModule$validateModuleSpecifications()`: Validate the module specifications

Usage:

`PheValuatorModule$validateModuleSpecifications(moduleSpecifications)`

Arguments:

`moduleSpecifications` The PheValuator module specifications

`PheValuatorModule$clone()`: The objects of this class are cloneable with this method.

Usage:

`PheValuatorModule$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

SelfControlledCaseSeriesModule

*Self-Controlled Case Series design with the
 Rhref<https://ohdsi.github.io/SelfControlledCaseSeries/HADES>
 SelfControlledCaseSeries Package*

Description

Module for performing Self-Controlled Case Series (SCCS) analyses against the OMOP Common Data Model.

Super class

`StrategusModule` -> `SelfControlledCaseSeriesModule`

Public fields

`tablePrefix` The table prefix for results tables

Methods

Public methods:

- `SelfControlledCaseSeriesModule$new()`
- `SelfControlledCaseSeriesModule$execute()`
- `SelfControlledCaseSeriesModule$createResultsDataModel()`
- `SelfControlledCaseSeriesModule$getResultsDataModelSpecification()`
- `SelfControlledCaseSeriesModule$uploadResults()`
- `SelfControlledCaseSeriesModule$createModuleSpecifications()`
- `SelfControlledCaseSeriesModule$validateModuleSpecifications()`
- `SelfControlledCaseSeriesModule$clone()`

SelfControlledCaseSeriesModule\$new(): Initialize the module

Usage:

```
SelfControlledCaseSeriesModule$new()
```

SelfControlledCaseSeriesModule\$execute(): Executes the SelfControlledCaseSeries package

Usage:

```
SelfControlledCaseSeriesModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

executionSettings An object of type ExecutionSettings as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

SelfControlledCaseSeriesModule\$createResultsDataModel(): Create the results data model for the module

Usage:

```
SelfControlledCaseSeriesModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = ""
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsDatabaseSchema The schema in the results database that holds the results data model.

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

SelfControlledCaseSeriesModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
SelfControlledCaseSeriesModule$getResultsDataModelSpecification(
  tablePrefix = ""
)
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

`SelfControlledCaseSeriesModule$uploadResults()`: Upload the results for the module

Usage:

```
SelfControlledCaseSeriesModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

`resultsDataModelSettings` The results data model settings as created using `createResultsDataModelSettings`

`SelfControlledCaseSeriesModule$createModuleSpecifications()`: Creates the SelfControlledCaseSeries Module Specifications

Usage:

```
SelfControlledCaseSeriesModule$createModuleSpecifications(
  sccsAnalysesSpecifications,
  sccsAnalysisList = NULL,
  exposuresOutcomeList = NULL,
  analysesToExclude = NULL,
  combineDataFetchAcrossOutcomes = NULL,
  sccsDiagnosticThresholds = NULL
)
```

Arguments:

`sccsAnalysesSpecifications` An R6 class created by `SelfControlledCaseSeries::createSccsAnalysesSpecification`

`sccsAnalysisList` Deprecated with SelfControlledCaseSeries v6 - please use the `sccsAnalysesSpecifications` parameter instead.

`exposuresOutcomeList` Deprecated with SelfControlledCaseSeries v6 - please use the `sccsAnalysesSpecifications` parameter instead.

`analysesToExclude` Deprecated with SelfControlledCaseSeries v6 - please use the `sccsAnalysesSpecifications` parameter instead.

`combineDataFetchAcrossOutcomes` Deprecated with SelfControlledCaseSeries v6 - please use the `sccsAnalysesSpecifications` parameter instead.

`sccsDiagnosticThresholds` Deprecated with SelfControlledCaseSeries v6 - please use the `sccsAnalysesSpecifications` parameter instead.

`SelfControlledCaseSeriesModule$validateModuleSpecifications()`: Validate the module specifications

Usage:

```
SelfControlledCaseSeriesModule$validateModuleSpecifications(
  moduleSpecifications
)
```

Arguments:

moduleSpecifications The SelfControlledCaseSeries module specifications

SelfControlledCaseSeriesModule\$clone(): The objects of this class are cloneable with this method.

Usage:

SelfControlledCaseSeriesModule\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

StrategusModule

StrategusModule defines the base class for each HADES module

Description

StrategusModule serves as an internal base class that defines the core functions and structure to be inherited and implemented by any specific HADES module. It provides a standardized framework for creating modular components within the Strategus pipeline.

Public fields

moduleName The name of the module taken from the class name. This is set in the constructor of the class.

moduleClassName The class name that identifies the module specifications in the overall analysis specification. This is set in the constructor of the class.

internalModuleSpecificationClassName A constant value. The base class name that identifies a module specification in the analysis specification.

internalSharedResourcesClassName A constant value. The class name that identifies the shared resources section in the overall analysis specification.

Methods

Public methods:

- [StrategusModule\\$new\(\)](#)
- [StrategusModule\\$getPackageInformation\(\)](#)
- [StrategusModule\\$execute\(\)](#)
- [StrategusModule\\$createResultsDataModel\(\)](#)
- [StrategusModule\\$getResultsDataModelSpecification\(\)](#)
- [StrategusModule\\$uploadResults\(\)](#)
- [StrategusModule\\$createModuleSpecifications\(\)](#)
- [StrategusModule\\$createSharedResourcesSpecifications\(\)](#)
- [StrategusModule\\$validateModuleSpecifications\(\)](#)
- [StrategusModule\\$validateSharedResourcesSpecifications\(\)](#)
- [StrategusModule\\$clone\(\)](#)

StrategusModule\$new(): Initialize the module

Usage:

StrategusModule\$new()

StrategusModule\$getPackageInformation(): Get the package identity associated with the module.

Usage:

```
StrategusModule$getPackageInformation()
```

Returns: A list containing the module package name, version, and an renv-compatible DESCRIPTION hash.

StrategusModule\$execute(): Executes the module

Usage:

```
StrategusModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

connectionDetails An object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

executionSettings An object of type ExecutionSettings as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

StrategusModule\$createResultsDataModel(): Create the results data model for the module

Usage:

```
StrategusModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = ""
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsDatabaseSchema The schema in the results database that holds the results data model.

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

StrategusModule\$getResultsDataModelSpecification(): Get the results data model specification for the module

Usage:

```
StrategusModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

tablePrefix A prefix to apply to the database table names (optional).

tablePrefix A prefix to apply to the database table names (optional).

StrategusModule\$uploadResults(): Upload the results for the module

Usage:

```
StrategusModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

resultsConnectionDetails The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)

analysisSpecifications An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpec](#)

resultsDataModelSettings The results data model settings as created using [createResultsDataModelSettings](#)

StrategusModule\$createModuleSpecifications(): Base function for creating the module settings object. Each module will have its own implementation and this base class method will be used to ensure the class of the specifications is set properly.

Usage:

```
StrategusModule$createModuleSpecifications(moduleSpecifications)
```

Arguments:

moduleSpecifications An object of type ModuleSpecifications

moduleSpecifications An object of type ModuleSpecifications

StrategusModule\$createSharedResourcesSpecifications(): Base function for creating the shared resources settings object. Each module will have its own implementation if it needs to create a shared resource.

Usage:

```
StrategusModule$createSharedResourcesSpecifications(
  className,
  sharedResourcesSpecifications
)
```

Arguments:

className The class name of the shared resources specifications

sharedResourcesSpecifications The shared resources specifications

StrategusModule\$validateModuleSpecifications(): Base function for validating the module settings object. Each module will have its own implementation and this base class method will be used to ensure the module specifications are valid ahead of execution

Usage:

```
StrategusModule$validateModuleSpecifications(moduleSpecifications)
```

Arguments:

moduleSpecifications An object of type ModuleSpecifications

moduleSpecifications An object of type ModuleSpecifications

StrategusModule\$validateSharedResourcesSpecifications(): Base function for validating the shared resources specification settings object. Each module will have its own implementation and this base class method will be used to ensure the module specifications are valid ahead of execution

Usage:

```
StrategusModule$validateSharedResourcesSpecifications(
  className,
  sharedResourcesSpecifications
)
```

Arguments:

className The class name of the shared resources specifications

sharedResourcesSpecifications The shared resources specifications

StrategusModule\$clone(): The objects of this class are cloneable with this method.

Usage:

```
StrategusModule$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

TreatmentPatternsModule

Evaluate phenotypes with the R
<https://github.com/darwin-eu/TreatmentPatterns/DARWIN> TreatmentPatterns Package

Description

Characterization and description of patterns of events (cohorts). against the OMOP Common Data Model.

Super class

[StrategusModule](#) -> TreatmentPatternsModule

Public fields

tablePrefix The table prefix to append to the results tables

Methods

Public methods:

- [TreatmentPatternsModule\\$new\(\)](#)
- [TreatmentPatternsModule\\$execute\(\)](#)
- [TreatmentPatternsModule\\$createResultsDataModel\(\)](#)
- [TreatmentPatternsModule\\$getResultsDataModelSpecification\(\)](#)
- [TreatmentPatternsModule\\$uploadResults\(\)](#)
- [TreatmentPatternsModule\\$createModuleSpecifications\(\)](#)
- [TreatmentPatternsModule\\$createMultiAnalysisModuleSpecification\(\)](#)
- [TreatmentPatternsModule\\$validateModuleSpecifications\(\)](#)

- [TreatmentPatternsModule\\$clone\(\)](#)

`TreatmentPatternsModule$new()`: Initialize the module

Usage:

```
TreatmentPatternsModule$new()
```

`TreatmentPatternsModule$execute()`: Execute Treatment Patterns

Usage:

```
TreatmentPatternsModule$execute(
  connectionDetails,
  analysisSpecifications,
  executionSettings
)
```

Arguments:

`connectionDetails` An object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`analysisSpecifications` An object of type `AnalysisSpecifications` as created by [createEmptyAnalysisSpecifications\(\)](#)

`executionSettings` An object of type `ExecutionSettings` as created by [createCdmExecutionSettings\(\)](#) or [createResultsExecutionSettings\(\)](#).

`TreatmentPatternsModule$createResultsDataModel()`: Create the results data model for the module

Usage:

```
TreatmentPatternsModule$createResultsDataModel(
  resultsConnectionDetails,
  resultsDatabaseSchema,
  tablePrefix = self$tablePrefix
)
```

Arguments:

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsConnectionDetails` The connection details to the results database which is an object of class `connectionDetails` as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

`resultsDatabaseSchema` The schema in the results database that holds the results data model.

`tablePrefix` A prefix to apply to the database table names (optional).

`tablePrefix` A prefix to apply to the database table names (optional).

`TreatmentPatternsModule$getResultsDataModelSpecification()`: Get the results data model specification for the module

Usage:

```
TreatmentPatternsModule$getResultsDataModelSpecification(tablePrefix = "")
```

Arguments:

`tablePrefix` A prefix to apply to the database table names (optional).

`tablePrefix` A prefix to apply to the database table names (optional).

`TreatmentPatternsModule$uploadResults()`: Upload the results for TreatmentPatterns

Usage:

```
TreatmentPatternsModule$uploadResults(
  resultsConnectionDetails,
  analysisSpecifications,
  resultsDataModelSettings
)
```

Arguments:

resultsConnectionDetails The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

resultsConnectionDetails The connection details to the results database which is an object of class `connectionDetails` as created by the `DatabaseConnector::createConnectionDetails()` function.

analysisSpecifications An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

analysisSpecifications An object of type `AnalysisSpecifications` as created by `createEmptyAnalysisSpec`

resultsDataModelSettings The results data model settings as created using `createResultsDataModelSettings`

TreatmentPatternsModule\$createModuleSpecifications(): Creates the TreatmentPatterns-Module Specifications

Usage:

```
TreatmentPatternsModule$createModuleSpecifications(
  analysisId = 1,
  cohorts,
  description = "",
  includeTreatments = NULL,
  indexDateOffset = NULL,
  minEraDuration = 0,
  splitEventCohorts = NULL,
  splitTime = NULL,
  eraCollapseSize = 30,
  combinationWindow = 30,
  minPostCombinationDuration = 30,
  filterTreatments = "First",
  maxPathLength = 5,
  ageWindow = 5,
  minCellCount = 1,
  censorType = "minCellCount",
  overlapMethod = "truncate",
  concatTargets = TRUE,
  startAnchor = "startDate",
  windowStart = 0,
  endAnchor = "endDate",
  windowEnd = 0,
  stratify = FALSE
)
```

Arguments:

analysisId (numeric(1)) Unique identifier for the TreatmentPatterns analysis

cohorts (data.frame())

Data frame containing the following columns and data types:

cohortId numeric(1) Cohort ID's of the cohorts to be used in the cohort table.

cohortName character(1) Cohort names of the cohorts to be used in the cohort table.

type character(1) ["**target**", "**event**", "**exit**"] Cohort type, describing if the cohort is a target, event, or exit cohort

description (character(1)) Description for analysis

includeTreatments (character(1): "startDate")
DEPRECATED
"startDate" Include treatments after the target cohort start date and onwards.
"endDate" Include treatments before target cohort end date and before.

indexDateOffset (integer(1): 0)
DEPRECATED Offset the index date of the Target cohort.

minEraDuration (integer(1): 0)
Minimum time an event era should last to be included in analysis

splitEventCohorts (character(n): "")
Specify event cohort to split in acute (< X days) and therapy (>= X days)

splitTime (integer(1): 30)
Specify number of days (X) at which each of the split event cohorts should be split in acute and therapy

eraCollapseSize (integer(1): 30)
Window of time between which two eras of the same event cohort are collapsed into one era

combinationWindow (integer(1): 30)
Window of time two event cohorts need to overlap to be considered a combination treatment

minPostCombinationDuration (integer(1): 30)
Minimum time an event era before or after a generated combination treatment should last to be included in analysis

filterTreatments (character(1): "First" ["first", "Changes", "all"])
Select first occurrence of (First); changes between (Changes); or all event cohorts (All).

maxPathLength (integer(1): 5)
Maximum number of steps included in treatment pathway

ageWindow (integer(n): 10)
Number of years to bin age groups into. It may also be a vector of integers. I.e. c(0, 18, 150) which will results in age group 0-18 which includes subjects < 19. And age group 18-150 which includes subjects > 18.

minCellCount (integer(1): 5)
Minimum count required per pathway. Censors data below x as <x. This minimum value will carry over to the sankey diagram and sunburst plot.

censorType (character(1))

"minCellCount" Censors pathways <minCellCount to minCellCount.
"remove" Censors pathways <minCellCount by removing them completely.
"mean" Censors pathways <minCellCount to the mean of all frequencies below minCellCount

overlapMethod (character(1): "truncate") Method to decide how to deal with overlap that is not significant enough for combination. "keep" will keep the dates as is. "truncate" truncates the first occurring event to the start date of the next event.

concatTargets (logical(1): TRUE) Should multiple target cohorts for the same person be concatenated or not?

startAnchor (character(1): "startDate") Start date anchor. One of: "startDate", "endDate"

windowStart (numeric(1): 0) Offset for startAnchor in days.

endAnchor (character(1): "endDate") End date anchor. One of: "startDate", "endDate"

windowEnd (numeric(1): 0) Offset for endAnchor in days.

stratify (logical(1))

This will perform pairwise stratification between age, sex, and index year if set TRUE

TreatmentPatternsModule\$createMultiAnalysisModuleSpecification(): Runs multiple analyses using a list of analysis specification objects (as produced by createModuleSpecifications) into a single module specification

Usage:

TreatmentPatternsModule\$createMultiAnalysisModuleSpecification(tpAnalysisList)

Arguments:

tpAnalysisList (list())

A list of analysis specification objects. Each element should be a list created by createAnalysisSpecification

TreatmentPatternsModule\$validateModuleSpecifications(): Validate the module specifications

Usage:

TreatmentPatternsModule\$validateModuleSpecifications(moduleSpecifications)

Arguments:

moduleSpecifications The treatment patterns module specifications

TreatmentPatternsModule\$clone(): The objects of this class are cloneable with this method.

Usage:

TreatmentPatternsModule\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

uploadResults

Upload results

Description

Upload the results for a given analysis

Usage

```
uploadResults(
  analysisSpecifications,
  resultsDataModelSettings,
  resultsConnectionDetails
)
```

Arguments

analysisSpecifications

An object of type AnalysisSpecifications as created by [createEmptyAnalysisSpecifications\(\)](#)

resultsDataModelSettings

The results data model settings as created using [createResultsDataModelSettings\(\)](#).

resultsConnectionDetails

The connection details to the results database which is an object of class connectionDetails as created by the [DatabaseConnector::createConnectionDetails\(\)](#) function.

zipResults	<i>Create a zip file with all study results for sharing with study coordinator</i>
------------	--

Description

Create a zip file with all study results for sharing with study coordinator

Usage

```
zipResults(resultsFolder, zipFile)
```

Arguments

resultsFolder	The root folder holding the study results.
zipFile	The path to the zip file to be created.

Details

Creates a .zip file of the .csv files found in the resultsFolder. The resulting .zip file will have relative paths to the root of the resultsFolder which is generally found in executionSettings\$resultsFolder.

Value

Does not return anything. Is called for the side-effect of creating the zip file with results.

Index

[addCharacterizationModuleSpecifications,](#)
[3](#)
[addCohortDiagnosticsModuleSpecifications,](#)
[4](#)
[addCohortGeneratorModuleSpecifications,](#)
[4](#)
[addCohortIncidenceModuleSpecifications,](#)
[5](#)
[addCohortMethodModuleSpecifications,](#)
[5](#)
[addEvidenceSynthesisModuleSpecifications,](#)
[6](#)
[addModuleSpecifications,](#) [7](#)
[addPatientLevelPredictionModuleSpecifications,](#)
[7](#)
[addPatientLevelPredictionValidationModuleSpecifications,](#)
[8](#)
[addPheValuatorModuleSpecifications,](#) [8](#)
[addSelfControlledCaseSeriesModuleSpecifications,](#)
[9](#)
[addSharedResources,](#) [9](#)
[addTreatmentPatternsModuleSpecifications,](#)
[10](#)

[CharacterizationModule,](#) [10](#)
[CohortDiagnosticsModule,](#) [14](#)
[CohortGenerator::getCohortTableNames\(\),](#)
[26](#)
[CohortGeneratorModule,](#) [17](#)
[CohortIncidenceModule,](#) [20](#)
[CohortMethod::getFileReference\(\),](#) [25](#)
[CohortMethod::getResultsSummary\(\),](#) [25](#)
[CohortMethodModule,](#) [23](#)
[createCdmExecutionSettings,](#) [26](#)
[createCdmExecutionSettings\(\),](#) [11, 15, 18,](#)
[21, 23, 31, 35, 36, 38, 41, 43, 46, 49,](#)
[52](#)
[createEmptyAnalysisSpecifications,](#) [27](#)
[createEmptyAnalysisSpecifications\(\),](#)
[27](#)
[createEmptyAnalysisSpecifications,](#) [27](#)
[createEmptyAnalysisSpecifications\(\),](#)
[3–12, 15, 18, 19, 21, 22, 24, 28, 31,](#)
[32, 35–39, 41, 43, 44, 46, 47, 49, 50,](#)
[52, 53, 55](#)
[createResultDataModel,](#) [28](#)
[createResultsDataModelSettings,](#) [28](#)
[createResultsDataModelSettings\(\),](#) [12,](#)
[16, 19, 22, 24, 28, 32, 37, 39, 41, 44,](#)
[47, 50, 53, 55](#)
[createResultsExecutionSettings,](#) [29](#)
[createResultsExecutionSettings\(\),](#) [11,](#)
[15, 18, 21, 23, 31, 35, 38, 41, 43, 46,](#)
[49, 52](#)

[DatabaseConnector::createConnectionDetails\(\),](#)
[11, 12, 14, 15, 18, 19, 21–24, 28, 31,](#)
[32, 35–39, 41, 43, 44, 46, 47, 49, 50,](#)
[52, 53, 55](#)

[EvidenceSynthesisModule,](#) [30](#)
[execute,](#) [35](#)
[getCdmDatabaseMetaData,](#) [36](#)
[getExecutionStatus,](#) [36](#)
[getUploadStatus,](#) [37](#)

[PatientLevelPredictionModule,](#) [37](#)
[PatientLevelPredictionValidationModule,](#)
[40](#)
[PheValuatorModule,](#) [42](#)

[SelfControlledCaseSeriesModule,](#) [45](#)
[StrategusModule,](#) [10, 14, 17, 20, 23, 30, 37,](#)
[40, 42, 45, 48, 51](#)

[TreatmentPatternsModule,](#) [51](#)

[uploadResults,](#) [55](#)
[uploadResults\(\),](#) [28](#)

[zipResults,](#) [56](#)