

This is a professional and structured version of your API Integration Guide, formatted and ready to be saved or printed as a PDF.

---

## API Documentation

**Version:** 1.0

**Base URL:** <https://www.findus.co.il/api/v1>

---

### 1. Authentication

All requests require a Bearer token in the Authorization header. This token is provided by the FindUs administrator upon API client creation.

#### Header Format:

HTTP

Authorization: Bearer YOUR\_API\_TOKEN

#### Error Response (401 Unauthorized):

If the token is missing or invalid:

JSON

```
{ "error": "Unauthorized" }
```

---

### 2. Endpoints

#### 2.1 Get Properties

GET /api/v1/properties

Returns all published properties enabled for API access.

#### Query Parameters

| Parameter    | Type   | Description                                           |
|--------------|--------|-------------------------------------------------------|
| city         | string | Filter by city name (partial match, case-insensitive) |
| propertyType | string | Filter by type (e.g., Apartment, Penthouse, Duplex)   |
| page         | number | Page number (default: 1)                              |

| Parameter | Type   | Description                              |
|-----------|--------|------------------------------------------|
| limit     | number | Results per page (default: 50, max: 100) |

#### Example Request

Bash

```
curl -H "Authorization: Bearer YOUR_TOKEN" \
  "https://www.findus.co.il/api/v1/properties?city=Larnaca&limit=10"
```

---

## 2.2 Get Projects

GET /api/v1/projects

Returns all published projects enabled for API access, including linked properties, images, and documents.

#### Example Request

Bash

```
curl -H "Authorization: Bearer YOUR_TOKEN" \
  https://www.findus.co.il/api/v1/projects
```

---

## 3. Data Schema & References

### 3.1 Response Codes

| Code | Meaning                                 |
|------|-----------------------------------------|
| 200  | Success                                 |
| 401  | Unauthorized — invalid or missing token |

### 3.2 Property Fields Reference

| Field | Type   | Description                         |
|-------|--------|-------------------------------------|
| id    | string | Unique identifier (Always included) |
| title | string | Property title                      |
| price | number | Price in the specified currency     |

| Field        | Type   | Description                   |
|--------------|--------|-------------------------------|
| currency     | string | Currency code (e.g., EUR)     |
| propertyType | string | Apartment, Penthouse, etc.    |
| areaSqm      | number | Area in square meters         |
| videoUrl     | string | YouTube tour URL              |
| status       | string | Current status (e.g., ACTIVE) |

### 3.3 Project Fields Reference

| Field          | Type   | Description                              |
|----------------|--------|------------------------------------------|
| developerName  | string | Developer or builder name                |
| completionDate | string | Expected completion (e.g., Q4 2027)      |
| totalUnits     | number | Total number of units in project         |
| documents      | array  | List of floor plans, brochures, and PDFs |

---

## 4. Implementation Details

### Field Availability & Permissions

The fields returned depend on your API client configuration set by the administrator.

- **Images:** Included only if "Include Images" is enabled. The primary image is always first in the array.
- **Documents:** Included only if "Include Documents" is enabled. Categories include plan, brochure, or other.

### Visibility Rules

Only entities meeting these criteria are returned:

1. **Published** by admin.
  2. **Status** is ACTIVE.
  3. **API Enabled** flag is ON.
-

## 5. Code Examples

### JavaScript (Fetch)

JavaScript

```
const response = await fetch('https://www.findus.co.il/api/v1/properties', {  
  headers: { 'Authorization': `Bearer ${TOKEN}` }  
});  
  
const result = await response.json();  
  
console.log(result.data);
```

### Python (Requests)

Python

```
import requests  
  
headers = {'Authorization': f'Bearer {TOKEN}'}  
  
response = requests.get('https://www.findus.co.il/api/v1/properties', headers=headers)  
  
data = response.json()['data']
```

### PHP (cURL)

PHP

```
$ch = curl_init('https://www.findus.co.il/api/v1/properties');  
  
curl_setopt($ch, CURLOPT_HTTPHEADER, ["Authorization: Bearer $token"]);  
  
curl_setopt($ch, CURLOPT_RETURNTRANSFER, true);  
  
$response = curl_exec($ch);
```

---

## 6. Support

For API access, token regeneration, or technical questions, please contact the **FindUs Admin Team**.

---