

VertKleen HCR Label

DOCUMENT ID	MAS-VK-HCR-LABEL
DISTRIBUTION REVISION	1.0
EFFECTIVE DATE	2026-07-24
SUPERSEDED STATUS	Current
OWNER	MASEST Consulting LLC
APPROVAL	Released for customer review
APPLICABLE SKU(S)	VK-HCR

TECHNICAL / LEGAL CLAIM REVIEW REQUIRED

Review boundary. This cover controls MASEST website distribution only. It does not certify technical, regulatory, legal, safety, performance, or customer-specific claims. Source pages follow unchanged and remain subject to original instructions, limitations, and dates.

Approval scope: Distribution approval only; technical and legal claim approval is not asserted.

VertKleen HCR

100% Synthetic, Non-Corrosive HCl Replacement



VertKleen HCR is a safe yet functional replacement for traditional hydrochloric acid treatments and other commonly used oil field acid treatments. VertKleen HCR is non-regulated by the U.S. DOT and carries a triple zero HMIS. VertKleen HCR biodegrades in less than 10 days and is manufactured with EPA Design for Environment and Cleangredients approved ingredients as prescribed by the U.S. EPA DfE Program for the manufacturing of environmentally safer chemicals.

USE DIRECTIONS

Recommended dilution rates: 30-100% with water based on the severity of the buildup and the reaction rate required for the project.

Note: VertKleen HCR does not contain any additional iron control agents, demulsifiers, or corrosion inhibitors. No organic acid additions are required.

A typical ratio for an acid frac is one part VertKleen HCR and one part water. Ratios may vary based on specific applications and recommendations from your dealer.

When pumping VertKleen HCR it is recommended to use hose couplings and fittings approved by your product supplier. 316 stainless steel, polypropylene or schedule 80 PVC is recommended. **DO NOT USE ALUMINUM FITTINGS.**

HAZARD STATEMENT

May be harmful if swallowed.
Causes mild skin irritation.
Causes eye irritation.

SIGNAL WORD

Warning

PRECAUTIONARY STATEMENTS

Keep container tightly closed. Do not eat or drink while using this product. Wash hands thoroughly after handling. Avoid strong oxidizers. Dispose of in accordance with local, regional, federal or international regulations as specified.

OTHER

May cause mild skin irritation if not rinsed off with soap and water. May cause eye irritation if not rinsed out with copious amounts of water.



FIRST AID

If swallowed, drink two glasses of water. In case of eye contact, flush with water for two minutes. If symptoms persist seek medical advice

In case of skin contact wash thoroughly with soapy water. As with all chemicals, keep out of reach of children.

For Commercial and Industrial Use Only

GUARANTEE

Masest guarantees this product to be free from defects and true to its contents when used per label directions.

PO Box 236231, Cocoa, Florida 32923 -813-406-3852- Matthew@masest.co

Net Contents:

☐ 2.5 Gallons ☐ 55 Gallons ☐ 275 Gallons

