

## VertKleen CRS Label

|                       |                              |
|-----------------------|------------------------------|
| DOCUMENT ID           | MAS-VK-CRS-LABEL             |
| DISTRIBUTION REVISION | 1.1                          |
| EFFECTIVE DATE        | 2026-09-26                   |
| SUPERSEDED STATUS     | Current                      |
| OWNER                 | MASEST Consulting LLC        |
| APPROVAL              | Released for customer review |
| APPLICABLE SKU(S)     | VK-CRS                       |

### TECHNICAL / LEGAL CLAIM REVIEW REQUIRED

**Review boundary.** This cover controls MASEST website distribution only. It does not certify technical, regulatory, legal, safety, performance, or customer-specific claims. Branding and shelf-life corrections are owner-authorized. Technical measurements, study methods, results, and source revision dates are retained.

**Approval scope:** Distribution approval only; technical and legal claim approval is not asserted.

# VertKleen CRS

**100% Synthetic, Non-Corrosive HCl Replacement**



**VertKleen CRS, Calcium, Rust and Scale remover** is a safe yet functional replacement, for traditional hazardous acids, that are used in many maintenance industries. It has the power to remove calcium, scale, rust and biological buildup, in one run, saving you time and money. **CRS** is non-fuming and non-corrosive, so no more chemical burns and no harm to stainless steel, rubber gaskets or other surfaces. It may also be used as an injection or sprayed on cleaner, for other critical systems. **CRS** biodegrades in less than 10 days and is made from 100% Cleangredients. Safe around people, animals, flora and fauna.

## DILUTION RATIO

Light Soil, Mild Odor- 10:1  
Moderate Soil and Odor- 5:1  
Severe Soil and Odor- 2:1

## USE DIRECTIONS

Apply to surface with spray or foam cannon. Let stand and work in for 10-15 minutes, then simply wash away. For heavily soiled areas let stand for 20 minutes. May also be injected at a variable rate to get a detailed cleaning.

CRS does not contain any additional iron control agents, demulsifiers, or corrosion inhibitors. No organic acid additions are required. Ratios may vary based on specific applications and recommendations from your dealer. When pumping CRS it is recommended to use hose couplings and fittings approved by your product supplier. 316 stainless steel, polypropylene or schedule 80 PVC is recommended.

## HAZARD STATEMENT

May be harmful if swallowed.  
Causes mild skin irritation.  
Causes eye irritation.

## SIGNAL WORD

Warning

## PRECAUTIONARY STATEMENTS

Keep container tightly closed. Do not eat or drink while using this product. Wash hands thoroughly after handling. Avoid strong oxidizers. Dispose of in accordance with local, regional, federal or international regulations as specified.

## OTHER

May cause mild skin irritation if not rinsed off with soap and water. May cause eye irritation if not rinsed out with copious amounts of water.



## FIRST AID

If swallowed, drink two glasses of water. In case of eye contact, flush with water for two minutes. If symptoms persist seek medical advice

In case of skin contact wash thoroughly with soapy water. As with all chemicals, keep out of reach of children.

For Commercial and Industrial Use Only

## GUARANTEE

Masest guarantees this product to be free from defects and true to its contents when used per label directions.



1361 Grand Cayman Dr, Merritt Island, FL 32952 | (813) 406-3852 | sales@masest.co

Net Contents:

☐ 2.5 Gallons ☐ 55 Gallons ☐ 275 Gallons

