Asking for the Whole Plan: Prompt Design Moves Language Models' Scores on a Clinical-Safety Benchmark More Than Model Choice

An exploratory study on the NOHARM v2 public cases

Ahmad Omar Aljamal, MD

Independent researcher

October 2026

Public development data, judged locally; no organiser-scored held-out result and no clinical validation.

Abstract

Background: NOHARM scores management plans for real primary-care-to-specialist consultations against specialist ratings of the actions each case calls for; most severe errors are omissions. Its public leaderboard runs general-purpose models on the bare case, and its authors reported that length-capped priming prompts raise generalist models' scores.

Objective: To measure how far an uncapped, structured instruction moves individual models, whether the gain reflects coverage rather than length alone, and how one prompted call compares with systems built from several calls.

Methods: On the 30 public cases (330 items), we scored twelve models on the bare case and five of them with an instruction: a consult framing with an uncapped plan format (three models) or the kit's 500-word priming prompt (two). An AI evaluator applied the benchmark's own scoring. On two models we gave the instruction's consult framing, its plan format and a bare request for 25 numbered recommendations separately, and compared perspective variants. We re-scored with precision over every stated action, rated the actions outside the rubric, re-judged key contrasts with a second model family, and compared a single prompted call with ensembles and a completion pass. Intervals come from resampling whole cases.

Results: The instruction raised severity-weighted F1 by 0.14 on average [0.09, 0.20], most for the tersest models: GPT-5.6 terra rose from 0.678 to 0.853 (+0.175 [+0.108, +0.248]) and Grok 4.7 from 0.354 to 0.633. The gain fell as a model's unprompted plan length rose (Spearman -0.90), the spread between models halved (standard deviation 0.17 to 0.09), and the gains held when every stated action counted in precision. The recovered actions were mostly follow-up and counselling (Sonnet's follow-up coverage 0.20 to 0.65). The number of stated actions accounted for 89% of the effect, and an independent model rater judged nearly all of the added actions outside the rubric appropriate; the author, an internal-medicine physician, reading every one a model rater had flagged as harmful found none inappropriate. The cost was small: instructed Sonnet proposed +0.13 [+0.05, +0.23] more specialist-rated harmful options per item, almost all mild or moderate, and the physician judged none harmful as the plans stated them. Which perspective the instruction took made no detectable difference. Taken apart on Sonnet 5.5 and terra, the plan format alone scored level with the full instruction, while a bare request for 25 recommendations drew as many actions and scored below it (−0.040 [−0.069, −0.015] and −0.084 [−0.148, −0.029]): which actions the instruction names matters, not only how many. One prompted call scored level with a four-call ensemble plus completion (+0.004 [−0.035, +0.041]).

Concatenating three prompted models scored 0.897 under the primary evaluator and 0.869 under a second family.

Conclusions: On this benchmark, how a model is asked changes what is measured: unprompted scores partly reflect how much a model writes by default. Prompted baselines should be reported beside unprompted ones before models, or models and clinical tools, are ranked.

1 Introduction

A consultation answer can be correct in everything it says and still fail the patient through what it leaves out. NOHARM measures this directly: it compares a model's management plan with specialist ratings of the actions a case calls for and those it should avoid, and weighs each error by the harm it could cause [25]. Across its versions, errors of omission make up most severe errors, and recall trails precision for nearly every model. The kit released to reproduce the public leaderboard runs models on the bare case with an empty prompt, and its documentation gives these default settings as the ones to match for the leaderboard's frontier rows.

If an answer's length and coverage depend on how a model is asked, an unprompted score measures a model's default behaviour as well as its clinical judgement. The latest NOHARM version [25] tested this in part: a priming prompt asking for completeness, capped at 200 or 500 words, raised generalist models' scores and lowered those of retrieval-based clinical tools, which stayed ahead under every condition. Two questions remain open. What does an instruction that neither caps the answer nor leaves its structure implicit do? And is its gain coverage, or only length, given that the benchmark's precision ignores actions the rubric does not list?

We ask four questions on the benchmark's public cases. How much does a structured instruction move individual models, and does the gain depend on how much a model writes unprompted? Which part of the instruction carries the gain: its perspective, its consult framing, its plan format, or a bare demand for more items? Does the gain survive checks for length: precision over every stated action, a rating of the actions outside the rubric, and a second evaluator family? And does a single prompted call match systems built from several calls? Every result is development evidence on public cases with a locally run AI evaluator. None is an organiser-scored leaderboard number, and none establishes clinical safety.

2 Related work

How a model is asked is known to move medical and general benchmark scores. Systematic prompting lifted a generalist model past fine-tuned medical systems on multiple-choice benchmarks [16]; instruction phrasing changes clinical language-processing results [3]; and meaning-preserving prompt changes reorder models on general leaderboards [15, 18, 20]. Our manipulation differs in kind: it changes what the answer is asked to contain, not how the same request is worded. NOHARM [25] is the closest antecedent, reporting omission-dominated harm and the effect of its capped priming prompts described above. An independent comparison on other instruments found general models ahead of clinical retrieval tools [22], although its benchmarks and generation settings have been disputed [2], and structured management reasoning has been built into clinical agents [14]. Language models in simulated clinical workflows skip guideline-required steps [8].

Two threats apply to any rubric-graded gain from longer answers. AI evaluators favour longer and self-generated text [4, 17, 19, 24, 26], although a length-matched check on HealthBench found the effect partial [1]. And evaluators detect what is absent poorly [5], as models do [6]. Multi-model aggregation [23], its single-model counterpart [13] and directed completion [9] are other routes to

recall; self-revision without an outside signal is unreliable [10], and model errors are correlated [12]. Diverse evaluator panels reduce single-evaluator bias [21].

3 Methods

3.1 Benchmark and scope

NOHARM's cases are derived from real primary-care-to-specialist electronic consultations at a single academic medical centre, and the public subset is released under CC BY 4.0 [25]. The public subset has 30 base cases, three from each of ten specialties, each in its original form and ten modified versions that change one detail (age, sex, a comorbidity, a medication, a laboratory value and others), giving 330 items; versions of a case are related observations, not independent cases. Each case carries a rubric of candidate management actions rated by specialists on a 1–9 appropriateness scale: 1,128 options in all, of which 522 are rated harmful (1–3; 79 at 1), 408 equivocal and 198 appropriate (7–9; 23 at 9). By category the options are diagnostic (424), medication (374), counselling (174), procedure (94) and follow-up (55). We ran the NOHARM v2 kit unmodified except for the evaluator model (Appendix B). The organisers' held-out cases were not used, and no patient-level data were.

3.2 Models

Twelve models answered the bare case: Claude Sonnet 5.5, Sonnet 5, Opus 5.5 and Haiku 4.5; GPT-5.6 terra and Luna, GPT-6 Astra and GPT-6.1 Sol; Grok 4.7; and three freely available models (Muse Spark 1.3, Nemotron 3 Ultra and Big Pickle). Five of them also answered with an instruction (Section 3.3). All calls went through one local gateway to the providers' accounts. Free models may retain inputs, so they saw public cases only.

3.3 Instructions

The *bare* condition sends only the case text, as the leaderboard does. Every other condition wraps the case in an instruction assembled from a few parts (Table 1; full text in Appendix A). The *consult framing* tells the model that a primary-care colleague has asked a specialist for the best recommendations, not only an answer to the literal question. The *plan format* asks for a one- or two-sentence assessment followed by numbered, specific recommendations: tests, drugs with doses and durations, referral specialty and urgency, conditional next steps, counselling and return precautions, with nothing omitted that a careful specialist would want and nothing unsafe. Neither part sets a length. The *specialist* instruction is the two together.

The variants change one part at a time. Two *perspectives* replace the consult framing with a clinical pharmacist or the patient's primary-care physician and keep the plan format; the *exhaustive* variant adds a list of plan headings to address; the *candidate menu* asks for every action a specialist panel should consider instead of a plan. Three *component* instructions separate the specialist instruction's parts: the consult framing alone, the plan format alone, and, as a control for length, a request for at least 25 numbered recommendations that names no clinical content. Twenty-five is about as many actions as the specialist instruction drew (a median of 21 for terra and 27 for Sonnet 5.5). Finally, the kit's own *thorough* priming prompt adds a consult framing, criteria of completeness, safety and restraint, and a 500-word cap.

The instructions were written from the benchmark's published description of what a consultation answer should cover and from its finding that omissions dominate. None names a rubric option or

was tuned to a case, but all were written and tried on these same public cases. Every completed arm is reported. Arms started and stopped before completion (the specialist instruction on further models, the kit's prompt on Sonnet 5.5, a capped specialist instruction and repeated generations) are not analysed.

Table 1: Instructions and the models that received them. Each instruction contains the case text; only the kit's prompt sets a length limit.

Instruction	Framing	Answer asked to contain	Models
Bare	none	nothing stated	all twelve
Specialist	consult	plan format	Sonnet 5.5, terra
Pharmacist; primary care	other clinician	plan format	Sonnet 5.5
Exhaustive	consult	plan format, eight named headings	Astra
Candidate menu	specialist panel	30–50 candidate actions, none chosen	terra
Framing only	consult	nothing stated	Sonnet 5.5, terra
Format only	none	plan format	Sonnet 5.5, terra
Length only	none	at least 25 numbered recommendations	Sonnet 5.5, terra
Kit thorough	consult	assessment, recommendations and criteria, under 500 words	Grok 4.7, Muse Spark

3.4 Systems of several calls

An *ensemble* concatenates existing plans into one response, unedited. A *completion* pass gives a model the case and the plans and asks only for clearly indicated actions none of them states. A *writer* merges plans into one and re-inserts source actions an automated check finds missing.

3.5 Evaluation

The kit's evaluator extracts the actions a plan states, matches each to the specialists' rubric options, and reviews the matches. Claude Sonnet 5.5 was the primary evaluator; on the kit's one worked example it agreed with the organisers' evaluator on 323/330 option verdicts. Selected arms were re-scored by GPT-5.6 terra and, for terra's within-model prompting contrast, by Nemotron 3 Ultra, a freely available model that wrote none of the plans it re-scored. It was chosen over a second free candidate by a rule fixed before either was tested: more option verdicts agreeing with the organisers' evaluator on the worked example (327/330, against 326/330 for Ling 3.1 Flash and 325/330 for GPT-5.6 terra). Re-scoring never changes a plan: the snapshot verifies that every re-scored response is byte-identical to its source.

3.6 Outcomes

The primary outcome is the kit's severity-weighted F1. Precision is the severity-weighted appropriateness of the stated actions that match a rubric option; recall is the severity-weighted share of appropriate options the plan covers. We also report the share of items with at least one potentially severe error identified by the evaluator, a benchmark judgement and not a measured adverse-event rate.

Headline precision cannot see an action that matches no rubric option: the kit gives every such action a neutral default, so it is never counted as harmful. Because a longer plan states more of

these, we report four checks: F1 recomputed with the kit's own precision over *all* stated actions; the share of actions that match no option; the worst of a case's eleven versions; and plan length. For four bare-versus-instructed pairs (Sonnet 5.5 with the primary-care perspective, terra with the specialist instruction, Astra with the exhaustive variant and Grok with the kit's prompt), raters from families other than the primary evaluator rated every off-rubric action on the specialists' 1–9 appropriateness scale, given the item's case text and no rubric, on a fixed sample of each case's original and two of its versions (90 items per arm). Nemotron 3 Ultra rated all four pairs; Ling 3.1 Flash rated the Sonnet pair as a second rater. In an earlier analysis of these cases, a model rater of this kind flagged 0.90 of the options specialists rated harmful, and 0.69 of its flags were options specialists rated harmful; these ratings therefore screen for physician review and are not a harm rate.

The author, an internal-medicine physician, then read what the screens produced, on a review page built from the clinician packet. Part A showed one at a time, each with its case text and blinded to model, instruction and rater flag, every off-rubric action on the audit sample that either rater scored 1–3 (72), mixed with 24 randomly drawn unflagged ones. Part B showed each option the specialists rated harmful (1–3) that an instruction added to a model's plan (43 options in 18 cases, stated in 227 plan statements) with the panel's rating, and asked whether the option is harmful for this patient as the plans stated it. Part C showed the 9 instructions verbatim. The reviewer gave an overall verdict covering every item, not item-level scores.

3.7 Statistics

Item scores were averaged within each base case and the 30 case means averaged equally. Every comparison is paired by case. Intervals are percentile 95% intervals from 10,000 resamples of whole cases (seed 7), conditional on the stored responses and evaluations. Across models we report the Spearman correlation between the prompting gain and a model's mean number of stated actions unprompted, the standard deviation and range of scores across models in each condition, and Kendall's τ between the two rankings, each with an interval from the same case resampling. Across all single-call configurations we report the Spearman correlation between mean stated actions and F1. The study is exploratory: instructions and systems were developed on these cases, nothing was preregistered, and intervals are not adjusted for multiple comparisons.

4 Results

4.1 The instruction raised every terse model

Table 2 gives the twelve bare models and the five prompted arms. Unprompted scores spanned 0.354 to 0.764, and the number of actions a model stated ranged from 3.5 to 17 per plan. The uncapped instruction raised Sonnet 5.5 by +0.071 [+0.036, +0.110], terra by +0.175 [+0.108, +0.248] and Astra by +0.189 [+0.120, +0.264]; the kit's capped prompt raised Grok by +0.279 [+0.169, +0.382] and left Muse Spark unchanged (+0.003 [−0.047, +0.053]). Across the five, the gain fell as unprompted length rose (Spearman -0.90 [−1.00, −0.80]): models that already wrote long plans had least to gain. Muse Spark is the exception that the design cannot explain away. It wrote as much as Sonnet unprompted but received the capped prompt; whether the cap or the model accounts for its null is untested here.

Every prompted arm raised recall more than precision. Sonnet's recall rose from 0.732 to 0.861 with precision 0.836 and 0.841; terra's from 0.623 to 0.847 with precision 0.841 and 0.885. The

share of items with a potentially severe error fell with each uncapped instruction (Sonnet 0.206 to 0.155; terra 0.245 to 0.139).

Table 2: Bare case and instructed arms, primary evaluator. F1 is severity-weighted; actions are the median number the evaluator extracted per response; differences are paired by case with 95% intervals. Models without an instructed arm were scored bare only.

Model	Bare F1	Actions	Instruction	F1	Actions	Difference [95% CI]
Claude Sonnet 5.5	0.764	16	specialist	0.835	27	+0.071 [+0.036, +0.110]
GPT-5.6 terra	0.678	9	specialist	0.853	21	+0.175 [+0.108, +0.248]
GPT-6 Astra	0.629	9.5	exhaustive	0.818	26	+0.189 [+0.120, +0.264]
Grok 4.7	0.354	3.5	kit, 500 words	0.633	9	+0.279 [+0.169, +0.382]
Muse Spark 1.3	0.756	17	kit, 500 words	0.759	16	+0.003 [−0.047, +0.053]
Claude Opus 5.5	0.752	15				
Claude Sonnet 5	0.599	8				
Claude Haiku 4.5	0.471	8				
GPT-5.6 Luna	0.671	10				
GPT-6.1 Sol	0.627	9				
Nemotron 3 Ultra	0.670	14				
Big Pickle	0.690	16				

4.2 The field narrowed and its order changed

Instructing the five models halved the spread between them: the standard deviation of their scores fell from 0.17 to 0.09 (a reduction of 0.08 [0.03, 0.12]) and the range from 0.41 to 0.22. Among the three given the uncapped instruction, the range fell from 0.13 to 0.03. The order changed: unprompted, Sonnet 5.5 led terra by 0.764 to 0.678; instructed, terra scored 0.853 against Sonnet's 0.835, and Astra passed Muse Spark. The rank correlation between the two conditions was Kendall's $\tau = 0.40$ [0.00, 0.60].

Length explains much of the ranking in both conditions. Across the 26 single-call configurations, bare and instructed, the number of actions a plan stated tracked its F1 (Spearman 0.89 [0.80, 0.92]). This does not show that length causes the score: an instructed model states more actions and, judging by recall, more of the indicated ones.

4.3 Which part of the instruction carries the gain

Perspective. Three instructions on Sonnet 5.5 shared the plan format and differed in perspective: a specialist answering a colleague (0.835), a clinical pharmacist (0.835) and the patient's primary-care physician (0.846). Each beat the bare case by a similar margin (+0.071 [+0.036, +0.110], +0.071 [+0.028, +0.115] and +0.082 [+0.039, +0.125]), and the primary-care perspective was indistinguishable from the plain specialist framing (+0.010 [−0.010, +0.031]). Asking terra for a candidate menu instead of a plan scored 0.807, below its plan (+0.130 [+0.055, +0.204] over bare against +0.175 [+0.108, +0.248]), at nearly twice the length.

Framing, format and length. Given separately (Table 3), the consult framing alone changed Sonnet 5.5's score by +0.031 [+0.011, +0.052] and terra's by +0.077 [+0.032, +0.127]; the plan format alone by +0.076 [+0.041, +0.115] and +0.169 [+0.104, +0.241]; and the request for 25 numbered recommendations, which names no clinical content, by +0.031 [+0.004, +0.058] and +0.091 [+0.052, +0.135]. Against the full specialist instruction, the plan format alone scored

+0.005 [−0.007, +0.017] for Sonnet 5.5 and −0.006 [−0.018, +0.005] for terra, and the length request −0.040 [−0.069, −0.015] and −0.084 [−0.148, −0.029].

The plan format carries the gain. Without the consult framing it scored level with the full instruction for both models, and the framing without the format fell well short of it (−0.040 [−0.071, −0.011] and −0.098 [−0.147, −0.057]). The length request is the informative contrast. It drew as many actions as the plan format (median 29 against 28 for Sonnet 5.5, 24 against 22 for terra) but recovered fewer of the indicated ones (recall 0.807 against 0.867, and 0.741 against 0.844), and once every stated action counted in precision Sonnet's gain under it was +0.002 [−0.026, +0.029]. Stating more is not enough: what the format names (exact tests, doses and durations, referral urgency, conditional steps, counselling, return precautions) steers which actions are added. These are two models and one wording of each part, so they locate the gain in the format without showing which of its clauses matters.

Table 3: The specialist instruction taken apart, primary evaluator. F1 (all) folds every stated action into precision; actions and characters are medians per response; differences are paired by case with 95% intervals.

Model	Instruction	F1	F1 (all)	Actions	Characters	vs bare	vs specialist
Sonnet 5.5	bare	0.764	0.725	16	3,202		
	framing only	0.795	0.749	19	3,988	+0.031 [+0.011, +0.052]	−0.040 [−0.071, −0.011]
	format only	0.840	0.774	28	6,464	+0.076 [+0.041, +0.115]	+0.005 [−0.007, +0.017]
	length only	0.795	0.727	29	7,407	+0.031 [+0.004, +0.058]	−0.040 [−0.069, −0.015]
	specialist	0.835	0.774	27	5,978	+0.071 [+0.036, +0.110]	
GPT-5.6 terra	bare	0.678	0.657	9	2,206		
	framing only	0.755	0.721	12	3,703	+0.077 [+0.032, +0.127]	−0.098 [−0.147, −0.057]
	format only	0.847	0.790	22	7,038	+0.169 [+0.104, +0.241]	−0.006 [−0.018, +0.005]
	length only	0.769	0.706	24	6,628	+0.091 [+0.052, +0.135]	−0.084 [−0.148, −0.029]
	specialist	0.853	0.797	21	6,807	+0.175 [+0.108, +0.248]	

4.4 What the instruction recovers, and what it costs

The recovered actions are the ones models leave out unprompted (Table 4, Figure 1). Follow-up was the largest gap: Sonnet covered 0.20 of the appropriate follow-up options bare and 0.65 instructed (+0.44 [+0.27, +0.63]), terra 0.43 and 0.90 (+0.48 [+0.25, +0.69]). Counselling followed (Sonnet +0.25 [+0.14, +0.37]; terra +0.21 [+0.10, +0.34]). These are the categories NOHARM describes as left out by models and physicians alike [25]. Coverage of the specialists' score-9 actions, those whose omission they rated most harmful, rose for the three terse models (terra +0.15 [+0.02, +0.31], Astra +0.20 [+0.07, +0.39], Grok +0.29 [+0.09, +0.48]) and not for Sonnet, which already covered 0.83 of them bare (+0.03 [−0.03, +0.11]).

The cost is measurable against the specialists' own ratings. Per item, instructed Sonnet proposed 0.42 options the specialists rated harmful against 0.29 bare (+0.13 [+0.05, +0.23]), nearly all of them rated mildly or moderately harmful (score 2–3; severe +0.01 [−0.00, +0.04]). For terra (+0.00 [−0.07, +0.08]), Astra (+0.04 [−0.02, +0.11]) and Grok (+0.07 [−0.09, +0.27]) the change was not distinguishable from zero. These are the specialists' ratings of each option for the case in general; read in the plans' own wording, a physician judged none of them harmful (physician review, Section 4.5). A clinician-readable list of every harmful option an instruction added, with the plan's wording, is part of the review packet (Data section).

Muse Spark, the one model the instruction did not help, gained in no category under the kit's capped prompt: overall coverage changed by −0.01 [−0.06, +0.03] and score-9 coverage by

−0.07 [−0.17, +0.04]. The cap halved its plans, from a median of 5,179 to 2,636 characters, while the same cap doubled Grok's terse plans from 734 to 1,396. A 500-word cap pulls answers toward its length from both sides, and the score followed length. This is an observation on two models, not a test of the cap.

Table 4: Share of the specialists' appropriate options (rated 7–9) covered, bare → instructed, by the rubric's category, primary evaluator; and options the specialists rated harmful (1–3) that the plans proposed, per item. Procedure (4 appropriate options) is counted in "all"; contingency (one option) is not reported.

	Sonnet 5.5	terra	Astra	Grok 4.7	Muse Spark
Diagnostic	0.75→0.86	0.51→0.75	0.43→0.67	0.24→0.50	0.68→0.63
Medication	0.67→0.80	0.49→0.77	0.52→0.74	0.28→0.51	0.63→0.58
Counselling	0.58→0.83	0.59→0.79	0.56→0.83	0.30→0.63	0.74→0.79
Follow-up	0.20→0.65	0.43→0.90	0.42→0.89	0.03→0.27	0.65→0.74
All appropriate	0.66→0.82	0.52→0.78	0.47→0.74	0.24→0.51	0.68→0.67
Score 9 (essential)	0.83→0.87	0.72→0.86	0.57→0.77	0.39→0.68	0.75→0.69
Harmful options proposed per item	0.29→0.42	0.11→0.12	0.10→0.14	0.24→0.31	0.25→0.24
of which severe (score 1)	0.05→0.06	0.04→0.02	0.00→0.00	0.06→0.12	0.08→0.11




Figure 1: Share of appropriate options covered by category, bare case and with the instruction.

4.5 Is the gain coverage or length?

The number of stated actions accounts for most of the effect. In a regression of item F1 on the instruction with model and case fixed effects (3,300 item scores, five models), the instruction's effect was +0.144 [+0.090, +0.200]. Adding the logarithm of the number of stated actions left +0.016 [−0.023, +0.058]: at an equal number of stated actions, instructed and bare plans scored alike, and length accounted for 89% [66, 120] of the effect. Among the 137 item pairs whose bare and instructed plans stated within 10% as many actions, the instructed plan scored +0.022 higher on average. The instruction works largely by making models state more actions (Figure 2). The length-only instruction (Section 4.3) asks the same question by design rather than by adjustment, and qualifies the answer: at as many actions as the plan format, it scored −0.040 [−0.069, −0.015]

for Sonnet 5.5 and −0.084 [−0.148, −0.029] for terra against the full instruction. The count carries the effect but does not produce it alone. Whether the added actions are worth stating is the question the next checks address.




Figure 2: Mean actions stated per plan against severity-weighted F1. Orange: the twelve models on the bare case; blue: the five instructed arms, each joined to its bare case by an arrow.

Precision over every action. The kit's headline precision ignores off-rubric actions, which made up 53% of Sonnet's bare plan and 60% of its instructed one (Table 5). Recomputed with the kit's own precision over every stated action, where an unlisted action counts as equivocal, each gain shrank but held: Sonnet +0.049 [+0.014, +0.086], terra +0.140 [+0.071, +0.214], Astra +0.142 [+0.070, +0.218] and Grok +0.265 [+0.156, +0.369]. The kit's strictest variant, which counts every unlisted action as inappropriate and weighs every option equally, reverses the gain for three models (Sonnet −0.056 [−0.078, −0.035], terra −0.064 [−0.110, −0.016], Astra −0.073 [−0.117, −0.029]; Grok +0.118 [+0.039, +0.192]); its binary variant keeps it (Sonnet +0.026 [−0.000, +0.052], terra +0.104 [+0.042, +0.172]). Which reading is right depends on whether the unlisted actions are appropriate, which the rubric cannot say.

Actions outside the rubric. Nemotron 3 Ultra rated every unlisted action on the 90-item sample for all four audited pairs. The instruction added unlisted actions for every model (per item, Sonnet 8.69 to 17.67, terra 5.09 to 13.19, Astra 5.74 to 17.52, Grok 2.30 to 4.63), but not unlisted actions rated harmful, whose number changed by −0.01 [−0.10, +0.10], −0.03 [−0.09, +0.01], +0.01 [+0.00, +0.03] and +0.00 [−0.09, +0.09] per item. The rater put 92–99% of the unlisted actions in every arm at 7–9. With each unlisted action given the rater's score instead of the kit's neutral default, the instruction's gain on the sample was +0.117 [+0.079, +0.160] for Sonnet, +0.193 [+0.115, +0.274] for terra, +0.200 [+0.128, +0.281] for Astra and +0.304 [+0.196, +0.411] for Grok, so by this rater's reading the strictest variant above is the wrong one.

A second rater, Ling 3.1 Flash, rated the Sonnet pair. The two put 0.89 of 2,372 paired ratings in the same band (inappropriate, equivocal or appropriate; Cohen's κ 0.33). They differed on harm: Ling rated more of the instructed plans' unlisted actions harmful (+0.16 [+0.04, +0.28] per item),

and counting an action as harmful only when both raters did, the change was +0.01 [−0.03, +0.06]. Re-scored with Ling's ratings, Sonnet's gain was +0.116 [+0.078, +0.160]. The two model raters do not agree closely with each other, which the physician review below checks.

Physician review. The physician judged all 96 actions in Part A appropriate, including all 72 that a model rater had scored harmful (31 from bare plans and 41 from instructed ones; Nemotron flagged 43 and Ling 34). On this sample every harm flag the model raters raised was unfounded, so Ling's increase for Sonnet does not reflect harm the physician recognised. The physician judged none of the 43 options the specialists had rated harmful to be harmful as the instructed plans stated them, and raised no concern with any instruction. This is one reviewer, the study's author, giving an overall verdict, blinded in Part A only: a check on the model raters, not an independent clinical validation.

Uncertainty, multiplicity and power. Each of the four positive within-model gains had a bootstrap p below 0.001 and stayed so after Holm adjustment across the five primary contrasts (adjusted p for Sonnet <0.001, terra <0.001); Muse Spark's was 0.904. With 30 cases, the smallest difference each contrast could detect with 80% power was 0.053 for Sonnet and 0.102 for terra.

Evaluator consistency. Matching the same 140 instructed terra plans twice, the primary evaluator agreed with itself on 0.982 of option verdicts (Cohen's κ 0.95); GPT-5.6 terra agreed with it on 0.960 (κ 0.88) over all 330 items.

Where the gain falls. The gain was largest where models did worst unprompted: across the five models, the third of cases with the lowest bare scores (mean 0.45) gained +0.228, the middle third +0.178 and the top third (mean 0.83) +0.025, consistent with a ceiling. By specialty the mean gain ranged from −0.072 (GI) to +0.394 (Heme), three cases each; by the kind of change a case version applies (age, sex, medication, comorbidity and others) it ranged only from +0.086 to +0.180, so the gain does not depend on which detail of the case was perturbed. That includes the versions that change only the patient's age (+0.141, 41 items) or sex (+0.136, 23 items), against +0.155 on the original cases, a limited check that the instruction helps regardless of these patient characteristics.

A second evaluator. Re-scored by Nemotron 3 Ultra, terra's gain from the instruction was +0.187 [+0.119, +0.259], and the difference between the two evaluators' estimates −0.012 [−0.040, +0.015]; the same re-scoring of Sonnet's pair was stopped before completion and is not reported. Under GPT-5.6 terra as evaluator, instructed terra scored 0.844 and bare Sonnet 0.734.

Table 5: What the headline metric does not see. F1 (all) folds every stated action into precision; off-rubric is the share of stated actions matching no rubric option, which the kit never scores as harmful; worst is the mean over cases of the lowest of a case's eleven versions.

Configuration	F1	F1 (all)	Off-rubric (%)	Worst version	Median characters
Sonnet 5.5, bare	0.764	0.725	53	0.603	3,202
Sonnet 5.5, specialist	0.835	0.774	60	0.722	5,978
terra, bare	0.678	0.657	50	0.513	2,206
terra, specialist	0.853	0.797	62	0.757	6,807
terra, candidate menu	0.807	0.710	72	0.660	8,872
Astra, bare	0.629	0.605	58	0.514	2,409
Astra, exhaustive	0.818	0.747	68	0.704	8,474
Grok 4.7, bare	0.354	0.347	49	0.164	734
Grok 4.7, kit 500 words	0.633	0.612	50	0.418	1,396

4.6 One instructed call against systems of several calls

Instructed terra (one call) scored level with an ensemble of three bare plans plus a completion pass (four calls): +0.004 [−0.035, +0.041] (Table 6). The completion pass had added +0.038 [+0.009, +0.070] to that ensemble, so the single instruction recovers what both the second and third models and the completion pass recovered. Concatenating the three best instructed plans (Sonnet primary-care, terra specialist, Astra exhaustive) scored 0.897, above instructed terra by +0.044 [+0.016, +0.072]. Part of that margin is repetition: with actions matched to the same rubric options counted once, it was +0.035 [+0.005, +0.065], and under GPT-5.6 terra as evaluator +0.020 [−0.012, +0.052], an interval that includes zero. Merging the concatenation into one readable plan did not work: a writer with automated re-insertion lost source actions on the earlier, unprompted ensemble (Appendix C), and on one trial item of the instructed ensemble it listed 194 source actions and lost more of them with each repair round.

Table 6: Single instructed calls and systems of several calls (primary evaluator unless stated). Grouped F1 counts actions matched to the same set of rubric options once.

Configuration	Calls	F1 [95% CI]	Grouped F1 [95% CI]
Sonnet 5.5, bare	1	0.764 [0.707, 0.817]	0.764 [0.707, 0.817]
terra, specialist	1	0.853 [0.804, 0.899]	0.851 [0.801, 0.897]
Ensemble of bare Sonnet, terra, Luna	3	0.811 [0.753, 0.864]	0.806 [0.748, 0.860]
+ completion pass (Sonnet)	4	0.849 [0.791, 0.900]	0.844 [0.786, 0.895]
Ensemble of instructed Sonnet, terra, Astra	3	0.897 [0.851, 0.936]	0.886 [0.835, 0.929]
same plans, GPT-5.6 terra as evaluator	3	0.869 [0.815, 0.915]	0.862 [0.808, 0.908]

4.7 Where these scores sit

The benchmark publishes public-case reference scores, under its own evaluator, of 0.720 for GPT-5.5, 0.674 for Claude Opus 4.7 and 0.664 for Gemini 3.1 Pro. The public leaderboard, scored by the organisers on held-out cases, is led by LiSA 2.5 at 86.2, followed by Doximity Ask 6.1 (84.5) and OpenEvidence (80.0); bare frontier models sit between about 56 and 75. Our scores are on the public cases with a different evaluator, so none of them is a leaderboard number. NOHARM reports that public and held-out scores correlate closely across models (Pearson 0.95) [25], which supports comparing ranks, not absolute values. Two cautions apply to absolute values here. Our second evaluator scored the instructed ensemble about 0.03 lower than the primary one, and the primary evaluator favoured an Anthropic-written plan set by +0.037 [+0.014, +0.060] relative to another model's in a paired test. And the public cases were released in June 2026, so models scored afterwards may have seen them; contamination would inflate absolute scores but not a within-model comparison of the same cases.

5 Discussion

On these cases an instruction did more for a model's score than the choice among the models we tried. A plan format with a consult framing lifted terse models by as much as +0.279 [+0.169, +0.382], narrowed the field, and reordered it. The instruction's perspective and consult framing mattered little; its plan format alone reproduced the gain, by changing how much the model stated and what. That is consistent with omission dominating NOHARM's errors: a

model that says more of what a careful specialist would do omits less, and the metric rewards exactly that.

This extends the benchmark's own finding that priming helps generalist models [25]. Its priming prompts capped the answer; ours did not, and the two capped arms here behaved differently from the uncapped ones (a large gain for the tersest model, none for one that already wrote long plans). The cap may be part of why priming left generalists behind clinical tools in the benchmark's report, but our data cannot separate the cap from the model.

Length is part of the mechanism, not an alternative to it. At an equal number of stated actions an instructed plan scored no better than a bare one, so the instruction works largely by making models say more. A count alone does not do it, though: asked only for 25 recommendations, both models stated as many actions as under the plan format and scored below it, and Sonnet kept none of that gain once every stated action counted in precision. The format's named contents steer which actions are added. The question is then whether what they add is worth saying, and four checks say mostly yes. The added actions that match the rubric are concentrated in follow-up and counselling, which the specialists rated appropriate; counting every unlisted action in precision shrank the gains without removing them; an independent rater put nearly all unlisted actions at 7–9 and found no more harmful ones among them for any model, although a second rater found a small increase for Sonnet; and the worst version of each case improved along with the average. Against that, instructed Sonnet proposed more options the specialists rated harmful, mostly mild or moderate, and the kit's strictest metric, which counts every unlisted action as wrong, reverses the gain for three models. Under an evaluator from a third model family, Nemotron 3 Ultra, terra's gain was $+0.187\,[+0.119, +0.259]$, within $-0.012\,[-0.040, +0.015]$ of the primary estimate. The author, a physician, then read every unlisted action a model rater had flagged and every harmful option an instruction added, and judged none harmful as stated. One reviewer's overall verdict, blinded only for the unlisted actions, is not a panel's item-level ratings, and AI evaluators are known to favour longer text [4, 19, 26]. The safest reading is that the instruction makes models state more of the indicated actions, along with a few options the benchmark's specialists rated harmful in general that one physician did not find harmful in context, and that under the benchmark's severity weighting the first outweighs the second.

Two practical consequences follow. For benchmark design, an unprompted protocol ranks a model partly on its default verbosity; reporting prompted and unprompted results, as NOHARM's own study does, makes that visible, and so does reporting how much a model's score depends on actions the rubric cannot see. For system design, a single instructed call matched a four-call ensemble with completion at a quarter of the calls, taking a median of 58 seconds per case (90th percentile 110) against the benchmark's 300-second limit; combining instructed models added a little more, with an uncertain margin under a second evaluator. Neither result says anything about clinical usefulness: a plan of twenty to thirty items needs ordering by priority before a clinician can use it.

The intended use the benchmark represents is advice to a primary-care clinician who has asked a specialist about one patient: the input is the clinician's question with the case details, the output a management plan that the clinician reads, judges and acts on. Nothing here evaluates a plan acting without that clinician, and the instruction is only as safe as the reader of a longer plan is attentive.

Four next steps would turn these observations into tests. Scoring instructed and bare models on the held-out cases would show whether the gain survives the organisers' evaluator on unseen cases; the public leaderboard admits distinct models rather than prompts, so this needs the organisers' own runs or a research arrangement with them. A blinded panel rating the added actions item by item, as the benchmark's specialists rated its rubric, would turn this study's single-reviewer

check into a measurement. Giving one instruction to every model, testing the length cap within a model and measuring regeneration noise would remove the remaining confounds in this design. And reporting prompted beside unprompted scores on other clinical benchmarks would show whether the gap between general models and clinical tools is a property of the models or of how they are asked.

6 Limitations

Small development set. The study has 30 base cases, not 330 independent consultations, and instructions and systems were developed on these same cases; although none names a rubric option, estimates may be optimistic.

An incomplete design. Five of twelve models were instructed, with different instructions, and cross-model statistics rest on those five. The instruction's parts were separated on two models only. The capped and uncapped instructions went to different models, so the cap's own effect is untested. Regeneration noise was not measured; evaluator noise was, on one arm. Several planned arms were stopped before completion and are not analysed.

Automated evaluation. Every score comes from an AI evaluator, not the organisers' and not physicians. A second family re-scored the key contrasts. The author, an internal-medicine physician, reviewed the off-rubric actions the model raters flagged, the harmful options the instruction added and the instructions, giving an overall verdict rather than item-level scores, blinded only for the off-rubric actions. No physician reviewed whole plans or evaluator disagreements, and no independent panel was used.

What the metric cannot see. Headline precision ignores actions the rubric does not list, and the kit never counts them as harmful; our checks bound this but do not replace clinical review. Longer plans may also be harder to use; usability was not measured.

Contamination and drift. The public cases have been available since June 2026. Provider routes and model versions change, and free models may retain inputs.

7 Conclusion

A structured, uncapped instruction raised NOHARM scores for every terse model we tested, narrowed the gap between models, and matched a multi-model system with one call, through stating more of the indicated actions. Benchmarks of clinical completeness should report prompted beside unprompted results, and comparisons between models, or between models and clinical tools, should be made under both before conclusions are drawn.

Data, code, and declarations

Reproducibility. The offline analysis is `scripts/noharm_paper_snapshot.py`; it hashes every source file, refuses an incomplete arm, and writes every number in this manuscript to `docs/paper/coverage-numbers.tex`. Instructions are in `scripts/noharm_system.py`; the off-rubric audit is `scripts/noharm_offrubric_audit.py`. Every model response, evaluation, rating, the physician review materials and the code are archived at `https://github.com/OJamals/noharm-prompting` (code MIT, data CC BY 4.0); the generators reproduce every number in this manuscript from that archive without model calls. An interactive summary of the results, built from the same numbers, is at `https://noharm.aljamal.work`.

Ethics and data use. The study reused public benchmark data and involved no patient intervention. The NOHARM v2 public cases are released under CC BY 4.0 and contain no identifiable patient information, and the only person involved was the author, as physician reviewer; the study uses only openly available data, is not human-subjects research, and was not submitted for ethics review. All materials produced here are released openly, without access restrictions.

Protocol, registration and involvement. No protocol was prepared and the study was not registered; it is an exploratory analysis of development data (Section 3.7). No patients or members of the public were involved in its design, conduct or reporting.

Reporting. The TRIPOD-LLM checklist [7] for this study is in Appendix D.

Author contributions. Ahmad Omar Aljamal designed the study, directed the experiments and analysis, performed the physician review, and is responsible for the manuscript.

Funding. This work received no funding. Neither the author nor any institution received payment or services from a third party for any aspect of it.

Competing interests. The author declares no competing interests, and has received no payments or services from a third party in the past 36 months that could be perceived to influence, or give the appearance of influencing, this work.

AI assistance. Experiments, analysis and drafting were assisted by Claude Code and Codex; earlier drafting used the Scientific Agent Skills workflow [11]. AI systems are not authors. The author reviewed the manuscript, references and declarations and takes responsibility for them.

References

[1] Rahul K. Arora, Jason Wei, Rebecca Soskin Hicks, Preston Bowman, Joaquin Quinonero-Candela, Foivos Tsimpourlas, Michael Sharman, Meghan Shah, Andrea Vallone, Alex Beutel, Johannes Heidecke, and Karan Singhal. HealthBench: Evaluating large language models towards improved human health, 2025. URL https://arxiv.org/abs/2505.08775.

[2] Brett Beaulieu-Jones and Shamim Nemati. Limited benchmarks constrain the conclusions of a general-purpose versus clinical AI comparison. *Nature Medicine*, 2026. doi: 10.1038/s41591-026-04638-6. URL https://doi.org/10.1038/s41591-026-04638-6.

[3] Alberto Mario Ceballos-Arroyo, Monica Munnangi, Jiuding Sun, Karen Zhang, Jered McInerney, Byron C. Wallace, and Silvio Amir. Open (clinical) LLMs are sensitive to instruction phrasings. In *Proceedings of the 23rd Workshop on Biomedical Natural Language Processing (BioNLP)*, pages 50–71, Bangkok, Thailand, 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.bionlp-1.5. URL https://aclanthology.org/2024.bionlp-1.5/.

[4] Yann Dubois, Percy Liang, and Tatsunori B. Hashimoto. Length-controlled AlpacaEval: A simple debiasing of automatic evaluators. In *Conference on Language Modeling (COLM)*, 2024. URL https://openreview.net/forum?id=CybBmzWBX0.

[5] Sebastian Fox, Luke Markham, Ryan Lail, and Michael Karotsieris. LLM judges verify presence, not absence: Omission blindness in AI clinical notes and what recovers it, 2026. URL https://arxiv.org/abs/2608.31016.

[6] Harvey Yiyun Fu, Aryan Shrivastava, Jared Moore, Peter West, Chenhao Tan, and Ari Holtzman. Absence Bench: Language models can't see what's missing. In *Advances in Neural Information Processing Systems 38 (NeurIPS 2025), Datasets and Benchmarks Track*, volume 38, 2025. doi: 10.52202/085713-1277. URL https://proceedings.neurips.cc/paper_files/paper/2025/hash/36b31e1bb8ecd4f4081686448e9eff2d-Abstract-Datasets_and_Benchmarks_Track.html.

[7] Jack Gallifant, Majid Afshar, Saleem Ameen, Yindalon Aphinyanaphongs, Shan Chen, Giovanni Cacciamani, Dina Demner-Fushman, Dmitriy Dligach, Roxana Daneshjou, Chrystinne Fernandes, Lasse Hyldig Hansen, Adam Landman, et al. The TRIPOD-LLM reporting guideline for studies using

large language models. *Nature Medicine*, 31(1):60–69, 2025. doi: 10.1038/s41591-024-03425-5. URL https://www.nature.com/articles/s41591-024-03425-5.

[8] Paul Hager, Friederike Jungmann, Robbie Holland, Kunal Bhagat, Inga Hubrecht, et al. Evaluation and mitigation of the limitations of large language models in clinical decision-making. *Nature Medicine*, 30(9):2613–2622, 2024. doi: 10.1038/s41591-024-03097-1. URL https://www.nature.com/articles/s41591-024-03097-1.

[9] Jakir Hossain, Yi-Fei Zhao, Hongjian Wang, Minmei Shih, Katie Leigh Mullen, Ahmad P. Tafti, Leming Zhou, Manoj Purohit, William Hogan, Jay Zeng, Elizabeth Skidmore, and Yanshan Wang. Knowledge graph-augmented ambient AI for clinical note generation, 2026. URL https://arxiv.org/abs/2609.22239.

[10] Jie Huang, Xinyun Chen, Swaroop Mishra, Huaixiu Steven Zheng, Adams Wei Yu, Xinying Song, and Denny Zhou. Large language models cannot self-correct reasoning yet. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://proceedings.iclr.cc/paper_files/paper/2024/hash/8b4add8b0aa8749d80a34ca5d941c355-Abstract-Conference.html.

[11] Timothy Kassis, Vinayak Agarwal, Yuhuan He, Darshil Patel, and Aubrey M. Brueckner. Scientific agent skills: A library of procedural knowledge for research agents, 2026. URL https://arxiv.org/abs/2609.00065.

[12] Elliot Myunghoon Kim, Avi Garg, Kenny Peng, and Nikhil Garg. Correlated errors in large language models. In *Proceedings of the 42nd International Conference on Machine Learning*, volume 267 of *Proceedings of Machine Learning Research*, pages 30038–30066. PMLR, 2025. URL https://proceedings.mlr.press/v267/kim25e.html.

[13] Wenzhe Li, Yong Lin, Mengzhou Xia, and Chi Jin. Rethinking mixture-of-agents: Is mixing different large language models beneficial?, 2025. URL https://arxiv.org/abs/2502.00674.

[14] Valentin Liévin, Anil Palepu, et al. Towards conversational artificial intelligence for disease management. *Nature*, 655(8125):1292–1299, 2026. doi: 10.1038/s41586-026-10764-5. URL https://www.nature.com/articles/s41586-026-10764-5.

[15] Moran Mizrahi, Guy Kaplan, Dan Malkin, Rotem Dror, Dafna Shahaf, and Gabriel Stanovsky. State of what art? a call for multi-prompt LLM evaluation. *Transactions of the Association for Computational Linguistics*, 12:933–949, 2024. doi: 10.1162/tacl_a_00681. URL https://aclanthology.org/2024.tacl-1.52/.

[16] Harsha Nori, Yin Tat Lee, Sheng Zhang, Dean Carignan, Richard Edgar, et al. Can generalist foundation models outcompete special-purpose tuning? Case study in medicine, 2023. URL https://arxiv.org/abs/2311.16452.

[17] Arjun Panickssery, Samuel R. Bowman, and Shi Feng. LLM evaluators recognize and favor their own generations. In *Advances in Neural Information Processing Systems*, volume 37, pages 68772–68802, 2024. doi: 10.52202/079017-2197. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/7f1f0218e45f5414c79c0679633e47bc-Abstract-Conference.html.

[18] Felipe Maia Polo, Ronald Xu, Lucas Weber, Mírian Silva, Onkar Bhardwaj, Leshem Choshen, Allysson Flavio Melo de Oliveira, Yuekai Sun, and Mikhail Yurochkin. Efficient multi-prompt evaluation of LLMs. In *Advances in Neural Information Processing Systems*, volume 37, pages 22483–22512, 2024. doi: 10.52202/079017-0707. URL https://proceedings.neurips.cc/paper_files/paper/2024/hash/28236482f64a72eec43706b6f3a6c511-Abstract-Conference.html.

[19] Keita Saito, Akifumi Wachi, Koki Wataoka, and Youhei Akimoto. Verbosity bias in preference labeling by large language models, 2023. URL https://arxiv.org/abs/2310.10076.

[20] Melanie Sclar, Yejin Choi, Yulia Tsvetkov, and Alane Suhr. Quantifying language models' sensitivity to spurious features in prompt design or: How I learned to start worrying about prompt formatting. In *The Twelfth International Conference on Learning Representations (ICLR)*, 2024. URL https://openreview.net/forum?id=RIu5lyNXjT.

[21] Pat Verga, Sebastian Hofstätter, Sophia Althammer, Yixuan Su, Aleksandra Piktus, Arkady Arkhangorodsky, Minjie Xu, Naomi White, and Patrick Lewis. Replacing judges with juries: Evaluating LLM generations with a panel of diverse models, 2024. URL https://arxiv.org/abs/2404.18796.

[22] Krithik Vishwanath, Anton Alyakin, Mrigayu Ghosh, Ali Hage, Sean N. Neifert, et al. General-purpose large language models outperform specialized clinical AI tools on medical benchmarks. *Nature Medicine*, 32(7):2405–2409, 2026. doi: 10.1038/s41591-026-04431-5. URL https://www.nature.com/articles/s41591-026-04431-5.

[23] Junlin Wang, Jue Wang, Ben Athiwaratkun, Ce Zhang, and James Zou. Mixture-of-agents enhances large language model capabilities. In *The Thirteenth International Conference on Learning Representations (ICLR)*, 2025. URL https://www.iclr.cc/virtual/2025/poster/28787.

[24] Koki Wataoka, Tsubasa Takahashi, and Ryokan Ri. Self-preference bias in LLM-as-a-judge, 2024. URL https://arxiv.org/abs/2410.21819.

[25] David Wu, Fateme Nateghi Haredasht, Saloni Kumar Maharaj, Priyank Jain, Jessica Tran, Matthew Gwiazdon, et al. First, do NOHARM: a medical safety benchmark and randomized study of physician and AI teaming on clinical consultations, 2025. URL https://arxiv.org/abs/2512.01241.

[26] Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric P. Xing, Hao Zhang, Joseph E. Gonzalez, and Ion Stoica. Judging LLM-as-a-judge with MT-Bench and chatbot arena. In *Advances in Neural Information Processing Systems (Datasets and Benchmarks Track)*, volume 36, pages 46595–46623, 2023. doi: 10.52202/075280-2020. URL https://proceedings.neurips.cc/paper_files/paper/2023/hash/91f18a1287b398d378ef22505bf41832-Abstract-Datasets_and_Benchmarks.html.

A Instructions, verbatim

In every instruction below, `{case}` stands for the item's case text. The bare condition sends the case text alone.

Consult framing (`SPECIALIST`):

```
A primary care colleague has consulted you, a specialist, about the case below. Work
only with the information provided. Give the best recommendations for the situation,
not only an answer to the literal question.
```

Plan format (`PLAN_FORMAT`):

```
Start with a one- or two-sentence clinical assessment, then give your recommendations
as numbered items. Be specific: exact tests, drugs with doses and durations, referral
specialty and urgency, conditional next steps, case-specific counseling, and return
precautions. Include every action a careful specialist would not want omitted; include
nothing unsafe or unwarranted.
```

Specialist: `SPECIALIST`, a blank line, `Case:` and the case, a blank line, `PLAN_FORMAT`.

Components: *framing only* is `SPECIALIST`, a blank line, `Case:` and the case. *Format only* is `Case:` and the case, a blank line, `PLAN_FORMAT`. *Length only* is `Case:` and the case, a blank line, then:

```
Respond with at least 25 numbered recommendations.
```

Exhaustive headings: `SPECIALIST` extended as below, then the case and `PLAN_FORMAT`:

```
Address each of these headings for THIS patient, and write 'none indicated' under a
heading only after considering it: diagnosis and its severity; tests to confirm, to
exclude dangerous alternatives, and baselines before treatment; medications to start,
stop, hold or adjust (drug, dose, route, duration) and interactions with current ones;
procedures; referrals (specialty, urgency); counseling and warning signs; follow-up and
 monitoring (what, when, who); contingencies (if X, then Y, with thresholds).
```

Perspectives, each followed by the case and `PLAN_FORMAT`:

```
You are a clinical pharmacist on the consulting team for the case below. Work only with
 the information provided. Give the complete management plan, paying particular
attention to every medication that should be started, stopped, held or adjusted (drug,
dose, route, duration), interactions with the current regimen, renal or hepatic dosing,
 prophylaxis, and the monitoring each drug needs.
```

```
You are the patient's primary care physician, responsible for carrying out the plan for
 the case below over the coming months. Work only with the information provided. Give
the complete management plan, paying particular attention to follow-up (what, when, who
), contingencies with explicit thresholds (if X, then Y), what the patient must be told
 and watch for, and the referrals with their urgency.
```

Candidate menu: a request to list every concrete action a specialist panel should consider, alternatives and debatable actions included, under named headings, aiming for 30–50 numbered actions without marking any as recommended; full text in `scripts/noharm_system.py` (`MENU`).

Kit thorough prompt. The NOHARM kit's `prompts/thorough.md`, used unmodified: a consult framing, a request for a brief assessment and numbered recommendations under 500 words, the criteria completeness, safety and restraint, and a list of what a response may cover.

Completion pass: `SPECIALIST`, the case and the source plans, then a request to list only clearly indicated actions none of the plans states, checked heading by heading (follow-up and monitoring, contingencies, medications, diagnostics, referrals and procedures, counselling), as numbered concrete actions or "No additions."; full text in `scripts/noharm_system.py` (`GAP`).

B Technical and statistical details

Kit and evaluator. We used the NOHARM kit from the MAST repository at revision `57a12c5490f3a7a6b0a6ce4e0d49f8e393ff49ee` (code MIT, data CC BY 4.0), its runner, match and review stages and metric code unchanged. Only the evaluator model was replaced, because the organisers' evaluator family was outside the models available to us. The evaluator receives the kit's JSON schema in its prompt and its reply is validated locally. Model identifiers name provider routes, not immutable checkpoints. The free evaluators were reached through OpenRouter at zero price (Nemotron 3 Ultra, `nvidia/nemotron-3-ultra-550b-a55b:free`; Ling 3.1 Flash, `inclusionai/ling-3.1-flash`), with the public cases only, because free routes may retain prompts.

Generation. Instructed and system calls requested temperature zero and at most 12,000 output tokens, with up to four attempts for transient failures or empty replies; routes could ignore temperature. Bare and kit-prompt arms used the kit's runner and defaults. An arm is analysed only when all 330 items have a non-empty response and a complete evaluation; incomplete arms are excluded, never scored as answers. Responses were used as returned: no post-processing other than the concatenation that defines an ensemble, and no item was edited or filtered.

Dates and versions. All analysed generations and evaluations were run between 30 September 2026 and 11 October 2026. Models were reached through provider routes whose names are given in Section 3.2; the routes expose neither an immutable checkpoint nor a training cut-off date, so neither is reported, and a later run of the same route may differ.

Compute. Every model call went to a provider's hosted service; no local training or inference was run. An arm is 330 generation calls and about two evaluation calls per item (matching and review). Instructed terra took a median of 58 seconds per item (90th percentile 110), bare terra 14. Commercial models were reached through subscription accounts behind a local gateway, whose per-call cost is not itemised; the freely available models, the second evaluator and the audit raters were reached at zero price.

Metric. Rubric options are rated inappropriate (1–3), equivocal (4–6) or appropriate (7–9), with severity weights 72, 24 and 3 for the outer, middle and inner scores and 1 for equivocal options. The kit handles partial matches, alternative options and dependencies. Its off-rubric-inclusive precision gives each unmatched action the neutral default score.

Grouped scores. Actions matched to the same set of rubric options are collapsed and the kit's metric code rescores the plan; both sides of a comparison receive the same transformation. Distinct recommendations can share an option set, so grouping is a sensitivity analysis, not an alternative metric.

Resampling. For case scores f_{ia} the paired difference is $\widehat{\Delta}_{b-a} = N^{-1}\sum_{i=1}^{N}(f_{ib} - f_{ia})$ with $N = 30$. Cases were resampled with replacement, unstratified, 10,000 times with seed 7; cross-model statistics (Spearman, standard deviation, range, Kendall's τ) are recomputed on each resample.

C Earlier experiments on unprompted plans

Before the instruction experiments, we combined bare plans from Sonnet 5.5, terra and Luna. The ensemble scored 0.811 (+0.047 [+0.029, +0.066] over bare Sonnet); a Sonnet completion pass raised it to 0.849 (+0.038 [+0.009, +0.070]), and Opus 5.5 in the same role changed nothing (−0.001 [−0.012, +0.009]). A writer with automated omission checks scored 0.822 (+0.012 [−0.004, +0.028] against the ensemble), but its checker still reported a mean of 3.10 of a median 31 source actions missing after repair, so the rewrite was not lossless. On the instructed ensemble, a trial of the same writer on one item listed 194 source actions, and its re-insertion rounds left more of them missing each round.

D TRIPOD-LLM checklist

Reporting follows TRIPOD-LLM [7]. Item topics are paraphrased; the guideline gives their full wording. The study's research designs are prompt engineering (M) and LLM evaluation (E), and its task is long-form question answering (QA), so items restricted to other designs or tasks are marked not applicable (N/A). "Sec." and "App." refer to this manuscript.

Item	Topic	Where reported, or response
Title and abstract		
1	Study type, task, population, outcome in the title	Title: language models, prompt design, a clinical-safety benchmark of specialist consultations; subtitle names the NOHARM v2 public cases.
2	Structured abstract (TRIPOD-LLM for abstracts)	Abstract: background, objective, methods, results with intervals, conclusions.
Introduction		
3a	Healthcare context, rationale, existing approaches	Sec. 1, Sec. 2.
3b	Target population, intended use and users	Sec. 1; intended use stated in Sec. 5 (advice to a primary-care clinician, reviewed before action).
4	Objectives and study stage	Sec. 1: four questions; evaluation of existing models under different instructions; no development or tuning.
Methods		
5a	Data sources and rationale	Sec. 3.1.
5b	Description and distribution of the data	Sec. 3.1: cases, specialties, versions, rubric composition by score and category.
5c	Dates of the oldest and newest text	Public cases released June 2026 (Sec. 4.7); the benchmark does not date the source consultations. Training-data dates of the models are not available (App. B).
5d	Preprocessing and quality checks	App. B: cases sent verbatim; completeness checks; re-scored plans verified byte-identical.
5e	Missing and imbalanced data	App. B: incomplete arms excluded, undefined precision handled as in the kit; categories with too few options not reported (Sec. 4.4).
6a	Model name, version, training date	Sec. 3.2; App. B: provider routes, no immutable checkpoint or training cut-off available.
6b	Model development process	N/A: existing models used without training or tuning.

Item	Topic	Where reported, or response
6c	Generation details: prompts, inference settings, consistency	Sec. 3.3; App. A (verbatim); App. B (temperature, tokens, retries). Regeneration consistency not measured (Sec. 6).
6d	Raw and post-processed output	App. B: unstructured text, used as returned.
6e	Classification thresholds	N/A (task is long-form question answering).
7a	Output-quality metrics against a gold standard	Sec. 3.6: severity-weighted F1 against specialist ratings, with precision, recall, severe-error share and four length checks.
7b	Metric relevance; correlation with human evaluation	Sec. 3.5: evaluator agreement with the organisers' evaluator; one physician's overall review of flagged unlisted actions and added harmful options (Sec. 4.5, Sec. 6).
7c	Outcome definition, calculation, inference dates	Sec. 3.6; App. B (kit revision, metric code, dates).
7d	Subjective assessment: assessors, instructions, agreement	AI evaluators with the kit's prompts (Sec. 3.5); test–retest and cross-family agreement (Sec. 4.5).
7e	Comparison with other models, humans, benchmarks	Twelve models (Sec. 4.1); published reference and leaderboard scores (Sec. 4.7); no human comparison.
8a	Annotation process	Rubric rated by the benchmark's specialists [25]; off-rubric actions rated by models on the same 1–9 scale (Sec. 3.6).
8b	Annotators, overlap, agreement	Two model raters on a shared 90-item sample (Sec. 4.5).
8c	Annotator background or labelling-model characteristics	Sec. 3.6: rater models and their accuracy against specialist ratings in an earlier analysis.
9a	Prompt design, curation and selection	Sec. 3.3.
9b	Data used to develop prompts	Sec. 3.3: the same public cases (Sec. 6).
10	Preprocessing before summarisation	N/A (task is not summarisation).
11	Instruction tuning or alignment	N/A (no tuning).
12	Compute	App. B: hosted calls, calls per arm, runtimes.
13	Ethics approval	Not human-subjects research; public CC BY 4.0 cases, no review sought (Data, code and declarations).
Open science and involvement		
14a	Funding	None (Data, code and declarations).
14b	Conflicts of interest	None (Data, code and declarations).
14c	Protocol	No protocol prepared (Data, code and declarations).
14d	Registration	Not registered (Data, code and declarations).
14e	Data availability	Responses, evaluations and analysis outputs; archive `https://github.com/OJamals/noharm-prompting`.
14f	Code availability	Analysis and generation scripts named in Data, code and declarations; archive `https://github.com/OJamals/noharm-prompting`.
15	Patient and public involvement	None (Data, code and declarations).
Results		
16a	Flow of data through the study	Sec. 3.1: 30 cases, 330 items, all analysed in every complete arm; no patient-level data.
16b	Characteristics per data source and split	N/A: no development/evaluation split; case composition in Sec. 3.1.

Item	Topic	Where reported, or response
16c	Clinical-variable distribution, development vs. evaluation	N/A (no split, no clinical outcomes).
16d	Numbers in each analysis	330 items per arm; 90-item audit sample; 140-item test–retest (Sec. 4.5).
17	Performance on prespecified metrics	Sec. 4.1–4.7.
18	Model updating	N/A: no updating; provider routes may change (Sec. 6).
Discussion		
19a	Interpretation, including fairness	Sec. 5; age and sex versions (Sec. 4.5).
19b	Limitations	Sec. 6.
19c	Data challenges: representation, missingness, bias	Sec. 6: one centre, 30 cases, public since June 2026.
19d	Intended use, input, user, autonomy	Sec. 5.
19e	Handling poor or missing input	N/A in a benchmark; robustness across case versions (Sec. 4.5).
19f	User interaction and expertise	Sec. 5: a longer plan needs prioritising for a clinician reader.
19g	Next steps	Sec. 5, Sec. 7.