

Module Guide for Software Engineering

Team #11, OKKM Insights

Mathew Petronilho

Oleg Glotov

Kyle McMaster

Kartik Chaudhari

January 18, 2025

1 Revision History

Date	Version	Notes
January 17th	1.0	

2 Reference Material

This section records information for easy reference.

2.1 Abbreviations and Acronyms

See SRS Documentation [here](#)

Contents

1	Revision History	i
2	Reference Material	ii
2.1	Abbreviations and Acronyms	ii
3	Introduction	1
4	Anticipated and Unlikely Changes	2
4.1	Anticipated Changes	2
4.2	Unlikely Changes	3
5	Module Hierarchy	3
6	Connection Between Requirements and Design	8
7	Module Decomposition	9
7.1	Hardware Hiding Modules (M1)	9
7.2	Behaviour-Hiding Module	9
7.2.1	Account Creation Interface (M2)	9
7.2.2	Account Database (M4)	10
7.2.3	Account Database Connector (M3)	10
7.2.4	Account Update Interface (M5)	10
7.2.5	Login Interface (M6)	10
7.2.6	Access Token (M7)	11
7.2.7	Labeler (M8)	11
7.2.8	Client (M9)	11
7.2.9	User (M10)	11
7.2.10	Satellite Image Request Interface (M14)	11
7.2.11	Satellite Image Request (M16)	12
7.2.12	Project Creation Interface (M17)	12
7.2.13	Project (M19)	12
7.2.14	Service Request Failure Interface (M20)	12
7.2.15	Image Upload Interface (M21)	12
7.2.16	Report Interface (M22)	13
7.2.17	Report (M24)	13
7.2.18	Project Selection Interface (M25)	13
7.2.19	Labeling Interface (M27)	13
7.2.20	Image (M29)	13
7.2.21	Label Server (30)	14
7.2.22	Label Database Connector (31)	14
7.2.23	Label Database (32)	14
7.2.24	ImageObject Database Connector (33)	14

7.2.25	ImageObject Database (34)	14
7.2.26	Labeller Database Connector (35)	15
7.2.27	Labeller Database (36)	15
7.2.28	Object Extraction Manager (37)	15
7.2.29	Image Service Manager (38)	15
7.2.30	ModelCreation (Abstract Class) (M39)	16
7.2.31	CNNModelCreation (M40)	16
7.2.32	OtherModelCreation (M41)	16
7.2.33	ModelManager (M42)	16
7.2.34	MLModelDatabase (M43)	17
7.3	Software Decision Module	17
7.3.1	Account Creation Controller (M11)	17
7.3.2	Account Update Controller (M12)	17
7.3.3	Authentication Controller (M13)	18
7.3.4	Satellite Image Request Controller (M15)	18
7.3.5	Project Creation Controller (M18)	18
7.3.6	Report Controller (M23)	18
7.3.7	Project Selection Controller (M26)	19
7.3.8	Labeling Controller (M28)	19
7.3.9	Label Confidence Service (44)	19
7.3.10	Object Extraction Service (45)	19
7.3.11	Image Prior Analyzer (46)	19
7.3.12	Labeller Expertise Calculator (47)	20
7.3.13	Image Mask Service (48)	20
7.3.14	Image Selection Service (49)	20
7.3.15	ModelComparision Evaluation (M50)	20
7.3.16	CrossValidation Evaluation (M51)	21
7.3.17	ModelTrainingService (M52)	21
7.3.18	ModelEvaluationService (M53)	21
8	Traceability Matrix	21
9	Use Hierarchy Between Modules	23
10	User Interfaces	29
11	Design of Communication Protocols	34
12	Timeline	35

List of Tables

1	Module Hierarchy	6
---	------------------	---

2	Module Hierarchy	7
3	Module Hierarchy	8
4	Trace Between Requirements and Modules	22
5	Trace Between Anticipated Changes and Modules	23

List of Figures

1	ML Model	28
2	Home Page	29
3	Login Page	29
4	Forgot Password	30
5	Register Page	30
6	Projects to Label Page	31
7	Label Page	31
8	Client Projects Page	32
9	Project Status Page	33
10	User Information Page	33
11	Page Flow Diagram	34

3 Introduction

Decomposing a system into modules is a commonly accepted approach to developing software. A module is a work assignment for a programmer or programming team (Parnas et al., 1984). We advocate a decomposition based on the principle of information hiding (Parnas, 1972). This principle supports design for change, because the “secrets” that each module hides represent likely future changes. Design for change is valuable in SC, where modifications are frequent, especially during initial development as the solution space is explored.

Our design for OrbitWatch follows the rules layed out by Parnas et al. (1984), as follows:

- System details that are likely to change independently should be the secrets of separate modules.
- Each data structure is implemented in only one module.
- Any other program that requires information stored in a module’s data structures must obtain it by calling access programs belonging to that module.

After completing the first stage of the design, the Software Requirements Specification (SRS), the Module Guide (MG) is developed (Parnas et al., 1984). The MG specifies the modular structure of the system and is intended to allow both designers and maintainers to easily identify the parts of the software. The potential readers of this document are as follows:

- New project members: This document can be a guide for a new project member to easily understand the overall structure and quickly find the relevant modules they are searching for.
- Maintainers: The hierarchical structure of the module guide improves the maintainers’ understanding when they need to make changes to the system. It is important for a maintainer to update the relevant sections of the document after changes have been made.
- Designers: Once the module guide has been written, it can be used to check for consistency, feasibility, and flexibility. Designers can verify the system in various ways, such as consistency among modules, feasibility of the decomposition, and flexibility of the design.

The rest of the document is organized as follows. Section 4 lists the anticipated and unlikely changes of the software requirements. Section 5 summarizes the module decomposition that was constructed according to the likely changes. Section 6 specifies the connections between the software requirements and the modules. Section 7 gives a detailed description of the modules. Section 8 includes two traceability matrices. One checks the completeness of the design against the requirements provided in the SRS. The other shows the relation between anticipated changes and the modules. Section 9 describes the use relation between modules.

4 Anticipated and Unlikely Changes

This section lists possible changes to the system. According to the likeliness of the change, the possible changes are classified into two categories. Anticipated changes are listed in Section 4.1, and unlikely changes are listed in Section 4.2.

4.1 Anticipated Changes

Anticipated changes are the source of the information that is to be hidden inside the modules. Ideally, changing one of the anticipated changes will only require changing the one module that hides the associated decision. The approach adapted here is called design for change.

- AC1:** Change in labeling tool(s) used or the introduction of additional labeling tools.
- AC2:** Change in form parameters for project creation and account registration workflows.
- AC3:** Change in the set and presentation of project statistics displayed to clients.
- AC4:** Changes in algorithms used to calculate image priors.
- AC5:** Changes in algorithms for object extraction from images.
- AC6:** Changes in algorithms that update and refine labeller expertise metrics.
- AC7:** Changes in image serving and distribution algorithms.
- AC8:** Change in automated image retrieval methods from the PlanetLabs image provider.
- AC9:** Change in satellite image providers or addition of multiple providers, requiring adjustments in data ingestion modules.
- AC10:** Change in the compensation model or payment distribution logic for labellers and stakeholders.
- AC11:** Change in backend hosting services (e.g., switching or integrating additional cloud providers beyond AWS/Azure) affecting deployment modules.
- AC12:** Change in consensus algorithms or user accuracy models used to resolve labeling conflicts, impacting the data validation modules.
- AC13:** Change in regulatory compliance or data privacy requirements, necessitating adjustments in data handling and storage modules.

4.2 Unlikely Changes

The module design should be as general as possible. However, a general system is more complex. Sometimes this complexity is not necessary. Fixing some design decisions at the system architecture stage can simplify the software design. If these decision should later need to be changed, then many parts of the design will potentially need to be modified. Hence, it is not intended that these decisions will be changed.

UC1: The predefined user access levels and roles (e.g., admin, labeller, client) are considered stable.

UC2: The choice of database technology (e.g., relational database) and its core schema structure is fixed early on.

UC3: The foundational languages and frameworks selected for development (e.g., Node.js for backend services, Typescript for frontend) are assumed to remain constant.

UC4: Decisions around the overall architectural pattern (such as microservices) are made early and considered stable.

5 Module Hierarchy

This section provides an overview of the module design. Modules are summarized in a hierarchy decomposed by secrets in Table 3. The modules listed below, which are leaves in the hierarchy tree, are the modules that will actually be implemented.

M1: Hardware-Hiding Module

M2: Account Creation Interface

M3: Account Database Connector

M4: Account Database

M5: Account Update Interface

M6: Login Interface

M7: Access Token

M8: Labeler

M9: Client

M10: User

M11: Account Creation Controller

M12: Account Update Controller
M13: Authentication Controller
M14: Satellite Image Request Interface
M15: Satellite Image Request Controller
M16: Satellite Image Request
M17: Project Creation Interface
M18: Project Creation Controller
M19: Project
M20: Service Request Failure Interface
M21: Image Upload Interface
M22: Report Interface
M23: Report Controller
M24: Report
M25: Project Selection Interface
M26: Project Selection Controller
M27: Labeling Interface
M28: Labeling Controller
M29: Image
M30: Label Server
M31: Label Database Connector
M32: Label Database
M33: ImageObject Database Connector
M34: ImageObject Database
M35: Labeller Database Connector
M36: Labeller Database
M37: Object Extraction Manager

M38: Image Service Manager
M39: ModelCreation (Abstract Class)
M40: CNNModelCreation
M41: OtherModelCreation
M42: ModelManager
M43: MLModelDatabase
M44: Label Confidence Service
M45: Object Extraction Service
M46: Image Prior Analyzer
M47: Labeller Expertise Calculator
M48: Image Mask Service
M49: Image Selection Service
M50: ModelComparision Evaluation
M51: CrossValidation Evaluation
M52: ModelTrainingService
M53: ModelEvaluationService

Level 1	Level 2
Hardware-Hiding Mod- ule	

Table 1: Module Hierarchy

Level 1	Level 2
Behaviour-Hiding Module	Account Creation Interface
	Account Database
	Account Update Interface
	Login Interface
	Access Token
	Labeler
	Client
	User
	Satellite Image Request Interface
	Satellite Image Request
	Project Creation Interface
	Project
	Service Request Failure Interface
	Image Upload Interface
	Report Interface
	Report
	Project Selection Interface
	Labeling Interface
	Image
	Label Server
	Label Database Connector
	Label Database
	ImageObject Database Connector
	ImageObject Database
	Labeller Database Connector
	Labeller Database
	Object Extraction Manager
	Image Service Manager
	ModelCreation (Abstract Class)
	CNNModelCreation
	OtherModelCreation
	ModelManager
	MLModelDatabase

Table 2: Module Hierarchy

Level 1	Level 2
Software Decision Module	Account Creation Controller
	Account Database Connector
	Account Update Controller
	Authentication Controller
	Satellite Image Request Controller
	Project Creation Controller
	Report Controller
	Project Selection Controller
	Labeling Controller
	Label Confidence Service
	Object Extraction Service
	Image Prior Analyzer
	Labeller Expertise Calculator
	Image Mask Service
	Image Selection Service
	ModelComparision Evaluation
	CrossValidation Evaluation
	ModelTrainingService
	ModelEvaluationService

Table 3: Module Hierarchy

6 Connection Between Requirements and Design

The design of the system is intended to satisfy the requirements developed in the SRS. In this stage, the system is decomposed into modules. The connection between requirements and modules is listed in Table 4.

There are several key high level design decisions that were made to ensure the requirements outlined in the SRS are met. First, the system has been decomposed into several microservices. These services all connect to the same databases, but have the flexibility to operate on their own cadence. Each service can be mirrored by a duplicate service to improve capacity. These decisions are critical to ensuring the speed, uptime, capacity, and latency requirements. Each of the key algorithms in the system have been encapsulated in their own module. These include the object extraction service, image serving, ML model creation, and report generation, among others. This gives the development team the flexibility to experiment with alternative algorithms, allowing continuous improvement towards performance and accuracy requirements. The authentication service is designed to meet the authentication requirements by ensuring only approved users can access privileged information. Every functional requirement is covered by the functionality of a subsystem.

7 Module Decomposition

Modules are decomposed according to the principle of “information hiding” proposed by [Parnas et al. \(1984\)](#). The *Secrets* field in a module decomposition is a brief statement of the design decision hidden by the module. The *Services* field specifies *what* the module will do without documenting *how* to do it. For each module, a suggestion for the implementing software is given under the *Implemented By* title. If the entry is *OS*, this means that the module is provided by the operating system or by standard programming language libraries. *Software Engineering* means the module will be implemented by the Software Engineering software.

Only the leaf modules in the hierarchy have to be implemented. If a dash (–) is shown, this means that the module is not a leaf and will not have to be implemented.

7.1 Hardware Hiding Modules (M1)

Secrets: The data structure and algorithm used to implement the virtual hardware.

Services: Serves as a virtual hardware used by the rest of the system. This module provides the interface between the hardware and the software. So, the system can use it to display outputs or to accept inputs.

Implemented By: OS

7.2 Behaviour-Hiding Module

Secrets: The contents of the required behaviours.

Services: Includes programs that provide externally visible behaviour of the system as specified in the software requirements specification (SRS) documents. This module serves as a communication layer between the hardware-hiding module and the software decision module. The programs in this module will need to change if there are changes in the SRS.

Implemented By: –

7.2.1 Account Creation Interface (M2)

Secrets: The design format of the account creation user interface.

Services: Displays a form to collect user information and submits that information to be processed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.2 Account Database (M4)

Secrets: The data structure, storage, and access mechanisms for account related data.

Services: Can store, insert, update and retrieve user account data.

Implemented By: OrbitWatch

Type of Module: Abstract Data Type

7.2.3 Account Database Connector (M3)

Secrets: The database access key and database access algorithms.

Services: Can request storage, insertion, updates and retrieval of user account data from the database.

Implemented By: OrbitWatch

Type of Module: Abstract Data Type

7.2.4 Account Update Interface (M5)

Secrets: The design format of the update account information user interface.

Services: Displays a form with the users current information that can be modified and submits any updated information to be processed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.5 Login Interface (M6)

Secrets: The design format of the login user interface.

Services: Displays a form to collect login credentials and submits that information to be processed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.6 Access Token (M7)

Secrets: Token structure, encryption, expiration, and renewal mechanisms.

Services: Can determine if a user's token has expired and allows the token to be renewed.

Implemented By: OrbitWatch

Type of Module: Abstract Data Type

7.2.7 Labeler (M8)

Secrets: The format and structure of Labeler data.

Services: Takes in the necessary data to create a Labeler.

Implemented By: OrbitWatch

Type of Module: Record

7.2.8 Client (M9)

Secrets: The format and structure of Client data.

Services: Takes in the necessary data to create a Client.

Implemented By: OrbitWatch

Type of Module: Record

7.2.9 User (M10)

Secrets: The format and structure of User data.

Services: Takes in the necessary data to create a User.

Implemented By: OrbitWatch

Type of Module: Record

7.2.10 Satellite Image Request Interface (M14)

Secrets: The design format of the interface for requesting satellite images.

Services: Displays a form to collect specifics on the satellite images, calculates estimated cost based on current form entries and submits the form information to be processed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.11 Satellite Image Request (M16)

Secrets: The format and structure of the data needed for a satellite image request.

Services: Takes in the necessary data to create a satellite image request.

Implemented By: OrbitWatch

Type of Module: Record

7.2.12 Project Creation Interface (M17)

Secrets: The design format of the project creation interface.

Services: Displays a form to collect project details, calculates an estimated cost using these details and submits that information to be processed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.13 Project (M19)

Secrets: The format and structure of the data needed for a Project.

Services: Takes in the necessary data to create a Project.

Implemented By: OrbitWatch

Type of Module: Record

7.2.14 Service Request Failure Interface (M20)

Secrets: The design format of the request failure interface.

Services: Displays a warning to users that something went wrong.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.15 Image Upload Interface (M21)

Secrets: The design format of the image upload interface.

Services: Allows users to upload images from their device, and validates they are images of the correct format.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.16 Report Interface (M22)

Secrets: The design format of the summary report interface.

Services: Displays statistics and results of a specific project.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.17 Report (M24)

Secrets: The format and structure of Report data.

Services: Takes in the necessary data to create a Report.

Implemented By: OrbitWatch

Type of Module: Record

7.2.18 Project Selection Interface (M25)

Secrets: The design format of the project selection interface.

Services: Display all available projects that a user can label images from.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.19 Labeling Interface (M27)

Secrets: The design format of the labeling interface.

Services: Displays an image to be labeled, displays label choices which can be selected, and allows images to be skipped.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.20 Image (M29)

Secrets: The format and structure of Image data.

Services: Takes in the necessary data to create a Image.

Implemented By: OrbitWatch

Type of Module: Record

7.2.21 Label Server (30)

Secrets: The steps to accept and store a label.

Services: Converts a label JSON object and passes it to be stored in the database.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.22 Label Database Connector (31)

Secrets: The steps to connect to and manipulate a database.

Services: Connects to a database and executes pushing and fetching of data.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.23 Label Database (32)

Secrets: The storing and retrieving of data.

Services: Allows connection by a database connector to facilitate the storage and retrieval of data.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.24 ImageObject Database Connector (33)

Secrets: The steps to connect to and manipulate a database.

Services: Connects to a database and executes pushing and fetching of data.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.25 ImageObject Database (34)

Secrets: The storing and retrieving of data.

Services: Allows connection by a database connector to facilitate the storage and retrieval of data.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.26 Labeller Database Connector (35)

Secrets: The steps to connect to and manipulate a database.

Services: Connects to a database and executes pushing and fetching of data.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.27 Labeller Database (36)

Secrets: The storing and retrieving of data.

Services: Allows connection by a database connector to facilitate the storage and retrieval of data.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.28 Object Extraction Manager (37)

Secrets: The algorithms used to aggregate labels into usable ImageObjects for Model training.

Services: Calls other modules to efficiently compute the most likely set of objects from a set of independent labels.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.29 Image Service Manager (38)

Secrets: The algorithms used to select images to be served to a user.

Services: Calls other modules to select the next images to be server to a user.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.2.30 ModelCreation (Abstract Class) (M39)

Secrets: The abstract details of how machine learning (ML) model creation is organized, including any hidden complexities of managing configuration parameters.

Services: Defines the interface for creating ML models. Specific implementations (e.g., Convolutional Neural Networks, Support Vector Machines) extend this class to instantiate the appropriate model structure.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.31 CNNModelCreation (M40)

Secrets: The underlying architecture for a convolutional neural network model, including details about layer definitions, activation functions, and other internal configurations.

Services: Accepts layer configurations and constructs a CNN model suitable for training or inference tasks.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.32 OtherModelCreation (M41)

Secrets: The hyperparameter configurations and implementation details necessary for creating alternative model types (e.g., Decision Trees, SVMs).

Services: Allows the instantiation of various ML models by applying specific parameters (such as maximum tree depth or kernel functions) to build a model instance.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.33 ModelManager (M42)

Secrets: The internal logic that governs model lifecycle management (e.g., statuses such as “Training,” “Evaluating,” or “Completed”) as well as the way creation and update timestamps are maintained.

Services: Manages ML models by creating new instances, updating their status, retrieving existing models, and deleting models as needed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.2.34 MLModelDatabase (M43)

Secrets: The database schema, connection details, and query mechanisms for storing and retrieving ML model metadata and configurations.

Services: Provides persistent storage for ML model data, supporting operations such as create, read, update, and delete (CRUD).

Implemented By: OrbitWatch

Type of Module: Abstract Data Type

7.3 Software Decision Module

Secrets: The design decision based on mathematical theorems, physical facts, or programming considerations. The secrets of this module are *not* described in the SRS.

Services: Includes data structure and algorithms used in the system that do not provide direct interaction with the user.

Implemented By: –

7.3.1 Account Creation Controller (M11)

Secrets: Form validation and account creation algorithms.

Services: Validates the form information, creates an account with that information, and can upload the account to the database.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.2 Account Update Controller (M12)

Secrets: Form validation and account modification algorithms.

Services: Gets current user information, validates the update form information and can pass account updates to the database.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.3 Authentication Controller (M13)

Secrets: Credential validation, access token validation, and access token generation algorithms.

Services: Validates credentials given by user, generates access tokens, and validates access tokens.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.4 Satellite Image Request Controller (M15)

Secrets: Form validation and image request algorithms.

Services: Validates the form information, creates and sends a request to a third party for the necessary pictures.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.5 Project Creation Controller (M18)

Secrets: Form validation and project creation algorithms.

Services: Validates project information provided and creates a new project.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.6 Report Controller (M23)

Secrets: Logic for getting statistics of a project and exporting images onto the users device.

Services: Get statistics and labeled images of project, and exports images to external devices.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.7 Project Selection Controller (M26)

Secrets: Logic for getting active projects and redirecting labelers upon selection.

Services: Gets valid projects that are currently available, and redirects labelers to a selected project labeling interface.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.8 Labeling Controller (M28)

Secrets: Algorithms for label creation, removal and submission.

Services: Creates label for an image, removes label from an image, and submits labels to be processed.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.9 Label Confidence Service (44)

Secrets: The algorithms used to determine confidence in detected ImageObjects.

Services: Calculates the confidence of a detected ImageObject.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.3.10 Object Extraction Service (45)

Secrets: The algorithms used to extract ImageObjects.

Services: Calculates the most likely ImageObjects from a set of labels and priors.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.3.11 Image Prior Analyzer (46)

Secrets: The algorithms used to calculate ImagePriors.

Services: Calculates the prior likelihood of a pixel being relevant.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.3.12 Labeller Expertise Calculator (47)

Secrets: The algorithms used to calculate Labeller Expertise.

Services: Calculates the expertise of a labeller in a given class using previous labels.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.3.13 Image Mask Service (48)

Secrets: The algorithms used to modify a given image.

Services: Modifies an image in an attempt to improve labelling accuracy or efficiency.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.3.14 Image Selection Service (49)

Secrets: The algorithms used to select the next image to show a user.

Services: Selects an image to show to a given user.

Implemented By: [OrbitWatch]

Type of Module: [Abstract Object]

7.3.15 ModelComparison Evaluation (M50)

Secrets: The evaluation metrics and internal comparison algorithms (e.g., accuracy, F1-score) used to contrast multiple ML models.

Services: Evaluates one or more models against provided test data, calculates a set of performance metrics, and produces a comparison summary or report.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.16 CrossValidation Evaluation (M51)

Secrets: The logic behind performing K-fold cross-validation (or alternative validation schemes), including how folds are formed and results are averaged.

Services: Executes cross-validation on a given model and dataset, aggregates the results of each fold, and computes final performance metrics such as mean accuracy, mean precision, etc.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.17 ModelTrainingService (M52)

Secrets: The training algorithms, hyperparameter optimization logic, and internal routines for monitoring the status of model training.

Services: Orchestrates the process of training ML models using specified data and configuration parameters; can also halt training if requested.

Implemented By: OrbitWatch

Type of Module: Abstract Object

7.3.18 ModelEvaluationService (M53)

Secrets: The design and algorithms for evaluating models, combining metrics, and aggregating results for final output.

Services: Evaluates a trained model on test data, computes relevant performance metrics, and exposes them for reporting or further analysis.

Implemented By: OrbitWatch

Type of Module: Abstract Object

8 Traceability Matrix

This section shows two traceability matrices: between the modules and the requirements and between the modules and the anticipated changes.

Table 4: Trace Between Requirements and Modules

Req.	Modules
FR0	M11, M2, M3, M4, M10, M9
FR1	M13, M6, M7, M3, M4, M10, M9
FR2	M13, M7, M3, M4, M12, M5, M10, M9
FR4	
FR5	
FR6	
FR7	
FR8	
FR9	M11, M2, M3, M4, M10, M9
FR10	M13, M6, M7, M3, M4, M10, M8
FR11	M13, M7, M3, M4, M12, M5, M10, M9
FR13	M27, M28, M??, M30, M32, M31, M38, M49
FR14	M22, M23, M37, M44, M45, M46, M48
LF0	M5, M6, M2, M14, M20, M17, M21, M22, M25, M27
LF1	M5, M6, M2, M14, M20, M17, M21, M22, M25, M27
LF2	M5, M6, M2, M14, M20, M17, M21, M22, M25, M27
UH0	M5, M6, M2, M14, M20, M17, M21, M22, M25, M27
UH1	M5, M6, M2, M14, M20, M17, M21, M22, M25, M27
UH2	M5, M12
UH6	M27
UH7	M20
UH9	M27
PR0	M2, M11, M9
PR1	M2, M11, M8
PR2	M22, M23, M24
PR3	M27, M28, M29, M38, M49
PR5	M22, M23, M37, M44, M45, M46, M48
PR6	Related to all modules
PR7	Related to all modules
PR8	M21, M14, M15, M16, M48, M38, M49, M46, M34, M33,
PR9	Related to all modules
OE0	Related to all modules
OE1	M14, M15, M16
OE4	M39, M40, M41, M52, M53
OE5	M34, M33, M52, M53, M42, M39
MR0	Related to all modules

Continued on next page

Req.	Modules
SE0	M13, M7, M27, M28, M25, M26
SE1	M13, M7, M17, M18
SE2	M2, M11
SE3	M2, M11
SE4	M20
SE5	M11, M12, M18, M37, M44, M45, M46, M48
SE6	
SE7	M4, M3, M34, M33, M35, M36, M31, M32, M43
SE8	M12, M11, M4
SE10	M3, M33, M35, M31

AC	Modules
AC1	M1
AC2	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??
AC??	M??

Table 5: Trace Between Anticipated Changes and Modules

9 Use Hierarchy Between Modules

In this section, the uses hierarchy between modules is provided. Parnas (1978) said of two programs A and B that A *uses* B if correct execution of B may be necessary for A to complete the task described in its specification. That is, A *uses* B if there exist situations in which the correct functioning of A depends upon the availability of a correct implementation of B. Figure 12 illustrates the use relation between the modules. It can be seen that the graph is a directed acyclic graph (DAG). Each level of the hierarchy offers a testable and usable subset of the system, and modules in the higher level of the hierarchy are essentially simpler because they use modules from the lower levels.

Level 1: Foundational Modules

- **Label Database**

- **Secrets:** The storing and retrieving of data.
- **Services:** Allows connection by a database connector to facilitate the storage and retrieval of data.

- **ImageObject Database**

- **Secrets:** The storing and retrieving of data.
- **Services:** Allows connection by a database connector to facilitate the storage and retrieval of data.

- **Labeller Database**

- **Secrets:** The storing and retrieving of data.
- **Services:** Allows connection by a database connector to facilitate the storage and retrieval of data.

Level 2: Database Connectors

- **Label Database Connector**

- **Uses:** Label Database
- **Secrets:** The steps to connect to and manipulate a database.
- **Services:** Connects to a database and executes pushing and fetching of data.

- **ImageObject Database Connector**

- **Uses:** ImageObject Database
- **Secrets:** The steps to connect to and manipulate a database.
- **Services:** Connects to a database and executes pushing and fetching of data.

- **Labeller Database Connector**

- **Uses:** Labeller Database
- **Secrets:** The steps to connect to and manipulate a database.
- **Services:** Connects to a database and executes pushing and fetching of data.

Level 3: Core Services

- **Label Server**

- **Uses:** Label Database Connector
- **Secrets:** The steps to accept and store a label.
- **Services:** Converts a label JSON object and passes it to be stored in the database.

- **Object Extraction Manager**

- **Uses:** Label Confidence Service, Object Extraction Service, Labeller Expertise Calculator
- **Secrets:** The algorithms used to aggregate labels into usable ImageObjects for model training.
- **Services:** Calls other modules to efficiently compute the most likely set of objects from a set of independent labels.

- **Image Service Manager**

- **Uses:** Image Selection Service, Image Mask Service, Image Prior Analyzer
- **Secrets:** The algorithms used to select images to be served to a user.
- **Services:** Calls other modules to select the next images to be served to a user.

Level 4: Specialized Services

- **Label Confidence Service**

- **Secrets:** The algorithms used to determine confidence in detected ImageObjects.
- **Services:** Calculates the confidence of a detected ImageObject.

- **Object Extraction Service**

- **Secrets:** The algorithms used to extract ImageObjects.
- **Services:** Calculates the most likely ImageObjects from a set of labels and priors.

- **Image Prior Analyzer**

- **Secrets:** The algorithms used to calculate ImagePriors.
- **Services:** Calculates the prior likelihood of a pixel being relevant.

- **Labeller Expertise Calculator**

- **Secrets:** The algorithms used to calculate Labeller Expertise.

- **Services:** Calculates the expertise of a labeller in a given class using previous labels.
- **Image Mask Service**
 - **Secrets:** The algorithms used to modify a given image.
 - **Services:** Modifies an image to improve labelling accuracy or efficiency.
- **Image Selection Service**
 - **Secrets:** The algorithms used to select the next image to show a user.
 - **Services:** Selects an image to show to a given user.

Directed Acyclic Graph (DAG)

The following hierarchy is represented as a directed acyclic graph, with arrows showing the *uses* relationship:

- **Foundational Modules** (Label Database, ImageObject Database, Labeller Database)
 - Used by their respective connectors.
- **Database Connectors** (Label Database Connector, ImageObject Database Connector, Labeller Database Connector)
 - Used by core services like Label Server, Object Extraction Manager, and Image Service Manager.
- **Core Services** (Label Server, Object Extraction Manager, Image Service Manager)
 - Use specialized services to provide advanced functionalities.
- **Specialized Services** (Label Confidence Service, Object Extraction Service, Image Prior Analyzer, Labeller Expertise Calculator, Image Mask Service, Image Selection Service)
 - Provide algorithms and computations needed by the core services.

Source Module	Target Module	Relationship
Label Database	Label Database Connector	Uses
ImageObject Database	ImageObject Database Connector	Uses
Labeller Database	Labeller Database Connector	Uses
Label Database Connector	Label Server	Uses
ImageObject Database Connector	Object Extraction Manager	Uses

Labeller Database Connector	Object Extraction Manager	Uses
Label Server	Label Database Connector	Uses
Label Server	Label Confidence Service	Uses
Object Extraction Manager	Label Confidence Service	Uses
Object Extraction Manager	Object Extraction Service	Uses
Object Extraction Manager	Labeller Expertise Calculator	Uses
Image Service Manager	Image Selection Service	Uses
Image Service Manager	Image Mask Service	Uses
Image Service Manager	Image Prior Analyzer	Uses
Label Confidence Service	N/A	Provides algorithms
Object Extraction Service	N/A	Provides algorithms
Image Prior Analyzer	N/A	Provides algorithms
Labeller Expertise Calculator	N/A	Provides algorithms
Image Mask Service	N/A	Provides algorithms
Image Selection Service	N/A	Provides algorithms




Figure 1: ML Model

10 User Interfaces




Figure 2: Home Page




Figure 3: Login Page




Figure 4: Forgot Password




Figure 5: Register Page




Figure 6: Projects to Label Page




Figure 7: Label Page




Figure 8: Client Projects Page




Figure 9: Project Status Page

OrbitWatch \$XXXX.XX [Avatar] Logout

User Information

Back Edit

Current Balance: \$XXXX.XX

Withdraw Balance Change Password

Email: user@example.com

First Name: John

Last Name: Doe

Skills (comma separated): Image Classification, Object Detection

Availability (hours per week): 40

Figure 10: User Information Page




Figure 11: Page Flow Diagram

11 Design of Communication Protocols

Our platform will center around secure, efficient, and scalable communication protocols to facilitate interactions between the frontend, backend, and external services. Below is an outline of the key design considerations:

1. Client-to-Backend Communication:

HTTPS/RESTful APIs: All communication between the web-based frontend and the backend will occur over HTTPS using RESTful API endpoints. This ensures data in transit is encrypted and secure.

Authentication & Authorization: We will implement robust authentication mechanisms such as OAuth2 or JWT tokens for verifying and controlling access to API resources.

Structured Data Format: Requests and responses will primarily use JSON for lightweight, human-readable, and easily parsed messages.

Statelessness: The APIs will be stateless, allowing for easier scaling and handling of parallel requests, critical for enabling multiple users to label the same images concurrently.

2. Backend Infrastructure and AWS Communication:

AWS Hosting: The backend services will be deployed on AWS, taking advantage of its scalable infrastructure and regional availability to reduce latency and increase reliability.

Microservices & API Gateway: We may structure the backend as microservices behind an API Gateway to manage routing, authentication, and rate limiting more efficiently.

AWS Database Connectivity: The backend will communicate with AWS-hosted databases (Amazon RDS) via secure connections using AWS SDKs or native drivers over HTTPS or proprietary secured protocols.

12 Timeline

Milestone	Deadline	Tasks (Code)	Tasks (Documentation)
Revision 0 Demonstration	Feb 3 – Feb 14	<ul style="list-style-type: none"> - Implement foundational modules: - Oleg: Databases (Label, ImageObject, Labeller) and connectors. - Kartik and Kyle: Backend APIs for connectors. - Mathew: Frontend for basic database interactions. 	<ul style="list-style-type: none"> - Describe the purpose of foundational modules. - Write an overview of functionality and initial design.
V&V Report Revision 0	March 7	<ul style="list-style-type: none"> - Begin core services implementation: - Kartik and Kyle: Label Server. - Oleg: Database and API integration testing. - Mathew: Develop basic UI for Label Server interactions. 	<ul style="list-style-type: none"> - Document module-level testing strategies. - Include high-level testing results. - Update SRS and V&V plans.
Final Demonstration (Rev 1)	March 24 – March 30	<ul style="list-style-type: none"> - Complete core services: - Kartik and Kyle: Object Extraction Manager, Image Service Manager. - Oleg: Optimize database queries for scalability. - Mathew: Build advanced frontend for services. 	<ul style="list-style-type: none"> - Document core service implementations and integration steps. - Update diagrams and traceability matrices.
EXPO Demonstration	April TBD	<ul style="list-style-type: none"> - Implement specialized services: - Kartik: Labeller Expertise Calculator. - Kyle: Image Mask Service. - Oleg: Refine backend for API reliability. - Mathew: Enhance frontend interactivity. 	<ul style="list-style-type: none"> - Create presentation materials. - Include screenshots, results, and use cases for EXPO demo.
Final Documentation (Rev 1)	April 2	<ul style="list-style-type: none"> - Conduct end-to-end testing: - Kartik and Kyle: Verify ML pipelines. - Oleg: Test backend and database robustness. - Mathew: Test UI for edge cases. 	<ul style="list-style-type: none"> - Finalize and submit SRS, V&V Plan, and test results. - Complete user/admin manuals and deployment guide.

References

David L. Parnas. On the criteria to be used in decomposing systems into modules. *Comm. ACM*, 15(2):1053–1058, December 1972.

David L. Parnas. Designing software for ease of extension and contraction. In *ICSE '78: Proceedings of the 3rd international conference on Software engineering*, pages 264–277, Piscataway, NJ, USA, 1978. IEEE Press. ISBN none.

D.L. Parnas, P.C. Clement, and D. M. Weiss. The modular structure of complex systems. In *International Conference on Software Engineering*, pages 408–419, 1984.