

Ticket A2T2

create oc user

```
#!/bin/bash
```

```
OUTDIR="/var/lib/owncloud/templates"
```

```
mkdir -p "$OUTDIR"
```

```
echo "username,password" > "$OUTDIR/user_list.csv.erb"
```

```
for i in $(seq -w 1 20)
```

```
do
```

```
    name="ocuser${i}"
```

```
    randPw=$(openssl rand -base64 32 | tr -dc 'A-Za-z0-9' | head -c 12)
```

```
    export OC_PASS="$randPw"
```

```
    # Check if user exists first
```

```
    if sudo -u www-data php /var/www/owncloud/occ user:info "$name" >/dev/null 2>&1
```

```
    then
```

```
        echo "$name already exists, skipping"
```

```
    else
```

```
        sudo -u www-data php /var/www/owncloud/occ user:add \
```

```
            --password-from-env \
```

```
            --display-name="$name" "$name"
```

```
    fi
```

```
    echo "${name},${randPw}" >> "$OUTDIR/user_list.csv.erb"
```

```
done
```

```
exit 0
```

the script loops through numbers 01 to 20, generating usernames (ocuser01–ocuser20) and secure 12-character alphanumeric passwords, then creates each user in OwnCloud if they don't already exist. It also saves each username and password into a CSV file in /var/lib/owncloud/templates/ for later delivery.

[Image Failed to Load]