

Ticket A2T2

create oc user

```
#!/bin/bash

OUTDIR="/var/lib/owncloud/templates"
mkdir -p "$OUTDIR"
echo "username,password" > "$OUTDIR/user_list.csv.erb"

for i in $(seq -w 1 20)
do
    name="ocuser${i}"
    randPw=$(openssl rand -base64 32 | tr -dc 'A-Za-z0-9' | head -c 12)

    export OC_PASS="$randPw"

    # Check if user exists first
    if sudo -u www-data php /var/www/owncloud/occ user:info "$name" >/dev/null
2>&1
    then
        echo "$name already exists, skipping"
    else
        sudo -u www-data php /var/www/owncloud/occ user:add \
            --password-from-env \
            --display-name="$name" "$name"
    fi

    echo "${name},${randPw}" >> "$OUTDIR/user_list.csv.erb"

done

exit 0
```

the script loops through numbers 01 to 20, generating usernames (ocuser01–ocuser20) and secure 12-character alphanumeric passwords, then creates each user in OwnCloud if they don't already exist. It also saves each username and password into a CSV file in /var/lib/owncloud/templates/ for later delivery.

```
Notice: /Stage[main]/Owncloud_users/Exec[create_owncloud_users]/returns: executed successfully (corrective)
Notice: Applied catalog in 8.84 seconds
group-d@app-d:~$
```