
# ME 599/699 Robot Modeling & Control Fall 2021

# **Sampling-Based Motion Planning**


Hasan A. Poonawala

Department of Mechanical Engineering University of Kentucky


Email: hasan.poonawala@uky.edu
Web: https://www.engr.uky.edu/~hap




Motion Planning Problem




Over-simplify the problem




A valid continuous path How would we obtain such a path using graph search?




Randomly pick configurations to be nodes



Randomly pick configurations to be nodes Discard nodes in obstacles



Randomly pick configurations to be nodes Discard nodes in obstacles Build graph by adding edges



Randomly pick configurations to be nodes Discard nodes in obstacles Build graph by adding edges that can be physically realized

Sampling-based motion planning (MP) algorithms define nodes/edges for continuous space and then develop a graph (PRM/RRG) or a tree (RRT).

PRM: Probabilistic Road Map

► RRT: Rapidly-Expanding Random Tree

RRG: Rapidly-Expanding Random Graph

Sampling-based motion planning (MP) algorithms define nodes/edges for continuous space and then develop a graph (PRM/RRG) or a tree (RRT).

- PRM: Probabilistic Road Map
- ► RRT: Rapidly-Expanding Random Tree
- RRG: Rapidly-Expanding Random Graph

This conversion of MP into a graph enables use of graph search algorithms

Sampling-based motion planning (MP) algorithms define nodes/edges for continuous space and then develop a graph (PRM/RRG) or a tree (RRT).

- PRM: Probabilistic Road Map
- ► RRT: Rapidly-Expanding Random Tree
- ► RRG: Rapidly-Expanding Random Graph

This conversion of MP into a graph enables use of graph search algorithms

The large variety in sampling-based motion planning algorithms are variations of the two following steps.

- 1. Randomly sample configurations to create 'nodes'
- 2. Use motion models/constraints to 'connect' samples

#### Every algorithm has

- ► Sampling mechanism + collision check for creating nodes
- ▶ Select existing nodes to try and connect new samples to
- ▶ Local planner to check if we can connect new sample with selected existing nodes (dynamics, obstacles along path, local planner, etc.)

#### **Evolution:**

► Early methods generated new sample by randomly choosing a control and 'taking a step'. Poor exploration.

- ► Early methods generated new sample by randomly choosing a control and 'taking a step'. Poor exploration.
- ▶ PRM said choose a configuration, use planner to figure out control between them. Often connections failed.

- ► Early methods generated new sample by randomly choosing a control and 'taking a step'. Poor exploration.
- ▶ PRM said choose a configuration, use planner to figure out control between them. Often connections failed.
- RRT said create new sample, then create sample corresponding to step from existing node towards new sample. Rapid exploration unlocked.

- ► Early methods generated new sample by randomly choosing a control and 'taking a step'. Poor exploration.
- ▶ PRM said choose a configuration, use planner to figure out control between them. Often connections failed.
- RRT said create new sample, then create sample corresponding to step from existing node towards new sample. Rapid exploration unlocked.
- ▶ RRT\*: rewire connections so that all paths in **tree** are optimal

- ► Early methods generated new sample by randomly choosing a control and 'taking a step'. Poor exploration.
- ▶ PRM said choose a configuration, use planner to figure out control between them. Often connections failed.
- RRT said create new sample, then create sample corresponding to step from existing node towards new sample. Rapid exploration unlocked.
- ▶ RRT\*: rewire connections so that all paths in **tree** are optimal
- ▶ RRG: Connect to multiple neighbors, use shortest-path algos later.