

TEST REPORT

Applicant: TFIVE PTY LTD
Address: 10/29 Lorne Ave Killara NSW 2071 Australia
Equipment Type: Wireless Remote Switch H1 (Double Rocker)
Model Name: WRS-R02
Brand Name: Aqara
Test Standard: Radiation Protection Series S-1 (refer section 3.1)
Sample Arrival Date: Nov. 30, 2022
Test Date: Dec. 20, 2022 - Dec. 21, 2022
Date of Issue: Jan. 12, 2023

ISSUED BY:

Shenzhen BALUN Technology Co., Ltd.

Tested by: Chen Huiming

Checked by: Xiong Lining

Approved by: Tolan Tu
(Testing Director)

Chen Huiming

Xiong Li Ning

Tolan Tu

Revision History

<u>Version</u>	<u>Issue Date</u>	<u>Revisions Content</u>
<u>Rev. 01</u>	<u>Jan. 12, 2023</u>	<u>Initial Issue</u>

TABLE OF CONTENTS

1	GENERAL INFORMATION.....	3
1.1	Test Laboratory	3
1.2	Test Location	3
2	PRODUCT INFORMATION	4
2.1	Applicant Information	4
2.2	Manufacturer Information.....	4
2.3	Factory Information.....	4
2.4	General Description for Equipment under Test (EUT).....	4
2.5	Ancillary Equipment.....	4
2.6	Technical Information	5
3	STANDARD INFORMATION	6
3.1	Test Standards	6
4	DEVICE CATEGORY AND LEVELS LIMITS	7
5	MPE ASSESSMENT	9
5.1	Output Power	9
5.2	Assessment Result.....	9
5.3	Conclusion.....	9

1 GENERAL INFORMATION

1.1 Test Laboratory

Name	Shenzhen BALUN Technology Co., Ltd.
Address	Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
Phone Number	+86 755 6685 0100

1.2 Test Location

Name	Shenzhen BALUN Technology Co., Ltd.
Location	<input checked="" type="checkbox"/> Block B, 1/F, Baisha Science and Technology Park, Shahe Xi Road, Nanshan District, Shenzhen, Guangdong Province, P. R. China
	<input type="checkbox"/> 1/F, Building B, Ganghongji High-tech Intelligent Industrial Park, No. 1008, Songbai Road, Yangguang Community, Xili Sub-district, Nanshan District, Shenzhen, Guangdong Province, P. R. China

2 PRODUCT INFORMATION

2.1 Applicant Information

Applicant	TFIVE PTY LTD
Address	10/29 Lorne Ave Killara NSW 2071 Australia

2.2 Manufacturer Information

Manufacturer	Lumi United Technology Co., Ltd.
Address	8th Floor, JinQi Wisdom Valley, No.1 Tangling Road, Liuxian Ave, Taoyuan Residential District, Nanshan District, Shenzhen, China

2.3 Factory Information

Factory	N/A
Address	N/A

2.4 General Description for Equipment under Test (EUT)

EUT Name	Wireless Remote Switch H1 (Double Rocker)
Model Name Under Test	WRS-R02
Series Model Name	N/A
Description of Model name differentiation	N/A
Hardware Version	T0
Software Version	0.0.0_0021
Dimensions (Approx.)	N/A
Weight (Approx.)	N/A

2.5 Ancillary Equipment

Ancillary Equipment 1	Battery	
	Brand Name	Panasonic
	Model No.	CR2450
	Serial No.	N/A
	Capacity	620 mAh
	Rated Voltage	3.0 V
	Limit Charge Voltage	N/A

2.6 Technical Information

Network and Wireless connectivity	Zigbee
-----------------------------------	--------

The requirement for the following technical information of the EUT was tested in this report:

Operating Mode	Zigbee	
Frequency Range	Zigbee	2402 MHz ~ 2480MHz
Antenna Type	Zigbee	PCB Antenna
Exposure Category	General Population/Uncontrolled Exposure	
EUT Stage	Mobile Device	

3 STANDARD INFORMATION

3.1 Test Standards

No.	Identity	Document Title
1	Radiation Protection Series S-1(Rev. 1)	Standard for Limiting Exposure to Radiofrequency Fields - 100 kHz to 300 GHz
2	AS/NZS 2772.2:2016+AMD1:2018	Australian/New Zealand Standard Radiofrequency fields Part 2: Principles and methods of measurement and computation—3 kHz to 300 GHz
3	Radiocommunications Equipment (General) Rules 2021	Radiocommunications Equipment (General) Rules 2021

4 DEVICE CATEGORY AND LEVELS LIMITS

The field calculation does not take into account the antenna size, which is assumed to be a point source. An ideal isotropic antenna is used as a reference to compare the performance of practical antennas: P watts is radiated, from a point, uniformly over the surface of sphere of radius r . The POINTING VECTOR gives the power density:

Assumed use distance from EUT to Human, **20 cm** separation distance warning is required. In this section, the power density at 20 cm location is calculated to examine if it is lower than the limit.

$$S = \frac{PG}{4\pi R^2}$$

Where:

S = power density

P = output power (W)

G = power gain of the antenna in the direction of interest relative to an isotropic radiator

R = Separation distance between radiator and human body (m)

Systems operating under the provisions of this section shall be operated in a manner that ensures that the public is not exposed to radio frequency energy levels in excess of the following limits.

Compliance criteria

The worst case maximum exposure levels (Non Occupational) are given in Table 7 of the ARPANSA standard as shown below. The limits are given as Reference Levels which vary with the frequency. The General Public exposure category is applicable for this report.

ARPANSA Standard, Table 4: Reference levels for whole body exposure, averaged over 30 minutes, to RF electromagnetic fields from 100 kHz to 300 GHz (unperturbed rms values)

Exposure Category	Frequency range	Incident E-field Strength E_{inc} (V m ⁻¹)	Incident H-field Strength H_{inc} (A m ⁻¹)	Incident Power Density S_{inc} (W m ⁻²)
Occupational	0.1 - 6.943 MHz	ES	$4.9 / f_M$	N/A
	6.943 - 30 MHz	$660 / f_M^{0.7}$	$4.9 / f_M$	N/A
	30 – 400 MHz	61	0.16	10
	400 – 2000 MHz	$3 \times f_M^{0.5}$	$0.008 \times f_M^{0.5}$	$f_M / 40$
	2 – 300 GHz	N/A	N/A	50
General Public	0.1 – 6.27 MHz	ES	$2.2 / f_M$	N/A
	6.27 – 30 MHz	$300 / f_M^{0.7}$	$2.2 / f_M$	N/A
	30 – 400 MHz	27.7	0.073	2
	400 – 2000 MHz	$1.375 \times f_M^{0.5}$	$0.0037 \times f_M^{0.5}$	$f_M / 200$
	2 – 300 GHz	N/A	N/A	10

Note:

1. 'NA' signifies 'not applicable' and does not need to be taken into account when determining compliance.
2. 'ES' signifies that no reference level is available, as it would be greater than the reference level for spatial peak and temporal peak field strengths based on electrostimulation effects shown in Table 7.
3. f_M is frequency in MHz.
4. S_{inc} , E_{inc} and H_{inc} are to be averaged over 30 minutes, over the whole-body space. Temporal and spatial averaging of each of E_{inc} and H_{inc} must be conducted by averaging over the relevant square values (see ICNIRP 2020a for details).
5. For frequencies of 100 kHz to 30 MHz, regardless of the far-field/near-field zone distinctions, compliance is demonstrated if neither E_{inc} nor H_{inc} exceeds the above reference level values.
6. For frequencies of >30 MHz to 2 GHz:
 - a) within the far-field and radiating near field zones: compliance is demonstrated if either S_{inc} , E_{inc} or H_{inc} , does not exceed the above reference level values (only one is required); S_{eq} derived from either E_{inc} or H_{inc} may be substituted for S_{inc} ;
 - b) within the reactive near-field zone: compliance is demonstrated if both E_{inc} and H_{inc} do not exceed the above reference level values; S_{inc} cannot be used to demonstrate compliance, and so basic restrictions must be assessed.
7. For frequencies of >2 GHz to 300 GHz:
 - a) within the far-field and radiating near field zones: compliance is demonstrated if S_{inc} does not exceed the above reference level values; S_{eq} derived from either E_{inc} or H_{inc} may be substituted for S_{inc} ;
 - b) within the reactive near-field zone, reference levels cannot be used to determine compliance, and so basic restrictions must be assessed.

5 MPE ASSESSMENT

5.1 Output Power

Zigbee			
Mode	Low Channel	Middle Channel	High Channel
EIRP (dBm)	9.70	9.40	9.40
Note: This report listed the worst case EIRP power value, please refer to Report No. BL-SZ22B1234-601 for more details.			

5.2 Assessment Result

Mode	EIRP (dBm)	Distance (cm)	Power Density (W/m ²)	Limit of Power Density (W/m ²)	Verdict
Zigbee	9.700	20.000	0.019	10.000	Pass

5.3 Conclusion

This EUT is deemed to comply with the reference level limits by Council Recommendation Radiation Protection Series S-1 therefore the basic restrictions are compliant with human exposure limits.

Statement

1. The laboratory guarantees the scientificity, accuracy and impartiality of the test, and is responsible for all the information in the report, except the information provided by the customer. The customer is responsible for the impact of the information provided on the validity of the results.
2. The report without China inspection body and laboratory Mandatory Approval (CMA) mark has no effect of proving to the society.
3. For the report with CNAS mark or A2LA mark, the items marked with "☆" are not within the accredited scope.
4. This report is invalid if it is altered, without the signature of the testing and approval personnel, or without the "inspection and testing dedicated stamp" or test report stamp.
5. The test data and results are only valid for the tested samples provided by the customer.
6. This report shall not be partially reproduced without the written permission of the laboratory.
7. Any objection shall be raised to the laboratory within 30 days after receiving the report.

--END OF REPORT--