



# TEST REPORT

**Report No.** ..... : **CTC20230975E12**

**Applicant** ..... : **Lumi United Technology Co., Ltd**

**Address**..... : Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

**Manufacturer**..... : Lumi United Technology Co., Ltd

**Address**..... : Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

**Product Name** ..... : **Wireless Mini Switch T1**

**Trade Mark** ..... : **Aqara**

**Model/Type reference**..... : WB-R01

**Listed Model(s)** ..... : WXKG13LM, WXKG13LM-G0, WB-R02D

**Standard** ..... : **AS/NZS 2772.2: 2016 + Amd 1: 2018**

**Date of receipt of test sample...** : Apr. 16, 2019

**Date of testing**..... : Apr. 17, 2019 ~ Apr. 27, 2019 and  
Apr. 22, 2023 ~ Apr. 28, 2023

**Date of issue**..... : May. 04, 2023

**Result**..... : **PASS**

Compiled by:

(Printed name+signature)

Terry Su

*Terry Su*

Supervised by:

(Printed name+signature)

Eric Zhang

*Eric Zhang*

Approved by:

(Printed name+signature)

Totti Zhao

*Totti Zhao*

**Testing Laboratory Name** ..... : **CTC Laboratories, Inc.**

**Address**..... : 2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.



## Table of Contents

## Page

<b>1. TEST SUMMARY .....</b>	<b>3</b>
1.1. TEST STANDARDS.....	3
1.2. REPORT VERSION.....	3
1.3. TEST FACILITY .....	3
<b>2. GENERAL INFORMATION .....</b>	<b>4</b>
2.1. CLIENT INFORMATION .....	4
2.2. GENERAL DESCRIPTION OF EUT .....	4
<b>3. TEST ITEM AND RESULTS .....</b>	<b>5</b>
3.1. RF EXPOSURE.....	5





# 1. TEST SUMMARY

## 1.1. Test Standards

The tests were performed according to following standards:

[AS/NZS 2772.2: 2016 + Amd 1: 2018](#) – Radiofrequency fields, Part 2: Principles and methods of measurement and computation - 3 kHz to 300 GHz

## 1.2. Report version

Revised No.	Date of issue	Description
01	May. 04, 2023	Original

## 1.3. Test Facility

### CTC Laboratories, Inc.

Add: 2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

### Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

#### FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC) Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.



## 2. GENERAL INFORMATION

### 2.1. Client Information

Applicant:	Lumi United Technology Co., Ltd
Address:	Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China
Manufacturer:	Lumi United Technology Co., Ltd
Address:	Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

### 2.2. General Description of EUT

Product Name:	Wireless Mini Switch T1
Trade Mark:	Aqara
Model/Type reference:	WB-R01
Listed Model(s):	WXKG13LM, WXKG13LM-G0, WB-R02D
Model Difference:	All these models are identical in the same PCB, layout and electrical circuit, only named differently for marketing purpose.
Power supply:	3Vdc from button battery
Hardware version:	V1.0.1
Software version:	V1.0.1
<b>Technical index for Zigbee</b>	
Modulation:	O-QPSK
Operation frequency:	2405-2480MHz
Antenna type:	PCB Antenna
Antenna gain:	2dBi



### 3. TEST ITEM AND RESULTS

#### 3.1. RF Exposure

##### Limit

AS/NZS 2772.2: 2016 + Amd 1: 2018 APPENDIX E3.2

Exposure category	Frequency range	E-field strength (V/m rms)	H-field strength (A/m rms)	Equivalent plane wave power flux density $S_{eq}$ (W/m <sup>2</sup> )
Occupational	100 kHz – 1 MHz	614	$1.63/f$	—
	1 MHz – 10 MHz	$614/f$	$1.63/f$	$1000/f^2$ (see note 5)
	10 MHz – 400 MHz	61.4	0.163	10 (see note 5)
	400 MHz – 2 GHz	$3.07 \times f^{0.5}$	$0.00814 \times f^{0.5}$	$f/40$
	2 GHz – 300 GHz	137	0.364	50
General public	100 kHz – 150 kHz	86.8	4.86	—
	150 kHz – 1 MHz	86.8	$0.729/f$	—
	1 MHz – 10 MHz	$86.8/f^{0.5}$	$0.729/f$	—
	10 MHz – 400 MHz	27.4	0.0729	2 (see note 6)
	400 MHz – 2 GHz	$1.37 \times f^{0.5}$	$0.00364 \times f^{0.5}$	$f/200$
	2 GHz – 300 GHz	61.4	0.163	10

##### MPE Calculation Method

$$S = \frac{PG}{4\pi d^2}$$

Where:

S = power flux density, in watts per square meters

P = power transmitted, in watts

G = antenna gain

d = distance from antenna, in meters

$\pi$  : 3.1416

**Test Results**

Frequency (MHz)	Antenna Gain (dBi)	Maximum Power EIRP(dBm)	Tune up tolerance (dBm)	Max. Tune up Power (dBm)	d (m)	power flux density (W/m2)	Limit (W/m2) @ power flux density
2405	2	11.41	11±1	12	0.2	0.005	10
2440	2	11.67	11±1	12	0.2	0.005	10
2480	2	10.97	11±1	12	0.2	0.005	10

**Note**

For a more detailed features description, please refer to the RF Test Report.

\*\*\*\*\*THE END\*\*\*\*\*

