



TEST REPORT

Reference No...... : WTX25X05122823W003
Manufacturer..... : Lumi United Technology Co., Ltd.
Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370,
Address..... : Liuxian Avenue, Fuguang Community, Taoyuan Residential District,
Nanshan District, Shenzhen, China
Product Name..... : Smart Lock B50
Model No...... : DL-D12E
Standards..... : **AS/NZS 2772.2:2016+A1:2018**
Date of Receipt sample.... : 2025-05-14
Date of Test..... : 2025-05-14 to 2025-05-28
Date of Issue..... : 2025-05-28
Test Report Form No...... : WTX_AS/NZS 2772_2_2016W
Test Result..... : **Pass**

Remarks:

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

Prepared By:

Waltek Testing Group (Shenzhen) Co., Ltd.

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,
Block 70 Bao'an District, Shenzhen, Guangdong, China
Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

Dashan Chen

Dashan Chen/Project Engineer

Approved by:

Jason Su

Jason Su/Manager



TABLE OF CONTENTS

1. GENERAL INFORMATION.....	4
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 COMPLIANCE STANDARDS	6
1.3 TEST METHODOLOGY.....	6
1.4 TEST FACILITY	6
2. RF EXPOSURE REFERENCE LEVELS	7
2.1 STANDARD APPLICABLE.....	7
2.2 REFERENCE LEVELS LIMIT.....	7
2.3 EVALUATION METHODS	8
2.4 EVALUATION RESULTS.....	9
EXHIBIT 1 - EUT PHOTOGRAPHS.....	11

WALTEK



Report version

Version No.	Date of issue	Description
Rev.00	2025-05-28	Original
/	/	/

WALTEK



1. GENERAL INFORMATION

1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Smart Lock B50
Trade Name:	Aqara
Model No.:	DL-D12E
Adding Model(s):	/
Rated Voltage:	DC6V
Battery Capacity:	/
Power Adapter:	/
Software Version:	V2.5.3_0004
Hardware Version:	V1.0
<i>Note: The test data is gathered from a production sample, provided by the manufacturer.</i>	

WALTEK



Technical Characteristics of EUT	
Bluetooth	
Bluetooth Version:	Bluetooth V5.3(BLE Mode)
Frequency Range:	2402MHz-2480MHz
Max.RF Output Power:	1Mbps: 5.12dBm (EIRP) 2Mbps: 5.15dBm (EIRP)
Type of Modulation:	GFSK
Data Rate:	1Mbps, 2Mbps
Quantity of Channels	40
Channel Separation:	2MHz
Type of Antenna:	Internal Antenna
Antenna Gain:	1dBi
Wi-Fi(2.4GHz)	
Support Standards:	802.11b, 802.11g, 802.11n-HT20/40, 802.11ax-HE20/40
Frequency Range:	2412-2472MHz for 802.11b/g/n/ax(HT/HE20) 2422-2462MHz for 802.11n/ax(HT/HE40)
Max.RF Output Power:	16.34dBm (EIRP)
Type of Modulation:	CCK, OFDM, QPSK, BPSK, 16QAM, 64QAM
Quantity of Channels	13 for 802.11b/g/n/ax(HT/HE20) 9 for 802.11n/ax(HT/HE40)
Channel Separation:	5MHz
Type of Antenna:	Internal Antenna
Antenna Gain:	1dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	



1.2 Compliance Standards

The tests were performed according to following standards:

AS/NZS 2772.2:2016+A1:2018: Radiofrequency fields Part2: Principles and methods of measurement and measurement and computation-3 kHz to 300 GHz

EN IEC 62311:2020: Assessment of electronic and electrical equipment related to human exposure restrictions for electromagnetic fields (0Hz to 300GHz)

Maintenance of compliance is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained.

1.3 Test Methodology

All measurements contained in this report were conducted with EN 50665, The equipment under test (EUT) was configured to measure its highest possible emission level. For more detail refer to the Operating Instructions.

1.4 Test Facility

FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.



2. RF EXPOSURE REFERENCE LEVELS

2.1 Standard Applicable

This International Standard applies to electronic and electrical equipment for which no dedicated product- or product family standard regarding human exposure to electromagnetic fields applies. The frequency range covered is 0 Hz to 300 GHz.

The object of this generic standard is to provide assessment methods and criteria to evaluate such equipment against basic restrictions or reference levels on exposure of the general public related to electric, magnetic and electromagnetic fields and induced and contact current.

2.2 Reference Levels Limit

According to the EN 62311:2020, the criteria listed in the following table shall be used to evaluate the environmental impact of human exposure to radio-frequency (RF) radiation.

Reference levels of electric, magnetic, and electromagnetic fields
(0MHz to 300GHz, unperturbed rms values)

Frequency range	E-field strength (V/m)	H-field strength (A/m)	B-field (uT)	Equivalent plane wave power density S_{Eq} (W/m ²)
0-1Hz	—	3.2×10^4	4×10^4	—
1-8Hz	10000	$3.2 \times 10^4 / f^2$	$4 \times 10^4 / f^2$	—
8-25Hz	10000	$4000 / f$	$5000 / f$	—
0.025-0.8kHz	$250 / f$	$4 / f$	$5 / f$	—
0.8-3kHz	$250 / f$	5	6.25	—
3-150kHz	87	5	6.25	—
0.15-1MHz	87	$0.73 / f$	$0.92 / f$	—
1-10MHz	$87 / f^{1/2}$	$0.73 / f$	$0.92 / f$	—
10-400MHz	28	0.073	0.092	2
400-2000MHz	$1,375 f^{1/2}$	$0.0037 f^{1/2}$	$0.0046 f^{1/2}$	$f / 200$
2-300GHz	61	0.16	0.20	10

Note:

1. f as indicated in the frequency range column
2. For frequencies between 100 kHz and 10 GHz, S_{Eq} , E^2 , H^2 , and B^2 are to be averaged over any sixty-minute period.
3. For frequencies exceeding 10GHz, S_{Eq} , E^2 , H^2 , and B^2 are to be averaged over any $68/f^{1.05}$ -minute period (f in GHz).



Reference No.: WTX25X05122823W003

4. No E-field value is provided for frequencies < 1 Hz, which are effectively static electric fields. For most people the annoying perception of surface electric charges will not occur at field strengths less than 25 kV/m, Spark discharges causing stress or annoyance should be avoided.

2.3 Evaluation Methods

The antenna of the product, under normal use condition is at least 20 cm away from the body of the user. Warning statement to the user to keeping at least 20 cm separation distance and the prohibition of operating to a person has been printed on the user's manual. So, this product under normal use is located on electromagnetic far field between the human body.

Far Field Calculation Formula

$$E = \eta_0 H = \frac{\sqrt{30PG(\theta, \phi)}}{r}$$

G=antenna gain relative to an isotropic antenna

θ, ϕ =elevation and azimuth angles to point of investigation

r=distance from observation point to the antenna

η_0 =Characteristic impedance of free space

WALTEK



2.4 Evaluation Results

Mode/CH	Output Power (dBm)	Antenna Gain G(θ, φ)	min distance m	E-field Strength (V/m)	E-field Strength Limit (V/m)	Result Pass/Fail
802.11b/1	14.41	1.259	0.2	5.11	61.00	Pass
802.11b/7	15.34	1.259	0.2	5.68	61.00	Pass
802.11b/13	14.36	1.259	0.2	5.08	61.00	Pass
802.11g/1	12.77	1.259	0.2	4.23	61.00	Pass
802.11g/7	13.53	1.259	0.2	4.61	61.00	Pass
802.11g/13	12.83	1.259	0.2	4.26	61.00	Pass
802.11n-HT20/1	13.37	1.259	0.2	4.53	61.00	Pass
802.11n-HT20/7	14.11	1.259	0.2	4.93	61.00	Pass
802.11n-HT20/13	13.39	1.259	0.2	4.54	61.00	Pass
802.11ax-HE20/1	12.42	1.259	0.2	4.06	61.00	Pass
802.11ax-HE20/7	13.15	1.259	0.2	4.42	61.00	Pass
802.11ax-HE20/13	12.69	1.259	0.2	4.19	61.00	Pass
802.11n-HT40/3	12.79	1.259	0.2	4.24	61.00	Pass
802.11n-HT40/7	12.93	1.259	0.2	4.31	61.00	Pass
802.11n-HT40/11	12.51	1.259	0.2	4.10	61.00	Pass
802.11ax-HE40/3	12.55	1.259	0.2	4.12	61.00	Pass
802.11ax-HE40/7	12.85	1.259	0.2	4.27	61.00	Pass
802.11ax-HE40/11	12.36	1.259	0.2	4.03	61.00	Pass



Reference No.: WTX25X05122823W003

1Mbps

Mode/CH	Output Power (dBm)	Antenna Gain $G(\theta, \phi)$	min distance m	E-field Strength (V/m)	E-field Strength Limit (V/m)	Result Pass/Fail
BLE/00	4.02	1.259	0.2	1.54	61.00	Pass
BLE/19	4.12	1.259	0.2	1.56	61.00	Pass
BLE/39	2.69	1.259	0.2	1.32	61.00	Pass

2Mbps

Mode/CH	Output Power (dBm)	Antenna Gain $G(\theta, \phi)$	min distance m	E-field Strength (V/m)	E-field Strength Limit (V/m)	Result Pass/Fail
BLE/00	3.93	1.259	0.2	1.53	61.00	Pass
BLE/19	4.15	1.259	0.2	1.57	61.00	Pass
BLE/39	2.71	1.259	0.2	1.33	61.00	Pass

Note: $G(\theta, \phi) = 10^{(G/10)}$

Since the maximum E-field strength of this device based on 20cm separation distance cannot exceed the E-field strength of reference levels limit.

WALTEK



EXHIBIT 1 - EUT PHOTOGRAPHS

Please refer to “ANNEX_ASNZS”.

***** END OF REPORT *****

WALTEK