



# TEST REPORT

**Reference No.**..... : WTX25X06169770W004  
**Manufacturer**..... : Lumi United Technology Co., Ltd  
Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370,  
**Address**..... : Liuxian Avenue, Fuguang Community, Taoyuan Residential District,  
Nanshan District, Shenzhen, China  
**Product Name**..... : Light Switch H2 Horizontal (4 Buttons, 3 Channels), Light Switch H2  
Horizontal (2 Buttons, 2 Channels), Light Switch H2 Horizontal (2 Buttons, 1  
Channel)  
**Model No.**..... : WS-K14D, WS-K13D, WS-K12D  
**Standards**..... : **AS/NZS 2772.2:2016+A1:2018**  
**Date of Receipt sample**.... : 2025-06-27  
**Date of Test**..... : 2025-06-27 to 2025-07-28  
**Date of Issue**..... : 2025-07-28  
**Test Report Form No.**..... : WTX\_AS/NZS 2772\_2\_2016W  
**Test Result**..... : **Pass**

**Remarks:**

The results shown in this test report refer only to the sample(s) tested, this test report cannot be reproduced, except in full, without prior written permission of the company. The report would be invalid without specific stamp of test institute and the signatures of approver.

**Prepared By:**

**Waltek Testing Group (Shenzhen) Co., Ltd.**

Address: 1/F., Room 101, Building 1, Hongwei Industrial Park, Liuxian 2nd Road,  
Block 70 Bao'an District, Shenzhen, Guangdong, China

Tel.: +86-755-33663308 Fax.: +86-755-33663309 Email: sem@waltek.com.cn

Tested by:

*Dashan Chen*

Dashan Chen/ Project Engineer

Approved by:

*Jason Su*

Jason Su/Manager



## **TABLE OF CONTENTS**

<b>1. GENERAL INFORMATION.....</b>	<b>4</b>
1.1 PRODUCT DESCRIPTION FOR EQUIPMENT UNDER TEST (EUT).....	4
1.2 COMPLIANCE STANDARDS .....	6
1.3 TEST METHODOLOGY.....	6
1.4 TEST FACILITY .....	6
<b>2. RF EXPOSURE BASIC RESTRICTIONS.....</b>	<b>7</b>
2.1 STANDARD APPLICABLE.....	7
2.2 EVALUATION METHODS.....	8
2.3 EVALUATION RESULTS.....	8
<b>EXHIBIT 1 - EUT PHOTOGRAPHS.....</b>	<b>9</b>

# WALTEK



Report version

Version No.	Date of issue	Description
Rev.00	2025-07-28	Original
/	/	/

WALTEK





## 1. GENERAL INFORMATION

### 1.1 Product Description for Equipment Under Test (EUT)

General Description of EUT	
Product Name:	Light Switch H2 Horizontal (4 Buttons, 3 Channels), Light Switch H2 Horizontal (2 Buttons, 2 Channels), Light Switch H2 Horizontal (2 Buttons, 1 Channel)
Trade Name:	Aqara
Model No.:	WS-K14D
Adding Model(s):	WS-K13D, WS-K12D
Rated Voltage:	110-240VAC
Battery Capacity:	/
Adapter Model:	/
Software Version:	1.0.1.0
Hardware Version:	1.0.0.0
<i>Note: The test data is gathered from a production sample, provided by the manufacturer. The appearance of others models listed in the report is different from main-test model WS-K14D, but the circuit and the electronic construction do not change, declared by the manufacturer.</i>	



<b>Technical Characteristics of EUT</b>	
<b>Bluetooth</b>	
Bluetooth Version:	Bluetooth V5.0(LE Mode)
Frequency Range:	2402MHz-2480MHz
Max.RF Output Power:	1Mbps: 1.84dBm (EIRP) 2Mbps: 1.89dBm (EIRP)
Type of Modulation:	GFSK
Data Rate:	1Mbps, 2Mbps
Quantity of Channels	40
Channel Separation:	2MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	0dBi
<b>Zigbee</b>	
Frequency Range:	2405MHz-2480MHz
Max.RF Output Power:	7.24dBm (EIRP)
Modulation:	QPSK
Quantity of Channels:	16
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	0dBi
<b>Thread</b>	
Frequency Range:	2405MHz-2480MHz
Max.RF Output Power:	7.03dBm (EIRP)
Modulation:	QPSK
Quantity of Channels:	16
Channel Separation:	5MHz
Type of Antenna:	Integral Antenna
Antenna Gain:	0dBi
<i>Note: The Antenna Gain is provided by the customer and can affect the validity of results.</i>	



## 1.2 Compliance Standards

The tests were performed according to following standards:

**AS/NZS 2772.2:2016+A1:2018:** Radiofrequency fields Part2: Principles and methods of measurement and measurement and computation-3 kHz to 300 GHz

**EN 62479:2010:** Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz).

**Maintenance of compliance** is the responsibility of the manufacturer. Any modification of the product maybe which result in lowering the emission/immunity should be checked to ensure compliance has been maintained

## 1.3 Test Methodology

All measurements contained in this report were conducted with EN 62479, the equipment under test (EUT) was configured to measure its highest possible emission level. For more detail refer to the Operating Instructions.

## 1.4 Test Facility

### FCC – Registration No.: 125990

Waltek Testing Group (Shenzhen) Co., Ltd. Laboratory has been recognized to perform compliance testing on equipment subject to the Commissions Declaration Of Conformity (DOC). The Designation Number is CN5010, and Test Firm Registration Number is 125990.

### Industry Canada (IC) Registration No.: 11464A

The 3m Semi-anechoic chamber of Waltek Testing Group (Shenzhen) Co., Ltd. has been registered by Certification and Engineering Bureau of Industry Canada for radio equipment testing with Registration No.: 11464A.





## 2. RF EXPOSURE BASIC RESTRICTIONS

### 2.1 Standard Applicable

According to EN 62479:2010, Assessment of the compliance of low power electronic and electrical equipment with the basic restrictions related to human exposure to electromagnetic fields (10 MHz to 300 GHz).

#### Low-power exclusion level $P_{\max}$ based on considerations of SAR

When SAR is the basic restriction, a conservative minimum value for  $P_{\max}$  can be derived, equal to the localized SAR limit ( $SAR_{\max}$ ) multiplied by the averaging mass ( $m$ ):

$$P_{\max} = SAR_{\max} m \quad (A.1)$$

Example values of  $P_{\max}$  according to Equation (A.1) are provided in Table A.1 for cases described by the ICNIRP guidelines [1], IEEE Std C95.1-1999 [2] and IEEE Std C95.1-2005 [3] where SAR limits are defined. Other exposure guidelines or standards may be applicable depending on national regulations.

**Table A.1 – Example values of SAR-based  $P_{\max}$  for some cases described by ICNIRP, IEEE Std C95.1-1999 and IEEE Std C95.1-2005**

Guideline / Standard	SAR limit, $SAR_{\max}$ W/kg	Averaging mass, $m$ g	$P_{\max}$ mW	Exposure tier <sup>a</sup>	Region of body <sup>a</sup>
ICNIRP [1]	2	10	20	General public	Head and trunk
	4	10	40	General public	Limbs
	10	10	100	Occupational	Head and trunk
	20	10	200	Occupational	Limbs
IEEE Std C95.1-1999 [2]	1,6	1	1,6	Uncontrolled environment	Head, trunk, arms, legs
	4	10	40	Uncontrolled environment	Hands, wrists, feet and ankles
	8	1	8	Controlled environment	Head, trunk, arms, legs
	20	10	200	Controlled environment	Hands, wrists, feet and ankles
IEEE Std C95.1-2005 [3]	2	10	20	Action level	Body except extremities and pinnae
	4	10	40	Action level	Extremities and pinnae
	10	10	100	Controlled environment	Body except extremities and pinnae
	20	10	200	Controlled environment	Extremities and pinnae

<sup>a</sup> Consult the appropriate standard for more information and definitions of terms.



## 2.2 Evaluation Methods

Based on the above standard limit, the basic restriction at frequency between 10MHz to 300GHz is on localized SAR in the head. Any device with output power below 20mW cannot produce an exposure exceeding this restriction under the most pessimistic exposure conditions.

The basic restriction is 2W/Kg for general public device, so any unit which supplies less than 20mW from it's antenna port, averaged over 6 minutes, will meet the basic restriction.

## 2.3 Evaluation Results

Maximum Average Output Power

Modulation/ Frequency (MHz)	ERP/EIRP dBm	ERP/EIRP mW	Limit mW	Result Pass/Fail
BLE 1Mbps				
2402	1.84	1.5276	20	Pass
2440	0.5	1.1220	20	Pass
2480	1.4	1.3804	20	Pass
BLE 2Mbps				
2402	1.89	1.5453	20	Pass
2440	0.53	1.1298	20	Pass
2480	1.42	1.3868	20	Pass
Zigbee				
2405	6.57	4.5394	20	Pass
2440	6.3	4.2658	20	Pass
2480	7.24	5.2966	20	Pass
Thread				
2405	6.48	4.4463	20	Pass
2440	6.25	4.2170	20	Pass
2480	7.03	5.0466	20	Pass

Since average output power at worse case is: 5.2966mW which cannot exceed the exempt condition, 20mW specified in EN 62479. It is deemed to full fit the requirement of RF exposure basic restriction specified in EC Council Recommendation (1999/519/EC).





## EXHIBIT 1 - EUT PHOTOGRAPHS

---

Please refer to “ANNEX\_ASNZS”.

\*\*\*\*\* END OF REPORT \*\*\*\*\*

# WALTEK