



**CTC Laboratories, Inc.**



2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

Certificate #4340.01

Tel: +86-755- 27521059 Fax: +86-755- 27521011 Http://www.sz-ctc.org.cn

## TEST REPORT

**Report No.** ..... : CTC20230973E10

**Applicant** ..... : Lumi United Technology Co., Ltd

**Address**..... : Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

**Manufacturer**..... : Lumi United Technology Co., Ltd

**Address**..... : Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

**Product Name** ..... : Water Leak Sensor T1

**Trade Mark** ..... : Aqara

**Model/Type reference**..... : WLS-S01

**Listed Model(s)** ..... : SJCGQ12LM, SJCGQ12LM-G0, WL-S02D

**Standard** ..... : AS/NZS CISPR 32: 2015 + AMD 1: 2020

**Date of receipt of test sample**....: Apr. 20, 2023

**Date of testing**.....: Apr. 21, 2023 ~ Apr. 28, 2023

**Date of issue**.....: May. 04, 2023

**Result**.....: PASS

Compiled by:

(Printed name+signature) Terry Su

Supervised by:

(Printed name+signature) Eric Zhang

Approved by:

(Printed name+signature) Totti Zhao

**Testing Laboratory Name** ..... : CTC Laboratories, Inc.

**Address**..... : 2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China

This test report may be duplicated completely for legal use with the approval of the applicant. It should not be reproduced except in full, without the written approval of our laboratory. The client should not use it to claim product endorsement by CTC. The test results in the report only apply to the tested sample. The test report shall be invalid without all the signatures of testing engineers, reviewer and approver. Any objections must be raised to CTC within 15 days since the date when the report is received. It will not be taken into consideration beyond this limit. The test report merely correspond to the test sample.



## Table of Contents

	Page
<b>1. TEST SUMMARY .....</b>	<b>3</b>
1.1. TEST STANDARDS .....	3
1.2. REPORT VERSION .....	3
1.3. TEST DESCRIPTION .....	4
1.4. TEST FACILITY .....	5
1.5. MEASUREMENT UNCERTAINTY .....	5
1.6. ENVIRONMENTAL CONDITIONS .....	6
<b>2. GENERAL INFORMATION .....</b>	<b>7</b>
2.1. CLIENT INFORMATION .....	7
2.2. GENERAL DESCRIPTION OF EUT .....	8
2.3. ACCESSORY EQUIPMENT INFORMATION .....	9
2.4. DESCRIPTION OF TEST MODES.....	10
2.5. MEASUREMENT INSTRUMENTS LIST .....	11
<b>3. EMC EMISSION TEST .....</b>	<b>12</b>
3.1. RADIATED EMISSION.....	12
3.2. CONDUCTED EMISSION (AC MAINS) .....	18
3.3. CONDUCTED EMISSION (SIGNAL MAINS).....	19
<b>4. EUT TEST PHOTOS .....</b>	<b>20</b>
<b>5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL .....</b>	<b>21</b>



# 1. TEST SUMMARY

## 1.1. Test Standards

The tests were performed according to following standards:

[AS/NZS CISPR 32: 2015 + AMD 1: 2020](#) – Electromagnetic compatibility of multimedia equipment - Emission requirements

## 1.2. Report version

Revised No.	Date of issue	Description
01	May. 04, 2023	Original



### 1.3. Test Description

Emission			
Test Item	Standard requirement (AS/NZS CISPR 32)	Result	Test Engineer
Radiated Emission	A.2	Pass	Ice Lu
Conducted Emission(AC Mains)	A.3	N/A	N/A
Conducted Emission(Signal Mains)	A.3	N/A	N/A

Note: "N/A" is no application

The measurement uncertainty is not included in the test result.



## 1.4. Test Facility

### Address of the report laboratory

**CTC Laboratories, Inc.**

Add: 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Shenzhen, Guangdong, China

### Laboratory accreditation

The test facility is recognized, certified, or accredited by the following organizations:

#### A2LA-Lab Cert. No.: 4340.01

CTC Laboratories, Inc. EMC Laboratory has been accredited by A2LA for technical competence in the field of electrical testing, and proved to be in compliance with ISO/IEC 17025:2017 General Requirements for the Competence of Testing and Calibration Laboratories and any additional program requirements in the identified field of testing.

#### Industry Canada (Registration No.: 9783A, CAB Identifier: CN0029)

CTC Laboratories, Inc. EMC Laboratory has been registered by Certification and Engineer Bureau of Industry Canada for the performance of with Registration NO.: 9783A on Jan, 2016.

#### FCC (Registration No.: 951311, Designation Number CN1208)

CTC Laboratories, Inc. EMC Laboratory has been registered and fully described in a report filed with the (FCC)Federal Communications Commission. The acceptance letter from the FCC is maintained in our files. Registration 951311, Aug 26, 2017.

## 1.5. Measurement Uncertainty

The data and results referenced in this document are true and accurate. The reader is cautioned that there may be errors within the calibration limits of the equipment and facilities. The measurement uncertainty was calculated for all measurements listed in this test report acc. to TR-100028-01 " Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 1" and TR-100028-02 "Electromagnetic compatibility and Radio spectrum Matters (ERM);Uncertainties in the measurement of mobile radio equipment characteristics; Part 2 " and is documented in the CTC Laboratories, Inc. quality system acc. to DIN EN ISO/IEC 17025. Furthermore, component and process variability of devices similar to that tested may result in additional deviation. The manufacturer has the sole responsibility of continued compliance of the device.

Below is the best measurement capability for CTC Laboratories, Inc.



Test	Measurement Frequency Range	U (dB)	Note
Conducted Emission	9kHz ~ 30MHz	3.08	Main Power Port
Conducted Emission	150kHz ~ 30MHz	4.26	Telecommunication
Radiated Emission	30MHz ~ 1000MHz	4.51	3m chamber 2
Radiated Emission	30MHz ~ 1000MHz	4.5	3m chamber 3
Radiated Emission	1GHz ~ 6GHz	5.7	3m chamber 3

Note: This uncertainty represents an expanded uncertainty expressed at approximately the 95% confidence level using a coverage factor of k=2.

## 1.6. Environmental conditions

During the measurement the environmental conditions were within the listed ranges:

Normal Temperature:	25°C
Lative Humidity	55 %
Air Pressure	102kPa



## 2. GENERAL INFORMATION

### 2.1. Client Information

Applicant:	Lumi United Technology Co., Ltd
Address:	Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China
Manufacturer:	Lumi United Technology Co., Ltd
Address:	Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

---

CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cn



For anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



## 2.2. General Description of EUT

Product Name:	Water Leak Sensor T1
Trade Mark:	Aqara
Model/Type reference:	WLS-S01
Listed Model(s):	SJCGQ12LM, SJCGQ12LM-G0, WL-S02D
Model Difference:	All these models are identical in the same PCB, layout and electrical circuit, only named differently for marketing purpose.
Power supply:	3Vdc from button battery
Hardware version:	V1.0.1
Software version:	V1.0.1
<b>Zigbee</b>	
Modulation:	O-QPSK
Operation frequency:	2405MHz ~ 2480MHz



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cnFor anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



## 2.3. Accessory Equipment Information

<b>Equipment Information</b>			
Name	Model	S/N	Manufacturer
Aqara Hub	ZHWG17LM	/	Aqara
Mobile phone	P20 Pro	/	HUAWEI
Router	E8820 V3	---	ZTE

<b>Cable Information</b>			
Name	Shielded Type	Ferrite Core	Length
/	/	/	/



CTC Laboratories, Inc.

2/F., Building 1 and 1-2/F., Building 2, Jiaquan Building, Guanlan High-Tech Park, Longhua District, Shenzhen, Guangdong, China  
Tel.: (86)755-27521059 Fax: (86)755-27521011 Http://www.sz-ctc.org.cnFor anti-fake verification, please visit the official website of Certification and Accreditation Administration of the People's Republic of China : <http://yz.cnca.cn>



## 2.4. Description of Test Modes

Test mode	Normal Working + Zigbee
1	■

Note:

- is operation mode.

Test item	Test mode
Radiated Emission	T1
Conducted Emission(AC Mains)	N/A
Conducted Emission(Signal Mains)	N/A



## 2.5. Measurement Instruments List

Conducted Emission					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	LISN	R&S	ENV216	101112	Dec. 16, 2023
2	LISN	R&S	ENV216	101113	Dec. 16, 2023
3	EMI Test Receiver	R&S	ESCS30	100353	Dec. 16, 2023
4	ISN CAT6	Schwarzbeck	NTFM 8158	CAT6-8158-0046	Dec. 16, 2023
5	ISN CAT5	Schwarzbeck	NTFM 8158	CAT5-8158-0046	Dec. 16, 2023
6	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	102414	Dec. 16, 2023

Radiated Emission (3m chamber 2)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	9168-1013	Dec. 07, 2024
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-648	Dec. 07, 2024
3	Spectrum Analyzer	R&S	FSU26	100105	Dec. 16, 2023
4	Spectrum Analyzer	R&S	FSV40-N	101331	Mar. 14, 2024
5	Pre-Amplifier	SONOMA	310	186194	Dec. 16, 2023
6	Low Noise Pre-Amplifier	EMCI	EMC051835	980075	Dec. 16, 2023
7	Test Receiver	R&S	ESCI7	100967	Dec. 16, 2023
8	3m chamber 2	Frankonia	EE025	/	Oct. 23, 2024
9	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	102414	Dec. 16, 2023

Radiated Emission (3m chamber 3)					
Item	Test Equipment	Manufacturer	Model No.	Serial No.	Calibrated until
1	Trilog-Broadband Antenna	Schwarzbeck	VULB 9168	01026	Dec. 18, 2024
2	Horn Antenna	Schwarzbeck	BBHA 9120D	9120D-647	Dec. 01, 2024
3	Test Receiver	Keysight	N9038A	MY56400071	Dec. 16, 2023
4	Broadband Premplifier	SCHWARZBECK	BBV9743B	259	Dec. 16, 2023
5	Mirowave Broadband Amplifier	SCHWARZBECK	BBV9718C	111	Dec. 16, 2023
6	3m chamber 3	YIHENG	EE106	/	Sep. 09, 2023
7	Wideband Radio Communication Tester	Rohde & Schwarz	CMW500	102414	Dec. 16, 2023

Note: The Cal. Interval was one year.

### 3. EMC EMISSION TEST

#### 3.1. Radiated Emission

##### LIMIT


Please refer to CISPR 32 Table A.4 & A.5

Frequency range (MHz)	Quasi-peak limits dB $\mu$ V/m@3m	Quasi-peak limits dB $\mu$ V/m@10m
30~230	40	30
230~1000	47	37


Frequency range (GHz)	Average limits dB $\mu$ V/m@3m	Peak limits dB $\mu$ V/m@3m
1 ~ 3	50	70
3 ~ 6	54	74

#### TEST CONFIGURATION

(A) Radiated Emission Test Set-Up Frequency below 1 GHz



(B) Radiated Emission Test Set-Up Frequency above 1GHz



## TEST PROCEDURE


Please refer to CISPR 55032 Clause 6.3 for the measurement methods


## TEST MODE

Please refer to the Clause 2.4

## TEST RESULTS

## (1) 30MHz-1000MHz







No.	Frequency (MHz)	Reading (dB <sub>UV</sub> )	Factor (dB/m)	Level (dB <sub>UV</sub> /m)	Limit (dB <sub>UV</sub> /m)	Margin (dB)	Detector
1	36.7662	43.87	-17.81	26.06	40.00	-13.94	QP
2	110.5687	47.58	-20.10	27.48	40.00	-12.52	QP
3 *	184.4898	53.30	-19.14	34.16	40.00	-5.84	QP
4	209.3129	51.37	-20.08	31.29	40.00	-8.71	QP
5	233.3487	44.06	-19.21	24.85	47.00	-22.15	QP
6	651.9417	41.90	-9.79	32.11	47.00	-14.89	QP

Remark:

1. Factor (dB/m) = Antenna Factor (dB/m)+Cable Factor (dB)-Pre-amplifier Factor  
2. Margin value = Level -Limit value

## (2) Above 1000MHz





### 3.2. Conducted Emission (AC Mains)


#### LIMIT

Please refer to AS/NZS CISPR 32: 2015 Clause A.3

Frequency range MHz	Limits dB(μV)	
	Quasi-peak	Average
0,15 to 0,50	66 to 56	56 to 46
0,50 to 5	56	46
5 to 30	60	50

NOTE 1 The lower limit shall apply at the transition frequencies.  
 NOTE 2 The limit decreases linearly with the logarithm of the frequency in the range 0,15 MHz to 0,50 MHz.

#### TEST CONFIGURATION



Note: 1. Support units were connected to second LISN.  
 2. Both of LISNs (AMH) are 80 cm from EUT and at least 80 cm from other units and other metal planes

#### TEST PROCEDURE

Please refer to CENELEC EN 55032 Annex A3 Table A.8

#### TEST MODE

Please refer to the Clause 2.4

#### TEST RESULTS

Note: The test item is not applicable.

### 3.3. Conducted Emission (Signal Mains)


#### LIMIT

Please refer to AS/NZS CISPR 32: 2015 Clause A.11

Frequency range (MHz)	Voltage Limits dB(μV)		Current limits dB(μA)	
	Quasi-peak	Average	Quasi-peak	Average
0.15 ~ 0.5	84 ~ 74	74 ~ 64	40 ~ 30	30 ~ 20
0.5 ~ 30	74	64	30	20

**Note:** if "150Ω to 50Ω adaptor" applied, correction factor of 9.5dB should be added to the test data.

#### TEST CONFIGURATION



#### TEST PROCEDURE

Please refer to CENELEC EN 55032 section C4

#### TEST MODE

Please refer to the Clause 2.4

#### TEST RESULTS

Note: The test item is not applicable.

## 4. EUT TEST PHOTOS

Radiated Measurement (30MHz~1000MHz)





Radiated Measurement (1000~6000MHz)



## 5. PHOTOGRAPHS OF EUT CONSTRUCTIONAL


### External Photographs









## Internal photographs





\*\*\*\*\*THE END\*\*\*\*\*