

# Test Report

Verified code: 556823

Report No.: E202304209404-1

Customer: Lumi United Technology Co., Ltd

Address: Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

Sample Name: Presence Sensor FP2

Sample Model: PS-S02E

Receive Sample Date: Apr.25,2023

Test Date: Apr.25,2023 ~ Apr.27,2023

Reference Document: Radiocommunications (Electromagnetic Radiation — Human Exposure) Standard 2014 AS/NZS 2772.2:2016/Amdt 1:2018

Test Result: Pass

Prepared by: Chen Xiaocang

Reviewed by:

Jimmy Tan

Approved by: Zhao Zetian

GRG METROLOGY &amp; TEST GROUP CO., LTD.

Issued Date: 2023-04-28

GRG METROLOGY &amp; TEST GROUP CO., LTD.

Address: No.163, Pingyun Road, West of Huangpu Avenue, Guangzhou, Guangdong, China  
Tel: (+86) 400-602-0999 FAX: (+86) 020-38698685 Web: <http://www.grgtest.com>



## Statement

1. The report is invalid without "special seal for inspection and testing"; some copies are invalid; The report is invalid if it is altered or missing; The report is invalid without the signature of the person who prepared, reviewed and approved it.
2. The sample information is provided by the client and responsible for its authenticity; The content of the report is only valid for the samples sent this time.
3. When there are reports in both Chinese and English, the Chinese version will prevail when the language problems are inconsistent.
4. If there is any objection concerning the report, please inform us within 15 days from the date of receiving the report.
5. Without the agreement of the laboratory, the client is not authorized to use the test results for unapproved propaganda.

----- The following blanks -----

TABLE OF CONTENTS

1 GENERAL DESCRIPTION OF EUT..... 5

1.1 APPLICANT INFORMATION ..... 5

1.2 MANUFACTURER..... 5

1.3 BASIC DESCRIPTION OF EUT ..... 5

2 LABORATORY AND ACCREDITATIONS ..... 6

2.1 LABORATORY ..... 6

3 TECHNICAL REQUIREMENTS SPECIFICATION IN ..... 7

3.1 RF EXPOSURE EVALUATION..... 7

3.2 EVALUATION RESULTS..... 8

----- The following blanks -----

**REPORT ISSUED HISTORY**

Report Version	Report No.	Description	Compile Date
1.0	E202304209404-1	Original Issue	2023-04-28

- 1). The maximum output power of radar were refer to the report CR230422500-14 which issued on 04-27-2023 by China Certification ICT Co.,Ltd(Dongguan).
- 2). The maximum output power of BLE were refer to the report E20221124437601-2 which issued on 01-11-2023 by GUANGZHOU GRG METROLOGY & TEST CO., LTD.
- 3). The maximum output power of 2.4G WIFI were refer to the report E20221124437601-1 which issued on 01-10-2023 by GUANGZHOU GRG METROLOGY & TEST CO., LTD.

----- The following blanks -----

## 1 GENERAL DESCRIPTION OF EUT

### 1.1 APPLICANT INFORMATION

Name: Lumi United Technology Co., Ltd  
Address: Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

### 1.2 MANUFACTURER

Name: Lumi United Technology Co., Ltd  
Address: Room 801-804, Building 1, Chongwen Park, Nanshan iPark, No. 3370, Liuxian Avenue, Fuguang Community, Taoyuan Residential District, Nanshan District, Shenzhen, China

### 1.3 BASIC DESCRIPTION OF EUT

Product Name: Presence Sensor FP2  
Product Model: PS-S02E  
Adding Model: PS-S02D  
Trade Name: Aqara  
Models Difference: That EUT (Presence Sensor FP2) Model Numbers PS-S02E and PS-S02D have the same technical construction including circuit diagram, PCB layout, hardware version and software version identical, except sales area, packaging and accessories are different.  
Trade Name: Aqara  
Power Supply: DC 5V/1A  
Frequency Band: 2402MHz-2480MHz for Bluetooth LE with 1M  
2412MHz-2472MHz for 2.4G WIFI 802.11b/g/n HT20  
2422MHz-2462MHz for 2.4G WIFI 802.11n HT40  
60-63.35GHz&60.60-63.78GHz for Radar  
Antenna Specification: BLE&2.4GHz WIFI: FPC antenna with 1dBi gain (Max)  
Radar: Internal Integrated antenna with 5dBi gain (Max)  
Temperature Range: -10℃~40℃  
Hardware Version: X2  
Software Version: 1.0.0\_0004.0004  
Sample submitting way: ☒ Provided by customer ☐ Sampling  
Sample No: E20221124437601-0003, E20221124437601-0007, E20221124437601-0009  
Note: /

## 2 LABORATORY AND ACCREDITATIONS

### 2.1 LABORATORY

The tests & measurements refer to this report were performed by GRG METROLOGY & TEST GROUP CO., LTD.

Add.: No.1301 Guanguang Road Xinlan Community, Guanlan Street, Longhua District  
Shenzhen, 518110, People's Republic of China.

P.C.: 518110

Tel : 0755-61180008

Fax: 0755-61180008

----- The following blanks -----

### 3 TECHNICAL REQUIREMENTS SPECIFICATION IN

#### 3.1 RF EXPOSURE EVALUATION

The Australian Radiation Protection and Nuclear Safety Agency (ARPANSA) an agency of the (Australian) Commonwealth Department of Health has established a Radiation Protection Standard specifying limits for continuous exposure of the general public to RF fields shown in the following table.

**REFERENCE LEVELS FOR TIME AVERAGED EXPOSURE  
TO RMS ELECTRIC AND MAGNETIC FIELDS (UNPERTURBED)**

Exposure	Frequency range	<i>E</i> -field strength V/m rms	<i>H</i> -field strength A/m rms	Power flux density W/m <sup>2</sup>
Occupational (RF worker)	100 kHz–1 MHz	614	1.63/ <i>f</i>	N/A
	1 MHz–10 MHz	614/ <i>f</i>	1.63/ <i>f</i>	1000/ <i>f</i> <sup>2</sup>
	10 MHz–400 MHz	61.4	0.163	10
	400 MHz–2 GHz	$3.07 \times f^{0.5}$	$0.00814 \times f^{0.5}$	<i>f</i> /40
	2 GHz–300 GHz	137	0.364	50
Non-occupational (general public)	100 kHz–150 kHz	86.8	4.86	N/A
	150 kHz–1 MHz	86.8	0.729/ <i>f</i>	N/A
	1 MHz–10 MHz	$86.8/f^{0.5}$	0.729/ <i>f</i>	N/A
	10 MHz–400 MHz	27.4	0.0729	2.0
	400 MHz–2 GHz	$1.37 \times f^{0.5}$	$0.00364 \times f^{0.5}$	<i>f</i> /200
	2 GHz–300 GHz	61.4	0.163	10.0

**NOTES:**

- 1 *f* is frequency, in MHz.
- 2 There are also applicable limits for exposure to instantaneous rms electric and magnetic fields (unperturbed fields). These limits are less restrictive than the limits specified in Table I1 and as a result are not referenced in this measurement report.

----- The following blanks -----

### 3.2 EVALUATION RESULTS

Exposure Restrictions						
Mode	Max. Output Power (dBm)	Gain (dBi)	EIRP Power (dBm)	Frequency Band(MHz)	Power Density ( W/m <sup>2</sup> )	Limit of Power Density ( W/m <sup>2</sup> )
BLE-1M	5.94	1.00	6.94	2402-2480	0.010	10
2.4GWIFI-802.11b	15.01	1.00	16.01	2412-2472	0.080	10
2.4GWIFI-802.11g	11.02	1.00	12.02		0.030	10
2.4GWIFI-802.11n HT20	10.84	1.00	11.84		0.030	10
2.4GWIFI-802.11n HT40	10.14	1.00	11.14	2422-2462	0.030	10
Radar	6.75	5.0	11.75	60000-63780	0.03	10

Note:

- 1). The maximum output power of radar were refer to the report CR230422500-14 which issued on 04-27-2023 by China Certification ICT Co.,Ltd(Dongguan).
- 2). The maximum output power of BLE were refer to the report E20221124437601-2 which issued on 01-11-2023 by GUANGZHOU GRG METROLOGY & TEST CO., LTD.
- 3). The maximum output power of 2.4G WIFI were refer to the report E20221124437601-1 which issued on 01-10-2023 by GUANGZHOU GRG METROLOGY & TEST CO., LTD.
- 4). The field calculation does not take into account the antenna size, which is assumed to be a point source. An ideal isotropic antenna is used as a reference to compare the performance of practical antennas:  $P$  watts is radiated, from a point, uniformly over the surface of sphere of radius  $R$ . Assumed use distance from EUT to Human, **20 cm** separation distance warning is required.

The Formula

$$S = \frac{P}{4\pi R^2}$$

Whereas,

$S$  = power density

$R$ =distance from observation point to the antenna (m)

$P$ = The maximum e.i.r.p of the transmitter (W) .

In this section, the power density at 20 cm location is calculated to examine if it is lower than the limit.

**For simultaneously transmit system According to EN62311:2008 sections 8.5 Frequency range from 3 kHz – 300GHz (IEEE-based):**

When multiple sources are introduced into an environment, it becomes necessary to address the sources interdependently, since each source will contribute some percentage of the ME toward the total exposure at a fixed location. The sum of the ratios of the exposure from each source (expressed as a plane-wave equivalent power density) to the corresponding ME for the frequency of each source is evaluated. The exposure complies with the ME if the sum of the ratios is less than unity, i.e.,

$$\sum_{i=1}^n \frac{S_{E_i} (\text{duty factor})}{MPE_{E_i}} < 1$$

and

$$\sum_{i=1}^n \frac{S_{H_i} (\text{duty factor})}{MPE_{H_i}} < 1$$

For the calculated power density should comply with:

$$\sum_{i=1}^n \frac{S_i}{MPE_i} < 1$$

The BLE and WiFi do not support simultaneous transmission, the BLE and radar do not support simultaneous transmission, the wifi and radar support simultaneous.

The worst case:

Max. WWAN + Max. Radar:

Power Density of 2.4GWIFI-802.11b/ Limit of Power Density of 2.4GWIFI-802.11b + Power Density of Radar/

Limit of Power Density of Radar =  $0.08 (\text{W/m}^2) / 10 (\text{W/m}^2) + 0.03 (\text{W/m}^2) / 10 (\text{W/m}^2) = 0.01 < 1$

The sum of the MPE ratios is less than 1, the test result is passed.

----- End of Report -----