

Deploying to Cloud Run

Introduction

Cloud Run vs Agent Engine

In Part 2, you deployed to Agent Engine—the simplest path for ADK agents. This part shows Cloud Run as an alternative.

Factor	Agent Engine	Cloud Run
Ease of use	Easiest (one command)	Moderate
Session service	Automatic	Manual configuration
Web UI	Cloud Console only	Can include web UI
Best for	Standard ADK agents	Custom needs, UI deployment

Decision rule: Default to Agent Engine. Use Cloud Run when you need:

- Web UI deployed with agent (`--with_ui`)
- Custom container configuration
- Existing Cloud Run infrastructure



Deploying to Cloud Run

Basic deployment

Shell

```
adk deploy cloud_run \  
  --project=$GOOGLE_CLOUD_PROJECT \  
  --region=$GOOGLE_CLOUD_LOCATION \  
  --service_name=my-agent \  
  --with_ui \  
  /path/to/agent
```

Parameters:

- **--project**: Your Google Cloud project
- **--region**: Deployment region (e.g., us-central1)
- **--service_name**: Name for Cloud Run service
- **--with_ui**: Include web interface (optional but recommended)
- **/path/to/agent**: Your agent directory

What happens

- 1 ADK packages your agent code
- 2 Generates container image
- 3 Deploys to Cloud Run
- 4 Returns public URL

Deployment time: ~5-8 minutes

