Assignment Submission

Name: Omkar Patil
Email: omptil3559@gmail.com
Assignment: JSONLogic Implementation
Submitted to: Drona Pay

I have completed the assignment as per the given instructions.
I wrote and tested the JSONLogic code.
Initially, I tried running it on the given JSONLogic testing website, but it did not work properly.
So, I tested the logic using another method and confirmed the correct output.

Task 1 (Code) =

File Edit Selection View ···

JS Drona_Pay_Task1.js

C: > Users > Omkar > Downloads > JS Drona_Pay_Task1.js > ...

```javascript
// Task A - String Logic
function checkStrings(var1, var2) {

  // Check if var2 is part of var1
  if (var1.includes(var2)) {
    return var1;
  }

  // Check if var1 is part of var2
  else if (var2.includes(var1)) {
    return var2;
  }

  // If none of the above conditions match
  else {
    return "neither variable is a part of other";
  }
}

// Test cases for Task A
console.log("Task A Results:");
console.log(checkStrings("sat@google.com", "google.com"));
console.log(checkStrings("hello", "hello world"));
console.log(checkStrings("abc", "xyz"));
```

Task 1 (Output) =

```
PROBLEMS    DEBUG CONSOLE    OUTPUT    TERMINAL    PORTS    POSTMAN CONSOLE

PS C:\Users\Omkar> node "c:\Users\Omkar\Downloads\Drona_Pay_Task1.js"
Task A Results:
sat@google.com
hello world
neither variable is a part of other
PS C:\Users\Omkar>
```

This logic checks the required conditions and returns the expected result.

Task 1 (Logic Explanation)=

This logic checks whether var1 is a substring of var2 or var2 is a substring of var1.
If var1 is found inside var2, then return var1.
If var2 is found inside var1, then return var2.
If neither is a part of the other, return "neither variable is a part of other".

Task 2 (Code) =

File Edit Selection View ···

JS Drona_Pay_Task2.js

C: > Users > Omkar > Downloads > JS Drona_Pay_Task2.js > getScore

```javascript
// Task B - Score Logic
function getScore(transactionamount, transactioncount) {

  // Case 1: both less than threshold
  if (transactionamount < 1000 && transactioncount < 5) {
    return 0;
  }

  // Case 2: medium range
  else if (
    transactionamount >= 1000 &&
    transactionamount < 10000 &&
    transactioncount >= 5 &&
    transactioncount < 10
  ) {
    return 50;
  }

  // Case 3: high values
  else {
    return 100;
  }
}

// Test cases for Task B
console.log("\nTask B Results:");
console.log(getScore(500, 3));      // 0
console.log(getScore(5000, 7));     // 50
console.log(getScore(20000, 15));   // 100
```

Task 2 (Output) =

```
PROBLEMS    DEBUG CONSOLE    OUTPUT    TERMINAL    PORTS    POSTMAN CONSOLE

PS C:\Users\Omkar> node "c:\Users\Omkar\Downloads\Drona_Pay_Task2.js"

Task B Results:
0
50
100
PS C:\Users\Omkar>
```

This logic checks the required conditions and returns the expected result.

Task 2 (Logic Explanation)=

This logic calculates a score based on transactionamount and transactioncount.
If transactionamount is less than 1000 and transactioncount is less than 5, the score is 0.
If transactionamount is between 1000 and 10000 and transactioncount is between 5 and 10, the score is 50.
Otherwise, the score is 100.

Thank you for the opportunity.

Regards,
Omkar Patil