# Hadoop 程序编写

上海交通大学 OmniLab http://omnilab.sjtu.edu.cn

2013年11月27日更新

## 目录

1	Had	loop MapReduce 运行的一般过程	2
2	使用 Java 编写 Hadoop MapReduce 程序		
	2.1	示例程序运行	2
		2.1.1 示例代码WordCount.java	2
		2.1.2 编译 Java 程序代码	3
		2.1.3 准备数据	4
		2.1.4 运行作业	4
	2.2	程序模块说明	6
	2.3	初步优化建议	7
3	使用	Python 编写 Hadoop MapReduce 程序	7
4	使用	I C++ 编写 Hadoop MapRedducech 程序	7
5	TOI	00	7
6	参考	·····································	7

## 1 Hadoop MapReduce 运行的一般过程

## 2 使用 Java 编写 Hadoop MapReduce 程序

### 2.1 示例程序运行

#### 2.1.1 示例代码WordCount.java

```
package org.myorg;
import java.io.IOException;
import java.util.*;
import org.apache.hadoop.fs.Path;
import org.apache.hadoop.conf.*;
import org.apache.hadoop.io.*;
import org.apache.hadoop.mapred.*;
import org.apache.hadoop.util.*;
public class WordCount {
    public static class Map extends MapReduceBase implements Mapper<LongWritable
      private final static IntWritable one = new IntWritable(1);
      private Text word = new Text();
     public void map(LongWritable key, Text value,
OutputCollector<Text, IntWritable> output, Reporter reporter) throws IOException {
        String line = value.toString();
        StringTokenizer tokenizer = new StringTokenizer(line);
        while (tokenizer.hasMoreTokens()) {
          word.set(tokenizer.nextToken());
          output.collect(word, one);
     }
    public static class Reduce extends MapReduceBase implements Reducer<Text, IntWritable,
Text, IntWritable> {
      public void reduce(Text key, Iterator<IntWritable> values,
```

```
OutputCollector<Text, IntWritable> output, Reporter reporter) throws IOException {
    int sum = 0;
    while (values.hasNext()) {
      sum += values.next().get();
    output.collect(key, new IntWritable(sum));
}
public static void main(String[] args) throws Exception {
  JobConf conf = new JobConf(WordCount.class);
  conf.setJobName("wordcount");
  conf.setOutputKeyClass(Text.class);
  conf.setOutputValueClass(IntWritable.class);
  conf.setMapperClass(Map.class);
  conf.setCombinerClass(Reduce.class);
  conf.setReducerClass(Reduce.class);
  conf.setInputFormat(TextInputFormat.class);
  conf.setOutputFormat(TextOutputFormat.class);
  FileInputFormat.setInputPaths(conf, new Path(args[0]));
  FileOutputFormat.setOutputPath(conf, new Path(args[1]));
  JobClient.runJob(conf);
}
```

#### 2.1.2 编译 Java 程序代码

检查环境变量CLASSPATH是否设置为 CDH4 对应的位置:

```
$ echo $CLASSPATH
/opt/cloudera/parcels/CDH/lib/hadoop/*:/opt/cloudera/parcels/CDH/lib/hadoop/client-0.20/*:
```

编译代码:

```
$ mkdir wordcount_classes
```

```
$ javac -d wordcount_classes WordCount.java
```

生成 Jar 包:

```
$ jar -cvf wordcount.jar -C wordcount_classes/ .
```

#### 2.1.3 准备数据

随便抓取一些文本数据作为WordCount程序的输入。输入数据需要从本地复制到 HDFS 中。

```
$ mkdir input
$ curl http://www.sjtu.edu.cn > input/file01.txt
$ curl http://net.sjtu.edu.cn > input/file02.txt
$ hdfs dfs -mkdir /user/jianwen/wordcount
$ hdfs dfs -copyFromLocal input /user/jianwen/wordcount/input
$ hdfs dfs -ls /user/jianwen/wordcount/input
Found 2 items
-rw-r--r- 3 jianwen hadoop 74758 2013-11-21 14:35 /user/jianwen/wordcount/input/file01.txt
-rw-r--r- 3 jianwen hadoop 33553 2013-11-21 14:35 /user/jianwen/wordcount/input/file02.txt
```

#### 2.1.4 运行作业

使用hadoop命令提交作业,在参数中指定 jar 包、Java 主类、输入文件夹、输出文件夹。

```
$ hadoop jar wordcount.jar org.myorg.WordCount \
/user/jianwen/wordcount/input /user/jianwen/wordcount/output
```

运行很快就能完成,在运行过程中显示的作业信息如下:

```
13/11/21 14:38:41 WARN mapred.JobClient: Use GenericOptionsParser for parsing the arguments. Appli 13/11/21 14:38:41 INFO mapred.FileInputFormat: Total input paths to process: 2 13/11/21 14:38:41 INFO mapred.JobClient: Running job: job_201311150128_0050 13/11/21 14:38:42 INFO mapred.JobClient: map 0% reduce 0% 13/11/21 14:38:48 INFO mapred.JobClient: map 100% reduce 0% 13/11/21 14:38:53 INFO mapred.JobClient: map 100% reduce 41%
```

```
13/11/21 14:38:54 INFO mapred.JobClient: map 100% reduce 100%
13/11/21 14:38:55 INFO mapred.JobClient: Job complete: job_201311150128_0050
13/11/21 14:38:55 INFO mapred.JobClient: Counters: 33
13/11/21 14:38:55 INFO mapred.JobClient:
                                           File System Counters
13/11/21 14:38:55 INFO mapred.JobClient:
                                             FILE: Number of bytes read=56585
13/11/21 14:38:55 INFO mapred.JobClient:
                                             FILE: Number of bytes written=25028678
13/11/21 14:38:55 INFO mapred.JobClient:
                                             FILE: Number of read operations=0
13/11/21 14:38:55 INFO mapred.JobClient:
                                             FILE: Number of large read operations=0
13/11/21 14:38:55 INFO mapred.JobClient:
                                             FILE: Number of write operations=0
13/11/21 14:38:55 INFO mapred.JobClient:
                                             HDFS: Number of bytes read=120091
13/11/21 14:38:55 INFO mapred.JobClient:
                                             HDFS: Number of bytes written=51565
13/11/21 14:38:55 INFO mapred.JobClient:
                                             HDFS: Number of read operations=150
13/11/21 14:38:55 INFO mapred.JobClient:
                                             HDFS: Number of large read operations=0
13/11/21 14:38:55 INFO mapred.JobClient:
                                             HDFS: Number of write operations=288
13/11/21 14:38:55 INFO mapred.JobClient:
                                           Job Counters
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Launched map tasks=3
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Launched reduce tasks=144
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Data-local map tasks=3
                                             Total time spent by all maps in occupied slots (ms)=9
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Total time spent by all reduces in occupied slots (ms
13/11/21 14:38:55 INFO mapred.JobClient:
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Total time spent by all maps waiting after reserving
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Total time spent by all reduces waiting after reservi
13/11/21 14:38:55 INFO mapred.JobClient:
                                           Map-Reduce Framework
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Map input records=1468
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Map output records=5378
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Map output bytes=121396
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Input split bytes=399
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Combine input records=5378
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Combine output records=1891
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Reduce input groups=1587
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Reduce shuffle bytes=69083
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Reduce input records=1891
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Reduce output records=1587
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Spilled Records=3782
13/11/21 14:38:55 INFO mapred.JobClient:
                                             CPU time spent (ms)=196290
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Physical memory (bytes) snapshot=42758049792
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Virtual memory (bytes) snapshot=238107385856
13/11/21 14:38:55 INFO mapred.JobClient:
                                             Total committed heap usage (bytes)=146269863936
13/11/21 14:38:55 INFO mapred.JobClient:
                                           org.apache.hadoop.mapreduce.lib.input.FileInputFormatCo
```

可以在 HDFS 上直接查看运行结果, 当然还也可以把结果复制到本地。

BYTES\_READ=108311

13/11/21 14:38:55 INFO mapred.JobClient:

### 2.2 程序模块说明

使用 Java 开发 Hadoop 应用程序,使用的主要的类包括:

- Input and Output
- Mapper
- Reducer
- Partitioner
- Reporter
- OutputCollector

除此以外, Hadoop 还包含一个辅助工具包lib, 提供作业管理、数据分割、数据合并等辅助功能。

### 2.3 初步优化建议

- 3 使用 Python 编写 Hadoop MapReduce 程序
- 4 使用 C++ 编写 Hadoop MapRedducech 程序

### 5 TODO

- 在命令行, 而不是代码中指定这些参数: 作业名、并行 Mapper/Reducer 数量;
- Java Makefile http://geosoft.no/development/javamake.html

## 6 参考资料

- Cloudera Hadoop Tutorial http://www.cloudera.com/content/cloudera-content/cloudera-docs/HadoopTutorial/CDH4/Hadoop-Tutorial.html
- Apache Hadoop Commands Guide http://hadoop.apache.org/docs/r1.2.1/commands\_manual.html
- Java Doc: Package org.apache.hadoop.mapred.lib http://hadoop.apache.org/docs/current/api/org/apache/hadoop/mapred/lib/package-summary.html