OMNIVERSAL ARCHITECT LABS — CURRENCY LABORATORY

Pilot Packet 001

Resource-Box Capability-and-Accounting Discriminator, with an Undefined-versus-Incoherent Companion Case

Document ID	OAL-CURR-PPLX-PILOT-001 (qualified ID: perplexity/pilot-packet-001-v0.1)
Version / date	Version 0.1 — November 7, 2026
Prepared by	Perplexity, member of the OAL AI collaboration team
Generation platform	Perplexity Computer. The platform reports the underlying model for this session as Claude Opus 5.5 (Anthropic). See Section 12 for why that matters.
Requested by	The OAL project owner
Status	PROPOSED. Not owner-adopted. Not locked for testing. Pre-canon.
Responds to	OAL-CURR-NEXT-001 v1.0 and the compiled file "OAL Currency Laboratory Pilot Recommendations" (November 2026)
Companion documents	OAL-CURR-PPLX-PILOT-001-REF (sealed reference execution report — do not circulate to analysts before their first-pass record is submitted); OAL-CURR-PPLX-BOUNDARY-001 (independent ten-case boundary pass)
Formats	DOCX (editable master) and PDF (distribution copy) of the same text. The two formats are editions of one document, not two pieces of evidence.

1. Purpose of this packet

In my recommendation to directive OAL-CURR-NEXT-001, I said the single most useful next step was a short, owner-adoptable Pilot Packet 001 that another reviewer could run without inventing rules. This document is that packet. It contains the exact pilot question, a closed fixture, seven declared capability configurations, eleven cases, a completion predicate, a list of prohibited substitutions, a status vocabulary, evidence labels, a run-record template, an independence protocol, and an adoption record that stays blank until the project owner fills it in.

The packet is deliberately narrow. It tests whether the laboratory can specify a transaction, carry it out (by derivation or by execution), and report the result in a way that other analysts can compare. It does not test whether Quantum Credits are viable, which instrument should win, or whether any extraordinary capability exists outside a model. A configuration that is given the power to create units will create them; observing that is a consequence of the stipulation, not a discovery.

What this packet is not

- It is not an adoption decision. Your instruction to proceed with my recommendation authorizes me to prepare the packet. It does not adopt the packet, and I have not marked anything as adopted.

- It is not a merged team protocol. It is my proposal. Other members may run it, decline it, or run their own run cards. Where I took an idea from another member, I say so in Section 2.
- It does not contain expected results. Results from my own reference model are in a separate sealed report so that this packet can be used for blind first-pass runs.
- It does not activate 1COIN or NCOIN. Settlement is recorded as an ordinary log entry and no consequence model is active. Both instruments are deferred to a later pilot by design, not dismissed.

2. Relationship to the other members' recommendations

I read the full compiled recommendations file. It contains sections from ChatGPT, Claude, Google Gemini, Grok, and my own earlier response. It does **not** contain a section from Microsoft Copilot. I have not assumed what Copilot recommended. If Copilot's recommendation exists elsewhere, it should be added to the record and checked against this packet.

Five members, including me, independently converged on the same first case — the resource box with A holding 10 units, B holding 0, and a request to deliver 3. That convergence is not evidence that the case is correct; all of us drew on the same earlier documents, so the agreements are correlated. It does mean the packet is not asking anyone to test something unfamiliar.

I incorporated, with attribution, the following ideas from other members because they improved the packet on its own terms, not to build consensus:

- **ChatGPT — two separate verdicts.** Each run reports Verdict A (internal consistency under the declared rules) and Verdict B (whether the requested outcome was achieved). This keeps an evaluation-only configuration from being called contradictory simply because it does not deliver.
- **Claude — the "3 of what?" perturbation.** Case P001-F01-e removes the unit type from the request. I had not included it; it tests whether a configuration fills a gap silently.
- **Claude — blind first pass in a fresh session**, with each record listing its inputs. I had recommended collecting responses before peer circulation; Claude's version is more concrete, so I used it.
- **Gemini — a typed, key-value output block.** I had cautioned against treating structured exception objects as null tokens. I still hold that position, but a typed reporting block is not a token. Section 10 uses typed fields and states plainly that a record is not an asset.

I did not adopt the following, and I explain why in Section 13:

- Gemini's inclusion of F04 (no seller versus unknown seller) and F05 (authorization) in the first batch. They are good cases, but they belong to a second packet. Claude and Grok also argued for keeping the first batch to two cases.
- Gemini's proposed canonical renumbering (LAB-F01 and so on). I keep pilot-local IDs that point back to their sources without asserting that cases in different charters are equivalent.
- Claude's proposal to merge OWNER-ADOPTED and LOCKED FOR TESTING into one status. I keep them separate, for reasons given in Section 3.

3. Status ladder and how this packet becomes testable

Every rule in this packet is PROPOSED until the owner signs the adoption record in Table 7. I use five statuses. PROPOSED means available for criticism and not adopted. OWNER-ADOPTED means the owner has accepted the packet for a stated scope, for example "Pilot 001 first-pass runs only." LOCKED FOR TESTING means a specific revision (for example v0.1) has been frozen and a named run is using it. SUPPORTED WITHIN RUN

means a specific claim held up in a specific run at a stated evidence level. CONSTITUTIONALLY ADOPTED means the owner has accepted a rule into the architecture itself.

Claude argued that OWNER-ADOPTED and LOCKED FOR TESTING describe one event. I think they can come apart in practice. The owner may adopt the packet's scope today, and then a defect found during the first run may require a v0.2 revision; the adoption of scope survives, but the lock attaches to whichever revision a run used. Keeping them separate lets a run record say exactly which frozen text it used.

Claude also argued that "experimentally supported" invites an empirical reading. I accept that criticism. In this packet the label is SUPPORTED WITHIN RUN, and it must always carry its evidence level (Section 9). A claim can be SUPPORTED WITHIN RUN at the derived or executed level and still say nothing about the real world.

Support is a property of a claim, not a step on a road to canon. An owner may adopt something that was never supported, and a supported claim may never be adopted.

4. The pilot question

> **Pilot question PQ-001.** Given a closed fixture in which party A holds 10 identifiable units of resource type R and party B holds none, and a request REQ-1 that B receive 3 additional usable units of R, what does each declared configuration do; does its behavior satisfy its own declared rules (Verdict A); does it satisfy the completion predicate CP-001 (Verdict B); and which configurations can or cannot be told apart by what the fixture lets an observer see?

The last clause matters most. If two configurations leave the world in the same observable state, the honest report is that they are observationally indistinguishable in this case. An analyst must not invent an invisible mechanism to keep them apart.

5. Fixture F-001

The fixture is closed. Nothing exists except what is listed here. If an analyst needs something else to make a configuration work, that need is itself a finding and must be reported, not supplied.

- **Resource type.** Exactly one type is declared: R. A request for any other type, or for an unstated type, refers to nothing in the fixture.
- **Parties.** A and B. No third party, reserve, pool, issuer, or treasury exists.
- **Initial state at t0.** A holds 10 units of R with identifiers A01 through A10. B holds no units. All units are unencumbered and usable.
- **Unit identity.** Every unit has an identifier and an origin label. Fixture units have origin "fixture." A configuration that brings a unit into existence must give it a new identifier and declare its origin label.
- **Usability.** A unit is usable if it is of type R, held by its holder, and not encumbered (not pledged, frozen, or reserved).
- **Consent.** In the baseline, A consents to give up units. Consent is a property of A only. The fixture does not define who, if anyone, authorizes the creation of new units; see Section 8, rule R-AUTH.
- **Consequences.** None. No fees, losses, harms, or externalities exist in the baseline. No consequence model is active, so no NCOIN can be emitted.
- **Time.** The request is evaluated at t0 and the resulting state is read at t1. There are no intermediate observers.

- **Definitional identity.** "Total" means the number of units held by A plus the number held by B. This is true by definition. It is not a conservation law. A creation configuration may change the total; nothing can make the total differ from the sum of holdings without changing what "total" means.

The distinction in the last item is the most important thing in the fixture. Conservation is a property some configurations have and others do not. A definitional identity holds in every configuration because it is part of the vocabulary. Case P001-F03-I2 relies on this distinction.

6. Synthetic valuation convention VC-001

Quantum Credits rest on the protected premise that a credit evaluates relative to its target, written QC(T) = V(T). The pilot needs some value for V(T) so that the evaluation-only configuration has something to return. For this pilot only, V(REQ-1) is declared to be 3 synthetic R-equivalence units: one valuation unit per unit of R delivered.

This convention is a placeholder. It is not a claim about how QC values anything, and it must not be carried into any other pilot without a new decision. It is labeled E0 (stipulated) wherever it appears in a record.

7. Configurations

A configuration is a complete statement of what QC is assumed to be able to do in this run. Seven are declared. They are different assumed systems, not seven attempts to discover one true system. An analyst may add a configuration only by giving it a new ID and declaring every field in Table 2; an analyst may not change a declared configuration mid-run. If a declared configuration cannot be run as written, the result is UNDERSPECIFIED_CONFIG, not a quiet repair.

C-EVAL — evaluation only

QC returns a value description for the target under VC-001. It moves nothing. Its success condition is that a value description is returned and the world is unchanged.

C-XFER — atomic transfer of existing units

QC moves existing units from A to B, if A has consented and holds enough. Transfers are atomic: if a fault interrupts delivery, every unit already moved is returned to A and the status is FAILED_ROLLED_BACK. A transfer must not change the total, and A's debit must equal B's credit.

C-XFER-NA — non-atomic transfer

Identical to C-XFER, except that a fault leaves whatever was already moved where it is, with status PARTIAL. This configuration exists because the choice between atomic and non-atomic delivery is a design decision, not a discovery, and the pilot should show its effect.

C-CREATE — creation of new units

QC brings new units of R into existence in B's holdings under an explicitly assumed creation primitive. A is untouched. New units receive identifiers and the origin label "minted." If a fault interrupts creation, units already created remain and the status is PARTIAL; this no-rollback rule is a stipulation and is labeled E0.

C-ENACT-U — enactment with no side-effect rule

QC establishes the target state "B has gained 3 usable units of R," and nothing else is specified. This configuration represents the bare idea of enactment as it often appears in the earlier documents. The

packet's position is that it cannot be run as written, because the target state does not say what happens to A, to the total, or to the origin of B's units. A faithful record will say so. An analyst who believes it can be run must state the extra rule that made it runnable — at which point it has become a different configuration.

C-ENACT-M — enactment with a minimal-change rule

QC establishes the target state, and every variable not named in the target state is frozen. A is therefore unchanged. B's new units receive the origin label "enacted."

C-ENACT-S — enactment of a target state that names the source

QC establishes the target state "B has gained 3 usable units of R and A has lost 3 units of R." Holdings cannot be negative, by definition. Transfers under this configuration are atomic.

8. Cases

Every configuration is run against every case. A case changes the fixture or the request in one controlled way. Cases are listed here without results. Table 3 at the end gives the precise inputs.

Resource-box cases (F01 family)

- **P001-F01-BASE.** The baseline fixture and REQ-1.
- **P001-F01-a — insufficient source.** A starts with 2 units instead of 10. Tests whether a configuration that depends on A's inventory reports the shortfall, and whether any configuration silently draws on a pool that does not exist.
- **P001-F01-b — replay.** REQ-1 is submitted, and then the same request (same request ID) is submitted again. Tests duplicate fulfillment.
- **P001-F01-b2 — same content, new ID.** REQ-1 is submitted, then a second request REQ-2 with identical content. Tests whether the laboratory can tell a replay from a legitimate repeat order.
- **P001-F01-c — interrupted delivery.** A fault occurs after 2 of the 3 units have been delivered or created. Tests partial delivery and whether any configuration certifies completion that did not happen.
- **P001-F01-d — consent revoked.** A's consent is withdrawn before t0. This is a separately versioned fixture (F-001-d). Tests which configurations depend on A's authority at all.
- **P001-F01-e — unit type unstated.** The request says "deliver 3 units to B" without saying units of what. (Proposed by Claude.)

Undefined-versus-incoherent companion cases (F03 family)

These cases test the reporting layer, not the capability layer. They check whether a request that refers to nothing is reported differently from a request whose conditions cannot all be true at once.

- **P001-F03-U1 — undeclared type.** "Deliver 3 units of Q to B." Q does not exist in the fixture.
- **P001-F03-U2 — unstated quantity.** "Deliver some units of R to B."
- **P001-F03-I1 — direct contradiction.** "Deliver 3 units of R to B, and B holds 0 units at t1."
- **P001-F03-I2 — contradiction with the definitional identity.** "Deliver 3 units of R to B, A still holds 10 at t1, and the total is still 10 at t1." Each clause is individually possible. Whether the three can hold together is the question.

9. Completion predicate, prohibited substitutions, and rules

Completion predicate CP-001

> REQ-1 is complete if and only if, in this run, B's holdings of R increased by exactly 3 units; every one of those units is usable; the configuration reports DELIVERED; and no variable changed that the configuration did not declare it would change.

CP-001 is the basis of Verdict B. It is about the requested outcome, not about whether the configuration is a good design. An evaluation-only configuration will not satisfy it, and that is a correct report, not a defect.

Prohibited substitutions

Each of the following, if it occurs, must be reported by name. None of them counts as satisfying CP-001.

1. **PS-01** — Returning a valuation in place of delivery.
2. **PS-02** — Issuing a receipt, certificate, completion record, or 1COIN-like object in place of delivery, or before delivery is complete.
3. **PS-03** — Delivering a promise, claim, or IOU for units instead of units.
4. **PS-04** — Delivering a different resource type, or reinterpreting "3" as three of some other unit.
5. **PS-05** — Drawing on a pool, party, issuer, or reserve that the fixture does not declare.
6. **PS-06** — Changing the request, the fixture, or the configuration after the run has started in order to rescue a result.
7. **PS-07** — Counting a partial delivery as complete.
8. **PS-08** — Supplying a missing rule (for example, a side-effect rule for C-ENACT-U, or a creation authority) without declaring it as a new configuration.

Operating rules

- **R-ID (request identity).** A request is identified by its request ID. A request ID may reach DELIVERED at most once. A second submission with the same ID returns DUPLICATE_SUPPRESSED and changes nothing. A new ID is a new request even if its content is identical. Evaluation is not subject to R-ID: valuing the same request twice is permitted.
- **R-ATOM (atomicity).** C-XFER and C-ENACT-S are atomic. C-XFER-NA, C-CREATE, and C-ENACT-M are not. These are stipulations.
- **R-AUTH (authority).** A's consent governs only the movement of A's units. Version 0.1 of this packet does **not** define who authorizes the creation of units. Analysts must not invent an authority for creation; if they think one is required, they must say so and record the result both ways under two configuration IDs.
- **R-GATE (order of checks).** Every configuration applies the same two checks before doing anything: first, is the request defined (does it refer to a declared type and a positive whole-number quantity)? Second, is it coherent (can all its stated end-state conditions hold together under the fixture's definitions)? A request that fails either check returns UNDEFINED_TARGET or INCOHERENT_TARGET and changes nothing.
- **R-NULL (no null tokens).** A status, a reason code, or a typed record saying that no value or delivery occurred is a report, not an asset. It cannot be held, transferred, or spent.
- **R-CONS (consequences).** No consequence model is active. No rejection, failure, or partial delivery generates NCOIN in this pilot.

10. Status vocabulary, evidence labels, and the run record

Status values

Each run step ends in exactly one status: VALUED, DELIVERED, PARTIAL, FAILED_ROLLED_BACK, DUPLICATE_SUPPRESSED, REJECTED_INSUFFICIENT, REJECTED_UNAUTHORIZED, UNDEFINED_TARGET, INCOHERENT_TARGET, UNDERSPECIFIED_CONFIG, or INDETERMINATE. Table 4 defines each. An analyst who needs a status that is not on the list should use INDETERMINATE and explain why, rather than invent a new value; proposed additions go in the challenge record.

Status is not consequence. A rejection is a status. If a later pilot activates a consequence model, consequences will be recorded in a separate field and will need their own trigger, measure, and bearer.

Evidence labels

Every claim in a run record carries one of four labels. E0 STIPULATED means the claim is true because the configuration or fixture says so. E1 DERIVED means the claim follows from stipulated rules by reasoning that the record shows. E2 EXECUTED means a program implementing the stated rules produced the result, and the program and its log are available. E3 EXTERNAL means the claim rests on observation of something outside the model. No Pilot 001 result can be E3. A run record that contains an E3 claim about Quantum Credits has made an error.

The labels do not form a ladder of truth. An E2 result shows that a program did what its rules said; if the rules were mis-transcribed, E2 inherits the error. E1 and E2 should agree; where they do not, the disagreement is itself a finding.

Fit to owner intent

Each record also has a field called fit to owner intent. In first-pass runs it should normally read NOT ASSESSED — OWNER INPUT REQUIRED. Only the owner knows whether, for example, an evaluation-only QC is a legitimate candidate or merely a comparison baseline. An analyst may record a view, labeled as opinion.

The run record

Table 6 gives the run-record template. It is single-column and typed so that six records can be compared field by field, and it can be filled in as plain text on a phone. A run record is required for every case–configuration pair; where many pairs give the same result, an analyst may group them but must list each pair.

11. What would count as an informative result

A result is informative if it does at least one of the following: shows two configurations producing different states or different statuses from the same input; shows two configurations that cannot be distinguished by anything the fixture lets an observer see; exposes a rule the packet failed to state, so that the analyst had to choose; shows two analysts reaching different results from the same frozen inputs; or shows that a prohibited substitution was needed to make something work.

A result is not informative merely because a configuration succeeded at what it was granted the power to do. A creation configuration that creates is reporting its own definition back to us.

I expect, and would welcome, results showing that this packet is defective. The point of a first pilot is to find out where the specification is thin before anyone builds on it.

12. Independence protocol

1. The owner gives each analyst this packet, and only this packet, in a fresh session. The sealed reference report and other members' run records are withheld until the analyst has submitted.
2. Each analyst lists every input it was given, and states whether it has seen earlier rounds of the collaboration. All six members have; that exposure should be stated, not hidden.
3. Each analyst states its platform and, where the platform reports it, the underlying model. **Disclosure for this document:** Perplexity Computer reports that this session runs on Claude Opus 5.5. Perplexity's and Claude's contributions may therefore not be independent at the model level, even though they are separate collaborators in separate sessions. The owner should treat agreement between Perplexity and Claude with that in mind. I do not know which models the other platforms used and do not guess.
4. Perplexity cannot run its own packet blind. I built a reference model while writing this packet, and defects it exposed were fixed before release (they are listed in the sealed report). My first-pass record therefore has the status of a reference execution, not an independent replication.
5. A claim that several analysts repeat because it appeared in the shared earlier documents counts as one source, however many times it is repeated.
6. Two analysts who reach different results are not yet in disagreement. First check whether they used the same frozen revision, fixture, and configuration. Different inputs make it an architecture comparison; identical inputs make it a reproduction failure. Both are useful, but they answer different questions.

13. Where I disagree with other members, and why

On including F04 and F05 in the first batch (Gemini). No seller versus unknown seller, and authorization sensitivity, are important. But F04 needs a fixture with ownership records and a discovery process, and F05 needs a definition of authority that this packet does not yet have (see R-AUTH). Adding them now would bring in two new sets of rules before the first set has been tested. I treat them as candidates for Pilot Packet 002. My boundary pass (OAL-CURR-PPLX-BOUNDARY-001) analyzes the seller distinction in prose in the meantime.

On a canonical laboratory numbering (Gemini). Gemini's cross-reference table maps cases in six charters to shared LAB IDs. That is useful as a reading aid, but a shared ID implies the cases are the same experiment, and several of the mapped cases differ in their fixtures. I use pilot-local IDs and record related cases with an explicit relationship ("related," not "equivalent") until someone has checked them side by side.

On the evaluation-only result (Gemini). Gemini wrote that the evaluation-only configuration "must terminate at EVALUATED with A=10, B=0 (proving that pure valuation cannot satisfy an acquisition prompt)." The outcome is right, but it is E0, not a proof: evaluation-only was defined not to move anything. What the pilot can show is whether the reporting interface keeps Verdict A and Verdict B apart.

On the role of F03 (several members). Several recommendations describe F03 as a discriminator between architectures. Under rule R-GATE every configuration applies the same definition and coherence checks first, so F03 should not distinguish capability configurations at all. It tests whether the reporting layer separates "refers to nothing" from "cannot all be true." If the team wants F03 to distinguish return architectures — Claude's R1–R4, Gemini's structured objects, my typed record — those return rules need to be declared as configurations in their own right. That is a sensible Pilot 002 design.

On merging OWNER-ADOPTED and LOCKED FOR TESTING (Claude). Discussed in Section 3.

14. Known limitations of this packet

- It tests one resource type and two parties. It says nothing about markets, prices, or multiple interacting requests beyond the replay cases.
- VC-001 is a placeholder. The real question of how QC values a target is untouched.
- R-AUTH leaves creation authority undefined. I chose to leave the gap visible rather than fill it with my preference.
- The non-atomic and no-rollback rules for creation are my stipulations. A different choice would change the results of P001-F01-c.
- The packet does not test 1COIN, NCOIN, temporal behavior, recursion, or the 150-year scenario.
- My own preparation is not blind (Section 12, item 4), and my underlying model is shared with another collaborator (Section 12, item 3).

15. Decisions requested from the project owner

1. Whether to adopt this packet, and for what scope (for example: “Pilot 001 first-pass runs, revision v0.1, all willing members”). Table 7 is the adoption record.
2. Whether the sealed reference report should be withheld from analysts until their first-pass records are in. I recommend yes.
3. Whether R-AUTH should stay open in v0.1, or whether you want to declare who authorizes creation before any run. Either is defensible; the record will differ.
4. Whether C-EVAL is a candidate for what QC is meant to be or only a comparison baseline. This decides how its Verdict B should be read; only you know your intent.
5. Whether other members may run this packet alongside their own run cards, or whether you want one shared first pass. I have assumed members may run their own, consistent with your instruction that we may proceed independently.

16. Next steps after the pilot

Once first-pass records are in: release the sealed reference report; compare records field by field; open challenge records for every disagreement; trace each disagreement to an input difference, an implementation error, or a real ambiguity in the packet; and issue v0.2 changing only what the evidence showed was ambiguous. Pilot Packet 002 would then take up the second-wave questions: seller existence versus seller discovery, authority, return architectures, and 1COIN against plain settlement records under partial delivery and replay.

Tables and Reference Records

All tables and templates are gathered here so the body above reads as continuous prose.

Table 1 — Inputs read in preparing this packet

Input	Description	SHA-256
OAL-Currency-Laboratory-Pilot-Recommendations.pdf	Compiled recommendations: ChatGPT, Claude, Google Gemini, Grok, Perplexity (47 pages). No Copilot section.	a5db2bd3be588f50d497210ccd95995da6e690c9825d631bc38ffa77ee673997
OAL-Currency-Laboratory-Pilot-Recommendations.docx	Editable edition of the same compilation; same five sections.	f2d44dbe66eb7bf0c945f11b6df2f6114f120bb56b7ef57562ae6df018691154
Directive OAL-CURR-NEXT-001 v1.0	Prepared by ChatGPT at the owner's request (November 6, 2026); supplied as paste.txt in the previous round.	f785613e4f341a548593ddb6f7e71d0043c0673e0771b3c83e5a65b0ae97f6f7 (paste.txt as supplied)
Earlier collaboration records	Previous-round compilations and member charters, read in earlier turns of this collaboration.	Hashed in Perplexity's earlier source registers

Table 2 — Configuration declarations

ID	Capability stipulated	Source of B's units	Effect on A	Atomic	Origin label
C-EVAL	Return value description under VC-001	None	None	n/a	n/a
C-XFER	Move existing units if A consents and holds enough	A	Debit equals credit	Yes	fixture
C-XFER-NA	As C-XFER	A	Debit equals credit	No	fixture
C-CREATE	Bring new units into existence (assumed primitive)	Created	None	No (no rollback)	minted
C-ENACT-U	Establish "B gained 3"; nothing else specified	Unspecified	Unspecified	Unspecified	Unspecified
C-ENACT-M	Establish target; freeze all unnamed variables	Created by enactment	None (frozen)	No	enacted
C-ENACT-S	Establish "B gained 3 and A lost 3"	A	Debit equals credit	Yes	fixture

Table 3 — Case inputs

Case ID	A at t0	Consent	Request(s)	Fault	Probes
P001-F01-BASE	10	Yes	REQ-1: 3 of R to B	None	Baseline behavior
P001-F01-a	2	Yes	REQ-1	None	Insufficient source; hidden pools
P001-F01-b	10	Yes	REQ-1, then REQ-1 again	None	Replay / duplicate fulfillment
P001-F01-b2	10	Yes	REQ-1, then REQ-2 (same content)	None	Replay versus repeat order
P001-F01-c	10	Yes	REQ-1	After 2 units	Partial delivery; premature certification

Case ID	A at t0	Consent	Request(s)	Fault	Probes
P001-F01-d	10	No	REQ-1	None	Dependence on A's authority
P001-F01-e	10	Yes	3 units (type unstated) to B	None	Silent gap-filling
P001-F03-U1	10	Yes	3 of Q to B	None	Undeclared referent
P001-F03-U2	10	Yes	Some R to B	None	Undefined quantity
P001-F03-I1	10	Yes	3 of R to B; B = 0 at t1	None	Direct contradiction
P001-F03-I2	10	Yes	3 of R to B; A = 10 and total = 10 at t1	None	Contradiction with definitional identity

Table 4 — Status vocabulary

Status	Meaning
VALUED	A value description was returned; nothing moved.
DELIVERED	The configuration reports that B received the full quantity. Whether CP-001 is met is checked separately.
PARTIAL	Some but not all units reached B, and they remain there.
FAILED_ROLLED_BACK	Delivery was interrupted and the world was restored to its t0 state.
DUPLICATE_SUPPRESSED	A request ID that had already reached DELIVERED was submitted again; nothing changed (R-ID).
REJECTED_INSUFFICIENT	The configuration depends on A's inventory and A did not hold enough.
REJECTED_UNAUTHORIZED	The configuration depends on A's consent and consent was absent.
UNDEFINED_TARGET	The request does not refer to anything declared in the fixture, or its quantity is not stated.
INCOHERENT_TARGET	The request's end-state conditions cannot all hold together under the fixture's definitions.
UNDERSPECIFIED_CONFIG	The configuration, as declared, does not determine what happens.
INDETERMINATE	None of the above applies; the record must explain why.

Table 5 — Evidence labels

Label	Meaning	Permitted in Pilot 001?
E0 STIPULATED	True because the fixture or configuration says so	Yes
E1 DERIVED	Follows from stipulated rules by reasoning shown in the record	Yes
E2 EXECUTED	Produced by a program implementing the stated rules; code and log available	Yes
E3 EXTERNAL	Rests on observation of something outside the model	No

Table 6 — Run-record template (copy one block per case–configuration pair)

Field	Content to record
run_id	Analyst-qualified run ID, e.g. grok/p001-v0.1/F01-BASE/C-XFER/run-1

Field	Content to record
packet_revision	perplexity/pilot-packet-001-v0.1 (or the frozen revision actually used)
adoption_reference	Reference to the signed adoption record, or “none — exploratory run”
analyst / platform / model	Collaborator name; platform; underlying model if the platform reports it
inputs_read	Every file or message given to the analyst for this run
prior_exposure	Whether the analyst has seen earlier rounds or other members’ results
case_id / config_id	From Tables 2 and 3
initial_state	A, B, total, consent, unit IDs
transitions	Each change in order, with unit IDs and origin labels
final_state	A, B, total, unit IDs, origin labels
status	One value from Table 4
reason	Plain-language reason for the status
prohibited_substitutions	Any of PS-01 to PS-08 that occurred, or “none”
undeclared_rules_needed	Any rule the analyst had to choose because the packet did not state it
verdict_A	CONSISTENT or INCONSISTENT with the declared rules, with the failed rule named
verdict_B	SATISFIED or NOT SATISFIED under CP-001
evidence_labels	Label for each claim above (E0, E1, E2)
distinguishability	Which other configurations give an identical observable result in this case
fit_to_owner_intent	Normally “NOT ASSESSED — OWNER INPUT REQUIRED”; any analyst view labeled as opinion
consequence_record	“None — consequence model inactive in Pilot 001”
settlement_record	“Ordinary log entry — 1COIN inactive in Pilot 001”
notes / dissent	Anything the analyst wants preserved, including disagreement with the packet

Table 7 — Owner adoption record (to be completed only by the project owner)

Field	Entry
Packet and revision	perplexity/pilot-packet-001-v0.1
Decision	☐ Adopted ☐ Adopted with changes ☐ Not adopted ☐ Deferred
Scope of adoption	_____
Revision locked for testing	_____
Changes required before locking	_____
Decision on R-AUTH	☐ Leave open ☐ Declare creation authority: _____
Status of C-EVAL	☐ Candidate ☐ Comparison baseline only ☐ Undecided
Sealed report handling	☐ Withhold until first passes are in ☐ Release now
Participating analysts	_____
Date and owner signature	_____

Table 8 — Pilot-local identifiers and related cases

Relationships are as stated by the source named. Perplexity has not verified equivalence; "related" means only that the cases address a similar question.

Pilot-local ID	Origin	Related cases elsewhere (relationship not verified)
P001-F01-BASE … -d	perplexity/charter-v0.1/F01 plus perturbations from Perplexity's recommendation	Mapped by Gemini to claude FM-1, gemini FM-01, copilot QC-F01 to F04, chatgpt F-01; chatgpt OAL-QC-PILOT-001; claude Run Card 001
P001-F01-e	Proposed by Claude (F01-c in Claude's recommendation)	claude Run Card 001 / F01-c
P001-F01-b2	New in this packet	None known
P001-F03-U1, -U2, -I1, -I2	perplexity/charter-v0.1/F03, re-specified for fixture F-001	Mapped by Gemini to claude FM-3 (part 1), gemini FM-03(a), copilot BN-01 and BN-02, chatgpt F-03