OMNIVERSAL ARCHITECT LABS / CURRENCY LABORATORY

Pilot Configuration & Reporting Specification

Resource-Box Capability Discriminator + Companion Boundary Cases

DOCUMENT CONTROL	DETAIL
Document ID	OAL-CHATGPT-PILOT-SPEC-001
Contributor	ChatGPT (OpenAI GPT-6)
Version / Date	0.1 / 7 November 2026
Status	OWNER-DIRECTED INDEPENDENT PILOT; proposed mechanics / pre-canon
Commission	Prepared at the OAL project owner's request to proceed independently
Scope	Speculative architecture / deterministic synthetic modeling; no real monetary capability asserted

READING INSTRUCTION: Treat stated capabilities as assumptions, deductions as conditional, executed results as model behavior, and canon as separately authorized.

Executive decision and authorization boundary

The project owner directed each AI to move forward independently with its previously proposed next steps. This document therefore supplies a complete candidate pilot packet and permits a separately labeled independent exploratory execution. It does not claim that the owner adopted a Trinity currency constitution, selected any winning QC capability, or approved this exact packet as a shared six-AI standard.

The smallest useful common interface is one typed target statement, one frozen capability assumption per configuration, one defined completion predicate, one observable state trace, and one evidence-class label. This packet intentionally does not reconcile all historical Charters.

PILOT READINESS: Ready for independent analytical and deterministic synthetic execution; owner adoption of any future shared frozen run card remains a separate logged action.

1. Source lineage and attribution

Primary controlling compilation: “OAL Currency Laboratory Pilot Recommendations” (DOCX/PDF), submitted 7 November 2026. The copies are editions of the same source, not independent corroboration. Within that compilation, ChatGPT recommended a narrow run card and typed target/value semantics; Perplexity specified F01/F03/F04 and controls; Claude advocated perturbations; Gemini supported typed exception outputs; Grok proposed the small coordination sheet; Copilot discussed comparability and governance. Other pre-canon OAL source documents are historical inputs, not ratified rules.

Origin	Original identifier / substantive connection
ChatGPT	OAL-QC-PILOT-001; typed target, capability discrimination, dual verdict
Perplexity	perplexity/charter-v0.1/F01 (resource box); F03 (undefined/incoherent); F04 (seller authority); F07-F10 controls
Claude	claude/charter-v0.1/FM-1/FM-3, plus F01-a/b/c/d perturbation proposals
Gemini	gemini/charter-v0.1 typed return objects, exception/capability variants (not adopted as universal)
Grok	grok/charter-v0.1 minimal coordination, no automatic NCOIN rule
Copilot	copilot/foundational-v0.1 state and instrument necessity frameworks

2. Status vocabulary and approval boundary

Label	Operational meaning in this packet
SOURCE / HISTORICAL	Existing record or previous contributor proposal; does not imply acceptance
PROPOSED	Rule or fixture presented for analysis; not shared-team canon
OWNER-DIRECTED EXPLORATION	The owner asked ChatGPT to advance its own recommendations; this authorizes independent work
ADOPTED FOR NAMED RUN	Explicit owner approval of this exact run card/version for a controlled shared trial; not presumed here
EXECUTED IN MODEL	A deterministic implementation of explicit assumptions has been run and its checks recorded

Label	Operational meaning in this packet
CANON	Permanent design decision needing separately documented owner authorization; none created here

Design status must not be confused with experiment verdict. A model may be PROPOSED and yield a PASS for internal consistency; a blocked transaction may be a correct outcome rather than a failed model.

3. Scope and non-goals

- Included: a typed synthetic resource delivery, four distinct QC function assumptions, 11 scenarios, separately tracked transaction and negative-value statuses, analytical comparison, deterministic program output, and an initial adversarial critique.
- Excluded: physical resource creation, access to external systems, real financial transactions, claims of quantum physics, definitive QC governance, full Version 2 canon, a 150-year macroeconomic conclusion, and other collaborators' independent execution.
- Protected methodology: take target-relative valuation QC(T)=V(T) as a conceptual stipulation while forbidding an inference from valuation to delivery, authority, or settlement.
- Do not assume the four temporal models are resolved. The first pilot concerns capability only, not the multi-year timing fork.

4. Typed target, value, and capability contract

Field / type	Definition / permitted values
target.referent: string	Exact entity/state to which the requested operation refers
target.operation: enum	EVALUATE, TRANSFER, CREATE, ENACT; no automatic interchange
target.quantity: nonnegative integer	3 units in baseline; zero and negative cases excluded until separately defined
target.unit: string or absent	resource_unit; absence maps to UNDEFINED_TARGET for this run
target.scope: object	A, B, and any pool; which holdings are observable and can be modified
target.time: string	Single discrete transition at t0 → t1; replay refers to same request ID
authority: object	recipient authorization; transfer authorization; seller status
value: typed object	{domain: synthetic_resource_quantity, quantity: 3, unit: resource_unit}; not dollars
value.conversion: rule	One synthetic resource-equivalence unit for one resource_unit, for this fixture only
environment: enum	CLOSED_SYNTHETIC_LEDGER; not an external financial implementation
completion: predicate	B_after - B_before = 3 delivered usable units AND declared poststate accounted for
evidence: enum	ASSUMED, DERIVED, EXECUTED_STIPULATED_MODEL, EMPIRICAL; separate labels

The typed-value rule prohibits addition of unrelated utility, moral, rights, and resource quantities without an explicit mapping. For an incoherent target the simulator returns a reason code, not an invented infinite price.

5. Four frozen capability configurations

Mode	Stipulated capability	Authorized observable behavior
P0 / EVALUATE	Compute a typed equivalence claim, no delivery primitive.	State unchanged; EVALUATED_NO_DELIVERY for coherent valued targets.
P1 / TRANSFER	Move existing fungible units from A to B.	A decreases by 3, B increases by 3; total conserved; require inventory.
P2 / CREATE	Create 3 new units credited to B.	A unchanged, B increases by 3; total increases by 3.
P3 / ENACT-UNDERSPECIFIED	Assert postcondition B gains 3, without specifying A's holdings or resource provenance.	B asserted at +3; A and total undefined; settlement and accounting indeterminate.

All three delivery-oriented modes share declared target-coherence, seller, transferability, authorization and idempotency gates in this particular implementation. That is an additional local control assumption, not a universal claim that resource creation always requires an existing seller. P0 valuation does not itself require seller approval.

6. Baseline run card — OAL-QC-PILOT-001

Parameter	Frozen pilot value
Fixture	A=10 resource_unit; B=0; request deliver 3 resource_unit to B
Scope	A and B only; no undeclared treasury, subsidy pool or third party
Requested result	B receives three additional usable units
Initial authority	Seller present; recipient authorized; A transfer authorized
Valuation	Synthetic one-to-one quantity equivalent; no real market price
Transaction timing	One discrete request at t0 to t1; request ID is idempotent under replay test
Obligations / externalities	None assumed in baseline; no automatic 1COIN or NCOIN issuance
Evaluation rules	P0/P1/P2/P3 fixed prior to viewing results
Outcome rubric	Consistency and requested-result satisfaction evaluated separately
Consent / authorization	Owner's current request authorizes this independent exploration, not shared-team canonization

7. Common state machine and early-exit gates

Recommended normal trace: UNRESOLVED → EVALUATED → [AUTHORIZED] → [RESOURCE_ACTION] → [SETTLED]. A bracketed stage is traversed only when the configuration claims to perform it. Authorization/settlement are not implied by evaluation.

Ordering: target typing and identity → coherence → typed valuation availability → mode-specific seller/transfer/authority/idempotency checks → action or declared indeterminacy → status code. Each early exit leaves A and B unchanged in the implemented fixture. This order is test-specific, not a proposed universal ontological sequence.

Return reason	Exact scope in this pilot
UNDEFINED_TARGET	Missing unit or target referent; not the same as contradiction
INCOHERENT_TARGET	Target logically contradictory under fixed definitions
VALUATION_UNAVAILABLE	Coherent target but no stipulated valuation result
SELLER_UNKNOWN	Existing seller not identifiable / authority uncertain
NO_SELLER	No recognized seller exists
NONTRANSFERABLE	Coherent target cannot be transferred under declared rules
UNAUTHORIZED	Required consent or authority denied
INSUFFICIENT_INVENTORY	P1 lacks existing units
REPLAY_NO_OP	Previously fulfilled request ID; idempotency prevents re-execution
EVALUATED_NO_DELIVERY	P0 evaluated but did not supply resources
SETTLED	P1 or P2 action delivered and was fully accounted
UNDERDETERMINED_ACCOUNTING	P3 asserted goal with unspecified A and total

8. Companion case registry and perturbations

Case ID	Input difference from baseline	Purpose
RB-BASE	A10/B0, requested 3; ordinary permissions	Reference behavior and accounting
RB-SHORT	A2/B0 requested 3	Insufficient inventory separates transfer and creation
RB-DENIED	B lacks recipient authorization	Check whether outcome models ignore authority
RB-UNTYPED	Unit omitted (request “3 of what?”)	Test target typing and early exit
RB-REPLAY	Request ID already processed	Reject duplicate delivery; idempotency assumption
BR-UNDEFINED	Target referent unspecified	Undefined referent
BR-INCOHERENT	Contradiction under unchanged definitions	Logical incoherence
BR-NOVALUE	Coherent target, no value provided	Knowledge gap versus contradiction
BR-SELLER-UNKNOWN	Seller status UNKNOWN	Epistemic authority gap
BR-NO-SELLER	Seller status ABSENT	Structural seller gap
BR-NONTRANSFER	transferable=false	Valuation without ownership/transfer

Additional perturbations to be designed for later controlled comparisons: partial delivery under atomic/non-atomic rules; simultaneous unique claims; issuer loss; authority-copy attack; multi-valued targets; and stale or time-varying value. Do not imply these were executed in the present run.

9. Serialized result schema / standardized report

Field	Meaning
case_id, mode, version	Unique tuple for reproducibility and disambiguation
source_alias	Original contributor/document/case, such as perplexity/charter-v0.1/F01
target, typed_value	Referent, operation, unit, domain, conversion rule
before, after	A/B holdings and accounted total; null when genuinely unspecified
assumed_capability	What the model is GIVEN, never claimed as discovered
status, qc_state, event	Gate return, state-machine outcome, performed action if any
settled, completion_predicate	Settlement is separate from evaluated equivalence
onecoin_issued, ncoin_issued	Independent output flags; both false in this run
evidence_type	Which epistemic level each reported statement occupies
note, added_assumptions	What remains ambiguous, plus any locally introduced rule
consistency_verdict, goal_verdict	Two independent assessments, not one binary score
trace, author, exposure	Step sequence; contributor; non-blind input disclosures
file_hashes, checker_version	Verification of reproducible code/output revisions

10. Evidence levels and acceptance criteria

- ASSUMED: Rule appears on the run card, including P2 creation and P3 enactment. This is not experimental confirmation of a real capability.
- DERIVED: Arithmetic or logical implication such as transfer conserving 10 units or creation producing total 13.
- EXECUTED_STIPULATED_MODEL: Python interpreter performed the explicitly coded transitions and produced a record. This validates code behavior only.
- EXTERNAL_EMPIRICAL: Independent real-world observation. None is claimed or needed for this speculative laboratory stage.

Verdict A (internal coherence) asks whether the executed trace satisfies that mode's own promised invariants. Verdict B (goal satisfaction) asks whether the requested delivery, and any necessary accounting, are fulfilled. A P0 evaluator can be internally consistent but fail goal delivery. P3 is not a demonstrated full settlement merely because B is assigned an intended postcondition.

11. 1COIN and NCOIN controls

No settlement token or consequence currency is issued in the executed four-mode simulation. This is deliberate model isolation. A later 1COIN comparison should hold delivery capabilities constant while comparing (A) QC direct finalization, (B) ordinary audit receipt, and (C) distinct 1COIN; score mechanical necessity, operational advantage, and narrative utility separately.

A later NCOIN track should compare: failed action with no measured consequence; failed action with an independent measured consequence; and successful action with independent negative externality. A failed/null status is never, by itself, a valid NCOIN trigger. Conservation proposals must define units, quantity, boundary and observer.

12. Reproducibility and review instructions

- Run the included standard-library Python model locally to regenerate the JSON record; no internet access, credentials, financial systems or external resources are used.
- Before viewing another contributor's new pilot traces, have each reviewer record its precise run-card version and any additional rules it introduced.
- Use contributor-qualified IDs. Crosswalk aliases indicate relationships, not identical test semantics. Do not mechanically replace one author's case IDs with another's.
- Compare identical configurations for reproducibility and differing configurations for architectural discrimination; these are different experimental goals.
- Preserve original submissions; publish corrected/sanitized editions separately. Do not publish temporary signed attachment URLs.

Supporting model file	SHA-256
OAL_ChatGPT_Pilot_001_Model_v0.1.py	29da5251d83f5c2b79f03b070aefdf0f305e6214a542cae096c6cfe7bb70226a
OAL_ChatGPT_Pilot_001_Execution_Results_v0.1.json	073f6fc8a1a8668d50bd967a53d42204f35700a76116929f56a201ba1b48c09e

13. Open decisions / owner control

1. D1. Whether this run-card version is to be adopted for a later shared six-AI blind execution. Independent ChatGPT exploration has already been requested, but shared adoption is not asserted.
2. D2. Which objectives are primary: logical coherence, operational features, narrative value, or explicit weighting.
3. D3. Whether the synthetic authority and seller gates for P2/P3 are retained, disabled, or treated as separate modes in the next protocol revision.
4. D4. Which P3 enactment semantics should be granted if a fully specified state transition is required.
5. D5. When a provisional design rule merits canon; no present test is treated as sufficient.

Appendix A. Sample typed run record

case_id: RB-BASE mode: P1_TRANSFER target: deliver 3 resource_unit to B

before: {A:10, B:0, total:10} after: {A:7, B:3, total:10}

qc_state: SETTLED_RESOURCE_DELIVERY status: SETTLED

assumed_capability: existing-resource-transfer evidence: executed stipulated model

1COIN: no issuance NCOIN: no issuance external capability: not demonstrated

Distribution note: The document records ChatGPT's independent contribution. It is intended for peer circulation and GitHub publication, but neither other contributors' consent nor project-wide adoption is implied.