OAL Trinity Currency Laboratory - Project Owner Questions, Decisions, and Next-Step Recommendations

Consolidated multi-AI collaboration record | Version 1.0 | 7 November 2026

Purpose. Consolidate the project-owner questions, separate owner decisions from contributor engineering work, and preserve actionable recommendations for GitHub versioning and traceability.

Response flexibility. You may answer any item with a selection, plain-language direction, "undecided," "test both," "use the recommended default," or "leave this to the contributors."

Executive status

- Cycle 1A - Exploratory capability modeling: completed.
- Cycle 1B - Reproduction and adversarial checker audit: in progress.
- Formal owner-adopted shared run: not yet authorized.
- Physical or external QC validation: not performed.
- Canon adoption: none.

The documentation and contributor coverage have improved, and the published implementations are reproducible under the tested environments. The project is not fully reconciled: checker-adequacy gaps, authority rules, identifier governance, partial-delivery recovery, and instrument-retention standards remain open.

Part I - Priority owner questions

Q1. Intended Quantum Credit capability

What must a successful Quantum Credit ultimately accomplish? Select or describe the intended minimum: (A) determine or represent a target-relative value; (B) make required resources or purchasing capability available; (C) obtain access, rights, or another defined outcome involving the target; (D) directly establish the requested target state within the fictional or simulated framework; or (E) preserve several of these as separately tested candidate architectures.

Recommended default: Preserve the ambitious design objective while retaining evaluation-only configurations as controls. An answer of "test multiple architectures" is sufficient.

Q2. Authorization for the next phase

What work do you authorize next: continued independent exploratory work, one shared frozen run packet, or both with the results labeled separately? If a shared packet is authorized, which named packet and revision should be owner-adopted?

Recommended default: Authorize both tracks. Adopt a small, revision-specific shared packet for reproducibility while allowing independent experiments to continue.

Q3. Instrument-retention standard

What may justify retaining 1COIN or NCOIN: strict mechanical necessity, operational advantages such as separation of duties and audit clarity, narrative/worldbuilding value, or a disclosed combination?

Recommended default: Evaluate mechanical necessity, operational advantage, and narrative value separately. Do not describe narrative retention as mechanical indispensability.

Q4. Creation authority

Should creation require a distinct issuance authority such as AUTH_MINT? Should authority to take existing units, issue new units, deliver them to a recipient, and alter a simulated environment be treated as separate permissions?

Recommended default: Test separate authority profiles before selecting a permanent rule. Do not treat A's consent over existing units as automatically deciding authority to create new units.

Q5. Meaning of usable delivery

When B receives units, what must be true for delivery to count as successful? Is a correct balance sufficient, or must units also be valid, identifiable, correctly typed, unencumbered, permitted, and usable for a further operation?

Recommended default: Require genuine usability under the declared configuration; let the technical team propose the exact checks.

Q6. Partial-delivery recovery

If two of three units are delivered and execution stops, should retry resume the remainder, roll back and restart, preserve a terminal partial result, reject retry, use a compensating transaction, or compare these as alternative policies?

Recommended default: Compare alternatives initially. Duplicate suppression should not silently choose the recovery policy.

Part II - Additional owner questions

Q7. Shortfall classification

When A holds two units but a named-source operation requires three, should the result be REJECTED_INSUFFICIENT, INCOHERENT_TARGET, or a multi-field result separating request coherence, feasibility, execution status, and reason?

Recommended default: Use separate fields: request_coherence, feasibility_under_configuration, execution_status, and reason.

Q8. Request identity and replay

What counts as the same request: the same transaction ID, the same immutable payload, or the same underlying obligation even under a new ID? Should reuse of an ID with a changed payload be prohibited?

Recommended default: Bind each request ID to a canonical payload hash and distinguish same-ID replay from new-ID repetition.

Q9. Receipt meaning and timing

Should a receipt certify only final completion, or may it represent intermediate milestones? If intermediate records are permitted, should they be named differently from 1COIN or a final settlement certificate?

Recommended default: Use request-scoped receipts and ordered events. Final settlement certification should occur only after completion.

Q10. Blind and open review design

Should future rounds collect first-pass submissions before reference results are disclosed, conduct open challenge rounds, or use both as separately labeled stages?

Recommended default: Use both: staged blind submission followed by open adversarial review. The current round is reference-exposed and should remain labeled exploratory/non-blind.

Q11. Identifier standard

May the team preserve original contributor IDs while using a three-level comparison structure: Case ID, Configuration ID, and Run ID, with neutral aliases only after equivalence is checked?

Recommended default: Approve the three-level structure and preserve original identifiers as aliases.

Q12. Status and evidence vocabulary

Do you prefer a compact shared status set (PROPOSED, OWNER-ADOPTED, LOCKED FOR NAMED RUN, EXECUTED, SUPPORTED WITHIN NAMED RUN, CANON) with a separate evidence field (E0 STIPULATED, E1 DERIVED, E2 EXECUTED, E3 EXTERNAL)?

Recommended default: Keep design/adoption status separate from evidence level. Prefer SUPPORTED WITHIN RUN over wording that could imply physical validation.

Q13. Executable-code expectation

Must every future run include executable code and machine-readable output, or may analytical traces remain sufficient for some cases?

Recommended default: Require code only when transition rules are fully computational; permit clearly labeled analytical traces for non-computational boundary cases.

Q14. Model and exposure disclosure

Should contributors disclose underlying model/platform information and prior exposure to reference outputs? Should overlapping model families merely be disclosed or formally down-weighted?

Recommended default: Require disclosure. Avoid formal weighting until a defensible method is adopted.

Q15. Publication preparation authority

May the team prepare a document manifest, access index, Markdown companions, corrected publication editions, and a correction log while preserving untouched originals?

Recommended default: Authorize preparation for review; treat repository commits, renames, moves, and deletions as separate actions.

Q16. Reference-material handling

Should completed public reference materials remain online for transparency while new blind materials are privately staged, or should historical references be moved into a clearly marked post-disclosure area?

Recommended default: Keep historical artifacts available and clearly labeled; control pre-submission distribution for genuinely blind future rounds.

Q17. Excluded assumptions and speculative track

Are there conventional assumptions the resource-box models must not impose universally, such as conservation, seller requirements, consent, stable unit identity, or ordinary time ordering?

Recommended default: Name protected assumptions explicitly and test changed premises as separate configurations rather than retroactively altering earlier runs.

Q18. Next discriminating focus

After verification hardening, should the next shared work emphasize P3-Enact observability and resource identity, 1COIN ablation, NCOIN trigger falsification, or another priority?

Recommended default: Complete checker hardening first, then run P3 observability and 1COIN ablation before broad Cycle 2 claims.

Part III - Items the AI team should resolve without burdening the project owner

- Publish corrected v0.2 implementations as new artifacts while preserving all v0.1 originals and the Perplexity audit.
- Derive totals from authoritative holdings; independently verify debits, credits, delivery quantity, authority, and settlement.
- Use request-scoped receipts and append-only ordered events; remove global receipt flags and hard-coded quantity thresholds.
- Add deliberate mutation testing and report mutation-detection coverage separately from ordinary assertion counts.
- Bind request IDs to immutable payloads; distinguish same-ID replay, changed-payload conflict, and new-ID repeated demand.
- Strengthen Perplexity completion checks for type, encumbrance, identity, provenance, recipient, uniqueness, and usability.
- Create a commit-pinned Markdown access index and manifest; provide Markdown/text companions for major binary reports.
- Inspect hyperlink targets, not only visible text, and remove temporary signed URLs from corrected publication editions.
- Resolve artifact-presence disputes against one named repository commit and path rather than relying on prior session memory.
- Keep analytical, executed, externally validated, blind, non-blind, and reference-exposed results explicitly separated.

Part IV - Recommended immediate sequence

1. Record the project owner's answers, including undecided and test-both responses.
2. Freeze one revision-specific shared Run Card without canonizing currency mechanics.
3. Publish v0.2 verification-hardening packages and retain v0.1 plus the audit unchanged.
4. Conduct a challenge round focused on checker adequacy, partial delivery, replay, receipt timing, and usable delivery.
5. Only after hardening, begin broader P3-Enact observability and 1COIN/NCOIN ablation work.
6. Publish an access index, manifest, correction log, and Markdown companions using commit-pinned references.

Part V - Low-burden response template

Q1 - Intended Quantum Credit capability:

_____

Q2 - Authorization for the next phase:

_____

Q3 - Instrument-retention standard:

_____

Q4 - Creation authority: _____

Q5 - Meaning of usable delivery:

_____

Q6 - Partial-delivery recovery: _____

Q7 - Shortfall classification: _____

Q8 - Request identity and replay:

_____

Q9 - Receipt meaning and timing:

_____

Q10 - Blind and open review design:

_____

Q11 - Identifier standard: _____

Q12 - Status and evidence vocabulary:

_____

Q13 - Executable-code expectation:

_____

Q14 - Model and exposure disclosure:

_____

Q15 - Publication preparation authority:

_____

Q16 - Reference-material handling:

_____

Q17 - Excluded assumptions and speculative track:

Q18 - Next discriminating focus:

Source basis

- ChatGPT collaboration response and verifier self-audit.
- Claude AI response and confirmation of receipt, replay, and recovery gaps.
- Google Gemini response and proposed Cycle 2 transition questions.
- Microsoft 365 Copilot review and 18-question owner-decision list.
- Grok review and consolidated owner questions.
- Perplexity AI owner-question consolidation and technical cautions.
- OAL_Perplexity_Claude_ChatGPT_Code_Audit_2026-11-07.txt and .json.
- AI Collaborator GitHub Access, Troubleshooting, and questions.docx.

Scope statement: All findings concern stipulated models, analytical reasoning, and executed simulations. No document in this record establishes physical Quantum Credit capability or canon.