



WIKIPEDIA
The Free Encyclopedia

[Main page](#)
[Contents](#)
[Current events](#)
[Random article](#)
[About Wikipedia](#)
[Contact us](#)
[Donate](#)

[Contribute](#)

[Help](#)
[Community portal](#)
[Recent changes](#)
[Upload file](#)

[Tools](#)
[What links here](#)
[Related changes](#)
[Special pages](#)
[Permanent link](#)
[Page information](#)
[Wikidata item](#)
[Cite this page](#)

[Languages](#)

[العربية](#)
[Azərbaycanca](#)
[Български](#)
[Català](#)
[Čeština](#)
[Dansk](#)
[Deutsch](#)
[Eesti](#)
[Ελληνικά](#)
[Español](#)

Not logged in [Talk](#) [Contributions](#) [Create account](#) [Log in](#)

Article

[Talk](#)

Read

[Edit](#)

[View history](#)

Search Wikipedia



Blue screen of death

From Wikipedia, the free encyclopedia

A **stop error**^[1] or **exception error**,^[2] commonly called the **blue screen of death (BSoD)** or **blue screen**, is an **error screen** displayed on **Windows** computers following a **fatal system error**. It indicates a **system crash**, in which the **operating system** has reached a condition where it can no longer operate safely. This is caused by many different problems, such as a general hardware failure or a crucial process terminating unexpectedly.


Contents [\[hide\]](#)

- [History](#)
 - [Incorrect attribution](#)
- [Formats](#)
- [Windows NT](#)
 - [Details](#)
- [Windows 9x](#)
- [Windows CE](#)
- [Similar screens](#)
- [See also](#)
- [References](#)
- [External links](#)


History [\[edit\]](#)

BSoDs have been around since Windows 1.0. In Windows 1.0-3.0, if the system crashed, the OS would give a blue screen with white text listing loaded kernel modules and their respective memory address, including the module that caused the kernel fault. It appears as a blue screen with white letters telling of a problem. BSoDs have been present in **Windows NT 3.1** (the first version of the **Windows NT** family, released in 1993) and all Windows operating systems released afterwards. (See **History of Microsoft Windows**.) BSoDs can be caused by poorly written **device drivers** or malfunctioning hardware, such as faulty **memory**, power supply issues, overheating of components, or hardware running beyond its specification limits. In the **Windows 9x** era, incompatible **DLLs** or bugs in the operating system **kernel** could also cause BSoDs. Because of the instability and lack of memory protection in Windows 9x, BSoDs were much more common.^[*citation needed*]

Incorrect attribution [\[edit\]](#)



The Blue Screen of Death in **Windows 10** (versions 1607-1909), which includes a **sad emoticon** and a **QR code** for quick troubleshooting



The Blue Screen of Death in **Windows 8**, **Windows 8.1** & **Windows 10** (versions 1507-1511), which includes a **sad emoticon** and an Internet search for quick troubleshooting



A [Windows NT 4.0](#) BSoD, seen on a baggage claim monitor in [Geneva Airport](#) (1999)



Blue Screen of Death on Windows XP at a drugstore in 2019


On September 4, 2014, several online journals, including *[Business Insider](#)*,^[3] *[DailyTech](#)*,^[4] *[Engadget](#)*,^[5] *[Gizmodo](#)*,^[6] *[Lifehacker](#)*,^[7] *[Neowin](#)*,^[8] *[Softpedia](#)*,^[9] *[TechSpot](#)*,^[10] *[The Register](#)*,^[11] and *[The Verge](#)*^[12] attributed the creation of the Blue Screen of Death to [Steve Ballmer](#), Microsoft's former [CEO](#), while citing a source that does not say so: An article by the Microsoft employee [Raymond Chen](#), titled "Who wrote the text for the [Ctrl+Alt+Del](#) dialog in Windows 3.1?"^[13] The article was about the creation of [the first rudimentary task manager](#) in Windows 3.x, which shared visual similarities with a BSoD.^[13] In a follow-up on September 9, 2014, Raymond Chen complained about this widespread mistake, claimed responsibility for revising the BSoD in [Windows 95](#) and panned BGR.com for having "entirely fabricated a scenario and posited it as real".^[14] *[Engadget](#)* later updated its article to correct the mistake.^[5]

Formats [[edit](#)]

Until [Windows 8](#) and [Windows Server 2012](#), BSoDs showed [silver](#) text on a [royal blue](#) background with information about current memory values and register values. Windows Server 2012, [Windows 8](#) and [Windows 10](#) use a [cerulean](#) background.

Windows 95, [98](#) and [ME](#) BSoDs use 80×25 [text mode](#). BSoDs in the Windows NT family use 80×50 text mode on a 720×400 screen. Windows XP, Vista and 7 BSoDs use the [Lucida Console](#) font. Windows 8, Windows Server 2012 use [Segoe UI](#) and attempt to render the BSoD at native resolution (in case of newer PCs boot in UEFI mode), otherwise defaulting to 640x480 (in case of older PCs or newer PCs boot in CSM/Legacy BIOS mode). Windows 10 versions 1607 onwards uses the same format as Windows 8, but has a [QR code](#) which leads to a Microsoft survey about how the blue screen was caused.

Despite the "blue screen" name, in Windows 9x, the color of the message could be customized by the user.^[15] As of December 2016, [Windows Insider](#) builds of [Windows 10](#) feature the same format as in public release versions, but with a dark green background instead of a blue one.^[16]^[17]



A Blue Screen of Death as it appears on [Windows 1.0](#), [2.0](#), and [3.0](#)


Windows NT [[edit](#)]

In the [Windows NT](#) family of operating systems, the blue screen of death (officially known as a **stop error** and referred to as "[bug check](#)" in the Windows [software development kit](#) and [driver development kit](#) documentation) occurs when the kernel or a driver running in [kernel mode](#) encounters an error from which it cannot recover. This is usually caused by an [illegal operation](#) being performed. The only safe action the operating system can take in this situation is to [restart the computer](#). As a result, data may be lost, as users are not given an opportunity to save data that has not yet been saved to the hard drive.

The text on the error screen contains the code of the error and its symbolic name (e.g. "0x0000001E, KMODE_EXCEPTION_NOT_HANDLED") along with four error-dependent values in parentheses that are there to help software engineers fix the problem that occurred. Depending on the error code, it may display the address where the problem occurred, along with the driver which is loaded at that address. Under Windows NT, the second and third sections of the screen may contain information on all loaded drivers and a stack dump, respectively. The driver information is in three columns; the first lists the base



Windows 98 BSOD at Nashville International Airport



The Blue Screen of Death as seen in Windows XP, Vista, and 7

address of the driver, the second lists the driver's creation date (as a [Unix timestamp](#)), and the third lists the name of the driver.^[18]

By default, Windows will create a [memory dump](#) file when a stop error occurs. Depending on the OS version, there may be several formats this can be saved in, ranging from a 64kB "minidump" (introduced in Windows 2000) to a "complete dump" which is effectively a copy of the entire contents of physical memory ([RAM](#)). The resulting memory dump file may be debugged later, using a kernel [debugger](#). For Windows WinDBG or KD debuggers from [Debugging Tools for Windows](#) are used.^[19] A debugger is necessary to obtain a [stack trace](#), and may be required to ascertain the true cause of the problem; as the information on-screen is limited and thus possibly misleading, it may hide the true source of the error. By default, Windows XP is configured to save only a 64kB minidump when it encounters a stop error, and to then automatically reboot the computer. Because this process happens very quickly, the blue screen may be seen only for an instant or not at all. Users have sometimes noted this as a [random reboot](#) rather than a traditional stop error, and are only aware of an issue after Windows reboots and displays a notification that it has recovered from a serious error. This happens only when the computer has a function called "Auto Restart" enabled, which can be disabled in the Control Panel which in turn shows the stop error.

Microsoft Windows can also be configured to send live debugging information to a kernel debugger running on a separate [computer](#). If a stop error is encountered while a live kernel debugger is attached to the system, Windows will halt execution and cause the debugger to break in, rather than displaying the BSOD. The debugger can then be used to examine the contents of memory and determine the source of the problem.

A BSOD can also be caused by a critical boot loader error, where the operating system is unable to access the boot partition due to incorrect storage drivers, a damaged file system or similar problems. The error code in this situation is STOP 0x0000007B (INACCESSIBLE_BOOT_DEVICE).^[20] In such cases, there is no memory dump saved. Since the system is unable to boot from the hard drive in this situation, correction of the problem often requires using the repair tools found on the Windows installation disc.

Details [\[edit \]](#)

Before [Windows Server 2012](#), each BSOD displayed an error name in uppercase (e.g. APC_INDEX_MISMATCH), a hexadecimal error number (e.g. 0x00000001) and four parameters. The last two are shown together in the following



Windows XP BSOD at CNIT



Windows 7 BSOD on Vélo'v



ReactOS, an attempt at creating a [free and open-source](#) implementation of a Windows NT-compatible [operating system](#), also features its own BSOD

format:^[21]

similar to the one in the Windows NT family.

error code (parameter 1, parameter 2, parameter 3, parameter 4) error name

Depending on the error number and its nature, all, some, or even none of the parameters contain data pertaining to what went wrong, and/or where it happened. In addition, the error screens showed four paragraphs of general explanation and advice and may have included other technical data such the file name of the culprit and memory addresses.


With the release of Windows Server 2012, the BSoD was changed, removing all of the above in favor of the error name, and a concise description. Windows 8 added a sad emoticon as well. The hexadecimal error code and parameters can still be found in the [Windows Event Log](#) or in [memory dumps](#). Since Windows 10 Build 14393, Windows 10 has added [QR code](#) for quick troubleshooting.

Windows 9x [\[edit \]](#)

The blue screen of death frequently occurs in Microsoft's home desktop operating systems [Windows 95](#), [98](#), and [ME](#). In these operating systems, the BSoD is the main way for [virtual device drivers](#) to report errors to the user. It is internally referred to by the name of "`_VWIN32_FaultPopup`". A Windows 9x BSoD gives the user the option either to restart or continue.

The most common BSoD is an 80×25 screen which is the operating system's way of reporting an interrupt caused by a processor exception; it is a more serious form of the [general protection fault](#) dialog boxes. The memory address of the error is given and the error type is a hexadecimal number from 00 to 11 (0 to 17 decimal). The error codes are as follows:^[2]

- 00: Division [fault](#)
- 01: Startup Error
- 02: [Non-Maskable Interrupt](#)
- 03: Shutdown Error
- 04: Overflow Trap
- 05: Bounds Check Fault
- 06: Invalid Opcode Fault
- 07: "[Coproprocessor](#) Not Available" Fault
- 08: Double Fault
- 09: Coprocessor Segment Overrun
- 0A: Invalid Task State [Segment Fault](#)
- 0B: Not Present Fault
- 0C: Stack Fault
- 0D: General Protection Fault
- 0E: Page Fault



A blue screen of death, as appears on [Windows 9x](#)

- 0F: Error Message Limit Exceed
- 10: Coprocessor Error Fault
- 11: Alignment Check Fault

Reasons for BSoDs include:

- Problems that occur with incompatible versions of [DLLs](#): Windows loads these DLLs into memory when they are needed by application programs; if versions are changed, the next time an application loads the DLL it may be different from what the application expects. These incompatibilities increase over time as more new software is installed, and is one of the main reasons why a freshly installed copy of Windows is more stable than an "old" one.
- Faulty or poorly written [device drivers](#)
- Hardware incompatibilities

Damaged hardware may also cause a BSoD.

In Windows 95 and 98, a BSoD occurs when the system attempts to access the file "`c:\con\con`" or "`c:\aux\aux`" on the hard drive. This could be inserted on a website to crash visitors' machines. On 16 March 2000, Microsoft released a [security update](#) to resolve this issue.^[22]

One famous instance of a Windows 9x BSoD occurred during a presentation of a Windows 98 [beta](#) given by [Bill Gates](#) at [COMDEX](#) on April 20, 1998: The demo PC crashed with a BSoD when his assistant, [Chris Capossela](#), connected a scanner to the PC to demonstrate Windows 98's support for [Plug and Play](#) devices. This event brought thunderous applause from the crowd and Gates replied (after a nervous pause): "That must be why we're not shipping Windows 98 yet."^[23]

Windows CE [\[edit \]](#)

The simplest version of the blue screen occurs in [Windows CE](#) (except in [Pocket PC 2000](#) and [Pocket PC 2002](#)). The blue screen in Windows CE 3.0 is similar to the one in Windows NT.


Similar screens [\[edit \]](#)

"Red Screen of Death" redirects here. Red Screen of Death may also refer to an error message used on the PlayStation systems.


Stop errors are comparable to [kernel panics](#) in [macOS](#), [Linux](#), and other [Unix-like](#) systems, and to bugchecks in [OpenVMS](#). [Windows 3.1](#), like some versions of [macOS](#), displays a [Black Screen of Death](#) instead of a blue one.^{[14][24]} [Windows 98](#) displays a red error screen raised by the [Advanced Configuration and Power Interface](#) (ACPI) when the host computer's [BIOS](#) encounters a problem.^[25] The [bootloader](#) of the first [beta version](#) of [Windows Vista](#) also displays a red error screen in the event of a boot failure.^{[26][27][28]}

See also [\[edit \]](#)

- [Xbox 360 technical problems](#)^[3] (Red Ring of Death)
- [Purple diagnostic screen](#)
- [Sad Mac](#)




Windows CE 5.0 Blue Screen of Death



The Red Screen of Death in a post-reset [Windows Longhorn](#) build

- [Microsoft Windows](#)
- [Screens of Death](#)
- [Microsoft](#)

References [\[edit \]](#)

- [^] ^{**a**} ^{**b**} "Troubleshoot blue screen errors" [↗](#). *Support*. **Microsoft**. 10 April 2019.
- [^] ^{**a**} ^{**b**} "What Are Fatal Exception Errors" [↗](#). *Support*. **Microsoft**. 19 January 2007. Archived from [the original](#) [↗](#) on 23 August 2003. Retrieved 16 October 2013.
- [^] ^{**a**} ^{**b**} Smith, Dave (4 September 2014). "Steve Ballmer Wrote The Blue Screen Of Death" [↗](#). *Business Insider*. Business Insider Inc. Retrieved 10 September 2014.
- [^] Mick, Jason (4 September 2014). "Microsoft Exec Reveals Steve Ballmer Created Original Blue Screen of Death Message" [↗](#). *Daily Tech*. DailyTech LLC. Archived from [the original](#) [↗](#) on 2015-08-20. Retrieved 10 September 2014.
- [^] ^{**a**} ^{**b**} Fingas, Jon (4 September 2014). "Steve Ballmer wrote Windows' first Ctrl-Alt-Delete message (updated)" [↗](#). *Engadget*. AOL. Retrieved 10 September 2014.
- [^] Condliffe, Jamie (4 September 2014). "Steve Ballmer Wrote the Blue Screen of Death" [↗](#). *Gizmodo*. Gizmodo Media Group. Retrieved 10 September 2014.
- [^] Kidman, Alex (5 September 2014). "Steve Ballmer Wrote The BSOD, So Stop Slacking Off" [↗](#). *Lifehacker*. Allure Media. Retrieved 10 September 2014.
- [^] Sams, Brad (4 September 2014). "Steve Ballmer wrote the BSOD text" [↗](#). *Neowin*. Neowin LLC. Retrieved 10 September 2014.
- [^] Popa, Bogdan (4 September 2014). "Steve Ballmer Himself Created the First Blue Screen of Death Text" [↗](#). *Softpedia*. SoftNews SRL. Retrieved 10 September 2014.
- [^] Schiesser, Tim (4 September 2014). "The original Blue Screen of Death was written by Steve Ballmer" [↗](#). *TechSpot*. Retrieved 10 September 2014.
- [^] Sharwood, Simon (4 September 2014). "Ballmer PERSONALLY wrote Windows' Blue Screen of Death text" [↗](#). *The Register*. Retrieved 10 September 2014.
- [^] Warren, Tom (4 September 2014). "Steve Ballmer wrote the Blue Screen of Death message" [↗](#). *The Verge*. Vox Media. Retrieved 10 September 2014.
- [^] ^{**a**} ^{**b**} Chen, Raymond (2 September 2014). "Who wrote the text for the Ctrl+Alt+Del dialog in Windows 3.1?" [↗](#). *The Old New Thing*. Microsoft. Retrieved 10 September 2014.
- [^] ^{**a**} ^{**b**} Chen, Raymond (9 September 2014). "Steve Ballmer did not write the text for the blue screen of death" [↗](#). *The Old New Thing*. Microsoft. Retrieved 10 September 2014.
- [^] Scott Seely (2000). *Windows Shell Programming*. Prentice Hall PTR. pp. 232–233. ISBN 9780130254962. "BSOD stands for Blue Screen Of Death. One can customize the colors of this screen by setting a couple of variables in the 386Enh section of SYSTEM.INI: MessageTextColor and MessageBackColor. The user can only customize the BSOD under Windows 3.1, 95, and 98. These changes do not work under the Windows NT variants."
- [^] "Behold the Windows 10 GSOD -- Green Screen of Death" [↗](#). *BetaNews*. 2016-12-29. Retrieved 2017-01-13.
- [^] Warren, Tom (December 29, 2016). "Windows 10 testers will now get a Green Screen of Death" [↗](#). *The Verge*. Vox Media. Retrieved 1 February 2017.
- [^] *Microsoft Windows NT Workstation Resource Kit*  (1st ed.). Redmond, WA: Microsoft Press. 29 October 1996. ISBN 1-57231-343-9.
- [^] DOMARS. "Getting Started with WinDbg (Kernel-Mode)" [↗](#). *msdn.microsoft.com*. Retrieved 15 June 2018.
- [^] "Stop error code 0x0000007B (INACCESSIBLE_BOOT_DEVICE)" [↗](#). *support.microsoft.com*. 2018-04-17. Retrieved 2020-01-16.
- [^] "STOP: 0x00000001 (parameter, parameter, parameter, parameter) APC_INDEX_MIS" [↗](#). *msdn.microsoft.com*. Retrieved 15 June 2018.
- [^] Microsoft Corporation (2000). "Patch Available for "DOS Device in Path Name" Vulnerability" [↗](#). *TechNet*. Microsoft. Retrieved 4 March 2006.
- [^] Garmon, Jay (12 April 2007). "Video: Bill Gates, meet the Blue Screen of Death" [↗](#). *TechRepublic*. CBS Interactive. Retrieved 20 December 2013.
- [^] David W. Martin (6 August 2011). "Black Screen Of Death Plagues Some Mac Users After Lion Update" [↗](#). Retrieved 27 August 2018.
- [^] "Advanced Configuration and Power Interface Errors on Red Screen" [↗](#). *Support* (1.3 ed.). **Microsoft**. 10 January 2015. Archived from [the original](#) [↗](#) on 25 July 2015.
- [^] Kaplan, Michael (7 May 2005). "Longhorn on Virtual PC 2004" [↗](#). *Sorting it all Out*. Microsoft. Archived from [the original](#) [↗](#) on 3 January 2013.
- [^] Best, Jo (11 May 2005). "Red screen of death?" [↗](#). *CNET*. CBS Interactive. Archived [↗](#) from the original on 9 August 2011. Retrieved 9 September 2013.

28. [^] Farrell, Nick (3 June 2005). "Microsoft sees red over blue screen of death"[ⓘ]. *The Inquirer. Incisive Media. Archived*[ⓘ] from the original on 25 August 2009. Retrieved 9 September 2013.

External links [[edit](#)]

- Bug Check Codes (Microsoft Developer Network)[ⓘ]
- SysInternals BlueScreen Screen Saver v3.2[ⓘ]



Wikimedia Commons has media related to:
BSoD (category)

V · T · E	Error messages [hide]
System failure	Bomb icon · Fatal system error · Guru Meditation · Kernel panic · Linux kernel oops · Red Ring of Death · Sad Mac · Screen of death (Blue · Black)
Application failure	ABEND · Fatal exception error · Segmentation fault
Device and data errors	HTTP 403 · HTTP 404 · HTTP 500 · Ip0 on fire · Not a typewriter · PC LOAD LETTER
Other	Abort, Retry, Fail? · Bad command or file name · Halt and Catch Fire · HTTP 418 · Out of memory
Lists	List of HTTP status codes · List of FTP server return codes
Related	Spinning pinwheel · Windows wait cursor

Categories: [Computer errors](#) | [Windows administration](#) | [Screens of death](#) | [Microsoft Windows](#) | [Microsoft](#)