



TEST AND CALIBRATION DATA

Short Period OBS System

Serial No. T6J77/A4336/5173

DESIGNED AND MANUFACTURED BY:

**GÜRALP SYSTEMS LIMITED
3 MIDAS HOUSE
CALLEVA PARK
ALDERMASTON
READING
BERKS, RG7 8EA
ENGLAND**

Telephone: +44 (0) 118 9819056

Fax: +44 (0) 118 9819943

DM24 CALIBRATION

WORKS ORDER: 13072

DIGITISER SERIAL NUMBER: A4336

SYSTEM ID: 13072
UNIT ID: 4336
OUTPUT DATA FORMAT: GCF
BAUD RATE: 38400

CPLD: A0.E1
BOOTLOADER: MK3BOOT213.IMG
DSP SOFTWARE: DSP1090.BIN
SYSTEM: DMNET106b57d.IMG

VELOCITY CHANNELS

Channel:	4336Z2	Vertical	2.872 $\mu\text{V}/\text{Count}$
	4336N2	North/South	2.873 $\mu\text{V}/\text{Count}$
	4336E2	East/West	2.874 $\mu\text{V}/\text{Count}$

MASS POSITION CHANNELS

Sample Rate: 4 samples/sec (Default)

Channel:	4336M8	Vertical	291.022 $\mu\text{V}/\text{Count}$
	4336M9	North/South	290.358 $\mu\text{V}/\text{Count}$
	4336MA	East/West	290.166 $\mu\text{V}/\text{Count}$

Sample Rate: 1 samples/sec

Channel:	4336M8	Vertical	2.274 $\mu\text{V}/\text{Count}$
	4336M9	North/South	2.268 $\mu\text{V}/\text{Count}$
	4336MA	East/West	2.267 $\mu\text{V}/\text{Count}$

CAL SIGNAL MONITOR

4336X2	2.873 $\mu\text{V}/\text{Count}$
4336C2	0.424 $\mu\text{V}/\text{Count}$

GPS RECEIVER

PWM: 8000 Counts
At Temperature Reading: 23°C

POWER CONSUMPTION

Digitiser Power Consumption
GPS Power Consumption

80mA @ 12v
28mA @ 12v

CMG-6TF CALIBRATION SHEET




WORKS ORDER:	13072	DATE:	18-Mar-2013
SERIAL NUMBER:	T6J77	TESTED BY:	S. Goddard

	Velocity Output V/m/s (Differential)	Mass Position Output (Acceleration output) V/m/s ²	Feedback Coil Constant Amp/m/s ²
VERTICAL	2 x 1203	447	0.00447
NORTH/SOUTH	2 x 1203	404	0.00792
EAST/WEST	2 x 1208	422	0.00828


Power Consumption: 20mA @ +12V input
Calibration Resistor: 51000

NOTE: A factor of 2 x must be used when the sensor outputs are used differentially (also known as push-pull or balanced output). Under no conditions should the negative outputs be connected to the signal ground. A separate signal ground pin is provided.


Calibration Information for : T6J77, 13072




Normalized Frequency Response for : T6J77, 13072



Normalized Frequency Response for : T6J77, 13072



Normalized Frequency Response for : T6J77, 13072



Normalized Frequency Response for : T6J77, 13072

