a xylem brand

Model: 4831 Sensing Foil Batch No: 1206EM Serial No: 276

Certificate No: 4831 276 3509 Calibration Date: October 27, 2016

This is to certify that this product has been calibrated using the following instruments:

Fluke CHUB E-4	Serial No. A7C677		
Fluke 5615 PRT	Serial No. 802054		
Fluke 5615 PRT	Serial No. 849155		
Honeywell PPT	Serial No. 44074		
Calibration Bath model FNT 321-1-40			

Parameter: Internal Temperature:

Temperature coefficients

Index	0	1	2	3
TempCoef	2.68881E+01	-3.11470E-02	3.17064E-06	-4.59576E-09

Parameter: Oxygen:

	O2 Concentration	Air Saturation	
Range:	0-500 μM ¹⁾	0 - 120%	
Accuracy ¹⁾ :	< ±2µM or ±1.5%(whichever is greater)	±5%	
Resolution:	< 1 μM	< 0.4%	
Settling Time (63%):	< 25 seconds		

SVU coefficients

SVU C0 - C3	2.79235E-03	1.16350E-04	2.36253E-06	2.29787E+02
SVU C4 - C6	-3.75842E-01	-5.60660E+01	4.57187E+00	

Giving these coefficients

Index	0	1	2	3
Conentration Coef	0.00000E+00	1.03571E+00		
PhaseCoef	0.00000E+00	1.00000E+00	0.00000E+00	0.00000E+00

¹⁾ Valid for 0 to 2000m (6562ft) depth, salinity 33 - 37ppt

Date: Sign: Jason B Baxter

October 27, 2016

²⁾The calibration is performed in fresh water and the salinity setting is set to: 0