a xylem brand

Model: 4831 **Serial No:** 316

Certificate No: 4831 316 3510 Calibration Date: October 27, 2016

This is to certify that this product has been calibrated using the following instruments:

1206EM

Fluke CHUB E-4	Serial No. A7C677		
Fluke 5615 PRT	Serial No. 802054		
Fluke 5615 PRT	Serial No. 849155		
Honeywell PPT	Serial No. 44074		
Calibration Bath model FNT 321-1-40			

Parameter: Internal Temperature:

Temperature coefficients

Sensing Foil Batch No:

Index	0	1	2	3
TempCoef	2.60833E+01	-3.12393E-02	3.05970E-06	-4.48985E-09

Parameter: Oxygen:

	O2 Concentration	Air Saturation	
Range:	0-500 μM ¹⁾	0 - 120%	
Accuracy ¹⁾ :	< ±2µM or ±1.5%(whichever is greater)	±5%	
Resolution:	< 1 μM	< 0.4%	
Settling Time (63%):	< 25 seconds		

SVU coefficients

SVU C0 - C3	2.88470E-03	1.21006E-04	2.35068E-06	2.30717E+02
SVU C4 - C6	-3.72617E-01	-5.53313E+01	4.57212E+00	

Giving these coefficients

Index	0	1	2	3
Conentration Coef	0.00000E+00	1.08291E+00		
PhaseCoef	0.00000E+00	1.00000E+00	0.00000E+00	0.00000E+00

¹⁾ Valid for 0 to 2000m (6562ft) depth, salinity 33 - 37ppt

Date: Sign: Jason B Baxter

October 27, 2016

 $^{^{2)}}$ The calibration is performed in fresh water and the salinity setting is set to: 0