

a **xylem** brand

CALIBRATION CERTIFICATE

Form No 830, March 2021

Certificate no: 4831_476_00234898 Foil batch no: 1206EM

Product: 4831

Calibration date: 19.12.2024

Serial no: 476 Page 1 of 2

| Index | Temperature reference(°C) | [O2] Reference(µM) | Temperature raw data(mV) | Phase reading(°) |
|-------|---------------------------|--------------------|--------------------------|------------------|
| 0 | 30.263 | 2.09 | -137.793 | 60.41 |
| 1 | 20.446 | 1.07 | 180.113 | 61.40 |
| 2 | 10.302 | 0.19 | 512.320 | 62.17 |
| 3 | 0.879 | -1.06 | 799.867 | 62.80 |
| 4 | 0.936 | 18.44 | 798.207 | 60.28 |
| 5 | 1.073 | 36.95 | 794.267 | 58.11 |
| 6 | 1.126 | 57.60 | 792.747 | 55.91 |
| 7 | 1.134 | 102.96 | 792.520 | 51.73 |
| 8 | 1.186 | 140.56 | 791.027 | 48.84 |
| 9 | 1.199 | 211.87 | 790.693 | 44.35 |
| 10 | 1.211 | 315.27 | 790.307 | 39.50 |
| 11 | 1.243 | 409.58 | 789.400 | 36.24 |
| 12 | 1.244 | 511.86 | 789.360 | 33.48 |
| 13 | 10.541 | 14.75 | 504.667 | 59.53 |
| 14 | 10.398 | 30.88 | 509.247 | 56.83 |
| 15 | 10.342 | 47.43 | 511.053 | 54.39 |
| 16 | 10.313 | 79.98 | 511.967 | 50.30 |
| 17 | 10.310 | 115.98 | 512.053 | 46.60 |
| 18 | 10.291 | 164.94 | 512.680 | 42.62 |
| 19 | 10.294 | 246.81 | 512.600 | 37.67 |
| 20 | 10.283 | 328.25 | 512.940 | 34.15 |
| 21 | 10.308 | 411.64 | 512.107 | 31.42 |
| 22 | 20.553 | 12.18 | 176.600 | 58.57 |
| 23 | 20.399 | 25.64 | 181.693 | 55.40 |
| 24 | 20.381 | 40.05 | 182.287 | 52.48 |
| 25 | 20.334 | 64.55 | 183.813 | 48.36 |
| 26 | 20.326 | 92.27 | 184.093 | 44.59 |
| 27 | 20.324 | 134.72 | 184.107 | 40.14 |
| 28 | 20.314 | 196.57 | 184.493 | 35.53 |
| 29 | 20.319 | 261.78 | 184.300 | 32.07 |
| 30 | 20.315 | 328.33 | 184.400 | 29.47 |
| 31 | 30.387 | 10.58 | -141.667 | 57.50 |
| 32 | 30.417 | 21.37 | -142.640 | 54.05 |
| 33 | 30.430 | 33.22 | -143.033 | 50.88 |
| 34 | 30.442 | 54.98 | -143.400 | 46.16 |
| 35 | 30.451 | 76.06 | -143.653 | 42.57 |
| 36 | 30.460 | 108.88 | -143.927 | 38.29 |
| 37 | 30.479 | 162.43 | -144.560 | 33.45 |
| 38 | 30.493 | 213.34 | -145.007 | 30.27 |
| 39 | 30.500 | 268.38 | -145.207 | 27.77 |



CALIBRATION CERTIFICATE

Form No 830, March 2021


Certificate no: 4831_476_00234898 Product: 4831
Foil batch no: 1206EM Calibration date: 19.12.2024


a **xylem** brand

Serial no: 476 Page 2 of 2

Giving these coefficients

| Index | 0 | 1 | 2 | 3 | 4 | 5 | 6 |
|-------------|-------------|--------------|-------------|--------------|--------------|-------------|------------|
| SVUFoilCoef | 2.59272E-03 | 1.08203E-04 | 2.51931E-06 | 2.22810E02 | -2.03374E-01 | -5.16248E01 | 4.44356E00 |
| TempCoef | 2.59386E01 | -3.08886E-02 | 2.97357E-06 | -4.40396E-09 | 0.00000E00 | 0.00000E00 | |





With following settings

| Index | 0 | 1 | 2 | 3 |
|------------------|--------------|------------|------------|------------|
| PhaseCoef | -9.71000E-01 | 1.00000E00 | 0.00000E00 | 0.00000E00 |
| | | | | |
| Index | 0 (Offset) | 1 (Slope) | | |
| ConcCoef | 0.00000E00 | 1.00000E00 | | |
| Salinity | 0.00 | | | |
| | | | | |
| Firmware Version | 5.3.1 | | | |

Date:19.12.2024

admil Fordercory