

Home

PUBLIC

Questions

Tags

Users

COLLECTIVES

Explore Collectives

FIND A JOB

Jobs

Companies

TEAMS

Create free Team

## I'm Confused! Char, Char\* or String in C++

Asked 9 years, 9 months ago Modified 8 years, 10 months ago Viewed 4k times

when i use char or char\*, visual studio 2012(11) only couts last character such as:

```
#include <iostream>
#include <string>
int main(){
    using namespace std;
    char chName = 'Alex';
    cout<<chName;
}
```

It displays only "x". it is correct is i use `string strName = "Alex"` but in those function which have parameter as a char, string can not be passed on as argument. in this case, VS compiler says that strings cant be converted into int. also tell me what is difference between char and char\*. I am a PHP developer and C++ is so confusing. Please help me.

C++ C-strings

Share Edit Follow Flag

asked Jun 19, 2012 at 16:44

Suchal

193 +1 +7

4 When Using C++ use string. Inside double quotes is a constant string.If you want to return a char\* from a string use `c_str()`. Check the link [stackoverflow.com/questions/388242/](http://stackoverflow.com/questions/388242/) - DumbCoder Jun 19, 2012 at 16:48

Add a comment

Start a bounty

4 Answers

Active Oldest Votes

char can only keep 1 character at a time; in this case, it keeps your last character, 'x'. char\* is a pointer to one or more char objects, and if read correctly, can also be used as a string. So setting

```
const char *chName = "Alex";
cout << chName;
```

should output the whole name.

Another problem is your use of quotations. 'x' denotes a char, while "x" denotes an array of char's, known as a string literal.

If there is a function that requires you to pass a char \*, you could pass

```
const char *param = "this is da parameter";
function (param);
```

or

```
std::string param = "da parameter"; //std::string is a type of string as well.
function (param.c_str ());
```

You could also use the declaration

```
char chName[] = "Alex";
```

This would create an local array of char's (namely, 5 char's, because it appends a null character at the end of the array). So, calling `chName[3]` should return 'x'. This can also be streamed to `cout` like the others

```
cout << chName;
```

EDIT: By the way, you should return an `int` in your function `main ()`. Like 0.

Share Edit Follow Flag

edited Jun 19, 2012 at 17:35

answered Jun 19, 2012 at 16:49

GILGAMESH

1,687 +3 +20 +32

2 I don't know about "you should return an int in your function main." C++ allows main (but no other function) to omit the return statement. If it is omitted, 0 is returned. - Rob Jun 19, 2012 at 17:10

1 @Rob: C++ allows a lot of silly things. You should return an `int` from `main` even if you don't have to. - Mooing Duck Jun 19, 2012 at 17:26

@MooingDuck, what for, if `return 0` is implicit? - Griwes Jun 19, 2012 at 17:48

@MooingDuck, both of them are nonsense in this case. - Griwes Jun 19, 2012 at 19:39

"If there is a function that requires you to pass a char \*, you could pass " No nonono, only if it's one that wants a `const char*`. - Hatted Rooster Nov 29, 2016 at 9:48

Add a comment

```
char chName = 'Alex';
```

This is wrong. This way, you create a four-byte integer out of Alex, then you store it in a char -- of course, it doesn't fit into a one-byte char, so only its less significant byte, the x gets stored, which is then output. You need to use

```
const char *chName = "Alex";
```

to get the correct output.

An alternative to your problem: use `std::string`, as you're working in C++, but for those functions who expect a `char *` as their argument, use:

```
std::string str; // C++ string object
function_call(str.c_str());
```

Share Edit Follow Flag

edited May 21, 2013 at 11:40

answered Jun 19, 2012 at 16:47

Ken D

5,700 +1 +33 +58

user529758

4 Better to use a proper C++ `string` though, rather than an old skool C-style `char *`. - Paul R Jun 19, 2012 at 16:48

I'm not saying which is better; I'm answering OP's question. (Btw C being "old skool" is not necessarily true. Try to write an operating system in C...) - user529758 Jun 19, 2012 at 16:50

@H2CO3: Writing an operating system is a completely niche use and does not whatsoever prevent C from being a worthless pile of junk in the general case. - Puppy Jun 19, 2012 at 16:51

@H2CO3: We're talking about C++, not C. `char*` is definitely outmoded for most purposes in C++. - Fred Larson Jun 19, 2012 at 16:53

"prevent C from being a worthless pile of junk in the general case" Have you ever written a single line of C? - user529758 Jun 19, 2012 at 16:53

Add a comment | Show 2 more comments

The `char` type holds a single integral value, usually with the range -128 to 127. It is not a string type. Single quotes in C are used for character literals, not string literals. `'Alex'` is not the same as `"Alex"`.

The char literal syntax you used:

```
char chName = 'Alex';
```

is called a multi-character literal, and it has an implementation defined value of type `int`. Implementations I'm familiar with construct this by concatenating the values of the individual characters. So the value of `'Alex'` is probably `A 0x41, l 0x6C, e 0x65, x 0x78`, or `0x416C6578`. Then when you assign it to a char it gets truncated to just the last byte (since thats all a char can hold), which is `0x78`, or the same as `'x'`.

The `*` is the pointer dereference operator in C, and it's also used when declaring a pointer. So `const char *chName = "Alex";` declares a pointer to a `char` rather than a single `char`, and that pointer will point to the first character of the string literal `"Alex"`. So your program might look like:

```
#include <iostream>
int main(){
    const char *chName = "Alex";
    std::cout << chName;
}
```

Share Edit Follow Flag

edited Jun 19, 2012 at 17:27

answered Jun 19, 2012 at 16:50

bames53

82.4k +13 +167 +234

Add a comment

```
char chName = 'Alex';
```

is a multicharacter literal and it is implementation defined.

\_ C++ standard, §2.14.3/1 - Character literals \_

An ordinary character literal that contains more than one c-char is a multicharacter literal . A multicharacter literal has type `int` and implementation-defined value.

instead of this, you should use

```
const char *chPTR = "Alex";
```

or

```
char chName[] = "Alex";
```

**Difference between char and char\***

In `char ch`; `ch` is a *char variable* which can store a single ascii character, whereas `char *ch`; is a *pointer to char* which can store address of a char variable.

**Difference between char and String**  
see [this SO post](#).

Share Edit Follow Flag

edited May 23, 2017 at 10:24

answered Jun 19, 2012 at 16:52

Community Bot

1 +1

Eight

4,096 +5 +27 +51

Add a comment

Your Answer

B I

Community wiki

Post Your Answer

Not the answer you're looking for? Browse other questions tagged C++ C-strings or ask your own question.

The Overflow Blog

- ✓ Celebrating the Stack Exchange sites that turned ten years old in Q1 2022
- ✓ New data: What makes developers happy at work

Featured on Meta

- What goes into site sponsorships on SE?
- Stack Exchange Q&A access will not be restricted in Russia
- Announcing an A/B test for a Trending sort option
- New User Experience: Deep Dive into our Research on the Staging Ground - How...

Hot Meta Posts

- 27 What is the true intention in the "How to reference material written by..."
- 21 When choosing "Looks OK" in the "First answers" review queue, the wording...

Linked

- 4235 The Definitive C++ Book Guide and List
- 145 Difference between string and char[] types in C++

Related

- 3241 How do I iterate over the words of a string?
- 1013 How to convert a std::string to const char\* or char\*
- 77 error C2065: 'cout' : undeclared identifier
- 1 Cannot assign pointer in a self-referential object in Visual Studio 2010
- 1921 Easiest way to convert int to string in C++
- 433 std::string to char\*
- 12 c++11 sorting list using lambda
- 1 Invalid operands to binary expression when using unordered\_map?

Hot Network Questions

- What were the incentives behind WinWord.Concept computer virus?
- Why some FIDO security fobs use keyboard emulation mode?
- What do '4eCe' and '2eCe' mean in Lalo's Symphonie Espagnole?
- Can the Earth be seen from the moon when we have a total lunar eclipse at the perigee?
- I turned breaker off, now security alarm system won't stop beeping
- Are there "strongpeople" in Russia who push Putin to war?
- is non digital necessarily analog?
- How can the bear-man refer to a "Jack-in-the-box" in The Hobbit?
- semi perfect number - number of divisors
- Is there a time limit to publish PhD research?
- Earth-Moon Barycenter Perihelion
- In Excel, how do I access cells using fully-qualified numeric coordinates (worksheet, column, row)?
- insert comment in the beginning of specified line in file
- Is LastViewedDate field is always present on an object?
- How to make edges "tuck behind" each other in TikZ?
- Does Google return search results based on words that are found only in the site's domain name?
- Is there an easy way of plotting a part of a circle?
- Nintegrate does not converge for this integrand but Simpson's Rule does
- How to see constraint violation for network flow problem
- Same caption for two side-by-side figures
- What are those flight level values on an airway?
- Different color in citation with Hyperref
- Can you use SHAKE256\_XOF with XOR to make a stream cipher?
- What does human vapor smell like?

Question feed



STACK OVERFLOW

Questions  
Jobs  
Developer Jobs Directory  
Help

PRODUCTS

Teams  
Talent  
Advertising  
Enterprise

COMPANY

About  
Press  
Work Here  
Legal  
Privacy Policy  
Terms of Service  
Contact Us  
Cookie Settings  
Cookie Policy

STACK EXCHANGE NETWORK

Technology  
Culture & recreation  
Life & arts  
Science  
Professional  
Business  
API  
Data

Blog Facebook Twitter LinkedIn Instagram