

What does ampersand "&" do in front of pointers?

Asked 8 years, 3 months ago Modified 4 years, 11 months ago Viewed 28k times

When functions are being called I often see the ampersand in front of the pointer in the function parameter.

15 E.g.


```
int *ptr;
randomFunction(&ptr);
```

I have done some research and found that this means that the function uses pointers to pointers. Is the & sign in front of a pointer used just to indicate this or does it do something else?


c++ c pointers reference operators

Share Edit Follow Flag

edited Apr 11, 2015 at 3:05

 **herohuyongtao**
47.6k 25 123 162

asked Jan 22, 2014 at 3:15

 **user3213163**
497 3 7 10

- 4 returns the address of it. So &ptr will return an int** You would usually do this if you want the function to change what the pointer points at or do some sort of assignment to it. – Brandon Jan 22, 2014 at 3:16
- Address of ptr. ie int** here – Digital_Reality Jan 22, 2014 at 3:17
- @CantChooseUsernames: That's rather obsolete (C style). In C++, you'd use int*& for that. – MSalters Jan 22, 2014 at 8:48
- @MSalters We have different opinions on obsolete I guess. Sometimes you want the user to be able to enter "nullptr". You cannot do this with a reference. Also it makes it "more" obvious what is being done to the parameter passed. Other than that, you are indeed very right. I myself tend to use T* &ptr more than T**. But you know, sometimes there's always that exception mentioned above. – Brandon Jan 23, 2014 at 0:40
- @Brandon but you can change what pointer points to without getting pointer to the pointer and you can lead assignment too. – O.G. Sep 4, 2019 at 10:48

4 Answers

Sorted by: Highest score (default)


It's a pointer to the pointer.

& is the reference operator, and can be read as address of. In your example, it will get another pointer, that is the address of the pointer given as it's argument, i.e. a pointer to the pointer.

Look at the following example:

```
int **ipp;
int i = 5, j = 6, k = 7;
int *ip1 = &i, *ip2 = &j;
ipp = &ip1;
```

You will get:




In the above example, ipp is a pointer to pointer. ipp stores the address of ip1 and ip1 stores the address of i.


You can check out Pointers to Pointers for more info.

Share Edit Follow Flag

edited Jun 19, 2017 at 12:34

 **jdhao**
18k 10 114 202

answered Jan 22, 2014 at 3:18

 **herohuyongtao**
47.6k 25 123 162

- 1 Thanks! that website really helped – user3213163 Jan 22, 2014 at 5:25
- 3 Kind of off topic, but why would one want to use a pointer to a pointer? – user2344665 Feb 28, 2014 at 18:25
- @JDMDev One example would be COM uses ptr-to-ptr to return an interface pointer using CoCreateInstance() and IUnknown::QueryInterface(). Check out here for more info. – herohuyongtao Feb 28, 2014 at 18:30

Take a step back. The fundamental rules of pointer operators are:

- The * operator turns a value of type pointer to T into a variable of type T.
- The & operator turns a variable of type T into a value of type pointer to T.

So when you have

```
int *ptr;
```

ptr is a variable of type pointer to int. Therefore *ptr is a variable of type int -- the * turns a pointer into a variable. You can say *ptr = 123;.

Since ptr is a variable of type pointer to int, &ptr is a value -- not a variable -- of type pointer to pointer to int:


```
int **pp = &ptr;
```

&ptr is a value of type pointer to pointer to int. pp is a variable of type pointer to pointer to int. *pp is a variable of type pointer to int, and in fact is the same variable as ptr. The * is the inverse of the &.

Make sense?

Share Edit Follow Flag


answered Jan 22, 2014 at 16:13

 **Eric Lippert**
630k 172 1210 2051

It helps to think of "&" this way. int function_name (&(whatever)); You are passing the address of (whatever). Whatever can be a number of things: an elementary variable. a function. a structure. a union. an array. You should mentally translate "&" to "take the address of". So your example means : pass a COPY of the address of the address of the variable ptr of type int!

Share Edit Follow Flag

answered Jan 22, 2014 at 5:25

 **user3221497**
11 1


- Do you mean '&' should be '*' – Zo Has Jan 22, 2014 at 5:49
- @DamienJoe: No! & is the opposit of *. & takes the address of it's argument and * returns what's stored under it's argument (interpreting the argument as address). – alk Jan 22, 2014 at 7:43
- @alk Thanks for the info. Updated my concepts with that. – Zo Has Jan 22, 2014 at 8:51

```
Int *ptr;
```

&ptr returns the address of a pointer variable ptr. In short, double pointer or int** holds the address of ptr with &ptr.

Share Edit Follow Flag

answered Jan 22, 2014 at 5:07

 **Fahad Naeem**
504 6 15