

# Returning Rvalue Reference and Temporary Materialization

Asked 1 year, 11 months ago   Modified 1 year, 11 months ago   Viewed 106 times

Consider the following functions. I'd like answers for **C++17**.

3

▼

★  
1

🕒

```
MyClass&& func() {  
    return MyClass{};  
}  
  
int main() {  
    MyClass&& myRef = func();  
}
```

Questions:

1. Is the expression `func()` an xvalue? Why?
2. Why is `myRef` a dangling reference? Or, more specifically, why is `func()` returning a dangling reference? Wouldn't returning rvalue reference cause temporary materialization, and extend the temporary object's lifetime?

`c++` `return` `c++17` `rvalue-reference` `xvalue`

Share Edit Follow Flag

asked Jun 10, 2020 at 5:07

?

[zemageht](#)  
95 ● 6

▲ ["Is the expression func\(\) an xvalue? Why?" ... why wouldn't it be? – Nicol Bolas](#) Jun 10, 2020 at 5:17  
▼

[Add a comment](#)

[Start a bounty](#)

1 Answer

Sorted by: 

Highest score (default) ▼

▲

4

▼

✓

🕒

`func()` is an xvalue because one of the rules of the language is that if a function is declared to have a return type of rvalue reference to object, then an expression consisting of calling that function is an xvalue . (C++17 expr.call/11).

[Temporary materialization](#) occurs any time a reference is bound to a prvalue.

The *result* of the function is `myRef` which is initialized by the prvalue `func()` . However if we consult the lifetime extension rules in class.temporary/6 it has:

The lifetime of a temporary bound to the returned value in a function return statement is not extended; the temporary is destroyed at the end of the full-expression in the return statement.

So the temporary object materialized by `func()` is destroyed when the return statement completes, with no extension.

Share Edit Follow Flag

answered Jun 10, 2020 at 5:18

?

[M.M](#)  
135k ● 21 ● 188 ● 335

[Add a comment](#)