



Return by reference in C++ with Examples

Difficulty Level: Medium • Last Updated: 01 Aug, 2020

<u>Pointers</u> and <u>References</u> in C++ held close relation with one another. The major difference is that the pointers can be operated on like adding values whereas references are just an **alias** for another variable.

- Functions in C++ can return a **reference** as it's returns a **pointer**.
- When function returns a **reference** it means it returns a **implicit** pointer.

Return by reference is very different from <u>Call by reference</u>. Functions behaves a very important **role** when variable or pointers are returned as reference.

See this function signature of Return by Reference Below:

```
dataType& functionName(parameters);
where,
dataType is the return type of the function,
and parameters are the passed arguments to it.
```

Below is the code to illustrate the Return by reference:

CPP

```
#include <iostream>
    using namespace std;
    int& returnValue(int& x)
        cout << "x = " << x
             << " The address of x is "</pre>
             << &x << endl;
        return x;
    int main()
        int a = 20;
        int& b = returnValue(a);
        cout << "a = " << a
             << " The address of a is "
             << &a << endl;
        cout << "b = " << b
             << " The address of b is "
             << &b << endl;
        returnValue(a) = 13;
0
        cout << "a = " << a
             << " The address of a is "
             << &a << endl;
\triangleright
        return 0;
```

Output:

```
x = 20 The address of x is 0x7fff3025711c
a = 20 The address of a is 0x7fff3025711c
b = 20 The address of b is 0x7fff3025711c
x = 20 The address of x is 0x7fff3025711c
a = 13 The address of a is 0x7fff3025711c
```

Explanation:

Since **reference** is nothing but an **alias**(synonym) of another variable, the address of **a**, **b** and **x** never changes.

Note: We should never return a local variable as a reference, reason being, as soon as the functions returns, local variable will be erased, however, we still will be left with a reference which might be a security bug in the code.

Below is the code to illustrate the Return by reference:

C++

```
#include <iostream>
     using namespace std;
    int x;
    int& retByRef()
         return x;
    int main()
0
         retByRef() = 10;
0
         cout << x;</pre>
\triangleright
         return 0;
C
```

Return by reference in C++ with Examples - GeeksforGeeks 2022/5/7 22:02

> **Start Your Coding Journey Now!** Login Register

> > Vote for difficulty

Current difficulty : <u>Medium</u>

Easy Normal Medium Hard Expert

G Sign in to GeeksforGeeks with Google Guo Xinxin justnostop@gmail.com Continue as Guo

Article Contributed By:

ayush0x00 @ayush0x00

Company

About Us

Careers

In Media

Contact Us

Privacy Policy

Copyright Policy

Article Tags: cpp-references, return, C++ Programs

Learn

Algorithms

Data Structures

SDE Cheat Sheet

Machine learning

CS Subjects

Video Tutorials

Improve Article Report Issue

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

News

Top News

Technology

Business

Finance

Lifestyle

Work & Career

Load Comments

Cloning solutions as easy as 1, 2, 3

invitrogen
by Thermo Fisher Scientific

Golang

C#

SQL

Languages Python Java CPP

Web Development Web Tutorials Django Tutorial HTML CSS

JavaScript

Bootstrap

Contribute Write an Article Improve an Article Pick Topics to Write Write Interview Experience Internships Video Internship

2/2

@geeksforgeeks , Some rights reserved

GeeksforGeeks

5th Floor, A-118, Sector-136, Noida, Uttar Pradesh - 201305