



P1 header (GPIO names): 1 GPIO2, 2 GPIO4, 3 GPIO6, 4 GPIO16, 5 GPIO17, 6 GPIO18, 7 GPIO21, 8 GPIO8, 9 GPIO7, 10 GPIO10, 11 GPIO20 USB_D+, 12 GPIO19 USB_D-, 13 GND, 14 5V

P2 header (GPIO names): 1 3V3, 2 GND, 3 GPIO43 TXD, 4 GPIO44 RXD, 5 GPIO47, 6 GPIO48, 7 GPIO15, 8 GPIO13, 9 GPIO11, 10 GPIO12, 11 GPIO14, 12 GPIO9, 13 GND, 14 VBAT

Module connector: 1 3V3 | 2 GND | 3 IN1 = GPIO10 | 4 IN2 = GPIO7 | 5 ID = GPIO8 | 6 GPIO6 | 7 GPIO4 | 8 GPIO2

All six module signals are ADC1-capable (ADC continuous mode on the ESP32-S3 is ADC1 only).

Passive carrier: the module ID divider lives on each input module.

OPad

Sheet: /

File: controller_carrier_v1.kicad_sch

Title: OPad Controller Carrier V1

Size: A4

Date: 2026-09-14

Rev: V1.0

KiCad E.D.A. 10.0.6

Id: 1/1