

ORB External API

1.0.2

OAS 3.0

ORB External API – Integration guide for EHR systems.

ORB supports integration with clinical EHR systems, allowing clinicians to access NHS records on patients within the EHR. The API has two main parts:

- **Data Model Linkage** – connects Organisations, Users and Patients from the EHR into ORB
- **Data Access** – allows the EHR system to show specific Patient data when requested by a specific User

This API is **organisation-scoped**: all patient and user operations occur in the context of an Organisation.

External EHR IDs are used for Organisations, Users and Patients — ORB does not expose internal IDs.

Request validation (400): When the request cannot be parsed or accepted—for example malformed JSON, a required body field missing, a query or path value in the wrong form (such as `offset=0sd` when an integer is expected), a value outside the permitted set (such as `"sex": "Female1"` when only defined values are accepted), or a property not defined for that operation (such as an unknown field `"newField"` in a PATCH or POST request body)—and no narrower ORB `errorCode` applies, the response always includes `errorCode InvalidRequestData` and a single `errorMessage`. The body contains **only** these two members. `errorMessage` is intended for display: either a fixed general sentence or—commonly—a short line naming one query parameter and the rejected value when only that parameter is at fault (see `ErrorResponseInvalidRequestData` in components/schemas). Wording may change in later API versions; use `errorCode` for programmatic handling and **do not** parse `errorMessage` for business logic.

Servers

<https://api-test-app.orbforhealth.com/v1> - TEST / Development

Authorize

Organisations

Create, update, delete and list organisations under the governing body



GET

/organisations

List Organisations

Returns a list of organisations under the Governing Body linked to the API key. Includes suspension status and auto-delete date when suspended. Filtering by suspension status is optional.

Parameters

Try it out

Name	Description
suspended boolean	Filter by suspension status. Omit to return all results.

Name	Description
(query)	

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "extOrganisationId": "string", "organisationName": "string", "suspended": true, "autoDeleteDate": "2026-07-23" }]</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
404	Governing Body corresponding to given API key not found Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

POST

/organisations/{extOrganisationId} Create Organisation

 

Creates an Organisation in ORB under the GovBody associated with the API Key. Allowed before the organisation contract is signed (required for onboarding).

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey

extOrganisationKey

Request body required

application/json

Example Value | Schema

```
{
  "organisationName": "string",
  "address1": "string",
  "address2": "string",
  "address3": "string",
  "address4": "string",
  "postcode": "string",
  "phoneNumber": "string",
  "cqcRegistrationNumber": "string",
  "researchOptOut": false
}
```

Responses

Code	Description	Links
201	Organisation created	No links
400	Creation failed due to invalid request or validation error	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
<pre>{ "errorMessage": "One or more fields contain invalid values. Please verify the input data.", "errorCode": "InvalidRequestData" }</pre>		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
404	No external client found for the provided API key	No links
Media type		
application/json; charset=utf-8		

Code	Description	Links
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Organisation already exists with the same extOrganisationId (IdNotAvailable) or organisationName (NameNotAvailable)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "Organisation already exists", "errorCode": "IdNotAvailable" }</pre>	

PATCH

/organisations/{extOrganisationId} Update Organisation



Updates organisation details or suspends/unsuspends the organisation. Requires the organisation contract to be signed ([403](#) OrganisationContractNotSigned otherwise).

- If an organisation is suspended it is not considered for billing, and no Users can access data via API.
- Organisations cannot be suspended indefinitely. When suspending, the caller may specify [autoDeleteDays](#) to set when automatic deletion happens. If not specified this happens in 180 days.
- Organisations can be unsuspended to restore access for Users.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey

Request body required

application/json; charset=utf-8 ▾

[Example Value](#) | [Schema](#)

```
{
  "organisationName": "string",
  "address1": "string",
  "address2": "string",

```

```
"address3": "string",
"address4": "string",
"postcode": "string",
"phoneNumber": "string",
"cqcRegistrationNumber": "string",
"researchOptOut": true,
"suspended": true,
"autoDeleteDays": 180
}
```

Responses

Code	Description	Links
200	Organisation updated	No links
400	Update failed due to invalid request or validation error	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned)	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }	
404	Organisation or Governing Body not found	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }	

Code	Description	Links
	<pre>{ "errorCode": "ClientNotFound" }</pre>	
409	Organisation Name already exists	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		

GET	/organisations/{extOrganisationId} Get Organisation	 
Returns the organisation details for the given external organisation ID when it exists in the Governing Body linked to the API key.		
Parameters		Try it out
Name	Description	
extOrganisationId * required	External organisation ID (EHR)	
string (path)	Example : extOrganisationKey	
extOrganisationKey		
Responses		
Code	Description	Links
200	Organisation exists in Governing Body	No links
Media type		
application/json; charset=utf-8 ▾		
Controls Accept header.		
Example Value Schema		

Code	Description	Links
	<pre>{ "extOrganisationId": "string", "organisationName": "string", "suspended": true, "autoDeleteDate": "2026-07-23" }</pre>	
400	Bad request	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

DELETE

/organisations/{extOrganisationId} Delete Organisation



Delete the organisation and all associated users. Requires the organisation contract to be signed (**403** OrganisationContractNotSigned otherwise). Use this if an organisation asks to turn OFF the integration permanently or if it leaves the EHR system.

Once deleted:

- The extOrganisationId is no longer valid for use in any API calls.
- If a patient has no other organisations linked to their profile, they will no longer be able to login.

Parameters

Try it out

Name	Description
extOrganisationId * required string	External organisation ID (EHR) Example : extOrganisationKey

Name

Description

(path)

extOrganisationKey

Responses

Code	Description	Links
200	Organisation deleted (no response body)	No links
400	Deletion failed due to invalid request or validation error (including OrgAlreadyArchived if the organisation was already deleted)	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned)	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>		

Code	Description	Links
404	Organisation not found	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }		

GET	/organisations/{extOrganisationId}/contract-status Get Organisation Contract Status	🔒 ^
Returns whether the organisation has signed the ORB organisation contract and when. Available before the contract is signed (not gated). Used by the host to decide whether to show the signing iframe.		
Parameters		Try it out
NameDescription		
extOrganisationId * required	External organisation ID (EHR)	
string (path)	Example : extOrganisationKey	
extOrganisationKey		
Responses		
Code	Description	Links
200	Contract status for the organisation	No links
Media type		
application/json; charset=utf-8 ▾		
Controls Accept header.		
Examples		
Not signed ▾		
Example Value Schema		
{ "extOrganisationId": "org-123", }		

Code	Description	Links
	<pre>"contractSigned": false, "contractSignedAt": null }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled for this client	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found for this API key / client	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/contract-access-token
Request Contract Access Token

🔒 ↗

Generates a short-lived organisation-scoped token used to open the ORB organisation-contract signing iframe. Available before the contract is signed (not gated). The token identifies the API-key client and external organisation only (no patient or user claim). JWT claims include `clientScopeId`, `extOrganisationId`, and `tokenScope = organisation-contract`. See the Widget Integration Guide for iframe embedding and `postMessage ( SET_TOKEN , CONTRACT_SIGNED )`.

Parameters

Name

Description

extOrganisationId * requiredstring
(path)

External organisation ID (EHR). Must be the same ID used at Create Organisation under this API key; scopes the contract-signing iframe to that organisation

Example : extOrganisationKey

extOrganisationKey

Responses

Code

Description

Links

200

Contract access token issued

No links

Media type

application/json; charset=utf-8 ▾

Controls Accept header.

Example Value | Schema

```
{
  "accessToken": "string",
  "expiresIn": 900
}
```

401

Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.

No links

403

Organisation suspended, or EHR API disabled for this client

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

404

Organisation not found for this API key / client

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/branding

Set Organisation Branding



Updates the organisation logo and optional welcome title/subtitle shown on the patient-facing NHS linking page (the page patients see when the EHR uses Connect Patient by Email or Connect Patient by Link).

Requires the organisation contract to be signed (**403** OrganisationContractNotSigned otherwise).

Logo changes apply only when overwriteLogo is true: send a file to replace the logo, or send no file to remove it. When overwriteLogo is false or omitted, the existing logo is left unchanged (any uploaded file is ignored). Optionally include patientNHSActivationWelcomeTitle and/or patientNHSActivationWelcomeSubtitle to update NHS activation page text without resending the logo. Allowed logo formats: PNG, JPEG, JPG, SVG. Maximum file size: 1 MB.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey

extOrganisationKey

Request body

multipart/form-data ▾

file string(\$binary)	Logo image (PNG, JPEG, JPG, or SVG; max 1 MB)
last_modified string	
patientNHSActivationWelcomeTitle string	NHS activation page welcome title (applied when included in the request)
patientNHSActivationWelcomeSubtitle string	NHS activation page welcome subtitle (applied when included in the request)
overwriteLogo boolean	When true, update the stored logo (replace if a file is sent, remove if no file is sent). When false or omitted, the existing logo is not modified.

Responses

Code	Description	Links
204	Organisation branding updated	No links
400	Invalid request or validation error	No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed, or EHR API disabled	No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorCode": "OrganisationContractNotSigned",
  "errorMessage": "The organisation contract has not been signed. Com"
```

Code	Description	Links
	<pre>plete contract signing before using this API." }</pre>	
404	Organisation or Governing Body not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	
415	Unsupported media type (UnsupportedMediaType). Returned when the uploaded file is not PNG, JPEG, JPG, or SVG, when the file content does not match its declared type, or when the request is not multipart/form-data.	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorCode": "UnsupportedMediaType", "errorMessage": "This graphic must be supplied in PNG,JPEG or SVG f ormats." }</pre>	

Users

Create, update, list and delete EHR-linked users within an organisation (clinical and non-clinical via isClinician)



GET

/organisations/{extOrganisationId}/users

List Users



Returns users for the organisation (regardless of whether the organisation is currently suspended).
Pagination is optional — if no pagination parameters are provided, all users are returned as an array. If pagination parameters are provided, a paginated response with metadata is returned.

Parameters

Try it out

Name	Description
extOrganisationId * required	External organisation ID (EHR)
string	
(path)	Example : extOrganisationKey

Name	Description
	extOrganisationKey
limit integer (query)	Maximum number of users to return (1–1000). If omitted, all users are returned. limit
offset integer (query)	Number of users to skip before returning results. Only used when limit is provided. <i>Default value : 0</i> 0

Responses

Code	Description	Links
200	OK — returns either a plain array (no pagination) or an object with pagination metadata. Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "extUserId": "string", "firstName": "string", "lastName": "string", "professionalRegNumber": "string", "emailAddress": "string", "isClinician": true, "isLocum": true, "authorisedSignatory": true }]</pre>	No links
400	Invalid pagination parameters (limit > 1000, limit < 1, or offset < 0) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", }</pre>	No links

Code	Description	Links
	<pre>"errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/users/{extUserId} Create User

🔒 ⤴

Creates an ORB user within an ORB organisation, linked to the corresponding external User ID. Used to grant a user access to the integration. Set **isClinician** to **true** for clinical users and **false** for non-clinical users. Only users with **isClinician: true** may request patient access tokens (see Request Access Token).

- External IDs are unique within an Organisation and do not change.
- ORB does not link or merge users based on personal attributes (e.g. name, professional registration number).
- If the same person exists in multiple organisations in the EHR, a separate ORB user must be created for each.
- User counts during a month may be used in billing; creation and deletion are logged.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey

Name		Description
		extOrganisationKey
extUserId * required string (path)		External user ID (EHR) Example : extUserKey
		extUserKey
Request body required		application/json
Example Value Schema		
<pre>{ "firstName": "string", "lastName": "string", "professionalRegNumber": "string", "emailAddress": "string", "isClinician": true, "isLocum": true, "authorisedSignatory": true }</pre>		
Responses		
Code	Description	Links
201	User created	No links
400	Creation failed due to invalid request or validation error	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
Media type		

Code	Description	Links
	application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
409	User already exists in this organisation with the same extUserId (<code>IdNotAvailable</code>), or email already in use (<code>EmailNotAvailable</code>)	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	

PATCH

/organisations/{extOrganisationId}/users/{extUserId} Update User

🔒 ⤴

Updates one or more attributes of an existing user within an organisation.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey

Name		Description
extUserId * required		External user ID (EHR)
string (path)		Example : extUserKey
		extUserKey
Request body required		application/json; charset=utf-8 ▾
Example Value Schema		
<pre>{ "firstName": "string", "lastName": "string", "professionalRegNumber": "string", "emailAddress": "string", "isClinician": true, "islocum": true, "authorisedSignatory": true }</pre>		
Responses		
Code	Description	Links
200	User updated	No links
400	Invalid request or validation error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
Media type		
application/json; charset=utf-8 ▾		

Code	Description	Links
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	User or organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

DELETE

/organisations/{extOrganisationId}/users/{extUserId} Delete User



Deletes the specified user from the organisation. After deletion, the user will no longer be able to access the integration for this organisation.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extUserId * required string (path)	External user ID (EHR) <i>Example</i> : extUserKey extUserKey

Responses

Code	Description	Links
200	User deleted (no response body)	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>		
404	User or organisation not found	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>		

Patients

List, update, connect, and manage patient connections and permissions



GET

/organisations/{extOrganisationId}/patients

List Patients



Returns a list of patients for the specified organisation. Pagination is optional — if no pagination parameters are provided, all patients are returned as an array. If pagination parameters are provided, a paginated response with metadata is returned. Filters can be combined using AND logic.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
limit integer (query)	Maximum number of patients to return (1–1000). If omitted, all patients are returned. limit
offset integer (query)	Number of patients to skip before returning results. Only used when limit is provided. <i>Default value</i> : 0 0
connectionStatus string (query)	Filter by connection status. <i>Available values</i> : InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected -- ▾
dataAccessStatus string (query)	Filter by data access request status. <i>Available values</i> : RequestNotSent, RequestSent, Reviewed -- ▾
patientDataAccessLimited boolean (query)	When true, filter to patients which have restricted their data (patient-side). -- ▾
gpDataAccessLimited boolean (query)	When true, filter to patients which have their data blocked from GP side. -- ▾
dobMismatch boolean (query)	When true, filter to patients whose date of birth in ORB mismatches the one in NHS. -- ▾
surnameMismatch boolean (query)	When true, filter to patients whose surname in ORB mismatches the one in NHS. -- ▾

Name	Description
nhsNumber string (query)	Filter by NHS number from NHS Login in ORB (digits only; spaces/hyphens allowed in the query value)

nhsNumber

Responses

Code	Description	Links
200	OK — returns either a plain array (no pagination) or an object with pagination metadata. Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "extPatientId": "string", "title": "string", "firstName": "string", "lastName": "string", "dateOfBirth": "2026-07-23", "sex": "string", "emailAddress": "string", "postcode": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "nhsNumber": "string", "lastInvitationEmailDate": "2026-07-23T16:57:44.507Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.507Z" }]</pre>	No links
400	Invalid pagination parameters (limit > 1000, limit < 1, or offset < 0), or invalid filter value for connectionStatus, dataAccessStatus, patientDataAccessLimited, gpDataAccessLimited, dobMismatch, surnameMismatch, or nhsNumber, or invalid combination of these parameters (for example, patientDataAccessLimited or gpDataAccessLimited cannot be set if connectionStatus is not Connected) Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/patients/{extPatientId}/connection-email

Connect Patient by Email

🔒 ⬆

Sends an email inviting a patient to sign up and grant permission for the organisation to view NHS records.

- If the patient does not exist, ORB creates a new patient record and sends an NHS invitation email.
- If the patient exists but is not connected, ORB sends the invitation email directly.
- If the patient is already connected, it sends a data access request email.

The EHR may call this endpoint again to send a **reminder**. Rate limits apply: at most two NHS invitation emails and at most two data access request emails per patient per organisation per 24 hours; invitation can be resent when **resend** is true while the invitation limit allows.

Link validity: NHS registration links expire after a system-configurable period (7 days by default). Generating a replacement invalidates the previous registration link and restarts the expiry period. Data-access / consent emails open the ORB login page and do not expire after a fixed number of days (they are not timed invitation tokens); the patient must sign in before reviewing access.

Parameters

Try it out

Name		Description
extOrganisationId * required string (path)		External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extPatientId * required string (path)		External patient ID (EHR) <i>Example</i> : extPatientKey extPatientKey
Request body required		application/json ▼
Example Value Schema		
<pre>{ "title": "string", "firstName": "string", "lastName": "string", "dateOfBirth": "2026-07-23", "sex": "string", "emailAddress": "string", "postcode": "string", "requestingClinicianId": "string", "resend": true }</pre>		
Responses		
Code	Description	Links
200	Invite path — connectionStatus is InviteSent (invitation email sent, or already invited and invite flow still applies) Media type application/json; charset=utf-8 ▼ Controls Accept header. Example Value Schema	No links
<pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, }</pre>		

Code	Description	Links
	<pre> "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.512Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.512Z" } </pre>	
201	Patient is Connected (NHS registration complete; a data-access request email may be sent when applicable) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre> { "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.512Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.512Z" } </pre>	No links
400	Connection failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre> { "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" } </pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre> { "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" } </pre>	No links
404	Organisation or requesting clinician not found Media type application/json; charset=utf-8 ▾	No links

Code	Description	Links
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Conflict — external patient ID already in use by another patient, or request body DOB/surname does not match existing ORB patient record (PatientDetailsMismatch when email already exists with different demographics). Distinct from 422 (NHS→ORB mismatch). Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
422	DataMismatch — NHS login revealed a mismatch between ORB and NHS data Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.513Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.513Z" }</pre>	No links
429	Rate limit exceeded — the maximum number of connection emails allowed per patient per organisation in 24 hours has been reached Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "Rate limit exceeded", "errorCode": "ResendLimitExceeded" }</pre>	No links

POST

/organisations/{extOrganisationId}/patients/{extPatientId}/connection-link
Connect Patient by Link



Returns an invitation link which can be sent to a patient as part of a link request.

- If the patient does not exist, ORB creates a new patient record and returns an NHS invitation link.
- If the patient exists but is not connected, an NHS invitation link is returned.
- If the patient is already connected, response code 201 is returned with no invitation link.

In all previous cases, if a data access request link can still be issued under the rate limits, a data access request link is built and returned too.

Calling this endpoint again allows the EHR to obtain a fresh link as a **reminder**. Invitation and data access request links are only returned while the respective limits in the last 24 hours for this patient and organisation have not been exceeded (at most two NHS invitation links and at most two data access request links per 24 hours).

Link validity: NHS registration links expire after a system-configurable period (7 days by default). Generating a replacement invalidates the previous registration link and restarts the expiry period. The data-access / consent link opens the ORB login page and does not expire after a fixed number of days (it is not a timed invitation token); the patient must sign in before reviewing access.

Parameters

[Try it out](#)

Name

Description

extOrganisationId * required

string
(path)

External organisation ID (EHR)

Example : extOrganisationKey

extOrganisationKey

extPatientId * required

string
(path)

External patient ID (EHR)

Example : extPatientKey

extPatientKey

Request body required

application/json



Example Value | Schema

```
{
  "title": "string",
  "firstName": "string",
  "lastName": "string",
  "dateOfBirth": "2026-07-23",
  "sex": "string",
  "emailAddress": "string",
  "postcode": "string",
  "requestingClinicianId": "string",
  "resend": true
}
```

Responses

Code	Description	Links
200	connectionStatus is InviteNotSent or InviteExpired — NHS invitation and/or data-access links returned when applicable Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "invitationLink": "string", "dataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.516Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.516Z" }</pre>	No links
201	connectionStatus is InviteSent or Connected — no new invite link unless resend is true; data-access link returned when applicable Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "invitationLink": "string", "dataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.517Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.517Z" }</pre>	No links
400	Connection failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", }</pre>	No links

Code	Description	Links
	<pre>"errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation or requesting clinician not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Conflict — external patient ID already in use by another patient, or request body DOB/surname does not match existing ORB patient record (PatientDetailsMismatch when email already exists with different demographics). Distinct from 422 (NHS→ORB mismatch).	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
422	DataMismatch — NHS login revealed a mismatch between ORB and NHS data	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	

Code	Description	Links
	<pre>{ "invitationLink": "string", "dataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.518Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.518Z" }</pre>	
429	Rate limit exceeded — the maximum number of connection links allowed per patient per organisation in 24 hours has been reached Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "Rate limit exceeded", "errorCode": "ResendLimitExceeded" }</pre>	No links

GET

/organisations/{extOrganisationId}/patients/{extPatientId}/connection

Get Patient Connection Status

🔒 ⤴

Returns the connection status and access levels for the patient.

Includes **nhsNumber** when present on the patient's NHS Login record in ORB (read-only; omitted or null otherwise).

Parameters

Try it out

Name	Description
extOrganisationId * required	External organisation ID (EHR)
string (path)	Example : extOrganisationKey

extOrganisationKey

Name	Description
extPatientId * required string (path)	External patient ID (EHR) <i>Example</i> : extPatientKey

extPatientKey

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-23", "lastInvitationEmailDate": "2026-07-23T16:57:44.520Z", "lastAccessRequestEmailDate": "2026-07-23T16:57:44.520Z", "nhsNumber": "string" }</pre>	No links
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled) Media type	No links

Code	Description	Links
	application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Patient or organisation not found Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

DELETE

/organisations/{extOrganisationId}/patients/{extPatientId}/connection
Remove Patient Connection

🔒 ⤴

Removes the link between the patient and the organisation. Use this when a patient leaves a clinic; doing so is treated as an implied retraction of the organisation's permission to view that patient's records.

This is an **unlink** only for the organisation in the request:

- The EHR connection for this organisation is removed (List Patients / token / connection / status / permissions for this patient and organisation fail).
- The patient-to-organisation link for that organisation is also removed.
- The underlying patient account, PatientLogin, and NHS record data are retained. Other organisation links are untouched.
- If the patient still has other organisations, they can continue to log in and use those.
- If this was the patient's last organisation, they cannot log in until linked to at least one organisation again; the account and any completed NHS registration are kept.
- On re-connect, ORB treats them as an existing patient and typically returns a data-access / data-share link rather than a new NHS invitation link.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extPatientId * required	External patient ID (EHR)

Name

string

(path)

Description

Example : extPatientKey

extPatientKey

Responses

Code	Description	Links
200	Connection removed (no response body)	No links
400	Deletion failed due to invalid request or validation error	No links
	Media type application/json; charset=utf-8	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Patient or organisation not found	No links
	Media type application/json; charset=utf-8	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key",</pre>	

Code	Description	Links
	<pre>"errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>		

GET

/organisations/{extOrganisationId}/patients/{extPatientId}/permissions

Get Granted Permissions

🔒 ⤴

Returns the list of data permissions that the patient has granted to this organisation. Requires that the patient is connected to the organisation.

If the patient connection status is **Connected**, this endpoint returns the granted permissions. If the connection status is **InviteSent** or **DataMismatch**, this endpoint returns 404.

Issuing an access token checks that the patient is Connected and that organisation/patient data access is not limited. It does not check individual dataset grants (e.g. Allergies, Documents); those are enforced inside the widget when NHS record data is fetched. This permissions endpoint is informational for the EHR.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey
extPatientId * required string (path)	External patient ID (EHR) Example : extPatientKey extPatientKey

Responses

Code	Description	Links
200	OK — returns array of permission names Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>["Allergies", "Medication History", "Immunisations"]</pre>	<i>No links</i>
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	<i>No links</i>
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	<i>No links</i>
403	Organisation not authorised to view this patient Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	<i>No links</i>
404	Patient or organisation not found, or patient connection not established Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	<i>No links</i>

PATCH

/organisations/{extOrganisationId}/patients/{extPatientId} Update Patient



Updates one or more demographic attributes of an existing patient within an organisation. Typically used when the EHR updates patient details such as contact information or postcode.

- If `dateOfBirth` or `lastName` are supplied, they are **validated** against existing ORB data (not overwritten). If they do not match, the request fails with 409.
- Other supplied fields overwrite ORB data according to data priority rules (NHS data takes precedence).

Parameters

Try it out

Name

Description

extOrganisationId * required

External organisation ID (EHR)

string
(path)

Example : extOrganisationKey

extOrganisationKey

extPatientId * required

External patient ID (EHR)

string
(path)

Example : extPatientKey

extPatientKey

Request body required

application/json



Example Value | Schema

```
{
  "title": "string",
  "firstName": "string",
  "lastName": "string",
  "dateOfBirth": "2026-07-23",
  "sex": "string",
  "emailAddress": "string",
  "postcode": "string"
}
```

Responses

Code

Description

Links

200

Patient updated — returns current demographic fields stored in ORB after the update

No links

Code

Description

Links

Media type

 ▾

Controls Accept header.

Example Value | Schema

```
{
  "title": "Ms",
  "sex": "Male",
  "dateOfBirth": "1933-11-14",
  "firstName": "Simon",
  "lastName": "OLLEY",
  "postcode": "asdas123",
  "emailAddress": "patient@example.com"
}
```

400

Update failed due to invalid request or validation error

No links

Media type

 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

401

Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.

No links

403

Organisation contract not signed (**OrganisationContractNotSigned**), or EHR API disabled (**ApiDisabled**)

No links

Media type

 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

404

Patient or organisation not found

No links

Media type

 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

Code	Description	Links
409	Conflict — request body DOB/surname does not match existing ORB patient record	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		
500	Unexpected server error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		

Patient Access

Request short-lived access tokens for the ORB widget



POST	/organisations/{extOrganisationId}/patients/{extPatientId}/access-token Request Access Token	
Returns a short-lived JWT used to access patient data via the ORB widget (iframe).		
Security Model: - The EHR must make this request server-side (never from the browser). - The request must include the <code>extUserId</code> of the clinician requesting access. - ORB validates that the user exists and belongs to the organisation, the user has <code>isClinician: true</code>, the organisation is not suspended, the organisation has access to the patient, the patient is Connected, and organisation/patient data access is not limited. Individual dataset grants are enforced inside the widget when data is fetched, not at token issue. - The returned JWT is scoped to the specific user, patient, and organisation and includes <code>clientScopeId</code>. - Token expires in 15 minutes. - Requesting an access token is recorded as clinician access for audit purposes. - Issuing a token does not mean clinician widget T&C are accepted. T&C are enforced inside the ORB widget (per user per organisation, mandatory tick-box; NHS data blocked until accepted). The External API does not expose accept/query endpoints for T&C.		
Parameters	Try it out	

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extPatientId * required string (path)	External patient ID (EHR) <i>Example</i> : extPatientKey extPatientKey

Request body **required**

application/json ▼

Example Value | Schema

```
{  
  "extUserId": "string"  
}
```

Responses

Code	Description	Links
200	Token issued successfully Media type application/json; charset=utf-8 ▼ Controls Accept header. Example Value Schema <pre>{ "accessToken": "string", "expiresIn": 900 }</pre>	No links
400	Invalid request (missing extUserId) Media type application/json; charset=utf-8 ▼ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Access denied — NonClinicianAccess (isClinician: false); OrgIsSuspended ; PatientInvalidStatus (patient not Connected, or patient/GP data access limited); OrganisationContractNotSigned ; or ApiDisabled / ApiKeyExpired	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Patient, user, or organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Internal server error	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

 [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

Enum:

 [RequestNotSent, RequestSent, Reviewed]

ErrorCode string

Enum:

 [ClientNotFound, OrgNotFound, OrgLinkNotFound, UserNotFound, PatientNotFound, InvalidParameter, InvalidProperty, InvalidRequestData, UnsupportedMediaType, IdNotAvailable, NameNotAvailable, EmailNotAvailable, DobMismatch, SurnameMismatch, PatientInvalidStatus, PatientDetailsMismatch, ResendLimitExceeded, NonClinicianAccess, OrgIsSuspended, ApiDisabled, ApiKeyExpired, OrgAlreadyArchived, OrganisationContractNotSigned, OrganisationContractAlreadySigned, TermsNotAccepted, GenericError]

ErrorResponse {

errorMessage*

 string

example: Organisation not found
Human-readable error message

errorCode

ErrorCode  ErrorCode string

Enum:

 [ClientNotFound, OrgNotFound, OrgLinkNotFound, UserNotFound, PatientNotFound, InvalidParameter, InvalidProperty, InvalidRequestData, UnsupportedMediaType, IdNotAvailable, NameNotAvailable, EmailNotAvailable, DobMismatch, SurnameMismatch, PatientInvalidStatus, PatientDetailsMismatch, ResendLimitExceeded, NonClinicianAccess, OrgIsSuspended, ApiDisabled, ApiKeyExpired, OrgAlreadyArchived, OrganisationContractNotSigned, OrganisationContractAlreadySigned, TermsNotAccepted, GenericError]

}

example: { "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }

ErrorResponseInvalidRequestData ▾ {

description:

Returned when the request body, query string, or path cannot be parsed or validated successfully, and no narrower **errorCode** applies. The response body is always the compact JSON object with **errorCode** and **errorMessage** only, as for **InvalidRequestData** in the API specification (Common Errors). **errorMessage** is assigned as follows:

- **General message** – Used when more than one validation issue is reported for the same request, and in typical cases where the problem lies in the **JSON request body** only—including a value outside a permitted enumeration (for example **"sex": "Female1"** when only defined values are accepted), or a property not defined for that operation (for example an unknown or misspelled field name in a PATCH or POST body). Request bodies must contain only properties listed for that endpoint; extra properties are rejected with 400, not ignored. In these cases **errorMessage** is a single standard sentence; clients must not assume a field-by-field breakdown in the message text.
- **Per-parameter message (query)** – Typically used when a single query (or equivalent) parameter does not match its expected type; **errorMessage** may then identify the parameter and the supplied value.

Other isolated query-parameter errors may follow the same pattern. The exact wording of **errorMessage** is not guaranteed across API versions; use it for display only and base integration logic on **errorCode**.

errorCode*

▾ **string**

Enum:

▾ [**InvalidRequestData**]

errorMessage*

▾ **string**

example: One or more fields contain invalid values. Please verify the input data.

Intended for display: either the fixed general sentence, or—commonly—a short per-parameter line naming one query parameter and the rejected value when only that parameter is at fault (for example **The value '0sd' is not valid for Offset.**).

}

example: { "errorCode": "InvalidRequestData", "errorMessage": "One or more fields contain invalid values. Please verify the input data." }

PaginationMetadata ▾ {

total*

▾ **integer**

Total number of records

limit*

▾ **integer**

Number of records requested per page

offset*

▾ **integer**

Number of records skipped

hasMore*

▾ **boolean**

Whether there are more records available

}

CreateOrganisationRequest ▾ {

organisationName* ▾ **string**
Unique Organisation name (case-insensitive)

address1* ▾ **string**
First line of address

address2* ▾ **string**
Second line of address

address3 ▾ **string**
Third line of address

address4 ▾ **string**
Fourth line of address

postcode* ▾ **string**
Postcode

phoneNumber* ▾ **string**
Phone number

cqcRegistrationNumber* ▾ **string**
CQC registration number

researchOptOut ▾ **boolean**
default: false
Research opt-out flag (defaults to false)

}

UpdateOrganisationRequest ▾ {

```
  organisationName      ▾ string
                        Unique Organisation name (case-insensitive)

  address1              ▾ string
                        First line of address

  address2              ▾ string
                        Second line of address

  address3              ▾ string
                        Third line of address

  address4              ▾ string
                        Fourth line of address

  postcode              ▾ string
                        Postcode

  phoneNumber           ▾ string
                        Phone number

  cqcRegistrationNumber ▾ string
                        CQC registration number

  researchOptOut        ▾ boolean
                        Research opt-out flag

  suspended             ▾ boolean
                        Suspended flag

  autoDeleteDays        ▾ integer
                        maximum: 180
                        default: 180
                        Auto-delete after suspension in days (max 180, default 180)

}
```

OrganisationSummary ▾ {

```
  extOrganisationId*   ▾ string
                        External organisation ID (EHR)

  organisationName*    ▾ string
                        Organisation name

  suspended*           ▾ boolean
                        Suspension status

  autoDeleteDate       ▾ string($date)
                        nullable: true
                        Auto-delete date in YYYY-MM-DD format when suspended; null if not set

}
```

ContractStatusResponse ▾ {

extOrganisationId* ▾ **string**
External organisation ID (EHR); same value as in the path

contractSigned* ▾ **boolean**
true after successful organisation-contract signing; false until then

contractSignedAt ▾ **string**(\$date-time)
nullable: true
UTC ISO-8601 timestamp of signing; present only when contractSigned is true, otherwise null

}

CreateUserRequest ▾ {

firstName* ▾ **string**
User's first name

lastName* ▾ **string**
User's last name

professionalRegNumber* ▾ **string**
Professional registration number

emailAddress ▾ **string**
User's email address

isClinician* ▾ **boolean**
true if the user is a clinical user; **false** for non-clinical users (e.g. administrative). Only clinical users may request patient access tokens.

isLocum* ▾ **boolean**
true if the user is a temporary locum; **false** if a permanent employee

authorisedSignatory* ▾ **boolean**
true if this user is an authorised signatory for the organisational contract (host-side marker; ORB does not re-check this flag when accepting the organisation contract in the iframe)

}

UpdateUserRequest ▾ {

```
  firstName
    ▾ string
    User's first name

  lastName
    ▾ string
    User's last name

  professionalRegNumber
    ▾ string
    Professional registration number

  emailAddress
    ▾ string
    User's email address

  isClinician
    ▾ boolean
    If supplied, updates whether the user is a clinical user
    ( true ) or non-clinical ( false )

  isLocum
    ▾ boolean
    If supplied, updates whether the user is a locum ( true ) or
    permanent ( false )

  authorisedSignatory
    ▾ boolean
    If supplied, updates authorised signatory flag for the
    organisational contract

}
```

User ▾ {

```
  extUserId*
    ▾ string
    External user ID (EHR)

  firstName*
    ▾ string
    User's first name

  lastName*
    ▾ string
    User's last name

  professionalRegNumber*
    ▾ string
    Professional registration number

  emailAddress
    ▾ string
    User's email address

  isClinician*
    ▾ boolean
    true if clinical user; false if non-clinical

  isLocum*
    ▾ boolean
    true if locum; false if permanent employee

  authorisedSignatory*
    ▾ boolean
    true if authorised signatory for the organisational contract

}
```

PaginatedUsersResponse ▾ {

users*

▾ [User ▾ {

extUserId*

▾ string

External user ID (EHR)

firstName*

▾ string

User's first name

lastName*

▾ string

User's last name

professionalRegNumber*

▾ string

Professional registration number

emailAddress

▾ string

User's email address

isClinician*

▾ boolean

true if clinical user; false if non-clinical

isLocum*

▾ boolean

true if locum; false if permanent employee

authorisedSignatory*

▾ boolean

true if authorised signatory for the organisational contract

}]

pagination*

PaginationMetadata ▾ {

total*

▾ integer

Total number of records

limit*

▾ integer

Number of records requested per page

offset*

▾ integer

Number of records skipped

hasMore*

▾ boolean

Whether there are more records available

}

}

UpdatePatientRequest ▾ {

```
  title
    ▾ string
    Patient title

  firstName
    ▾ string
    Patient's first name

  lastName
    ▾ string
    Patient's last name (surname) – validated, not overwritten

  dateOfBirth
    ▾ string($date)
    Date of birth in YYYY-MM-DD format – validated, not overwritten

  sex
    ▾ string
    Patient sex (e.g. Male, Female)

  emailAddress
    ▾ string
    Patient email address

  postcode
    ▾ string
    Patient postcode

}
```

PatientDemographics ▾ {

```
  description:
    Current patient demographic fields in ORB after a successful
    update. Does not include extPatientId, connectionStatus, or other
    list-only fields. Values may differ from the PATCH request where
    NHS data takes precedence or where dateOfBirth / lastName were
    validated but not overwritten.

  title
    ▾ string
    Patient title (e.g. Mr, Ms)

  sex
    ▾ string
    Patient sex (e.g. Male, Female)

  dateOfBirth
    ▾ string($date)
    Date of birth in YYYY-MM-DD format

  firstName*
    ▾ string
    Patient's first name

  lastName*
    ▾ string
    Patient's last name (surname)

  postcode*
    ▾ string
    Patient postcode

  emailAddress
    ▾ string
    nullable: true
    Patient email address

}
```

PatientSummary ▾ {

extPatientId*

▾ string

External patient ID (EHR)

title

▾ string

Patient title

firstName*

▾ string

Patient's first name

lastName*

▾ string

Patient's last name

dateOfBirth*

▾ string(\$date)

Date of birth in YYYY-MM-DD format

sex

▾ string

Patient sex (e.g. Male, Female)

emailAddress*

▾ string

Patient email address

postcode

▾ string

Patient postcode

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

```
Enum:
    ▼ [ RequestNotSent, RequestSent, Reviewed ]
oldestNhsRecordDate
    ▼ string($date)
    nullable: true
    Date of oldest NHS record received (ISO-8601); null if none

nhsNumber
    ▼ string
    nullable: true
    NHS number from NHS Login in ORB (read-only; optional;
    omitted or null if not on record)

lastInvitationEmailDate
    ▼ string($date-time)
    nullable: true
    ISO-8601 date of the last NHS registration invitation email
    sent

lastAccessRequestEmailDate
    ▼ string($date-time)
    nullable: true
    ISO-8601 date of the last data access request email sent

}
```

PaginatedPatientsResponse ▾ {

patients*

▾ [PatientSummary ▾ {

extPatientId*

▾ string

External patient ID (EHR)

title

▾ string

Patient title

firstName*

▾ string

Patient's first name

lastName*

▾ string

Patient's last name

dateOfBirth*

▾ string(\$date)

Date of birth in YYYY-MM-DD format

sex

▾ string

Patient sex (e.g. Male, Female)

emailAddress*

▾ string

Patient email address

postcode

▾ string

Patient postcode

connectionStatus*

ConnectionStatus ▾

ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited	▼ boolean True if the GP has blocked the patient's data partially or totally
dataAccessStatus	DataAccessStatus ▼ DataAccessStatus string Whether the patient has been asked to grant data access and whether they have done so. - RequestNotSent - Request not sent yet - RequestSent - Request sent to the patient - Reviewed - Patient granted the organisation access to some NHS data Enum: ▼ [RequestNotSent, RequestSent, Reviewed]
oldestNhsRecordDate	▼ string(\$date) nullable: true Date of oldest NHS record received (ISO-8601); null if none
nhsNumber	▼ string nullable: true NHS number from NHS Login in ORB (read-only; optional; omitted or null if not on record)
lastInvitationEmailDate	▼ string(\$date-time) nullable: true ISO-8601 date of the last NHS registration invitation email sent
lastAccessRequestEmailDate	▼ string(\$date-time) nullable: true ISO-8601 date of the last data access request email sent
pagination*	}} PaginationMetadata ▼ { total* ▼ integer Total number of records limit* ▼ integer Number of records requested per page offset* ▼ integer Number of records skipped hasMore* ▼ boolean Whether there are more records available }
	}

PatientConnectionStatus ▾ {

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

Enum:

▾ [RequestNotSent, RequestSent, Reviewed]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

}

PatientConnectionStatusResponse ▾ {

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

Enum:

▾ [RequestNotSent, RequestSent, Reviewed]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

nhsNumber

▾ string

nullable: true

NHS number from the patient's NHS Login record in ORB (read-only; set via NHS Login verification only). Omitted or null if the patient has no NHS Login on record.

}

ConnectPatientByEmailRequest ▾ {

title*	▾ string Patient title
firstName*	▾ string Patient's first name
lastName*	▾ string Patient's last name
dateOfBirth*	▾ string(\$date) Date of birth in YYYY-MM-DD format
sex*	▾ string Patient sex (e.g. Male, Female)
emailAddress*	▾ string Patient email address
postcode*	▾ string Patient postcode
requestingClinicianId*	▾ string External user ID of the requesting clinician
resend	▾ boolean True to force resend of the email if already invited

}

ConnectPatientByLinkRequest ▾ {

```
  title*  
    ▾ string  
    Patient title  
  
  firstName*  
    ▾ string  
    Patient's first name  
  
  lastName*  
    ▾ string  
    Patient's last name  
  
  dateOfBirth*  
    ▾ string($date)  
    Date of birth in YYYY-MM-DD format  
  
  sex*  
    ▾ string  
    Patient sex (e.g. Male, Female)  
  
  emailAddress*  
    ▾ string  
    Patient email address  
  
  postcode*  
    ▾ string  
    Patient postcode  
  
  requestingClinicianId*  
    ▾ string  
    External user ID of the requesting clinician  
  
  resend  
    ▾ boolean  
    True to force resend of the link if already invited
```

}

ConnectPatientByLinkResponse ▾ {

invitationLink

▾ string

nullable: true

URL to the patient invitation that can be shared or displayed

dataAccessRequestLink

▾ string

nullable: true

URL for the patient to grant data access to the organisation

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent – Invitation not yet sent
- InviteSent – Invitation sent, patient has not logged in via NHS yet
- InviteExpired – Invitation sent but expired
- DataMismatch – NHS login revealed a mismatch between ORB and NHS data
- Connected – Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent – Request not sent yet
- RequestSent – Request sent to the patient
- Reviewed – Patient granted the organisation access to some NHS data

Enum:

▾ [RequestNotSent, RequestSent, Reviewed]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

}

AccessTokenRequest ▾ {

extUserId*

▾ string

External user ID (EHR) of the requesting clinician

}

AccessTokenResponse ▾ {

accessToken*

▾ string

Short-lived JWT token for accessing patient data (expires in expiresIn seconds)

expiresIn*

▾ integer

example: 900

Token expiration time in seconds (typically 900 = 15 minutes)

}

ContractAccessTokenResponse ▾ {

accessToken*

▾ string

Short-lived JWT for the organisation-contract signing iframe only (not the patient records widget). Pass into the iframe via SET_TOKEN / openOrbWidget (see Widget Integration Guide)

expiresIn*

▾ integer

example: 900

Seconds until the token expires from issue time (configured on ORB; typically 900 = 15 minutes). Generate a new token if the iframe session outlives this value

}