

ORB External API

1.0.2

OAS 3.0

ORB External API – Integration guide for EHR systems.

ORB supports integration with clinical EHR systems, allowing clinicians to access NHS records on patients within the EHR. The API has two main parts:

- **Data Model Linkage** – connects Organisations, Users and Patients from the EHR into ORB
- **Data Access** – allows the EHR system to show specific Patient data when requested by a specific User

This API is **organisation-scoped**: all patient and user operations occur in the context of an Organisation.

External EHR IDs are used for Organisations, Users and Patients — ORB does not expose internal IDs.

Request validation (400): When the request cannot be parsed or accepted—for example malformed JSON, a required body field missing, a query or path value in the wrong form (such as `offset=0sd` when an integer is expected), a value outside the permitted set (such as `"sex": "Female1"` when only defined values are accepted), or a property not defined for that operation (such as an unknown field `"newField"` in a PATCH or POST request body)—and no narrower ORB `errorCode` applies, the response always includes `errorCode InvalidRequestData` and a single `errorMessage`. The body contains **only** these two members. `errorMessage` is intended for display: either a fixed general sentence or—commonly—a short line naming one query parameter and the rejected value when only that parameter is at fault (see `ErrorResponseInvalidRequestData` in components/schemas). Wording may change in later API versions; use `errorCode` for programmatic handling and **do not** parse `errorMessage` for business logic.

Servers

<https://api-test-app.orbforhealth.com/v1> - TEST / Development (placeholder – TBC)

Authorize



Organisations

Create, update, delete and list organisations under the governing body



GET

/organisations List Organisations



Returns a list of organisations under the Governing Body linked to the API key. Includes suspension status and auto-delete date when suspended. Filtering by suspension status is optional.

Parameters

Try it out

Name	Description
------	-------------

suspended boolean (query)	Filter by suspension status. Omit to return all results. -- ▾
---------------------------------	---

Responses

Code	Description	Links
200	OK	No links

Media type

application/json; charset=utf-8 ▾

Controls Accept header.

Example Value | Schema

```
[
  {
    "extOrganisationId": "string",
    "organisationName": "string",
    "suspended": true,
    "autoDeleteDate": "2026-07-17"
  }
]
```

404	Governing Body corresponding to given API key not found	No links
-----	---	----------

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

POST

/organisations/{extOrganisationId} Create Organisation



Creates an Organisation in ORB under the GovBody associated with the API Key. Allowed before the organisation contract is signed (required for onboarding).

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganizationKey extOrganizationKey

Request body **required**

application/json ▼

Example Value | Schema

```
{
  "organisationName": "string",
  "address1": "string",
  "address2": "string",
  "address3": "string",
  "address4": "string",
  "postcode": "string",
  "phoneNumber": "string",
  "cqcRegistrationNumber": "string",
  "researchOptOut": false
}
```

Responses

Code	Description	Links
201	Organisation created	No links
400	Creation failed due to invalid request or validation error Media type application/json; charset=utf-8 ▼ Example Value Schema <pre>{ "errorMessage": "One or more fields contain invalid values. Please verify the input data.", "errorCode": "InvalidRequestData" }</pre>	No links
404	No external client found for the provided API key Media type application/json; charset=utf-8 ▼ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Organisation already exists with the same extOrganisationId or organisationName	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "Organisation already exists", "errorCode": "IdNotAvailable" }</pre>	

PATCH

/organisations/{extOrganisationId} Update Organisation



Updates organisation details or suspends/unsuspends the organisation. Requires the organisation contract to be signed ([403](#) OrganisationContractNotSigned otherwise).

- If an organisation is suspended it is not considered for billing, and no Users can access data via API.
- Organisations cannot be suspended indefinitely. When suspending, the caller may specify [autoDeleteDays](#) to set when automatic deletion happens. If not specified this happens in 180 days.
- Organisations can be unsuspended to restore access for Users.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey

Request body required

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "organisationName": "string",
  "address1": "string",
  "address2": "string",
  "address3": "string",
  "address4": "string",
}
```

```
"postcode": "string",
"phoneNumber": "string",
"cqcrRegistrationNumber": "string",
"researchOptOut": true,
"suspended": true,
"autoDeleteDays": 180
}
```

Responses

Code	Description	Links
200	Organisation updated	No links
400	Update failed due to invalid request or validation error	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	
404	Organisation or Governing Body not found	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	
409	Organisation Name already exists	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	

GET

/organisations/{extOrganisationId} Get Organisation



Returns the organisation details for the given external organisation ID when it exists in the Governing Body linked to the API key.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey

Responses

Code	Description	Links
200	Organisation exists in Governing Body Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "extOrganisationId": "string", "organisationName": "string", "suspended": true, "autoDeleteDate": "2026-07-17" }</pre>	No links
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Organisation not found Media type	No links

Code

Description

Links

application/json; charset=utf-8

Example Value | Schema

```
{  "errorMessage": "No external client found for the provided API key",  "errorCode": "ClientNotFound"}
```

DELETE

/organisations/{extOrganisationId} Delete Organisation

^

Delete the organisation and all associated users. Requires the organisation contract to be signed (**403** OrganisationContractNotSigned otherwise). Use this if an organisation asks to turn OFF the integration permanently or if it leaves the EHR system.

Once deleted:

- The extOrganisationId is no longer valid for use in any API calls.
- If a patient has no other organisations linked to their profile, they will no longer be able to login.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey

Responses

Code	Description	Links
200	Organisation deleted (no response body)	No links
400	Deletion failed due to invalid request or validation error	No links

Media type

application/json; charset=utf-8

Example Value | Schema

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

GET

/organisations/{extOrganisationId}/contract-status

Get Organisation Contract Status

🔒 ⤴

Returns whether the organisation has signed the ORB organisation contract and when. Available before the contract is signed (not gated). Used by the host to decide whether to show the signing iframe.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey

Responses

Code	Description	Links
200	Contract status for the organisation	No links
Media type		
application/json; charset=utf-8 ▾		
Controls Accept header.		
Examples		
Not signed ▾		

Code	Description	Links
	Example Value Schema <pre>{ "extOrganisationId": "org-123", "contractSigned": false, "contractSignedAt": null }</pre>	
401	Missing or invalid API key	No links
403	EHR API disabled for this client	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found for this API key / client	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/contract-access-token

 

Request Contract Access Token

Mints a short-lived organisation-scoped token used to open the ORB organisation-contract signing iframe. Available before the contract is signed (not gated). The token identifies the API-key client and external organisation only (no patient or user claim). See the Widget Integration Guide for iframe embedding and postMessage (`SET_TOKEN` , `CONTRACT_SIGNED`).

Parameters

[Try it out](#)

Name

Description

extOrganisationId * required

string

(path)

External organisation ID (EHR)

Example : extOrganizationKey

extOrganizationKey

Responses

Code

Description

Links

200

Contract access token issued

No links

Media type

application/json; charset=utf-8 ▾

Controls Accept header.

Example Value | Schema

```
{
  "accessToken": "string",
  "expiresIn": 900
}
```

401

Missing or invalid API key

No links

403

Organisation suspended, or EHR API disabled for this client

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

404

Organisation not found for this API key / client

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/branding

Set Organisation Branding



Sets organisation branding used on the patient-facing NHS linking page (Connect Patient by Email / by Link): logo image and/or NHS activation welcome text.

Requires the organisation contract to be signed (**403** OrganisationContractNotSigned otherwise).

Logo changes apply only when overwriteLogo is true: send a file to replace the logo, or send no file to remove it. When overwriteLogo is false or omitted, the existing logo is left unchanged (any uploaded file is ignored). Optionally include patientNHSActivationWelcomeTitle and/or patientNHSActivationWelcomeSubtitle to update NHS activation page text without resending the logo. Allowed logo formats: PNG, JPEG, JPG, SVG. Maximum file size: 1 MB.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey
extOrganizationKey	

Request body

multipart/form-data ▾

file string(\$binary)	Logo image (PNG, JPEG, JPG, or SVG; max 1 MB)
--------------------------	---

last_modified
string

patientNHSActivationWelcomeTitle
string

NHS activation page welcome title (applied when included in the request)

patientNHSActivationWelcomeSubtitle
string

NHS activation page welcome subtitle (applied when included in the request)

overwriteLogo
boolean

When true, update the stored logo (replace if a file is sent, remove if no file is sent). When false or omitted, the existing logo is not modified.

Responses

Code	Description	Links
------	-------------	-------

204	Organisation branding updated	No links
-----	-------------------------------	----------

400	Invalid request or validation error	No links
-----	-------------------------------------	----------

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

403	Organisation contract not signed, or EHR API disabled	No links
-----	---	----------

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorCode": "OrganisationContractNotSigned",
  "errorMessage": "The organisation contract has not been signed. Complete contract signing before using this API."
}
```

404	Organisation or Governing Body not found	No links
-----	--	----------

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
415	Unsupported media type. Returned when the uploaded file is not PNG, JPEG, JPG, or SVG, when the file content does not match its declared type, or when the request is not multipart/form-data. Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorCode": "UnsupportedMediaType", "errorMessage": "This graphic must be supplied in PNG, JPEG or SVG formats." }</pre>	No links

Users

Create, update, list and delete EHR-linked users within an organisation (clinical and non-clinical via isClinician)



GET

/organisations/{extOrganisationId}/users

List Users



Returns users for the organisation (regardless of whether the organisation is currently suspended). Pagination is optional — if no pagination parameters are provided, all users are returned as an array. If pagination parameters are provided, a paginated response with metadata is returned.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey
limit integer (query)	Maximum number of users to return (1–1000). If omitted, all users are returned. limit

Name	Description
offset integer (query)	Number of users to skip before returning results. Only used when limit is provided. Default value : 0 0

Responses

Code	Description	Links
200	OK — returns either a plain array (no pagination) or an object with pagination metadata. Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "extUserId": "string", "firstName": "string", "lastName": "string", "professionalRegNumber": "string", "emailAddress": "string", "isClinician": true, "isLocum": true, "authorisedSignatory": true }]</pre>	No links
400	Invalid pagination parameters (limit > 1000, limit < 1, or offset < 0) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Organisation not found Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/users/{extUserId} Create User



Creates an ORB user within an ORB organisation, linked to the corresponding external User ID. Used to grant a user access to the integration. Set `isClinician` to `true` for clinical users and `false` for non-clinical users. Only users with `isClinician: true` may request patient access tokens (see Request Access Token).

- External IDs are unique within an Organisation and do not change.
- ORB does not link or merge users based on personal attributes (e.g. name, professional registration number).
- If the same person exists in multiple organisations in the EHR, a separate ORB user must be created for each.
- User counts during a month may be used in billing; creation and deletion are logged.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey
extUserId * required string (path)	External user ID (EHR) Example : extUserKey extUserKey

Request body required

application/json ▼

Example Value

Schema

```
{
  "firstName": "string",
  "lastName": "string",
  "professionalRegNumber": "string",
  "emailAddress": "string",
  "isClinician": true,
  "isLocum": true,
  "authorisedSignatory": true
}
```

Responses

Code	Description	Links
201	User created	No links
400	Creation failed due to invalid request or validation error	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
409	User already exists in this organisation with the same extUserId	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	

PATCH

/organisations/{extOrganisationId}/users/{extUserId} Update User



Updates one or more attributes of an existing user within an organisation.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganizationKey extOrganizationKey
extUserId * required string (path)	External user ID (EHR) <i>Example</i> : extUserKey extUserKey

Request body required

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "firstName": "string",
  "lastName": "string",
  "professionalRegNumber": "string",
  "emailAddress": "string",
  "isClinician": true,
  "isLocum": true,
  "authorisedSignatory": true
}
```

Responses

Code	Description	Links
200	User updated	No links
400	Invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	User or organisation not found	No links

Code

Description

Links

Media type

application/json; charset=utf-8

▼

Example Value | Schema

```
{  "errorMessage": "No external client found for the provided API key",  "errorCode": "ClientNotFound"}
```

DELETE

/organisations/{extOrganisationId}/users/{extUserId} Delete User



Deletes the specified user from the organisation. After deletion, the user will no longer be able to access the integration for this organisation.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganizationKey extOrganizationKey
extUserId * required string (path)	External user ID (EHR) <i>Example</i> : extUserKey extUserKey

Responses

Code	Description	Links
200	User deleted (no response body)	No links
404	User or organisation not found	No links

Media type

Code

Description

Links

application/json; charset=utf-8

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

Patients

List, update, connect, and manage patient connections and permissions

GET

/organisations/{extOrganisationId}/patients

List Patients

Returns a list of patients for the specified organisation. Pagination is optional — if no pagination parameters are provided, all patients are returned as an array. If pagination parameters are provided, a paginated response with metadata is returned. Filters can be combined using AND logic.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganizationKey extOrganizationKey
limit integer (query)	Maximum number of patients to return (1–1000). If omitted, all patients are returned. limit
offset integer (query)	Number of patients to skip before returning results. Only used when limit is provided. <i>Default value</i> : 0 0
connectionStatus string (query)	Filter by connection status. <i>Available values</i> : InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected --

Name	Description
dataAccessStatus string (query)	Filter by data access request status. Available values : RequestNotSent, RequestSent, Reviewed -- ▾
patientDataAccessLimited boolean (query)	When true, filter to patients which have restricted their data (patient-side). -- ▾
gpDataAccessLimited boolean (query)	When true, filter to patients which have their data blocked from GP side. -- ▾
dobMismatch boolean (query)	When true, filter to patients whose date of birth in ORB mismatches the one in NHS. -- ▾
surnameMismatch boolean (query)	When true, filter to patients whose surname in ORB mismatches the one in NHS. -- ▾

Responses

Code	Description	Links
200	OK — returns either a plain array (no pagination) or an object with pagination metadata.	No links

Media type

application/json; charset=utf-8 ▾

Controls Accept header.

Example Value | Schema

```
[
  {
    "extPatientId": "string",
    "title": "string",
    "firstName": "string",
    "lastName": "string",
    "dateOfBirth": "2026-07-17",
    "sex": "string",
    "emailAddress": "string",
    "postcode": "string",
    "connectionStatus": "InviteNotSent",
    "dobMismatch": true,
    "surnameMismatch": true,
    "patientDataAccessLimited": true,
    "gpDataAccessLimited": true,
    "dataAccessStatus": "RequestNotSent",
    "oldestNhsRecordDate": "2026-07-17",
```

Code	Description	Links
	<pre>"lastInvitationEmailDate": "2026-07-17T16:27:33.001Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.001Z" }]</pre>	
400	Invalid pagination parameters or invalid filter values / combinations	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/patients/{extPatientId}/connection-email
Connect Patient by Email



Sends an email inviting a patient to sign up and grant permission for the organisation to view NHS records.

- If the patient does not exist, ORB creates a new patient record and sends an NHS invitation email.
- If the patient exists but is not connected, ORB sends the invitation email directly.
- If the patient is already connected, it sends a data access request email.

The EHR may call this endpoint again to send a **reminder**. Rate limits apply: at most two NHS invitation emails and at most two data access request emails per patient per organisation per 24 hours; invitation can be resent when **resend** is true while the invitation limit allows.

Link validity: NHS registration links expire after a system-configurable period (7 days by default). Generating a replacement invalidates the previous registration link and restarts the expiry period. Data-access / consent emails use an authenticated ORB login URL with no separate link expiry.

Parameters

Try it out

Name	Description
extOrganisationId * required	External organisation ID (EHR)

Name		Description
string (path)		<i>Example</i> : extOrganizationKey extOrganizationKey
extPatientId * required string (path)		External patient ID (EHR) <i>Example</i> : extPatientKey extPatientKey
Request body required		application/json ▾
Example Value Schema		
<pre>{ "title": "string", "firstName": "string", "lastName": "string", "dateOfBirth": "2026-07-17", "sex": "string", "emailAddress": "string", "postcode": "string", "requestingClinicianId": "string", "resend": true }</pre>		
Responses		
Code	Description	Links
200	Invite sent Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.003Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.003Z" }</pre>	No links

Code	Description	Links
201	Patient already invited. No invite sent unless resend flag is true, but data access request is sent when applicable. Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.004Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.004Z" }</pre>	No links
400	Connection failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Organisation or requesting clinician not found Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
409	Conflict — external patient ID already in use, or DOB/surname mismatch with ORB record Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

Code	Description	Links
422	DataMismatch — NHS login revealed a mismatch between ORB and NHS data Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.004Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.004Z" }</pre>	No links
429	Rate limit exceeded — the maximum number of connection emails allowed per patient per organisation in 24 hours has been reached	No links

POST

/organisations/{extOrganisationId}/patients/{extPatientId}/connection-link
Connect Patient by Link



Returns an invitation link which can be sent to a patient as part of a link request.

- If the patient does not exist, ORB creates a new patient record and returns an NHS invitation link.
- If the patient exists but is not connected, an NHS invitation link is returned.
- If the patient is already connected, response code 201 is returned with no invitation link.

In all previous cases, if a data access request link can still be issued under the rate limits, a data access request link is built and returned too.

Calling this endpoint again allows the EHR to obtain a fresh link as a **reminder**. Invitation and data access request links are only returned while the respective limits in the last 24 hours for this patient and organisation have not been exceeded (at most two NHS invitation links and at most two data access request links per 24 hours).

Link validity: NHS registration links expire after a system-configurable period (7 days by default). Generating a replacement invalidates the previous registration link and restarts the expiry period. The data-access / consent link is an authenticated ORB login URL with no separate link expiry.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey

Name		Description
		extOrganizationKey
extPatientId * required		External patient ID (EHR)
string (path)		Example : extPatientKey
		extPatientKey
Request body required		application/json ▾
Example Value Schema		
<pre>{ "title": "string", "firstName": "string", "lastName": "string", "dateOfBirth": "2026-07-17", "sex": "string", "emailAddress": "string", "postcode": "string", "requestingClinicianId": "string", "resend": true }</pre>		
Responses		
Code	Description	Links
200	Patient was not invited yet, or invitation expired. Links returned.	No links
Media type		
application/json; charset=utf-8 ▾		
Controls Accept header.		
Example Value Schema		
<pre>{ "invitationLink": "string", "dataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.006Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.006Z" }</pre>		

Code	Description	Links
201	Patient already invited. No invite link returned unless resend flag is true, but data access request link is returned when applicable. Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "invitationLink": "string", "dataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.006Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.006Z" }</pre>	No links
400	Connection failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	No links
404	Organisation or requesting clinician not found Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	No links
409	Conflict — external patient ID already in use, or DOB/surname mismatch with ORB record Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API ke y",</pre>	No links

Code	Description	Links
	<pre>{ "errorCode": "ClientNotFound" }</pre>	
422	DataMismatch — NHS login revealed a mismatch between ORB and NHS data	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "invitationLink": "string", "dataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.007Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.007Z" }</pre>	
429	Rate limit exceeded — the maximum number of connection links allowed per patient per organisation in 24 hours has been reached	No links

GET

/organisations/{extOrganisationId}/patients/{extPatientId}/connection

Get Patient Connection Status

🔒 ⤴

Returns the connection status and access levels for the patient.

Includes **nhsNumber** when present on the patient's NHS Login record in ORB (read-only; omitted or null otherwise).

Parameters

Try it out

Name	Description
extOrganisationId * required	External organisation ID (EHR)
string (path)	Example : extOrganizationKey

extOrganizationKey

Name	Description
extPatientId * required string (path)	External patient ID (EHR) <i>Example</i> : extPatientKey

extPatientKey

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-07-17", "lastInvitationEmailDate": "2026-07-17T16:27:33.009Z", "lastAccessRequestEmailDate": "2026-07-17T16:27:33.009Z", "nhsNumber": "string" }</pre>	No links
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API ke y", "errorCode": "ClientNotFound" }</pre>	No links
404	Patient or organisation not found Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

DELETE

/organisations/{extOrganisationId}/patients/{extPatientId}/connection
Remove Patient Connection



Removes the link between the patient and the organisation. Use this when a patient leaves a clinic; doing so is treated as an implied retraction of the organisation's permission to view that patient's records.

This is an **unlink** only for the organisation in the request:

- The EHR connection for this organisation is removed (List Patients / token / connection / status / permissions for this patient and organisation fail).
- The patient-to-organisation link for that organisation is also removed.
- The underlying patient account, PatientLogin, and NHS/IM1 data are retained. Other organisation links are untouched.
- If the patient still has other organisations, they can continue to log in and use those.
- If this was the patient's last organisation, they cannot log in until linked to at least one organisation again; the account and any completed NHS registration are kept.
- On re-connect, ORB treats them as an existing patient and typically returns a data-access / data-share link rather than a new NHS invitation link.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganizationKey extOrganizationKey
extPatientId * required string (path)	External patient ID (EHR) <i>Example</i> : extPatientKey extPatientKey

Responses

Code	Description	Links
200	Connection removed (no response body)	No links
400	Deletion failed due to invalid request or validation error	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Patient or organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

GET

/organisations/{extOrganisationId}/patients/{extPatientId}/permissions

Get Granted Permissions

🔒 ⤴

Returns the list of data permissions that the patient has granted to this organisation. Requires that the patient is connected to the organisation.

If the patient connection status is **Connected**, this endpoint returns the granted permissions. If the connection status is **InviteSent** or **DataMismatch**, this endpoint returns 404.

This endpoint is informational only — the access token request endpoint will automatically validate permissions before issuing a token.

Parameters

Name

Description

extOrganisationId * requiredstring
(path)

External organisation ID (EHR)

Example : extOrganizationKey

extOrganizationKey

extPatientId * requiredstring
(path)

External patient ID (EHR)

Example : extPatientKey

extPatientKey

Responses

Code

Description

Links

200

OK — returns array of permission names

No links

Media type

application/json; charset=utf-8 ▾

Controls Accept header.

Example Value | Schema

```
[
  "Allergies",
  "Medication History",
  "Immunisations"
]
```

400

Bad request

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

403

Organisation not authorised to view this patient

No links

Media type

Code	Description	Links
	application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Patient or organisation not found, or patient connection not established Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links

PATCH

/organisations/{extOrganisationId}/patients/{extPatientId}

Update Patient

🔒 ⤴

Updates one or more demographic attributes of an existing patient within an organisation. Typically used when the EHR updates patient details such as contact information or postcode.

- If `dateOfBirth` or `lastName` are supplied, they are **validated** against existing ORB data (not overwritten). If they do not match, the request fails with 409.
- Other supplied fields overwrite ORB data according to data priority rules (NHS data takes precedence).

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganizationKey extOrganizationKey
extPatientId * required string (path)	External patient ID (EHR) Example : extPatientKey extPatientKey

Request body required

application/json

Example Value | Schema

```
{
  "title": "string",
  "firstName": "string",
  "lastName": "string",
  "dateOfBirth": "2026-07-17",
  "sex": "string",
  "emailAddress": "string",
  "postcode": "string"
}
```

Responses

Code	Description	Links
200	Patient updated — returns current demographic fields stored in ORB after the update Media type application/json; charset=utf-8 Controls Accept header. Example Value Schema <pre>{ "title": "Ms", "sex": "Male", "dateOfBirth": "1933-11-14", "firstName": "Simon", "lastName": "OLLEY", "postcode": "asdas123", "emailAddress": "patient@example.com" }</pre>	No links
400	Update failed due to invalid request or validation error Media type application/json; charset=utf-8 Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Patient or organisation not found Media type application/json; charset=utf-8	No links

Code	Description	Links
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Conflict — request body DOB/surname does not match existing ORB patient record Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
500	Unexpected server error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

Patient Access Request short-lived access tokens for the ORB widget



POST	/organisations/{extOrganisationId}/patients/{extPatientId}/access-token Request Access Token	
Returns a short-lived JWT used to access patient data via the ORB widget (iframe). Security Model: - The EHR must make this request server-side (never from the browser). - The request must include the extUserId of the clinician requesting access. - ORB validates that the user exists and belongs to the organisation, the user has isClinician: true, the organisation is not suspended, the organisation has access to the patient, and the patient has granted the necessary permissions. - The returned JWT is scoped to the specific user, patient, and organisation. - Token expires in 15 minutes. - Requesting an access token is recorded as clinician access for audit purposes. - Issuing a token does not mean clinician widget T&C are accepted. T&C are enforced inside the ORB widget (per user per organisation, mandatory tick-box; NHS data blocked until accepted). The External API does not expose accept/query endpoints for T&C.		

Parameters

[Try it out](#)

Name

Description

extOrganisationId * required

string
(path)

External organisation ID (EHR)

Example : extOrganizationKey

extOrganizationKey

extPatientId * required

string
(path)

External patient ID (EHR)

Example : extPatientKey

extPatientKey

Request body required

application/json

Example Value | Schema

```
{
  "extUserId": "string"
}
```

Responses

Code

Description

Links

200

Token issued successfully

No links

Media type

application/json; charset=utf-8

Controls Accept header.

Example Value | Schema

```
{
  "accessToken": "string",
  "expiresIn": 900
}
```

400

Invalid request (missing extUserId)

No links

Media type

application/json; charset=utf-8

Code	Description	Links
Example Value Schema		
403	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links
	Access denied — user not authorised (including <code>isClinician: false</code> , <code>errorCode</code> : <code>NonClinicianAccess</code>), organisation suspended, or patient permissions insufficient	
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
404	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links
	Patient, user, or organisation not found	
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
500	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links
	Internal server error	
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	

Schemas	⤴

ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

 [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

Enum:

 [RequestNotSent, RequestSent, Reviewed]

ErrorCode string

Enum:

 [ClientNotFound, OrgNotFound, OrgLinkNotFound, UserNotFound, PatientNotFound, InvalidParameter, InvalidProperty, InvalidRequestData, IdNotAvailable, NameNotAvailable, EmailNotAvailable, DobMismatch, SurnameMismatch, PatientInvalidStatus, ResendLimitExceeded, OrganisationContractNotSigned, GenericError]

ErrorResponse {

errorMessage*

 string

example: Organisation not found
Human-readable error message

errorCode

ErrorCode  ErrorCode string

Enum:

 [ClientNotFound, OrgNotFound, OrgLinkNotFound, UserNotFound, PatientNotFound, InvalidParameter, InvalidProperty, InvalidRequestData, IdNotAvailable, NameNotAvailable, EmailNotAvailable, DobMismatch, SurnameMismatch, PatientInvalidStatus, ResendLimitExceeded, OrganisationContractNotSigned, GenericError]

}

example: { "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }

ErrorResponseInvalidRequestData ▾ {

description:

Returned when the request body, query string, or path cannot be parsed or validated successfully, and no narrower **errorCode** applies. The response body is always the compact JSON object with **errorCode** and **errorMessage** only, as for **InvalidRequestData** in the API specification (Common Errors). **errorMessage** is assigned as follows:

- **General message** – Used when more than one validation issue is reported for the same request, and in typical cases where the problem lies in the **JSON request body** only—including a value outside a permitted enumeration (for example **"sex": "Female1"** when only defined values are accepted), or a property not defined for that operation (for example an unknown or misspelled field name in a PATCH or POST body). Request bodies must contain only properties listed for that endpoint; extra properties are rejected with 400, not ignored. In these cases **errorMessage** is a single standard sentence; clients must not assume a field-by-field breakdown in the message text.
- **Per-parameter message (query)** – Typically used when a single query (or equivalent) parameter does not match its expected type; **errorMessage** may then identify the parameter and the supplied value.

Other isolated query-parameter errors may follow the same pattern. The exact wording of **errorMessage** is not guaranteed across API versions; use it for display only and base integration logic on **errorCode**.

errorCode*

▾ **string**

Enum:

▾ [**InvalidRequestData**]

errorMessage*

▾ **string**

example: One or more fields contain invalid values. Please verify the input data.

Intended for display: either the fixed general sentence, or—commonly—a short per-parameter line naming one query parameter and the rejected value when only that parameter is at fault (for example **The value '0sd' is not valid for Offset.**).

}

example: { "errorCode": "InvalidRequestData", "errorMessage": "One or more fields contain invalid values. Please verify the input data." }

PaginationMetadata ▾ {

total*

▾ **integer**

Total number of records

limit*

▾ **integer**

Number of records requested per page

offset*

▾ **integer**

Number of records skipped

hasMore*

▾ **boolean**

Whether there are more records available

}

CreateOrganisationRequest ▾ {

organisationName* ▾ **string**
Unique Organisation name (case-insensitive)

address1* ▾ **string**
First line of address

address2* ▾ **string**
Second line of address

address3 ▾ **string**
Third line of address

address4 ▾ **string**
Fourth line of address

postcode* ▾ **string**
Postcode

phoneNumber* ▾ **string**
Phone number

cqcRegistrationNumber* ▾ **string**
CQC registration number

researchOptOut ▾ **boolean**
default: false
Research opt-out flag (defaults to false)

}

UpdateOrganisationRequest ▾ {

```
  organisationName      ▾ string
                          Unique Organisation name (case-insensitive)

  address1              ▾ string
                          First line of address

  address2              ▾ string
                          Second line of address

  address3              ▾ string
                          Third line of address

  address4              ▾ string
                          Fourth line of address

  postcode              ▾ string
                          Postcode

  phoneNumber           ▾ string
                          Phone number

  cqcRegistrationNumber ▾ string
                          CQC registration number

  researchOptOut        ▾ boolean
                          Research opt-out flag

  suspended             ▾ boolean
                          Suspended flag

  autoDeleteDays        ▾ integer
                          maximum: 180
                          default: 180
                          Auto-delete after suspension in days (max 180, default 180)

}
```

OrganisationSummary ▾ {

```
  extOrganisationId*   ▾ string
                          External organisation ID (EHR)

  organisationName*     ▾ string
                          Organisation name

  suspended*           ▾ boolean
                          Suspension status

  autoDeleteDate        ▾ string($date)
                          nullable: true
                          Auto-delete date in YYYY-MM-DD format when suspended; null if not set

}
```


ContractStatusResponse ▾ {

extOrganisationId* ▾ **string**
Echo of path parameter

contractSigned* ▾ **boolean**
true if the organisation contract has been signed

contractSignedAt ▾ **string(\$date-time)**
nullable: true
ISO-8601 timestamp of signing; null if not signed

}

CreateUserRequest ▾ {

firstName* ▾ **string**
User's first name

lastName* ▾ **string**
User's last name

professionalRegNumber* ▾ **string**
Professional registration number

emailAddress ▾ **string**
User's email address

isClinician* ▾ **boolean**
true if the user is a clinical user; **false** for non-clinical users (e.g. administrative). Only clinical users may request patient access tokens.

isLocum* ▾ **boolean**
true if the user is a temporary locum; **false** if a permanent employee

authorisedSignatory* ▾ **boolean**
true if this user is an authorised signatory for the organisational contract (host-side marker; ORB does not re-check this flag when accepting the organisation contract in the iframe)

}

UpdateUserRequest ▾ {

```
  firstName
    ▾ string
    User's first name

  lastName
    ▾ string
    User's last name

  professionalRegNumber
    ▾ string
    Professional registration number

  emailAddress
    ▾ string
    User's email address

  isClinician
    ▾ boolean
    If supplied, updates whether the user is a clinical user
    ( true ) or non-clinical ( false )

  isLocum
    ▾ boolean
    If supplied, updates whether the user is a locum ( true ) or
    permanent ( false )

  authorisedSignatory
    ▾ boolean
    If supplied, updates authorised signatory flag for the
    organisational contract

}
```

User ▾ {

```
  extUserId*
    ▾ string
    External user ID (EHR)

  firstName*
    ▾ string
    User's first name

  lastName*
    ▾ string
    User's last name

  professionalRegNumber*
    ▾ string
    Professional registration number

  emailAddress
    ▾ string
    User's email address

  isClinician*
    ▾ boolean
    true if clinical user; false if non-clinical

  isLocum*
    ▾ boolean
    true if locum; false if permanent employee

  authorisedSignatory*
    ▾ boolean
    true if authorised signatory for the organisational contract

}
```

PaginatedUsersResponse ▾ {

users*

▾ [User ▾ {

extUserId*

▾ string

External user ID (EHR)

firstName*

▾ string

User's first name

lastName*

▾ string

User's last name

professionalRegNumber*

▾ string

Professional registration number

emailAddress

▾ string

User's email address

isClinician*

▾ boolean

true if clinical user; false if non-clinical

isLocum*

▾ boolean

true if locum; false if permanent employee

authorisedSignatory*

▾ boolean

true if authorised signatory for the organisational contract

}]

pagination*

PaginationMetadata ▾ {

total*

▾ integer

Total number of records

limit*

▾ integer

Number of records requested per page

offset*

▾ integer

Number of records skipped

hasMore*

▾ boolean

Whether there are more records available

}

}

UpdatePatientRequest ▾ {

```
  title
    ▾ string
    Patient title

  firstName
    ▾ string
    Patient's first name

  lastName
    ▾ string
    Patient's last name (surname) – validated, not overwritten

  dateOfBirth
    ▾ string($date)
    Date of birth in YYYY-MM-DD format – validated, not overwritten

  sex
    ▾ string
    Patient sex (e.g. Male, Female)

  emailAddress
    ▾ string
    Patient email address

  postcode
    ▾ string
    Patient postcode

}
```

PatientDemographics ▾ {

```
  description:
    Current patient demographic fields in ORB after a successful
    update. Does not include extPatientId, connectionStatus, or other
    list-only fields. Values may differ from the PATCH request where
    NHS data takes precedence or where dateOfBirth / lastName were
    validated but not overwritten.

  title
    ▾ string
    Patient title (e.g. Mr, Ms)

  sex
    ▾ string
    Patient sex (e.g. Male, Female)

  dateOfBirth
    ▾ string($date)
    Date of birth in YYYY-MM-DD format

  firstName*
    ▾ string
    Patient's first name

  lastName*
    ▾ string
    Patient's last name (surname)

  postcode*
    ▾ string
    Patient postcode

  emailAddress
    ▾ string
    nullable: true
    Patient email address

}
```

PatientSummary ▾ {

extPatientId*

▾ string
External patient ID (EHR)

title

▾ string
Patient title

firstName*

▾ string
Patient's first name

lastName*

▾ string
Patient's last name

dateOfBirth*

▾ string(\$date)
Date of birth in YYYY-MM-DD format

sex

▾ string
Patient sex (e.g. Male, Female)

emailAddress*

▾ string
Patient email address

postcode

▾ string
Patient postcode

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string
Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean
True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean
True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean
True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean
True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string
Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

```
Enum:
  ▼ [ RequestNotSent, RequestSent, Reviewed ]

oldestNhsRecordDate
  ▼ string($date)
  nullable: true
  Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate
  ▼ string($date-time)
  nullable: true
  ISO-8601 date of the last NHS registration invitation email
  sent

lastAccessRequestEmailDate
  ▼ string($date-time)
  nullable: true
  ISO-8601 date of the last data access request email sent

}
```

PaginatedPatientsResponse ▾ {

patients*

▾ [PatientSummary ▾ {

extPatientId*

▾ string

External patient ID (EHR)

title

▾ string

Patient title

firstName*

▾ string

Patient's first name

lastName*

▾ string

Patient's last name

dateOfBirth*

▾ string(\$date)

Date of birth in YYYY-MM-DD format

sex

▾ string

Patient sex (e.g. Male, Female)

emailAddress*

▾ string

Patient email address

postcode

▾ string

Patient postcode

connectionStatus*

ConnectionStatus ▾

ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

	gpDataAccessLimited	▼ boolean True if the GP has blocked the patient's data partially or totally
	dataAccessStatus	DataAccessStatus ▼ DataAccessStatus string Whether the patient has been asked to grant data access and whether they have done so. - RequestNotSent - Request not sent yet - RequestSent - Request sent to the patient - Reviewed - Patient granted the organisation access to some NHS data Enum: ▼ [RequestNotSent, RequestSent, Reviewed]
	oldestNhsRecordDate	▼ string(\$date) nullable: true Date of oldest NHS record received (ISO-8601); null if none
	lastInvitationEmailDate	▼ string(\$date-time) nullable: true ISO-8601 date of the last NHS registration invitation email sent
	lastAccessRequestEmailDate	▼ string(\$date-time) nullable: true ISO-8601 date of the last data access request email sent
	}]	
pagination*	PaginationMetadata ▼ { total* limit* offset* hasMore*	▼ integer Total number of records ▼ integer Number of records requested per page ▼ integer Number of records skipped ▼ boolean Whether there are more records available
	}	
		}

PatientConnectionStatus ▾ {

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

Enum:

▾ [RequestNotSent, RequestSent, Reviewed]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

}

PatientConnectionStatusResponse ▾ {

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data

Enum:

▾ [RequestNotSent, RequestSent, Reviewed]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

nhsNumber

▾ string

nullable: true

NHS number from the patient's NHS Login record in ORB (read-only; set via NHS Login verification only). Omitted or null if the patient has no NHS Login on record.

}

ConnectPatientByEmailRequest ▾ {

title*	▾ string Patient title
firstName*	▾ string Patient's first name
lastName*	▾ string Patient's last name
dateOfBirth*	▾ string(\$date) Date of birth in YYYY-MM-DD format
sex*	▾ string Patient sex (e.g. Male, Female)
emailAddress*	▾ string Patient email address
postcode*	▾ string Patient postcode
requestingClinicianId*	▾ string External user ID of the requesting clinician
resend	▾ boolean True to force resend of the email if already invited

}

ConnectPatientByLinkRequest ▾ {

```
  title*  
    ▾ string  
    Patient title  
  
  firstName*  
    ▾ string  
    Patient's first name  
  
  lastName*  
    ▾ string  
    Patient's last name  
  
  dateOfBirth*  
    ▾ string($date)  
    Date of birth in YYYY-MM-DD format  
  
  sex*  
    ▾ string  
    Patient sex (e.g. Male, Female)  
  
  emailAddress*  
    ▾ string  
    Patient email address  
  
  postcode*  
    ▾ string  
    Patient postcode  
  
  requestingClinicianId*  
    ▾ string  
    External user ID of the requesting clinician  
  
  resend  
    ▾ boolean  
    True to force resend of the link if already invited
```

```
}
```

ConnectPatientByLinkResponse ▾ {

invitationLink ▾ **string**
nullable: true
URL to the patient invitation that can be shared or displayed

dataAccessRequestLink ▾ **string**
nullable: true
URL for the patient to grant data access to the organisation

connectionStatus* **ConnectionStatus** ▾ **ConnectionStatus** **string**
Patient's NHS login / connection state.

- InviteNotSent – Invitation not yet sent
- InviteSent – Invitation sent, patient has not logged in via NHS yet
- InviteExpired – Invitation sent but expired
- DataMismatch – NHS login revealed a mismatch between ORB and NHS data
- Connected – Patient completed a valid NHS registration with no mismatches

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected]

dobMismatch ▾ **boolean**
True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch ▾ **boolean**
True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited ▾ **boolean**
True if the patient has restricted their data partially or totally

gpDataAccessLimited ▾ **boolean**
True if the GP has blocked the patient's data partially or totally

dataAccessStatus **DataAccessStatus** ▾ **DataAccessStatus** **string**
Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent – Request not sent yet
- RequestSent – Request sent to the patient
- Reviewed – Patient granted the organisation access to some NHS data

Enum:

▾ [RequestNotSent, RequestSent, Reviewed]

oldestNhsRecordDate ▾ **string(\$date)**
nullable: true
Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate ▾ **string(\$date-time)**
nullable: true
ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate ▾ **string(\$date-time)**
nullable: true
ISO-8601 date of the last data access request email sent

}

AccessTokenRequest ▾ {

extUserId*

▾ string

External user ID (EHR) of the requesting clinician

}

AccessTokenResponse ▾ ▾ {

accessToken*

▾ string

Short-lived JWT token for accessing patient data (expires in expiresIn seconds)

expiresIn*

▾ integer

example: 900

Token expiration time in seconds (typically 900 = 15 minutes)

}