

ORB External API 1.0.3 OAS 3.0

ORB External API – Integration guide for EHR systems.

ORB supports integration with clinical EHR systems, allowing clinicians to access NHS records on patients within the EHR. The API has two main parts:

- **Data Model Linkage** – connects Organisations, Users and Patients from the EHR into ORB
- **Data Access** – allows the EHR system to show specific Patient data when requested by a specific User

This API is **organisation-scoped**: all patient and user operations occur in the context of an Organisation.

External EHR IDs are used for Organisations, Users and Patients — ORB does not expose internal IDs.

Request validation (400): When the request cannot be parsed or accepted—for example malformed JSON, a required body field missing, a query or path value in the wrong form (such as `offset=0sd` when an integer is expected), a value outside the permitted set (such as `"sex": "Female1"` when only defined values are accepted), or a property not defined for that operation (such as an unknown field `"newField"` in a PATCH or POST request body)—and no narrower ORB `errorCode` applies, the response always includes `errorCode InvalidRequestData` and a single `errorMessage`. The body contains **only** these two members. `errorMessage` is intended for display: either a fixed general sentence or—commonly—a short line naming one query parameter and the rejected value when only that parameter is at fault (see `ErrorResponseInvalidRequestData` in components/schemas). Wording may change in later API versions; use `errorCode` for programmatic handling and **do not** parse `errorMessage` for business logic.

Servers

https://api-test-app.orbforhealth.com/v1 - TEST / Development

Authorize

Organisations Create, update, delete and list organisations under the governing body

GET

/organisations

List Organisations

Returns a list of organisations under the Governing Body linked to the API key. Includes suspension status and auto-delete date when suspended. Filtering by suspension status is optional.

Parameters

Try it out

Name	Description
suspended boolean	Filter by suspension status. Omit to return all results. --

Name	Description
(query)	

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "extOrganisationId": "string", "organisationName": "string", "suspended": true, "autoDeleteDate": "2026-08-20" }]</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
404	Governing Body corresponding to given API key not found Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

POST

/organisations/{extOrganisationId} Create Organisation



Creates an Organisation in ORB under the GovBody associated with the API Key. Allowed before the organisation contract is signed (required for onboarding).

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey

extOrganisationKey

Request body required

application/json

Example Value | Schema

```
{
  "organisationName": "string",
  "address1": "string",
  "address2": "string",
  "address3": "string",
  "address4": "string",
  "postcode": "string",
  "phoneNumber": "string",
  "cqcRegistrationNumber": "string",
  "researchOptOut": false
}
```

Responses

Code	Description	Links
201	Organisation created	No links
400	Creation failed due to invalid request or validation error	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
<pre>{ "errorMessage": "One or more fields contain invalid values. Please verify the input data.", "errorCode": "InvalidRequestData" }</pre>		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
404	No external client found for the provided API key	No links
Media type		
application/json; charset=utf-8		

Code	Description	Links
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Organisation already exists with the same extOrganisationId (IdNotAvailable) or organisationName (NameNotAvailable)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "Organisation already exists", "errorCode": "IdNotAvailable" }</pre>	

PATCH

/organisations/{extOrganisationId} Update Organisation



Updates organisation details or suspends/unsuspends the organisation. Requires the organisation contract to be signed ([403](#) OrganisationContractNotSigned otherwise).

- If an organisation is suspended it is not considered for billing, and no Users can access data via API.
- Organisations cannot be suspended indefinitely. When suspending, the caller may specify [autoDeleteDays](#) to set when automatic deletion happens. If not specified this happens in 180 days.
- Organisations can be unsuspended to restore access for Users.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey

Request body required

application/json; charset=utf-8 ▾

[Example Value](#) | [Schema](#)

```
{
  "organisationName": "string",
  "address1": "string",
  "address2": "string",

```

```
"address3": "string",
"address4": "string",
"postcode": "string",
"phoneNumber": "string",
"cqcRegistrationNumber": "string",
"researchOptOut": true,
"suspended": true,
"autoDeleteDays": 180
}
```

Responses

Code	Description	Links
200	Organisation updated	No links
400	Update failed due to invalid request or validation error	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned)	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation or Governing Body not found	No links
	Media type	
	application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

Code	Description	Links
	<pre>{ "errorCode": "ClientNotFound" }</pre>	
409	Organisation Name already exists	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		

GET

/organisations/{extOrganisationId} Get Organisation



Returns the organisation details for the given external organisation ID when it exists in the Governing Body linked to the API key.

Parameters

Try it out

Name	Description
extOrganisationId * required	External organisation ID (EHR)
string (path)	<i>Example</i> : extOrganisationKey
	extOrganisationKey

Responses

Code	Description	Links
200	Organisation exists in Governing Body	No links
	Media type application/json; charset=utf-8 Controls Accept header. Example Value Schema	

Code	Description	Links
	<pre>{ "extOrganisationId": "string", "organisationName": "string", "suspended": true, "autoDeleteDate": "2026-08-20" }</pre>	
400	Bad request	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

DELETE
/organisations/{extOrganisationId} Delete Organisation


Delete the organisation and all associated users. Deletion does not require the organisation contract to be signed, so an organisation created by mistake can be removed before signing. Use this if an organisation asks to turn OFF the integration permanently or if it leaves the EHR system.

Once deleted:

- The extOrganisationId is no longer valid for use in any API calls.
- If a patient has no other organisations linked to their profile, they will no longer be able to login.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey

Responses

Code	Description	Links
200	Organisation deleted (no response body)	No links
400	Deletion failed due to invalid request or validation error (including OrgAlreadyArchived if the organisation was already deleted) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links
404	Organisation not found Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

GET

/organisations/{extOrganisationId}/contract-status
Get Organisation Contract Status



Returns whether the organisation has signed the ORB organisation contract and when. Available before the contract is signed (not gated). Used by the host to decide whether to show the signing iframe.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey

Responses

Code	Description	Links
200	Contract status for the organisation Media type application/json; charset=utf-8 Controls Accept header. Examples Not signed Example Value Schema <pre>{ "extOrganisationId": "org-123", "contractSigned": false, "contractSignedAt": null }</pre> <td>No links</td>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled for this client	No links

Code	Description	Links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Organisation not found for this API key / client	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
500	Unexpected server error	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	

POST

/organisations/{extOrganisationId}/contract-access-token

Request Contract Access Token



Generates a short-lived organisation-scoped token used to open the ORB organisation-contract signing iframe. Available before the contract is signed (not gated). The token identifies the API-key client and external organisation only (no patient or user claim). JWT claims include `clientScopeId`, `extOrganisationId`, and `tokenScope` = `organisation-contract`. See the Widget Integration Guide for iframe embedding and `postMessage` (`SET_TOKEN`, `CONTRACT_SIGNED`).

Parameters

Try it out

Name	Description
extOrganisationId * required string	External organisation ID (EHR). Must be the same ID used at Create Organisation under this API key; scopes the

Name	Description	
(path)	contract-signing iframe to that organisation Example : extOrganisationKey extOrganisationKey	
Responses		
Code	Description	Links
200	Contract access token issued Media type application/json; charset=utf-8 Controls Accept header. Example Value Schema <pre>{ "accessToken": "string", "expiresIn": 900}</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation suspended, or EHR API disabled for this client Media type application/json; charset=utf-8 Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links
404	Organisation not found for this API key / client Media type application/json; charset=utf-8 Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	No links

Code	Description	Links
500	Unexpected server error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }		

POST

/organisations/{extOrganisationId}/branding

Set Organisation Branding



Updates the organisation logo and optional welcome title/subtitle shown on the patient-facing NHS linking page (the page patients see when the EHR uses Connect Patient by Email or Connect Patient by Link).

Requires the organisation contract to be signed (**403** OrganisationContractNotSigned otherwise).

Logo changes apply only when overwriteLogo is true: send a file to replace the logo, or send no file to remove it. When overwriteLogo is false or omitted, the existing logo is left unchanged (any uploaded file is ignored). Optionally include patientNHSActivationWelcomeTitle and/or patientNHSActivationWelcomeSubtitle to update NHS activation page text without resending the logo. Allowed logo formats: PNG, JPEG, JPG, SVG. Maximum file size: 1 MB.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey

Request body

multipart/form-data ▾

file string(\$binary)	Logo image (PNG, JPEG, JPG, or SVG; max 1 MB)
last_modified string	

patientNHSActivationWelcomeTitle string	NHS activation page welcome title (applied when included in the request)
patientNHSActivationWelcomeSubtitle string	NHS activation page welcome subtitle (applied when included in the request)
overwriteLogo boolean	When true, update the stored logo (replace if a file is sent, remove if no file is sent). When false or omitted, the existing logo is not modified.

Responses

Code	Description	Links
204	Organisation branding updated	No links
400	Invalid request or validation error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed, or EHR API disabled	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorCode": "OrganisationContractNotSigned", "errorMessage": "The organisation contract has not been signed. Complete contract signing before using this API." }</pre>		
404	Organisation or Governing Body not found	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		

Code	Description	Links
415	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre> Unsupported media type (UnsupportedMediaType). Returned when the uploaded file is not PNG, JPEG, JPG, or SVG, when the file content does not match its declared type, or when the request is not multipart/form-data. Media type application/json; charset=utf-8 Example Value Schema <pre>{ "errorCode": "UnsupportedMediaType", "errorMessage": "This graphic must be supplied in PNG, JPEG or SVG formats." }</pre>	No links

Users

Create, update, list and delete EHR-linked users within an organisation (clinical and non-clinical via isClinician)

^

GET

/organisations/{extOrganisationId}/users

List Users



Returns users for the organisation (regardless of whether the organisation is currently suspended). Pagination is optional — if no pagination parameters are provided, all users are returned as an array. If pagination parameters are provided, a paginated response with metadata is returned.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey
limit integer (query)	Maximum number of users to return (1–1000). If omitted, all users are returned. limit
offset integer	Number of users to skip before returning results. Only used when limit is provided.

Name*(query)***Description***Default value : 0***Responses****Code****Description****Links**

200

OK — returns either a plain array (no pagination) or an object with pagination metadata.

No links

Media type

 ▾

Controls Accept header.

Example Value | Schema

```
[
  {
    "extUserId": "string",
    "firstName": "string",
    "lastName": "string",
    "professionalRegNumber": "string",
    "emailAddress": "string",
    "isClinician": true,
    "isLocum": true,
    "authorisedSignatory": true
  }
]
```

400

Invalid pagination parameters (limit > 1000, limit < 1, or offset < 0)

No links

Media type

 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

401

Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.

No links

403

Organisation contract not signed ([OrganisationContractNotSigned](#)), or EHR API disabled ([ApiDisabled](#))

No links

Media type

 ▾

Code	Description	Links
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

POST

/organisations/{extOrganisationId}/users/{extUserId} Create User



Creates an ORB user within an ORB organisation, linked to the corresponding external User ID. Used to grant a user access to the integration. Set **isClinician** to **true** for clinical users and **false** for non-clinical users. Only users with **isClinician: true** may request patient access tokens (see Request Access Token).

- External IDs are unique within an Organisation and do not change.
- ORB does not link or merge users based on personal attributes (e.g. name, professional registration number).
- If the same person exists in multiple organisations in the EHR, a separate ORB user must be created for each.
- User counts during a month may be used in billing; creation and deletion are logged.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey
extUserId * required string (path)	External user ID (EHR) Example : extUserKey extUserKey

Request body required

application/json

Example Value | Schema

```
{
  "firstName": "string",
  "lastName": "string",
  "professionalRegNumber": "string",
  "emailAddress": "string",
  "isClinician": true,
  "isLocum": true,
  "authorisedSignatory": true
}
```

Responses

Code	Description	Links
201	User created	No links
400	Creation failed due to invalid request or validation error	No links

Media type

application/json; charset=utf-8

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links

Media type

application/json; charset=utf-8

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

404	Organisation not found	No links
-----	------------------------	----------

Media type

application/json; charset=utf-8

Code	Description	Links
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	User already exists in this organisation with the same extUserId (IdNotAvailable), or email already in use (EmailNotAvailable)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

PATCH

/organisations/{extOrganisationId}/users/{extUserId} Update User



Updates one or more attributes of an existing user within an organisation.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extUserId * required string (path)	External user ID (EHR) <i>Example</i> : extUserKey extUserKey

Request body **required**

application/json; charset=utf-8 ▾

[Example Value](#) | [Schema](#)

```
{
  "firstName": "string",
  "lastName": "string",
  "professionalRegNumber": "string",
  "emailAddress": "string",
  "isClinician": true,
  "isLocum": true,
  "authorisedSignatory": true
}
```

Responses

Code	Description	Links
200	User updated	No links
400	Invalid request or validation error	No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

404	User or organisation not found	No links
-----	--------------------------------	----------

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

Code	Description	Links
	<pre>"errorCode": "ClientNotFound" }</pre>	

DELETE

/organisations/{extOrganisationId}/users/{extUserId} Delete User



Deletes the specified user from the organisation. After deletion, the user will no longer be able to access the integration for this organisation.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extUserId * required string (path)	External user ID (EHR) <i>Example</i> : extUserKey extUserKey

Responses

Code	Description	Links
200	User deleted (no response body)	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	User or organisation not found	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

Patients

List, update, connect, and manage patient connections and permissions



GET

/organisations/{extOrganisationId}/patients

List Patients



Returns a list of patients for the specified organisation. Pagination is optional — if no pagination parameters are provided, all patients are returned as an array. If pagination parameters are provided, a paginated response with metadata is returned. Filters can be combined using AND logic.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey
limit integer (query)	Maximum number of patients to return (1–1000). If omitted, all patients are returned. limit
offset integer (query)	Number of patients to skip before returning results. Only used when limit is provided. Default value : 0

Name		Description
		0
connectionStatus	string (query)	Filter by connection status. <i>Available values</i> : InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined --
dataAccessStatus	string (query)	Filter by data access request status. <i>Available values</i> : RequestNotSent, RequestSent, Reviewed, Declined --
patientDataAccessLimited	boolean (query)	When true, filter to patients which have restricted their data (patient-side). --
gpDataAccessLimited	boolean (query)	When true, filter to patients which have their data blocked from GP side. --
dobMismatch	boolean (query)	When true, filter to patients whose date of birth in ORB mismatches the one in NHS. --
surnameMismatch	boolean (query)	When true, filter to patients whose surname in ORB mismatches the one in NHS. --
nhsNumber	string (query)	Filter by NHS number from NHS Login in ORB (digits only; spaces/hyphens allowed in the query value) nhsNumber
Responses		
Code	Description	Links
200	OK — returns either a plain array (no pagination) or an object with pagination metadata. Media type application/json; charset=utf-8 Controls Accept header.	No links

Code

Description

Links

Example Value | Schema

```
[
  {
    "extPatientId": "string",
    "title": "string",
    "firstName": "string",
    "lastName": "string",
    "dateOfBirth": "2026-08-20",
    "sex": "string",
    "emailAddress": "string",
    "postcode": "string",
    "connectionStatus": "InviteNotSent",
    "dobMismatch": true,
    "surnameMismatch": true,
    "patientDataAccessLimited": true,
    "gpDataAccessLimited": true,
    "dataAccessStatus": "RequestNotSent",
    "oldestNhsRecordDate": "2026-08-20",
    "nhsNumber": "string",
    "lastInvitationEmailDate": "2026-08-20T15:42:47.737Z",
    "lastAccessRequestEmailDate": "2026-08-20T15:42:47.737Z"
  }
]
```

400

Invalid pagination parameters (limit > 1000, limit < 1, or offset < 0), or invalid filter value for connectionStatus, dataAccessStatus, patientDataAccessLimited, gpDataAccessLimited, dobMismatch, surnameMismatch, or nhsNumber

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

401

Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.

No links

403

Organisation contract not signed (**OrganisationContractNotSigned**), or EHR API disabled (**ApiDisabled**)

No links

Media type

application/json; charset=utf-8 ▾

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

404

Organisation not found

No links

Media type

Code

Description

Links

application/json; charset=utf-8

Example Value | Schema

```
{
  "errorMessage": "No external client found for the provided API key",
  "errorCode": "ClientNotFound"
}
```

POST

/organisations/{extOrganisationId}/patients/{extPatientId}/connection-email

Connect Patient by Email

Sends an email inviting a patient to sign up and grant permission for the organisation to view NHS records.

- If the patient does not exist, ORB creates a new patient record and sends an NHS invitation email.
- If the patient exists but is not connected, ORB validates that date of birth and surname match the existing ORB record (email match); a mismatch returns **409 PatientDetailsMismatch**. Other request fields are not applied on Connect (use Update Patient). ORB then sends the invitation email directly.
- If the patient is already connected, ORB may send a data-access request email only while **dataAccessStatus** is **RequestNotSent**, **RequestSent**, or **Declined** (not after **Reviewed**, and not when **connectionStatus** is **DataMismatch** or **Declined**), subject to the data-access rate limit.

The EHR may call this endpoint again to send a **reminder**. ORB may rate-limit NHS invitation and data-access request emails per patient per organisation over a rolling 24 hours. An NHS invitation can be resent when **resend** is true while InviteSent and the invitation limit allows, or without **resend** when connectionStatus is Declined. A data-access request reminder does not require **resend** and is issued while status is RequestNotSent, RequestSent, or Declined — only the data-access rate limit applies. Exceeding a limit returns **429 ResendLimitExceeded**.

Link validity: NHS registration links expire after a system-configurable period (7 days by default). Generating a replacement invalidates the previous registration link and restarts the expiry period. Data-access / consent emails open the ORB login page and do not expire after a fixed number of days (they are not timed invitation tokens); the patient must sign in before reviewing access.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey

extOrganisationKey

Name		Description
extPatientId * required		External patient ID (EHR)
string		Example : extPatientKey
(path)		
		extPatientKey
Request body required		application/json
Example Value Schema		
<pre>{ "title": "string", "firstName": "string", "lastName": "string", "dateOfBirth": "2026-08-20", "sex": "string", "emailAddress": "string", "postcode": "string", "requestingClinicianId": "string", "resend": true }</pre>		
Responses		
Code	Description	Links
200	Invite path — connectionStatus is InviteSent (invitation email sent, or already invited and invite flow still applies)	No links
Media type		
application/json; charset=utf-8		
Controls Accept header.		
Example Value Schema		
<pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.741Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.741Z" }</pre>		
201	Patient is Connected (NHS registration complete; a data-access request email may be sent when applicable)	No links
Media type		

Code	Description	Links
	application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.741Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.741Z" }</pre>	
400	Connection failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Organisation or requesting clinician not found Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

Code	Description	Links
409	Conflict — external patient ID in use, or DOB/surname mismatch (PatientDetailsMismatch). Same 409 on Connect by Email and Connect by Link. Distinct from 422. Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
422	DataMismatch — NHS login revealed a mismatch between ORB and NHS data Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.742Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.742Z" }</pre>	No links
429	Rate limit exceeded — the maximum number of connection emails allowed per patient per organisation in 24 hours has been reached (ResendLimitExceeded) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "Rate limit exceeded", "errorCode": "ResendLimitExceeded" }</pre>	No links

POST	/organisations/{extOrganisationId}/patients/{extPatientId}/connection-link Connect Patient by Link	  
Returns an invitation link which can be sent to a patient as part of a link request. - If the patient does not exist, ORB creates a new patient record and returns an NHS invitation link. - If the patient exists but is not connected, ORB validates that date of birth and surname match the existing ORB record (email match); a mismatch returns 409 PatientDetailsMismatch (same as Connect by Email).		

- Other request fields are not applied on Connect (use Update Patient). An NHS invitation link is then returned.
- If the patient is already connected, response code 201 is returned with no invitation link.

In all previous cases, a data-access request link is returned only while `dataAccessStatus` is **RequestNotSent**, **RequestSent**, or **Declined** (not after **Reviewed**, and not when `connectionStatus` is **DataMismatch** or **Declined**), subject to the data-access rate limit. When an invitation or data-access link is issued, `declineInvitationLink` and/or `declineDataAccessRequestLink` are returned as well.

Calling this endpoint again allows the EHR to obtain a fresh link as a **reminder**. An NHS invitation link is returned again only when `resend` is true while InviteSent (and the invitation rate limit allows), or without `resend` when connectionStatus is Declined. A data-access request link can be returned again only while status is RequestNotSent, RequestSent, or Declined and the data-access rate limit allows — `resend` is not required for data-access reminders. Exceeding a limit returns **429 ResendLimitExceeded**.

Link validity: NHS registration links expire after a system-configurable period (7 days by default). Generating a replacement invalidates the previous registration link and restarts the expiry period. The data-access / consent link opens the ORB login page and does not expire after a fixed number of days (it is not a timed invitation token); the patient must sign in before reviewing access.

Parameters

[Try it out](#)

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extPatientId * required string (path)	External patient ID (EHR) <i>Example</i> : extPatientKey extPatientKey

Request body **required**

application/json

Example Value | Schema

```
{
  "title": "string",
  "firstName": "string",
  "lastName": "string",
  "dateOfBirth": "2026-08-20",
  "sex": "string",
  "emailAddress": "string",
  "postcode": "string",
  "requestingClinicianId": "string",
  "resend": true
}
```

Responses

Code	Description	Links
200	connectionStatus is InviteNotSent or InviteExpired — NHS invitation and/or data-access links returned when applicable Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "invitationLink": "string", "declineInvitationLink": "string", "dataAccessRequestLink": "string", "declineDataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.744Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.744Z" }</pre>	No links
201	connectionStatus is InviteSent or Connected — no new invite link unless resend is true; data-access link returned when applicable Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "invitationLink": "string", "declineInvitationLink": "string", "dataAccessRequestLink": "string", "declineDataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.744Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.744Z" }</pre>	No links
400	Connection failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Organisation or requesting clinician not found	No links
	Media type application/json; charset=utf-8	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Conflict — external patient ID in use, or DOB/surname mismatch (PatientDetailsMismatch). Same 409 on Connect by Email and Connect by Link. Distinct from 422.	No links
	Media type application/json; charset=utf-8	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
422	DataMismatch — NHS login revealed a mismatch between ORB and NHS data	No links
	Media type application/json; charset=utf-8	
	Example Value Schema	

Code	Description	Links
	<pre>{ "invitationLink": "string", "declineInvitationLink": "string", "dataAccessRequestLink": "string", "declineDataAccessRequestLink": "string", "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.746Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.746Z" }</pre>	
429	Rate limit exceeded — the maximum number of connection links allowed per patient per organisation in 24 hours has been reached (ResendLimitExceeded) Media type application/json; charset=utf-8 ▼ Example Value Schema <pre>{ "errorMessage": "Rate limit exceeded", "errorCode": "ResendLimitExceeded" }</pre>	No links

GET	/organisations/{extOrganisationId}/patients/{extPatientId}/connection	  
Get Patient Connection Status		
Returns the connection status and access levels for the patient. Includes nhsNumber from the patient's NHS Login record after NHS Login verification (read-only; omitted or null if no NHS Login on record).		
Parameters		Try it out
Name	Description	
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey	extOrganisationKey
extPatientId * required string (path)	External patient ID (EHR) Example : extPatientKey	

Name		Description
		extPatientKey
Responses		
Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "connectionStatus": "InviteNotSent", "dobMismatch": true, "surnameMismatch": true, "patientDataAccessLimited": true, "gpDataAccessLimited": true, "dataAccessStatus": "RequestNotSent", "oldestNhsRecordDate": "2026-08-20", "lastInvitationEmailDate": "2026-08-20T15:42:47.747Z", "lastAccessRequestEmailDate": "2026-08-20T15:42:47.747Z", "nhsNumber": "string"} </pre>	No links
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"} </pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema	

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Patient or organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

DELETE

/organisations/{extOrganisationId}/patients/{extPatientId}/connection
Remove Patient Connection



Removes the link between the patient and the organisation. Use this when a patient leaves a clinic; doing so is treated as an implied retraction of the organisation's permission to view that patient's records.

This is an **unlink** only for the organisation in the request:

- The EHR connection for this organisation is removed (List Patients / token / connection / status / permissions for this patient and organisation fail).
- The patient-to-organisation link for that organisation is also removed.
- The underlying patient account, PatientLogin, and NHS record data are retained. Other organisation links are untouched.
- If the patient still has other organisations, they can continue to log in and use those.
- If this was the patient's last organisation, they cannot log in until linked to at least one organisation again; the account and any completed NHS registration are kept.
- On re-connect, ORB treats them as an existing patient and typically returns a data-access / data-share link rather than a new NHS invitation link.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) <i>Example</i> : extOrganisationKey extOrganisationKey
extPatientId * required string (path)	External patient ID (EHR) <i>Example</i> : extPatientKey

Name		Description
		extPatientKey
Responses		
Code	Description	Links
200	Connection removed (no response body)	No links
400	Deletion failed due to invalid request or validation error	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }		
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled)	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }		
404	Patient or organisation not found	No links
Media type		
application/json; charset=utf-8		
Example Value Schema		
{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }		

Code	Description	Links
500	Unexpected server error	No links
Media type		
application/json; charset=utf-8 ▾		
Example Value Schema		
<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>		

GET

/organisations/{extOrganisationId}/patients/{extPatientId}/permissions

Get Granted Permissions



Returns the list of data permissions that the patient has granted to this organisation. Requires that the patient is connected to the organisation.

If the patient connection status is **Connected**, this endpoint returns the granted permissions. If the connection status is **InviteSent** or **DataMismatch**, this endpoint returns 404.

Issuing an access token checks that the patient is Connected and that organisation/patient data access is not limited. It does not check individual dataset grants (e.g. Allergies, Documents); those are enforced inside the widget when NHS record data is fetched. This permissions endpoint is informational for the EHR.

Parameters

Try it out

Name	Description
extOrganisationId * required string (path)	External organisation ID (EHR) Example : extOrganisationKey extOrganisationKey
extPatientId * required string (path)	External patient ID (EHR) Example : extPatientKey extPatientKey

Responses

Code	Description	Links
200	OK — returns array of permission names Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>["Allergies", "Medication History", "Immunisations"]</pre>	No links
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation not authorised to view this patient Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Patient or organisation not found, or patient connection not established Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

PATCH

/organisations/{extOrganisationId}/patients/{extPatientId} Update Patient



Updates one or more demographic attributes of an existing patient within an organisation. Typically used when the EHR updates patient details such as contact information or postcode.

- **No NHS Login** — supplied `firstName`, `lastName`, and `dateOfBirth` overwrite ORB data; other supplied fields also overwrite. Omitted fields are unchanged.
- **NHS Login present** — `firstName`, `lastName`, and `dateOfBirth` are not overwritten. ORB compares these three fields on the request to the NHS-controlled values on record. A mismatch, including when any of them is omitted, returns **409 PatientDetailsMismatch**. To update other fields (`title`, `sex`, `emailAddress`, `postcode`), include matching `firstName`, `lastName`, and `dateOfBirth`.

Parameters

Try it out

Name

Description

extOrganisationId * required

string
(path)

External organisation ID (EHR)

Example : extOrganisationKey

extOrganisationKey

extPatientId * required

string
(path)

External patient ID (EHR)

Example : extPatientKey

extPatientKey

Request body * required

application/json

Example Value | Schema

```
{
  "title": "string",
  "firstName": "string",
  "lastName": "string",
  "dateOfBirth": "2026-08-20",
  "sex": "string",
  "emailAddress": "string",
  "postcode": "string"
}
```

Responses

Code	Description	Links
200	Patient updated — returns current demographic fields stored in ORB after the update Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>{ "title": "Ms", "sex": "Male", "dateOfBirth": "1933-11-14", "firstName": "Simon", "lastName": "OLLEY", "postcode": "asdas123", "emailAddress": "patient@example.com" }</pre>	No links
400	Update failed due to invalid request or validation error Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Organisation contract not signed (OrganisationContractNotSigned), or EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Patient or organisation not found Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
409	Conflict — patient has NHS Login and request <code>firstName</code> / <code>lastName</code> / <code>dateOfBirth</code> do not match the record, including when any of those fields is omitted (<code>PatientDetailsMismatch</code>)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Unexpected server error	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

Patient Access

Request short-lived access tokens for the ORB widget



POST	/organisations/{extOrganisationId}/patients/{extPatientId}/access-token Request Access Token	
Returns a short-lived JWT used to access patient data via the ORB widget (iframe). Security Model: • The EHR must make this request server-side (never from the browser). • The request must include the <code>extUserId</code> of the clinician requesting access. • ORB validates that the user exists and belongs to the organisation, the user has <code>isClinician: true</code>, the organisation is not suspended, the organisation has access to the patient, the patient is Connected, and organisation/patient data access is not limited (<code>patientDataAccessLimited</code> / <code>gpDataAccessLimited</code>). Individual dataset grants are enforced inside the widget when data is fetched, not at token issue. • The returned JWT is scoped to the specific user, patient, and organisation and includes <code>clientScopeId</code>. • Token expires in 15 minutes. • Requesting an access token is recorded as clinician access for audit purposes. • Issuing a token does not mean clinician widget T&C are accepted, and does not mean the organisation NHS module is enabled. T&C and the NHS-module unavailable screen are enforced inside the ORB widget (per user		

per organisation for T&C; mandatory tick-box; NHS data blocked until accepted). The External API does not expose accept/query endpoints for T&C.

Parameters

Try it out

Name

Description

extOrganisationId * required

string
(path)

External organisation ID (EHR)

Example : extOrganisationKey

extOrganisationKey

extPatientId * required

string
(path)

External patient ID (EHR)

Example : extPatientKey

extPatientKey

Request body **required**

application/json

Example Value | Schema

```
{
  "extUserId": "string"
}
```

Responses

Code

Description

Links

200

Token issued successfully

No links

Media type

application/json; charset=utf-8

Controls Accept header.

Example Value | Schema

```
{
  "accessToken": "string",
  "expiresIn": 900
}
```

400

Invalid request (missing extUserId)

No links

Code	Description	Links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	Access denied — NonClinicianAccess (isClinician: false); OrgIsSuspended ; PatientInvalidStatus (patient not Connected); PatientDataAccessLimited (patient/GP data access limited); OrganisationContractNotSigned ; or ApiDisabled / ApiKeyExpired	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
404	Patient, user, or organisation not found	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	
500	Internal server error	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

GET

/stats/links-sent

Get Links Sent Stats



Distinct patients sent an NHS invitation and/or a data-access request, per organisation.

Both Connect by Email and Connect by Link count as a send. Counts are distinct patients, not email/link volume. Without fromDate/toDate: current snapshot of patients who have ever been sent. With fromDate/toDate: distinct patients with at least one send in that window. Results are limited to organisations for this API key. Not gated by organisation-contract signing.

Parameters

Try it out

Name	Description
extOrganizationKey string (query)	EHR organisation ID (same value as extOrganisationId on other endpoints). Omit to return all organisations for this API key. extOrganizationKey
fromDate string(\$date-time) (query)	Include sends at or after this time (ISO-8601) fromDate
toDate string(\$date-time) (query)	Include sends at or before this time (ISO-8601) toDate

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 Controls Accept header. Example Value Schema [{ "organizationName": "string", "extOrganisationKey": "string", "invitationsSent": 0, },]	No links

Code	Description	Links
	<pre>"dataAccessRequestsSent": 0 }]</pre>	
400	Bad request (including fromDate after toDate) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Unknown API key (ClientNotFound), or extOrganizationKey is not an organisation for this API key (OrgNotFound) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

GET
/stats/consent-granted
Get Consent Granted Stats




Among patients sent a data-access request, how many currently have at least one NHS dataset granted to the organisation.

This is dataset access, not organisation-contract signing and not clinician widget T&C. Date-range filter (optional) selects patients by when the data-access request was sent; consentGranted uses current dataset flags. Results are limited to organisations for this API key. Not gated by organisation-contract signing.

Parameters

[Try it out](#)

Name	Description
extOrganizationKey string (query)	EHR organisation ID (same value as extOrganisationId on other endpoints). Omit to return all organisations for this API key. extOrganizationKey
fromDate string(\$date-time) (query)	Include sends at or after this time (ISO-8601) fromDate
toDate string(\$date-time) (query)	Include sends at or before this time (ISO-8601) toDate

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "organizationName": "string", "extOrganisationKey": "string", "dataAccessRequestsSent": 0, "consentGranted": 0 }]</pre>	No links
400	Bad request (including fromDate after toDate) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

Code	Description	Links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (<code>ApiDisabled</code>)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Unknown API key (<code>ClientNotFound</code>), or extOrganizationKey is not an organisation for this API key (<code>OrgNotFound</code>)	No links
	Media type application/json; charset=utf-8 ▾	
	Example Value Schema	
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	

GET

/stats/consent-declined

Get Consent Declined Stats



Patients who declined via the ORB decline page. Invitation decline (`connectionStatus = Declined`) and data-access decline (`dataAccessStatus = Declined`) are counted separately — distinct from no-response / not granted yet.

Date-range filter (optional) selects patients by when the invitation or data-access request was sent; decline fields use current status. Results are limited to organisations for this API key. Not gated by organisation-contract signing.

Parameters

Try it out

Name	Description
extOrganizationKey string (query)	EHR organisation ID (same value as extOrganisationId on other endpoints). Omit to return all organisations for this API key. extOrganizationKey
fromDate string(\$date-time)	Include sends at or after this time (ISO-8601)

Name	Description
(query)	fromDate
toDate	Include sends at or before this time (ISO-8601)
string(\$date-time) (query)	toDate

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "organizationName": "string", "extOrganisationKey": "string", "invitationsSent": 0, "declinedInvitations": 0, "dataAccessRequestsSent": 0, "dataAccessRequestsDeclined": 0 }]</pre>	No links
400	Bad request (including fromDate after toDate) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
404	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre> Unknown API key (ClientNotFound), or extOrganizationKey is not an organisation for this API key (OrgNotFound) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

GET

/stats/no-response

Get No-Response Stats



Patients sent an invitation or data-access request who have neither completed nor declined.

Invitation no-response: not Connected and not Declined (includes InviteSent, InviteExpired, DataMismatch). Data-access no-response: not dataAccessStatus = Declined and no NHS dataset enabled for the organisation. Date-range filter (optional) selects patients by when the send occurred; outcome fields use current status. Results are limited to organisations for this API key. Not gated by organisation-contract signing.

Parameters

Try it out

Name	Description
extOrganizationKey string (query)	EHR organisation ID (same value as extOrganisationId on other endpoints). Omit to return all organisations for this API key. extOrganizationKey
fromDate string(\$date-time) (query)	Include sends at or after this time (ISO-8601) fromDate
toDate string(\$date-time) (query)	Include sends at or before this time (ISO-8601) toDate

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "organizationName": "string", "extOrganisationKey": "string", "invitationsSent": 0, "noResponseInvitations": 0, "dataAccessRequestsSent": 0, "noResponseDataAccessRequests": 0 }]</pre>	No links
400	Bad request (including fromDate after toDate) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Unknown API key (ClientNotFound), or extOrganizationKey is not an organisation for this API key (OrgNotFound) Media type application/json; charset=utf-8 ▾ Example Value Schema	No links

Code	Description	Links
	<pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	

GET

/stats/widget-terms

Get Widget Terms Stats



Current snapshot of clinician widget Terms & Conditions acceptance per organisation (not the organisation contract). No date-range filter.

Results are limited to organisations for this API key (Governing Body). Archived EHR users are excluded. **isClinician** and **isLocum** are independent — a locum clinician is counted in both splits. Not-signed includes users who have never opened the widget (there is no T&C decline flag). Not gated by organisation-contract signing.

Parameters

Try it out

Name	Description
extOrganizationKey string (query)	EHR organisation ID (same value as extOrganisationId on other endpoints). Omit to return all organisations for this API key. extOrganizationKey

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 Controls Accept header. Example Value Schema <pre>[{ "organizationName": "string", "extOrganisationKey": "string", "signed": 0, "notSigned": 0, "clinicianSigned": 0, "clinicianNotSigned": 0, "locumSigned": 0, "locumNotSigned": 0 }]</pre> No links	

Code	Description	Links
	<pre>}]</pre>	
400	Bad request Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (ApiDisabled) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links
404	Unknown API key (ClientNotFound), or extOrganizationKey is not an organisation for this API key (OrgNotFound) Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }</pre>	No links

GET
/stats/nhs-records-viewed
Get NHS Records Viewed Stats




Distinct patients whose NHS records were viewed in the clinician widget, per organisation and per user.

Counts unique patients from successful clinician views in the widget, derived from ORB's confidential viewing audit (unsuccessful retrievals are excluded). Individual visits are not listed on the External API; requests to investigate a particular access event should be directed to ORB Support. Organisation **patientsViewed** is distinct patients for the practice, not the sum of per-user counts. All non-archived users are listed (including **patientsViewed: 0**). No page-level breakdown. Optional **fromDate** /

toDate filter views. Results are limited to organisations for this API key. Not gated by organisation-contract signing.

Parameters

[Try it out](#)

Name	Description
extOrganizationKey string (query)	EHR organisation ID (same value as extOrganisationId on other endpoints). Omit to return all organisations for this API key. extOrganizationKey
fromDate string(\$date-time) (query)	Include views at or after this time (ISO-8601) fromDate
toDate string(\$date-time) (query)	Include views at or before this time (ISO-8601) toDate

Responses

Code	Description	Links
200	OK Media type application/json; charset=utf-8 ▾ Controls Accept header. Example Value Schema <pre>[{ "organizationName": "string", "extOrganisationKey": "string", "patientsViewed": 0, "users": [{ "extUserId": "string", "userName": "string", "isClinician": true, "isLocum": true, "patientsViewed": 0 }] }]</pre>	No links
400	Bad request (including fromDate after toDate) Media type	No links

Code	Description	Links
	application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
401	Missing API key (empty body). Unknown key typically returns 404 ClientNotFound.	No links
403	EHR API disabled (ApiDisabled)	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	
404	Unknown API key (ClientNotFound), or extOrganizationKey is not an organisation for this API key (OrgNotFound)	No links
	Media type application/json; charset=utf-8 ▾ Example Value Schema <pre>{ "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound"}</pre>	

Schemas	⌵

ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches
- Declined - Patient declined the NHS invitation via the decline link (before NHS registration). Calling Connect again can send a new invitation.

Enum:

 [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined]

DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data
- Declined - Patient declined the data-access request via the decline link. Connect may send a new request unless connectionStatus is DataMismatch or Declined.

Connect issues a data-access request email/link while status is RequestNotSent, RequestSent, or Declined (not after Reviewed).

Enum:

 [RequestNotSent, RequestSent, Reviewed, Declined]

ErrorCode string

Enum:

 [ClientNotFound, OrgNotFound, OrgLinkNotFound, UserNotFound, PatientNotFound, InvalidParameter, InvalidProperty, InvalidRequestData, UnsupportedMediaType, IdNotAvailable, NameNotAvailable, EmailNotAvailable, PatientInvalidStatus, PatientDetailsMismatch, ResendLimitExceeded, NonClinicianAccess, OrgIsSuspended, ApiDisabled, ApiKeyExpired, OrgAlreadyArchived, OrganisationContractNotSigned, OrganisationContractAlreadySigned, PatientDataAccessLimited, TermsNotAccepted, GenericError]

ErrorResponse ▾ {

errorMessage*

▾ string

example: Organisation not found

Human-readable error message

errorCode

ErrorCode ▾ ErrorCode string

Enum:

▾ [ClientNotFound, OrgNotFound, OrgLinkNotFound, UserNotFound, PatientNotFound, InvalidParameter, InvalidProperty, InvalidRequestData, UnsupportedMediaType, IdNotAvailable, NameNotAvailable, EmailNotAvailable, PatientInvalidStatus, PatientDetailsMismatch, ResendLimitExceeded, NonClinicianAccess, OrgIsSuspended, ApiDisabled, ApiKeyExpired, OrgAlreadyArchived, OrganisationContractNotSigned, OrganisationContractAlreadySigned, PatientDataAccessLimited, TermsNotAccepted, GenericError]

}

example: { "errorMessage": "No external client found for the provided API key", "errorCode": "ClientNotFound" }

ErrorResponseInvalidRequestData ▾ {

description: Returned when the request body, query string, or path cannot be parsed or validated successfully, and no narrower **errorCode** applies. The response body is always the compact JSON object with **errorCode** and **errorMessage** only, as for **InvalidRequestData** in the API specification (Common Errors). **errorMessage** is assigned as follows:

- **General message** – Used when more than one validation issue is reported for the same request, and in typical cases where the problem lies in the **JSON request body** only—including a value outside a permitted enumeration (for example **"sex": "Female1"** when only defined values are accepted), or a property not defined for that operation (for example an unknown or misspelled field name in a PATCH or POST body). Request bodies must contain only properties listed for that endpoint; extra properties are rejected with 400, not ignored. In these cases **errorMessage** is a single standard sentence; clients must not assume a field-by-field breakdown in the message text.
- **Per-parameter message (query)** – Typically used when a **single query** (or equivalent) parameter does not match its expected type; **errorMessage** may then identify the parameter and the supplied value.

Other isolated query-parameter errors may follow the same pattern. The exact wording of **errorMessage** is not guaranteed across API versions; use it for display only and base integration logic on **errorCode**.

errorCode*

▾ **string**
Enum:

errorMessage*

▾ [**InvalidRequestData**]
▾ **string**

example: One or more fields contain invalid values. Please verify the input data.

Intended for display: either the fixed general sentence, or—commonly—a short per-parameter line naming one query parameter and the rejected value when only that parameter is at fault (for example **The value '0sd' is not valid for Offset.**).

}

example: { "errorCode": "InvalidRequestData", "errorMessage": "One or more fields contain invalid values. Please verify the input data." }

PaginationMetadata ▾ {

total*

▾ **integer**
Total number of records

limit*

▾ **integer**
Number of records requested per page

offset*

▾ **integer**
Number of records skipped

hasMore*

▾ **boolean**
Whether there are more records available

}

CreateOrganisationRequest ▾ {

organisationName* ▾ **string**
Unique Organisation name (case-insensitive)

address1* ▾ **string**
First line of address

address2* ▾ **string**
Second line of address

address3 ▾ **string**
Third line of address

address4 ▾ **string**
Fourth line of address

postcode* ▾ **string**
Postcode

phoneNumber ▾ **string**
Organisation phone number. May be omitted or empty.

cqcRegistrationNumber* ▾ **string**
CQC registration number

researchOptOut ▾ **boolean**
default: false
Research opt-out flag (defaults to false)

}

UpdateOrganisationRequest ▾ {

```
  organisationName      ▾ string
                          Unique Organisation name (case-insensitive)

  address1              ▾ string
                          First line of address

  address2              ▾ string
                          Second line of address

  address3              ▾ string
                          Third line of address

  address4              ▾ string
                          Fourth line of address

  postcode              ▾ string
                          Postcode

  phoneNumber           ▾ string
                          Phone number

  cqcRegistrationNumber ▾ string
                          CQC registration number

  researchOptOut        ▾ boolean
                          Research opt-out flag

  suspended             ▾ boolean
                          Suspended flag

  autoDeleteDays        ▾ integer
                          maximum: 180
                          default: 180
                          Auto-delete after suspension in days (max 180, default 180)

}
```

OrganisationSummary ▾ {

```
  extOrganisationId*   ▾ string
                          External organisation ID (EHR)

  organisationName*    ▾ string
                          Organisation name

  suspended*           ▾ boolean
                          Suspension status

  autoDeleteDate        ▾ string($date)
                          nullable: true
                          Auto-delete date in YYYY-MM-DD format when suspended; null if not set

}
```

ContractStatusResponse ▾ {

extOrganisationId* ▾ **string**
External organisation ID (EHR); same value as in the path

contractSigned* ▾ **boolean**
true after successful organisation-contract signing; false until then

contractSignedAt ▾ **string**(\$date-time)
nullable: true
UTC ISO-8601 timestamp of signing; present only when contractSigned is true, otherwise null

}

CreateUserRequest ▾ {

firstName* ▾ **string**
User's first name

lastName* ▾ **string**
User's last name

professionalRegNumber ▾ **string**
Professional registration number. May be omitted or empty (e.g. clinicians without a registration number).

emailAddress ▾ **string**
User's email address

isClinician* ▾ **boolean**
true if the user is a clinical user; **false** for non-clinical users (e.g. administrative). Only clinical users may request patient access tokens.

isLocum* ▾ **boolean**
true if the user is a temporary locum; **false** if a permanent employee

authorisedSignatory* ▾ **boolean**
true if this user is an authorised signatory for the organisational contract (host-side marker; ORB does not re-check this flag when accepting the organisation contract in the iframe)

}

UpdateUserRequest ▾ {

```
  firstName
    ▾ string
    User's first name

  lastName
    ▾ string
    User's last name

  professionalRegNumber
    ▾ string
    Professional registration number

  emailAddress
    ▾ string
    User's email address

  isClinician
    ▾ boolean
    If supplied, updates whether the user is a clinical user ( true )
    or non-clinical ( false )

  isLocum
    ▾ boolean
    If supplied, updates whether the user is a locum ( true ) or
    permanent ( false )

  authorisedSignatory
    ▾ boolean
    If supplied, updates authorised signatory flag for the
    organisational contract

}
```

User ▾ {

```
  extUserId*
    ▾ string
    External user ID (EHR)

  firstName*
    ▾ string
    User's first name

  lastName*
    ▾ string
    User's last name

  professionalRegNumber
    ▾ string
    nullable: true
    Professional registration number (may be null or empty)

  emailAddress
    ▾ string
    User's email address

  isClinician*
    ▾ boolean
    true if clinical user; false if non-clinical

  isLocum*
    ▾ boolean
    true if locum; false if permanent employee

  authorisedSignatory*
    ▾ boolean
    true if authorised signatory for the organisational contract

}
```

PaginatedUsersResponse ▾ {

users*

▾ [User ▾ {

extUserId*

▾ string

External user ID (EHR)

firstName*

▾ string

User's first name

lastName*

▾ string

User's last name

professionalRegNumber

▾ string

nullable: true

Professional registration number (may be null or empty)

emailAddress

▾ string

User's email address

isClinician*

▾ boolean

true if clinical user; **false** if non-clinical

isLocum*

▾ boolean

true if locum; **false** if permanent employee

authorisedSignatory*

▾ boolean

true if authorised signatory for the organisational contract

}}

pagination*

PaginationMetadata ▾ {

total*

▾ integer

Total number of records

limit*

▾ integer

Number of records requested per page

offset*

▾ integer

Number of records skipped

hasMore*

▾ boolean

Whether there are more records available

}

}

UpdatePatientRequest ▾ {

```
  title
    ▾ string
    Patient title

  firstName
    ▾ string
    Patient's first name

  lastName
    ▾ string
    Patient's last name (surname) – validated, not overwritten

  dateOfBirth
    ▾ string($date)
    Date of birth in YYYY-MM-DD format – validated, not overwritten

  sex
    ▾ string
    Patient sex (e.g. Male, Female)

  emailAddress
    ▾ string
    Patient email address

  postcode
    ▾ string
    Patient postcode

}
```

PatientDemographics ▾ {

```
  description:
    Current patient demographic fields in ORB after a successful
    update. Does not include extPatientId, connectionStatus, or other
    list-only fields. Values may differ from the PATCH request where
    NHS data takes precedence or where dateOfBirth / lastName were
    validated but not overwritten.

  title
    ▾ string
    Patient title (e.g. Mr, Ms)

  sex
    ▾ string
    Patient sex (e.g. Male, Female)

  dateOfBirth
    ▾ string($date)
    Date of birth in YYYY-MM-DD format

  firstName*
    ▾ string
    Patient's first name

  lastName*
    ▾ string
    Patient's last name (surname)

  postcode*
    ▾ string
    Patient postcode

  emailAddress
    ▾ string
    nullable: true
    Patient email address

}
```

PatientSummary ▾ {

extPatientId*

▾ string
External patient ID (EHR)

title

▾ string
Patient title

firstName*

▾ string
Patient's first name

lastName*

▾ string
Patient's last name

dateOfBirth*

▾ string(\$date)
Date of birth in YYYY-MM-DD format

sex

▾ string
Patient sex (e.g. Male, Female)

emailAddress*

▾ string
Patient email address

postcode

▾ string
Patient postcode

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string
Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches
- Declined - Patient declined the NHS invitation via the decline link (before NHS registration). Calling Connect again can send a new invitation.

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined]

dobMismatch

▾ boolean
True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean
True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean
True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean
True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string
Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient

- Reviewed – Patient granted the organisation access to some NHS data
- Declined – Patient declined the data-access request via the decline link. Connect may send a new request unless connectionStatus is DataMismatch or Declined.

Connect issues a data-access request email/link while status is RequestNotSent, RequestSent, or Declined (not after Reviewed).

Enum:

▼ [RequestNotSent, RequestSent, Reviewed, Declined]

oldestNhsRecordDate

▼ `string($date)`

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

nhsNumber

▼ `string`

nullable: true

NHS number from NHS Login in ORB (read-only; optional; omitted or null if not on record)

lastInvitationEmailDate

▼ `string($date-time)`

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▼ `string($date-time)`

nullable: true

ISO-8601 date of the last data access request email sent

}

PaginatedPatientsResponse ▾ {

patients*

▾ [PatientSummary ▾ {

extPatientId*

▾ string

External patient ID (EHR)

title

▾ string

Patient title

firstName*

▾ string

Patient's first name

lastName*

▾ string

Patient's last name

dateOfBirth*

▾ string(\$date)

Date of birth in YYYY-MM-DD format

sex

▾ string

Patient sex (e.g. Male, Female)

emailAddress*

▾ string

Patient email address

postcode

▾ string

Patient postcode

connectionStatus*

ConnectionStatus ▾

ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches
- Declined - Patient declined the NHS invitation via the decline link (before NHS registration). Calling Connect again can send a new invitation.

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited	▼ boolean True if the patient has restricted their data partially or totally
gpDataAccessLimited	▼ boolean True if the GP has blocked the patient's data partially or totally
dataAccessStatus	DataAccessStatus ▼ DataAccessStatus string Whether the patient has been asked to grant data access and whether they have done so. - RequestNotSent - Request not sent yet - RequestSent - Request sent to the patient - Reviewed - Patient granted the organisation access to some NHS data - Declined - Patient declined the data-access request via the decline link. Connect may send a new request unless connectionStatus is DataMismatch or Declined. Connect issues a data-access request email/link while status is RequestNotSent, RequestSent, or Declined (not after Reviewed). Enum: ▼ [RequestNotSent, RequestSent, Reviewed, Declined]
oldestNhsRecordDate	▼ string(\$date) <i>nullable: true</i> Date of oldest NHS record received (ISO-8601); null if none
nhsNumber	▼ string <i>nullable: true</i> NHS number from NHS Login in ORB (read-only; optional; omitted or null if not on record)
lastInvitationEmailDate	▼ string(\$date-time) <i>nullable: true</i> ISO-8601 date of the last NHS registration invitation email sent
lastAccessRequestEmailDate	▼ string(\$date-time) <i>nullable: true</i> ISO-8601 date of the last data access request email sent
pagination*	}} PaginationMetadata ▼ { total* ▼ integer Total number of records limit* ▼ integer Number of records requested per page

offset*

▼ integer

Number of records skipped

hasMore*

▼ boolean

Whether there are more records available

}

}

PatientConnectionStatus ▾ {

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches
- Declined - Patient declined the NHS invitation via the decline link (before NHS registration). Calling Connect again can send a new invitation.

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data
- Declined - Patient declined the data-access request via the decline link. Connect may send a new request unless connectionStatus is DataMismatch or Declined.

Connect issues a data-access request email/link while status is RequestNotSent, RequestSent, or Declined (not after Reviewed).

Enum:

▾ [RequestNotSent, RequestSent, Reviewed, Declined]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

}

PatientConnectionStatusResponse ▾ {

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches
- Declined - Patient declined the NHS invitation via the decline link (before NHS registration). Calling Connect again can send a new invitation.

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data
- Declined - Patient declined the data-access request via the decline link. Connect may send a new request unless connectionStatus is DataMismatch or Declined.

Connect issues a data-access request email/link while status is RequestNotSent, RequestSent, or Declined (not after Reviewed).

Enum:

▾ [RequestNotSent, RequestSent, Reviewed, Declined]

oldestNhsRecordDate

▾ string(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

lastInvitationEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastAccessRequestEmailDate

▾ string(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

nhsNumber

▾ string

```

    nullable: true
    NHS number from the patient's NHS Login record after NHS
    Login verification (read-only; not supplied on Connect or
    Update). Omitted or null if the patient has no NHS Login on
    record.
}

```

ConnectPatientByEmailRequest ▾ {

title*	▼ string Patient title
firstName*	▼ string Patient's first name
lastName*	▼ string Patient's last name
dateOfBirth*	▼ string(\$date) Date of birth in YYYY-MM-DD format
sex*	▼ string Patient sex (e.g. Male, Female)
emailAddress*	▼ string Patient email address
postcode*	▼ string Patient postcode
requestingClinicianId*	▼ string External user ID of the requesting clinician
resend	▼ boolean True to force resend of an NHS invitation email while connectionStatus is InviteSent. Not used for data-access request reminders.

}

ConnectPatientByLinkRequest ▾ {

```
  title*  
    ▾ string  
    Patient title  
  
  firstName*  
    ▾ string  
    Patient's first name  
  
  lastName*  
    ▾ string  
    Patient's last name  
  
  dateOfBirth*  
    ▾ string($date)  
    Date of birth in YYYY-MM-DD format  
  
  sex*  
    ▾ string  
    Patient sex (e.g. Male, Female)  
  
  emailAddress*  
    ▾ string  
    Patient email address  
  
  postcode*  
    ▾ string  
    Patient postcode  
  
  requestingClinicianId*  
    ▾ string  
    External user ID of the requesting clinician  
  
  resend  
    ▾ boolean  
    True to force a new NHS invitation link while connectionStatus is  
    InviteSent. Not used for data-access request links.  
  
}
```

ConnectPatientByLinkResponse ▾ {

invitationLink

▾ string

nullable: true

URL to the patient invitation that can be shared or displayed

declineInvitationLink

▾ string

nullable: true

ORB-hosted decline URL for the NHS invitation. Present when invitationLink is returned. If the patient opens it, connectionStatus becomes Declined.

dataAccessRequestLink

▾ string

nullable: true

URL for the patient to grant data access to the organisation

declineDataAccessRequestLink

▾ string

nullable: true

ORB-hosted decline URL for the data-access request. Present when dataAccessRequestLink is returned. If the patient opens it, dataAccessStatus becomes Declined.

connectionStatus*

ConnectionStatus ▾ ConnectionStatus string

Patient's NHS login / connection state.

- InviteNotSent - Invitation not yet sent
- InviteSent - Invitation sent, patient has not logged in via NHS yet
- InviteExpired - Invitation sent but expired
- DataMismatch - NHS login revealed a mismatch between ORB and NHS data
- Connected - Patient completed a valid NHS registration with no mismatches
- Declined - Patient declined the NHS invitation via the decline link (before NHS registration). Calling Connect again can send a new invitation.

Enum:

▾ [InviteNotSent, InviteSent, InviteExpired, DataMismatch, Connected, Declined]

dobMismatch

▾ boolean

True if date of birth mismatch detected (when connectionStatus is DataMismatch)

surnameMismatch

▾ boolean

True if surname mismatch detected (when connectionStatus is DataMismatch)

patientDataAccessLimited

▾ boolean

True if the patient has restricted their data partially or totally

gpDataAccessLimited

▾ boolean

True if the GP has blocked the patient's data partially or totally

dataAccessStatus

DataAccessStatus ▾ DataAccessStatus string

Whether the patient has been asked to grant data access and whether they have done so.

- RequestNotSent - Request not sent yet
- RequestSent - Request sent to the patient
- Reviewed - Patient granted the organisation access to some NHS data
- Declined - Patient declined the data-access request via the decline link. Connect may send a new request

unless connectionStatus is DataMismatch or Declined.

Connect issues a data-access request email/link while status is RequestNotSent, RequestSent, or Declined (not after Reviewed).

Enum:

▼ [RequestNotSent, RequestSent, Reviewed, Declined]

▼ **string**(\$date)

nullable: true

Date of oldest NHS record received (ISO-8601); null if none

oldestNhsRecordDate

▼ **string**(\$date-time)

nullable: true

ISO-8601 date of the last NHS registration invitation email sent

lastInvitationEmailDate

▼ **string**(\$date-time)

nullable: true

ISO-8601 date of the last data access request email sent

lastAccessRequestEmailDate

}

AccessTokenRequest ▼ {

extUserId*

▼ **string**

External user ID (EHR) of the requesting clinician

}

AccessTokenResponse ▼ {

accessToken*

▼ **string**

Short-lived JWT token for accessing patient data (expires in expiresIn seconds)

expiresIn*

▼ **integer**

example: 900

Token expiration time in seconds (typically 900 = 15 minutes)

}

ContractAccessTokenResponse ▼ {

accessToken*

▼ **string**

Short-lived JWT for the organisation-contract signing iframe only (not the patient records widget). Pass into the iframe via SET_TOKEN / openOrbWidget (see Widget Integration Guide)

expiresIn*

▼ **integer**

example: 900

Seconds until the token expires from issue time (configured on ORB; typically 900 = 15 minutes). Generate a new token if the iframe session outlives this value

}

LinksSentStats ▾ {

```
organizationName*           ▾ string
                              Organisation display name

extOrganisationKey*         ▾ string
                              EHR organisation ID (same value as extOrganisationId)

invitationsSent*            ▾ integer
                              Distinct patients sent an NHS invitation

dataAccessRequestsSent*     ▾ integer
                              Distinct patients sent a data-access request

}
```

ConsentGrantedStats ▾ {

```
organizationName*           ▾ string
                              Organisation display name

extOrganisationKey*         ▾ string
                              EHR organisation ID (same value as extOrganisationId)

dataAccessRequestsSent*     ▾ integer
                              Distinct patients sent a data-access request

consentGranted*             ▾ integer
                              Of those, patients with at least one NHS dataset enabled for the
                              organisation

}
```

ConsentDeclinedStats ▾ {

```
organizationName*           ▾ string
                              Organisation display name

extOrganisationKey*         ▾ string
                              EHR organisation ID (same value as extOrganisationId)

invitationsSent*            ▾ integer
                              Distinct patients sent an NHS invitation

declinedInvitations*        ▾ integer
                              Of those, connectionStatus = Declined

dataAccessRequestsSent*     ▾ integer
                              Distinct patients sent a data-access request

dataAccessRequestsDeclined* ▾ integer
                              Of those, dataAccessStatus = Declined

}
```

NoResponseStats ▾ {

```
  organizationName*  
    ▾ string  
    Organisation display name  
  
  extOrganisationKey*  
    ▾ string  
    EHR organisation ID (same value as extOrganisationId)  
  
  invitationsSent*  
    ▾ integer  
    Distinct patients sent an NHS invitation  
  
  noResponseInvitations*  
    ▾ integer  
    Of those, not Connected and not Declined  
  
  dataAccessRequestsSent*  
    ▾ integer  
    Distinct patients sent a data-access request  
  
  noResponseDataAccessRequests*  
    ▾ integer  
    Of those, not dataAccessStatus = Declined and no NHS  
    dataset enabled for the organisation  
  
}
```

WidgetTermsStats ▾ {

```
  organizationName*  
    ▾ string  
    Organisation display name  
  
  extOrganisationKey*  
    ▾ string  
    EHR organisation ID (same value as extOrganisationId)  
  
  signed*  
    ▾ integer  
    Non-archived users who have accepted widget T&Cs  
  
  notSigned*  
    ▾ integer  
    Non-archived users who have not accepted widget T&Cs (includes  
    never opened the widget)  
  
  clinicianSigned*  
    ▾ integer  
    Users with isClinician true who have accepted widget T&Cs  
  
  clinicianNotSigned*  
    ▾ integer  
    Users with isClinician true who have not accepted widget T&Cs  
  
  locumSigned*  
    ▾ integer  
    Users with isLocum true who have accepted widget T&Cs  
  
  locumNotSigned*  
    ▾ integer  
    Users with isLocum true who have not accepted widget T&Cs  
  
}
```

NhsRecordsViewedUserStats ▾ {

```
  extUserId*  
    ▾ string  
    EHR user ID  
  
  userName*  
    ▾ string  
    User display name  
  
  isClinician*  
    ▾ boolean  
  
  isLocum*  
    ▾ boolean  
  
  patientsViewed*  
    ▾ integer  
    Distinct patients this user viewed in the clinician widget (0 if none)  
  
}
```

NhsRecordsViewedStats ▾ {

```
  organizationName*  
    ▾ string  
    Organisation display name  
  
  extOrganisationKey*  
    ▾ string  
    EHR organisation ID (same value as extOrganisationId)  
  
  patientsViewed*  
    ▾ integer  
    Distinct patients viewed at this organisation (not the sum of per-user counts)  
  
  users*  
    ▾ [NhsRecordsViewedUserStats ▾ {  
      extUserId*  
        ▾ string  
        EHR user ID  
  
      userName*  
        ▾ string  
        User display name  
  
      isClinician*  
        ▾ boolean  
  
      isLocum*  
        ▾ boolean  
  
      patientsViewed*  
        ▾ integer  
        Distinct patients this user viewed in the clinician widget (0 if none)  
    }]  
  
}
```