

Arm® Cortex®-M23
32-bit Microcontroller

M251/M252 Series CMSIS BSP
Revision History

The information described in this document is the exclusive intellectual property of Nuvoton Technology Corporation and shall not be reproduced without permission from Nuvoton.

Nuvoton is providing this document only for reference purposes of NuMicro microcontroller based system design. Nuvoton assumes no responsibility for errors or omissions.

All data and specifications are subject to change without notice.

For additional information or questions, please contact: Nuvoton Technology Corporation.

www.nuvoton.com

Revision 3.00.005 (Released 2020-6-10)

- Added Apache-2.0 license declaration.
- Standard driver
 1. retarget.c
 - Fixed SendChar: Uninitialized pointer.
 2. TIMER driver
 - New API: TIMER_SET_OPMODE.
 3. UART driver
 - New API: UART_DEGLITCH_DISABLE, UART_DEGLITCH_ENABLE, UART_PDMA_DISABLE, UART_PDMA_ENABLE.
 4. USCI-UART driver
 - New API: UART_DEGLITCH_DISABLE, UART_DEGLITCH_ENABLE.
- Sample code
 1. New sample code: GPIO_SingleCycleIO, I2C_SMBus, MPU, SYS_PowerDownMode, Sys_PowerMode, USBD_CCID.
 2. Updated CLK_ClockDetector: HCLK clock source uses HXT instead of PLL.
 3. Fixed QSPI_DualMode_Flash, QSPI_QualMode_Flash, SPI_Flash: Miss the 256th byte written.

Revision 3.00.004 (Released 2019-12-31)

- Removed CRPTO support.
- Standard driver
 1. retarget.c
 - Fixed _write, SendChar_ToUART: '\r' issue.
 2. CRC driver
 - New API: CRC_SET_WDATA_LEN.
 3. FMC driver
 - Updated FMC_Write128: Note to run in SRAM instead of inline function.
 - Fixed FMC_WriteConfig: Return value.
 4. SYS driver
 - Replaced SYS_PLCTL_PLSEL_PL2 with SYS_PLCTL_PLSEL_PL3.
 5. TIMER_PWM driver
 - Fixed TPWM_ConfigOutputFreqAndDuty: Wrong configuration for 1 Hz.
- Sample code
 1. New sample code: ISP_DFU.
 2. Improved I2C_Wakeup_Slave: Wakeup robustness.
 3. Improved all USBD samples: USB compatability.

4. Updated FMC_MultiWordProgram: Use FMC driver API.
5. Fixed UART_LIN, UART_SingleWire: 'r' issue.

Revision 3.00.003 (Released 2019-8-30)

- M251.h
 1. Included core_cm23.h instead of core_armv8mbl.h.
- Peripheral header
 1. Updated clk_reg.h, rtc_reg.h: Base on TRM.
- Standard driver
 1. I2C driver
 - Improved I2C_SetSlaveAddr, I2C_SetSlaveAddrMask: Add support of 10-bit slave address and error handling for new transfer.
 2. TIMER driver
 - Fixed TIMER_GetModuleClock: Correct PCLK.
 - Fixed TIMER_Open: Return value.
 3. TIMER_PWM driver
 - New API: TPWM_ClearWakeupFlag, TPWM_DisableTrigger, TPWM_DisableWakeup, TPWM_EnableTrigger, TPWM_EnableWakeup, TPWM_GetWakeupFlag, TPWM_CLEAR_TRG_DAC_STATUS, TPWM_CLEAR_TRG_PDMA_STATUS, TPWM_GET_TRG_DAC_STATUS, TPWM_GET_TRG_PDMA_STATUS.
 - Removed TPWM_OUTPUT_TOGGLE, TPWM_OUTPUT_NOTHING, TPWM_OUTPUT_LOW, TPWM_OUTPUT_HIGH, TPWM_CLKSRC_HXT, TPWM_CLKSRC_LXT, TPWM_CLKSRC_PCLK, TPWM_CLKSRC_TX, TPWM_CLKSRC_LIRC, TPWM_CLKSRC_HIRC.
 4. USCI_SPI driver
 - Fixed USPI_SET_SS_HIGH: Implementation.
- Library
 1. Smartcard library
 - New API: SCLIB_CheckCDEvent_ByVar.
- Sample code
 1. New sample code: ISP samples, QSPI_Slave3Wire, SPI_HalfDuplex
 2. Improved EADC_BandGap: Show voltage result and modify extern sample time for band-gap.
 3. Improved FMC_ExecInSRAM: Add GCC project.
 4. Improved SC_ReadATR, SC_ReadSimPhoneBook: Add software card detection.
 5. Improved USCI_SPI_Loopback, USCI_SPI_MasterMode, USCI_SPI_SlaveMode: Add using GPIO pin instead of SS pin.

6. Replaced I2C_Master_PDMA and I2C_PDMA, I2C_Slave_PDMA with I2C_PDMA_TRX.
7. Fixed UART_TxRx_Function: Data lost.
8. Fixed all USBD samples: Potential issue.

Revision 3.00.002 (Released 2019-2-22)

- system_M251.c
 1. Set flash access cycle to 0x03.
- Standard driver
 1. CLK driver
 - Removed CLK_SET_PCLK_DIVIDER.
- Sample code
 1. Updated all samples: Use other clock source instead of HXT.
 2. Updated SYS_TrimHIRC: Add auto trim disable.
 3. Updated USBD_Audio_Codec: Clear buffer before play / record.

Revision 3.00.001 (Released 2018-12-25)

- Initial release.

Important Notice

Nuvoton Products are neither intended nor warranted for usage in systems or equipment, any malfunction or failure of which may cause loss of human life, bodily injury or severe property damage. Such applications are deemed, "Insecure Usage".

Insecure usage includes, but is not limited to: equipment for surgical implementation, atomic energy control instruments, airplane or spaceship instruments, the control or operation of dynamic, brake or safety systems designed for vehicular use, traffic signal instruments, all types of safety devices, and other applications intended to support or sustain life.

All Insecure Usage shall be made at customer's risk, and in the event that third parties lay claims to Nuvoton as a result of customer's Insecure Usage, customer shall indemnify the damages and liabilities thus incurred by Nuvoton.

*Please note that all data and specifications are subject to change without notice.
All the trademarks of products and companies mentioned in this datasheet belong to their respective owners.*