

**MAGENTA<sup>aps</sup>**

# **CPR BROKER**

## **Developer manual**

**MAGENTA<sup>aps</sup>**

© Copyright 2015

# TABLE OF CONTENTS

<b>1 Introduction.....</b>	<b>3</b>		
<b>2 BUILDING CLIENT APPLICATIONS.....</b>	<b>4</b>		
2.1 Concepts and facts.....	4		
2.2 First steps.....	4		
2.2.1 Add references.....	4		
2.2.2 Request and approve application token.....	4		
2.2.2.1 Request application token.....	5		
2.2.2.2 Approve application token.....	5		
2.2.3 Passing credentials.....	5		
2.3 Reading person data.....	5		
2.3.1 General notes on methods related to historical data.....	5		
2.3.2 Data source selection.....	6		
2.3.2.1 Notes.....	6		
2.3.3 GetUuid & Read.....	6		
2.3.4 RefreshRead.....	6		
2.3.5 ReadSnapshot.....	7		
2.3.6 ReadPeriod.....	7		
2.3.7 Calling List.....	7		
2.3.8 ListSnapshot.....	7		
2.3.9 ListPeriod.....	8		
2.3.10 Searching for people.....	8		
2.3.11 Enriched search (SearchList).....	9		
2.4 Subscribing to events.....	10		
2.4.1 Preparing a notification channel.....	10		
2.4.1.1 File share channels.....	10		
2.4.1.2 Web service channels.....	10		
2.4.2 Creating the subscription.....	11		
2.4.2.1 Creating general subscriptions.....	11		
2.4.2.2 Creating specialized subscriptions.....	11		
2.4.2.3 Using a web service channel.....	12		
2.4.2.4 Removing subscriptions.....	13		
<b>3 IMPLEMENTING NEW DATA SOURCES.....</b>	<b>14</b>		
3.1 Data provider class.....	14		
3.2 Register the provider type.....	14		
3.3 Add data provider instance.....	15		
<b>4 Setting up logging.....</b>	<b>16</b>		

# 1 INTRODUCTION

This document will describe how to build applications based on CPR Broker. This will include client applications and also how to extend the broker to include other data sources.

This document is organized as a 'how to' guide. The code examples will assume using Visual Studio .NET, but the concepts can be generalized to use other tools or platforms for building client applications.

## 2 BUILDING CLIENT APPLICATIONS

### 2.1 Concepts and facts

- Communication with the broker is done through SOAP 1.2 web services
- To be able to use the system, you need a valid application token
- All responses contain an object of StandardReturType that includes a status code and text.

### 2.2 First steps

#### 2.2.1 Add references

You need to add web references / service references that point to the broker web services.

This table summarizes the information about the services

URL	Description
http(s)://[CprBrokerUrl]/Services/Part.asmx	Main end point for CPR Broker. Allows client applications to read CPR Data
Http(s)://[CprBrokerUrl]/Services/Admin.asmx	A less common end point for doing administrative tasks, like setting data sources and client applications
http(s)://[EventBrokerUrl]/Services/Subscriptions.asmx	Used to manage subscriptions to CPR Broker events (data changes, birthdays, etc)

#### 2.2.2 Request and approve application token

**Note:** You can skip this step if you already have an application token created in CPR Broker's admin pages.

In order to call CPR Broker web services, you must use an approved application token. An application token is simply a string that identifies the client application that is calling CPR broker. You can do that using the user interface or through web service SOAP calls. This section describes the latter method. For details on how to do it through the user interface, please refer to CPR Broker installation guide.

For all web service calls to CPR broker, you need to fill the application token and the user token.

Example:

```
PartService.ApplicationHeaderValue = new Admin.ApplicationHeader() { ApplicationToken =  
"[token of approved application]", UserToken = "[Any string]" };
```

### 2.2.2.1 Request application token

```
string newAppName = "[Application name]";  
var newApplicationResult = AdminService.RequestAppRegistration(newAppName);  
var newApplication = newApplicationResult.Item;
```

### 2.2.2.2 Approve application token

```
AdminService.ApplicationHeaderValue = new Admin.ApplicationHeader() { ApplicationToken =  
"07059250-E448-4040-B695-9C03F9E59E38", UserToken = "[Any string]" };  
var result = AdminService.ApproveAppRegistration(TestData.AppToken);  
AdminService.ApplicationHeaderValue.ApplicationToken = newApplication.Token;
```

Now you should store the application token somewhere and use it from now on.

```
PartService.ApplicationHeaderValue = new Part.ApplicationHeader() { ApplicationToken =  
myApplicationToken, UserToken = "[Any string]" };  
SubscriptionsService.ApplicationHeaderValue = new Subscriptions.ApplicationHeader()  
{ ApplicationToken = myApplicationToken, UserToken = "[Any string]" };
```

## 2.2.3 Passing credentials

If the CPR broker administrator has decided to use Windows authentication instead of Anonymous authentication, you would probably also need to pass your current credentials to the service. You will need something like this:

```
PartService.Credentials = System.Net.CredentialCache.DefaultCredentials;
```

## 2.3 Reading person data

### 2.3.1 General notes on methods related to historical data

The methods ReadSnapshot, ReadPeriod, ListSnapshot and ListPeriod all rely on the broker containing historical data.

**To use these methods it is a requirement for the records of the broker be subscribed to historical data extracts from the CPR office.**

The methods will work on previously build up historical data in the broker, but inconsistency may appear. Corrections (a record field being corrected, caused by incorrect data) will, for instance, not be included and thereby the produced results may potentially be misleading.

## 2.3.2 Data source selection

Some of the methods allow the calling client to select how to (not)use local data in CPR Broker. This is achieved through a SOAP header called 'sourceUsageOrderHeader'. This header contains a single element (SourceUsageOrder) that can take values as the following table:

Value	Behaviour
LocalThenExternal	CPR broker first looks for data in its local database. If data is not found, it will start looking in external data providers. This is the default.
LocalOnly	Data is looked up only in local database. No attempts are made in external providers even if data is not found locally.
ExternalOnly	Local database is ignored and the broker goes directly to external providers.

### 2.3.2.1 Notes

- Usage of this parameter is limited to Read() and List() operations.
- If an external provider is used to get the result (in case of ExternalOnly or LocalThenExternal), the local database is updated with new data (if needed).

## 2.3.3 GetUuid & Read

```
var uuidResult = PartService.GetUuid(cprNumber);  
Part.LaesInputType input = new Part.LaesInputType() { UUID = uuidResult.UUID };  
  
// Optional  
PartService.SourceUsageOrderHeaderValue = new SourceUsageOrderHeader() { SourceUsageOrder  
= SourceUsageOrder.LocalThenExternal };  
  
LaesOutputType readResult = PartService.Read(input);  
  
var person = readResult.LaesResultat.Item as RegistreringType1  
  
var personName = reg.AttributListe.Egenskab[0].NavnStruktur.PersonNameStructure;  
  
Console.WriteLine(string.Format("{0} {1} {2}", personName.PersonGivenName,  
personName.PersonMiddleName, personName.PersonSurnameName);
```

## 2.3.4 RefreshRead

This method has exactly the same signature as Read, except that it will only get data from external data providers (DPR or KMD). It will not use the local database, but will update it if necessary.

### 2.3.5 ReadSnapshot

```
var uuid = PartService.GetUuid([cpr-nummer]);  
Part.LaesOejebliksbilledeInputType input = new Part.LaesOejebliksbilledeInputType() {  
    UUID = uuid.UUID,  
    VirkningDato = [dato],  
};  
LaesOutputType person = PartService.ReadSnapshot(input);
```

### 2.3.6 ReadPeriod

```
var uuid = PartService.GetUuid([cpr-nummer]);  
Part.LaesPeriodInputType test = new Part.LaesPeriodInputType() {  
    UUID = uuid.UUID,  
    VirkningFraDato = [fradato],  
    VirkningTilDato = [tildato],  
};  
LaesOutputType person = PartService.ReadSnapshot(input);
```

### 2.3.7 Calling List

List method can be used to get many persons in one request

```
Part.ListInputType input = new Part.ListInputType()  
{ UUID = new string[] { "[uuid 1", "uuid 2", .....} };  
  
// Optional  
PartService.SourceUsageOrderHeaderValue = new SourceUsageOrderHeader() { SourceUsageOrder  
= SourceUsageOrder.LocalThenExternal };  
  
var listResult =PartService.List(input);  
var persons = listResult .LaesResultat;
```

### 2.3.8 ListSnapshot

```
Part.ListOejebliksbilledeInputType listInput = new Part.ListOejebliksbilledeInputType() {  
    UUID = [cpr1, cpr2, cpr3, cpr4, cpr5, cpr6],  
    VirkningDato = [dato],  
};  
Part.ListOutputType1 listResult = partService.ListSnapshot(listInput);
```

### 2.3.9 ListPeriod

```
Part.ListPeriodInputType periodInput = new ListPeriodInputType() {
    UUID = [cpr1, cpr2, cpr3, cpr4, cpr5, cpr6],
    VirkningFraDato = [fradato],
    VirkningTilDato = [tildato],
};

Part.ListOutputType1 listResult = partService.ListPeriod(periodInput);
```

### 2.3.10 Searching for people

The broker implements search capabilities. A call to Search will search the broker's local database or one of the external sources that have a search feature. Search can be made for person name, CPR number and address.

The choice of search provider is controlled as described in 2.3.2Data source selection. Note that the options here are either LocalOnly or ExternalOnly (but not LocalThenExternal)

```
var searchCriteria = new Part.SoegInputType1(){
    SoegObjekt = new Part.SoegObjektType(){
        SoegAttributListe = new Part.SoegAttributListeType(){
            SoegEgenskab = new Part.SoegEgenskabType[]{
                new Part.SoegEgenskabType(){
                    NavnStruktur = new Part.NavnStrukturType(){
                        PersonNameStructure = new Part.PersonNameStructureType(){
                            PersonGivenName = "<first_name_here>",
                            PersonSurnameName = "<last_name_here>"
                        }
                    }
                }
            }
        }
    }
};

// Now get the result
var result = PartService.Search(searchCriteria);
var personUuids = result.Idliste;

// Call List() now to get the actual persons' data
```



### 2.3.11 Enriched search (SearchList)

It is also possible to get some basic data directly in the return if you call the SearchList method. This way you do not have to make another call in order to get the people's names.

```
var searchResult = service.SearchList(searchCriteria)
foreach (var person in searchResult.LaesResultat)
{
    var snapshot = person.Item as FiltreretOejebliksbilledeType;
    var name = snapshot.AttributListe.Egenskab.First().NavnStruktur.PersonNameStructure;
    Console.WriteLine(string.Format("{0} {1}", name.PersonGivenName,
        name.PersonSurnameName));
}
```

## 2.4 Subscribing to events

To receive events from CPR Broker/Event Broker, you need to do three steps:

- Preparing a notification channel/endpoint that should be called by the broker.
- Calling the `http://[EventBrokerUrl]/Services/Subscriptions.asmx` web service to create a subscription.

### 2.4.1 Preparing a notification channel

CPR Broker supports can deliver events in two ways: an XML file on a file share, or a call to a SOAP web service.

Both ways deliver exactly the same amount of information, so the choice depends on what is best for the environment where it is installed.

There are no restrictions on the number of subscriptions. A subscriptions can push notifications to its own channel, which could actually be the same channel of another subscription.

#### 2.4.1.1 File share channels

These are just normal Windows (or other) folders that could be located anywhere in the server environment. The only requirement is that the supplied path exists, and is accessible from the CPR Broker server.

For example:

- `C:\CPR_Notifications`
- `\\myserver\CPR_Notif\New`

After creating the subscription(s), you will start getting one XML file per notification in this folder. It is your responsibility to read these files and delete them from the file share.

#### 2.4.1.2 Web service channels

Another way to receive the events is to create a SOAP web service that can receive the events. This service should be build using the WSDL definition that is located at `http://[EventBrokerUrl]/Templates/Notification.wsdl`

**Tip:** In .NET environments, you can use this command to create the service definition:  
`wsdl.exe /serverInterface http://[EventBrokerUrl]/Services/Notification.asmx?WSDL`

You will then need to put an actual implementation of the interface, and host it somewhere that is accessible from CPR Broker server

After creating a subscription, your service will get one call per notification.

## 2.4.2 Creating the subscription

### 2.4.2.1 Creating general subscriptions

Subscriptions to any changes on persons can be attached via the Subscribe method.

The method takes two parameters (as shown below): a channel and an array of UUIDs.

```
var uuids = new Guid[]{uuid1, uuid2,...};  
// OR, for all persons  
// Guid[] uuids = null;  
var fileShareChannel = new Subscriptions.FileShareChannelType(){ Path="[Channel folder/UNC path]" };  
var subscriptionResult = SubscriptionsService.Subscribe(fileShareChannel, uuids);  
var subscription = subscriptionResult.Item;  
var subscriptionId = subscription.SubscriptionId;
```

### 2.4.2.2 Creating specialized subscriptions

There are two specialized subscription methods: `SubscribeOnBirthdate` and `SubscribeOnCriteria`.

#### 2.4.2.2.1 `SubscribeOnBirthdate`

This method attaches a subscription on persons set to a given age. A notification will be handed over to the client application (via the specified channel).

The method takes four parameters: a channel, the target age, the amount of days in advance the notification should be sent and an array of UUIDs.

```
var fileShareChannel = new Subscriptions.FileShareChannelType(){ Path="[Channel folder path]" };  
int birthdatePriordays = 10;  
int? birthdateAgeYears = null;  
var res = SubscriptionsService.SubscribeOnBirthdate( fileShareChannel, birthdateAgeYears,  
birthdatePriorDays, uuids);  
var subscriptionId = subscription.SubscriptionId;
```

#### 2.4.2.2.2 `SubscribeOnCriteria`

This method attaches a subscription to persons matching a given criterion (f.ex. municipality code). Subscriptions will then be put on each person meeting the criterion.

The method takes two parameters: a channel and a `SoegObjectType` describing the criterion.

**Note:** The action of this method is taking place in the brokers backend service and will (depending on the size of the dataset and machine power) take some minutes to finish (2 min. based on a dataset of 40000 records).

```
var fileShareChannel = new Subscriptions.FileShareChannelType(){ Path="[Channel folder path]" };
var SoegObjekt = new Subscriptions.SoegObjektType()
{
    SoegAttributListe = new Subscriptions.SoegAttributListeType()
    {
        SoegEgenskab = new Subscriptions.SoegEgenskabType[]
        {
            new Subscriptions.SoegEgenskabType()
            {
                AndreAdresser = new Subscriptions.AdresseType(
                {
                    Item = new Subscriptions.DanskAdresseType()
                    {
                        AddressComplete = new Subscriptions.AddressCompleteType()
                        {
                            AddressAccess = new Subscriptions.AddressAccessType()
                            {
                                MunicipalityCode = "[MunicipalityCode]"
                            }
                        }
                    }
                }
            }
        }
    }
};

var subscription = SubscriptionsService.SubscribeOnCriteria(fileShareChannel, SoegObjekt);
var subscriptionId = subscription.SubscriptionId;
```

### 2.4.2.3 Using a web service channel

If you want to use a web service channel, you can create it like this:

```
var webServiceChannel = new Subscriptions.WebServiceChannelType() { WebServiceUrl = "http://"
```

```
[web service url]" };
```

#### 2.4.2.4 Removing subscriptions

```
var res1 = SubscriptionsService.Unsubscribe( new Guid("[SubscriptionId]"));  
var res2 = TestRunner.SubscriptionsService.RemoveBirthDateSubscription( new  
Guid("[SubscriptionId]"));
```

## 3 IMPLEMENTING NEW DATA SOURCES

The broker does not own data itself. It relies on getting data from other sources and then stores this data into its database for usage in the future.

To implement a new data source, you need to do the steps in the following sections.

### 3.1 Data provider class

You need to create a class that gets the data provider. To do this, you need it to implement at least 2 interfaces. First is `CprBroker.Engine.IExternalDataProvider`. The other is the respective interface for the business need. For Example, the KMD data provider is defined as:

```
using CprBroker.Engine;

public partial class KmdDataProvider : IDataProvider, IExternalDataProvider,
IPartReadDataProvider
{
    public bool IsAlive() { // implementation }

    public DataProviderConfigPropertyInfo[] ConfigurationKeys
    get {
        return new DataProviderConfigPropertyInfo[]
        {
            new DataProviderConfigPropertyInfo(){Name="Address",Required=true,
Confidential=false},
            new DataProviderConfigPropertyInfo()
{Name="Username",Required=true,Confidential=false},
            new DataProviderConfigPropertyInfo(){Name="Password"
,Required=true,Confidential=true}
        };
    }

    public RegistreringType1 Read(CprBroker.Schemas.PersonIdentifier uuid, LaesInputType input,
Func<string, Guid> cpr2uuidFunc, out CprBroker.Schemas.QualityLevel? ql)
    {
        .....
    }
}
```

### 3.2 Register the provider type

Copy the DLL that contains the data provider to the /bin folder in the broker website.

Now in the Web.config file of CPR broker website, open the node configuration/dataProvidersGroup/dataProviders/knownTypes

Add a new 'add' node for the new type

```
<add type="CprBroker.Providers.KMD.KmdDataProvider, CprBroker.Providers.KMD"/>
```

### 3.3 Add data provider instance

Open [http://\[Cpr Broker Url\]/Pages/DataProviders.aspx](http://[Cpr Broker Url]/Pages/DataProviders.aspx)

You should see the new type in the table on top.

Now select the type from the drop down on the bottom of the page (Under 'New Data Provider'), fill the parameters and click 'Insert'

**CPR Broker**

Admin Applications **Data providers** View log

**Data provider types**

Possible types of data providers

Name	Assembly qualified name
DprDatabaseDataProvider	CprBroker.Providers.DPR.DprDatabaseDataProvider, CprBroker.Providers.DPR, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null
KmdDataProvider	CprBroker.Providers.KMD.KmdDataProvider, CprBroker.Providers.KMD, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null
PersonMasterDataProvider	CprBroker.Providers.PersonMaster.PersonMasterDataProvider, CprBroker.Providers.PersonMaster, Version=1.0.0.0, Culture=neutral, PublicKeyToken=null

**Data providers**

Available data providers. They will be used in the order listed here.

Type	Address	Port	Keep Subscription	Data Source	Initial Catalog	User ID	Enabled	Edit	Yes (Disable)	Ping	Delete
PersonMasterDataProvider	http://personmaster-service-test-01/PersonmasterServiceLibrary.BasicOp.svc						Yes	Edit	Yes (Disable)	Ping	Delete
DprDatabaseDataProvider	Address: ITJOBS-P03 Password: ***** Integrated Security: Other Connection String:	Port: 6003	Keep Subscription: True	Data Source: DPR	Initial Catalog: dpr	User ID: DPR-CRRBroker	Yes	Edit	Yes (Disable)	Ping	Delete
KmdDataProvider	Address: http://195.50.36.114/bcprod.asp Username: cesde Password: *****						Yes	Edit	Yes (Disable)	Ping	Delete

**New data provider**

Type: CprBroker.Providers.DPR.DprDatabaseDataProvider

Address:

Port:

Keep Subscription:

Data Source:

Initial Catalog:

User ID:

Password:

Integrated Security:

Other Connection String:

This is a basic interface but it does get the job done.

Normally when external applications register themselves with *CPR Broker Service* they get an application token, but they are not allowed to do anything with the service before the application has been *Approved*.

To approve an application, simply click *Edit* for the application in question and check the *Approved* check box. Then click *Update* (only shown after *Edit*).

You can also enter a new application manually. Simply give it a *Name*, a *Token* and whether it should be initially approved (it probably should). Then click *Insert*. The application is now listed under *Applications*.

## 4 SETTING UP LOGGING

CPR Broker can log to file, Windows Event Log, to the Database and to email.

There place to setup logging: In the *loggingConfiguration.config* file for CPR Broker web service. The default position for this is *C:\Program Files\ITST\CPR Broker(Event Broker)\Web\Config*

**Additional location for Event Broker:** in the *CprBroker.EventBroker.Backend.exe.config* file for the Backend service. The default position for this is *C:\Program Files\ITST\Event Broker\Web\bin\*.

The procedure is the same for both files. Locate the `<loggingConfiguration>` tag in the specific config file. Under the `<listeners>` tag you will find four `<add>` tags. The "CprDatabase" as well as the "EventLog" should be left untouched in all cases.

In "FlatFile" you should look for the `fileName` attribute. This should be set to the full path and name of the where to put the log file.

In `name="Email"` there are more settings. The ones most likely to be adjusted are: `toAddress`, `fromAddress`, `smtpServer` and perhaps `smtpPort`.

Please note: In the last 3 cases, you need to make sure that the 'NT AUTHORITY\NETWORK SERVICE' account has sufficient access rights to the destination.

You have now adjusted the settings for each type of logging, but you have yet to set what types of logging are *active*. You now look for the `<specialSources>/ <allEvents>` tag. In this you will another `<listeners>` tag. Per default "CprDatabase" is active, which can be seen from the fact that it is not commented out like e.g. `<!--add name="EventLog" /-->` is.

To enable a specific listener simply remove the `<!--` and `-->` characters from the line. And to disable a listener simply put them back in.



**MAGENTA<sup>aps</sup>**

**MAGENTA<sup>aps</sup>**

**adresse**

Stuðiestræde 14, 1.  
1455 Københavk K

**email**

info@magenta-aps.dk

**telefon**

(+45) 33 36 96 96