

OSIX Tech - Naming Conventions

1. Repositories & Projects

- **Language:** English.
- **Format:** kebab-case (nessie-ingestor , nessie-frontend).
- **Structure:** <project>-<module> , always descriptive.
- **Published packages:** follow ecosystem convention
 - npm → kebab-case (my-package)
 - PyPI → snake_case or kebab-case (my_package or my-package)

2. Variables, Classes & Packages

- **Variables & functions (JS, TS, Python):** snake_case.
- **Classes:** PascalCase.
- **Constants:** ALL_CAPS.
- **Published modules/packages:** follow the ecosystem's naming standard.

3. Commits

- **Format:** vX.Y.Z type[scope]: message in English, imperative form
Example: v1.4.2 fix[auth]: reject expired refresh tokens
- **SemVer rules:**
 - MAJOR → breaking changes
 - MINOR → new features without breaking
 - PATCH → fixes and internal improvements
- **Automation:** use tools like npm version , bump2version , standard-version or changesets to avoid manual versioning.
- **Scope:** optional but recommended.

4. Branching

- **Format:** kebab-case (feature/auth-token-rotation).
- **Prefixes:**
 - feature/
 - fix/
 - hotfix/
 - release/
 - chore/
- Ticket ID optional at the end.

5. Folders & Files

- **General rule:** kebab-case.
- **Exception:** React components use PascalCase (UserCard.jsx).
- **React Frontend specifics:**
 - Folders: kebab-case (user-profile).
 - Hooks: useCamelCase (useAuth.js).
 - Utils & services: kebab-case (api-client.js).
 - JSX props: camelCase.

6. Database & API

- **Database:**
 - Tables & columns: snake_case, plural (users , invoices).
 - Foreign keys: <singular_table>_id (user_id).
- **API:**
 - Routes: kebab-case, plural, versioned (/api/v1/user-accounts).

7. Environment Variables

- Format: ALL_CAPS_SNAKE_CASE (DATABASE_URL , API_KEY).

8. Containers & Services

- **Docker images:** kebab-case (nessie-backend , opills-dashboard).
- **Cloud services:** <project>--<module>--<env> (nessie-backend-prod).
- **Environments:** dev , staging , prod .

Quick Reference Table

Category	Format / Rule	Example(s)
Repo Names	kebab-case, <project>--<module>	nessie-ingestor , opills-dashboard
Vars/Funcs	snake_case	user_name , get_user_data()
Classes	PascalCase	UserProfile , AuthService
Constants	ALL_CAPS	MAX_USERS , API_KEY
Commits	vX.Y.Z type[scope]: message (SemVer)	v1.0.0 feat[auth]: add token refresh
Branches	kebab-case with prefix	feature/user-auth , fix/payment-bug
Folders	kebab-case	user-profile , api-client
React Components	PascalCase for files, kebab-case for folders	UserCard.jsx in user-card/
DB Tables	snake_case plural	users , invoices
API Routes	kebab-case plural, versioned	/api/v1/user-accounts
Env Vars	ALL_CAPS_SNAKE_CASE	DATABASE_URL
Docker Images	kebab-case	nessie-backend

Category	Format / Rule	Example(s)
Cloud Services	<project>-<module>-<env>	opills-dashboard-prod