


Scaffold protein titration motif

The model description

This particular motif describe one phosphorylation-desphosphorylation cycle (can be generalized to any futile cycles) with both kinase (K) and phosphatase (P) can be titrated by a scaffold protein (T).



The above reactions show a simple system that composed of one scaffold protein, one kinase, one phosphatase and one substrate. Here we try to descibe this simple system with differential equation following the mass action kinetics.

$$\begin{aligned}\frac{d[K]}{dt} &= -k[1][K][S] + k[2][KS] + k[3][KS] - k[7][T][K] + k[8][TK] + k[11]k_d - k_d[K], \\ \frac{d[P]}{dt} &= -k[4][P][S_p] + k[5][PS_p] + k[6][PS_p] - k[9][T][P] + k[10][TP], \\ \frac{d[S]}{dt} &= -k[1][K][S] + k[2][KS] + k[6][PS_p], \\ \frac{d[S_p]}{dt} &= -k[4][P][S_p] + k[3][KS] + k[5][PS_p], \\ \frac{d[KS]}{dt} &= k[1][K][S] - k[2][KS] - k[3][KS], \\ \frac{d[PS_p]}{dt} &= k[4][P][S_p] - k[5][PS_p] - k[6][PS_p], \\ \frac{d[T]}{dt} &= -k[7][T][K] + k[8][TK] - k[9][T][P] + k[10][TP], \\ \frac{d[TK]}{dt} &= k[7][T][K] - k[8][TK], \\ \frac{d[TP]}{dt} &= k[9][T][P] - k[10][TP].\end{aligned}$$

And the system need to follow these conservation equations:

$$\begin{aligned}[K] + [KS] + [TK] &= [K_{\text{tot}}], \\ [P] + [PS_p] + [TP] &= [P_{\text{tot}}], \\ [S] + [S_p] + [KS] + [PS_p] &= [S_{\text{tot}}], \\ [T] + [TK] + [TP] &= [T_{\text{tot}}].\end{aligned}$$

In the following setion, we will solve the differential equations to understand the dynamics and behaviour of such system.

Understanding the dynamics of the simple system with input pertubations (numerical study)

Since, it is a bit difficult to solve the differential equations analytically. Here we try to study them numerically. By defining two different way to characterising the dynamics with scoring their tempral dynamics when presented with input signal perturbation (the changing of [T]). The quantification can be derived from the actually fitness functons for ultrasensitive response and adaptive response. Then we save all the parameter sets as well as their score on ultrasensitivity and adaptation.

```
(NewKern) In[1]:= Clear["Global`*"];
SetDirectory[NotebookDirectory[]];
kd = 10;
des = {-k[1] * x[1][t] * x[3][t] + k[2] * x[5][t] + k[3] * x[5][t] -
      k[7] * x[1][t] * x[7][t] + k[8] * x[8][t] + k11[t] * kd - kd * x[1][t],
      -k[4] * x[2][t] * x[4][t] + k[5] * x[6][t] + k[6] * x[6][t] -
      k[9] * x[2][t] * x[7][t] + k[10] * x[9][t],
      -k[1] * x[1][t] * x[3][t] + k[2] * x[5][t] + k[6] * x[6][t],
      -k[4] * x[2][t] * x[4][t] + k[3] * x[5][t] + k[5] * x[6][t],
      k[1] * x[1][t] * x[3][t] - k[2] * x[5][t] - k[3] * x[5][t],
      k[4] * x[2][t] * x[4][t] - k[5] * x[6][t] - k[6] * x[6][t],
      -k[7] * x[1][t] * x[7][t] - k[9] * x[2][t] * x[7][t] +
      k[8] * x[8][t] + k[10] * x[9][t],
      k[7] * x[1][t] * x[7][t] - k[8] * x[8][t],
      k[9] * x[2][t] * x[7][t] - k[10] * x[9][t], 0};

init = {totK, totP, totS, 0, 0, 0, totT, 0, 0, 1. * 10^-4};
(*init=
  {tot[1], tot[2], tot[3], 0.00001, 0.00001, 0.00001, totT, 0.00001, 0.00001}; *)

AbsoluteTiming[
  totK = 0.0001; totP = 0.1; totS = 0.1;
  stepNum = 5;
  sampleSize = 10 000;

  pars = {};
  vars = Array[x, 9]; AppendTo[vars, k11];
  dvars = Thread[Derivative[1][vars]];
  SeedRandom[IntegerPart[SessionTime[]]];
  ts = {};
  For[num = 1, num ≤ sampleSize, num++,
    Block[{k, T, ssthreshold}, k[n_] := k[n] = 10^ (RandomReal[] * 6 - 3);
      (*tot[n_] := tot[n] = 10^ (RandomReal[] * 4 - 3); *)
      (*ksTest1 = Array[k, 10]; *)
      (*totT = 1. * 10^-3; *)
      totT = 1. * 10^ (RandomReal[] * 4 - 3);

      Block[{tPer, step},
        step = 0;
        tPer = {};
        ssthreshold = 1. * 10^-5;
        (* Print[des]; *) {sol} = NDSolve[{Through[dvars[t]] == des,
          Through[vars[0]] == init, With[{df = Through[dvars[t]]},
```

$$]_1]$$

```
precisionwithin100iterations,between = 68.65373517134225 and t = 68.7181894621442.1>>
NDSolve::evcvm1: Eventlocationfailedtoconvergetotherequestedaccuracyor
precisionwithin100iterations,between = 2814.902593999274 and t = 2815.1193214122145>>
NDSolve::evcvm1: Eventlocationfailedtoconvergetotherequestedaccuracyor
precisionwithin100iterations,between = 153.995914880530 and t = 154.16139072050237>>
```

```
(NewKern) Out[6]= {1790.6, Null}
```

```
(NewKern) In[9]:= ListPlot[Transpose[{transPars[[15]], transPars[[16]]}],
  PlotRange -> {{0, 1}, {0, 1}},
  (*AxesLabel->{"Ultrasensitive score", "Adaptive score"}, *)
  Ticks -> {{0, 0.5, 1}, {0.5, 1}}, PlotStyle -> {Thick, PointSize[0.01]},
  PlotTheme -> "Monochrome", PlotLabel -> None,
  LabelStyle -> {24, GrayLevel[0]}, ImageSize -> Large]
```



```
(NewKern) In[10]:= maxAndIndex[a_] :=
  {#, First@SparseArray[UnitStep[a - #]]["AdjacencyLists"]} &@Max@a
```

```
(NewKern) In[11]:= maxAndIndex[transPars[[15]]]
```

```
(NewKern) Out[11]=
  {0.946972, 5001}
```

```
(NewKern) In[12]:= maxAndIndex[transPars[[16]]]
```

```
(NewKern) Out[12]=
  {0.411586, 1516}
```

```
(NewKern) In[13]:= usIndex = maxAndIndex[transPars[[15]]] // Last;
  adIndex = maxAndIndex[transPars[[16]]] // Last;
  pars[[usIndex]]
```

```
(NewKern) Out[15]=
  {0.125241, 2.33764, 0.137923, 0.0676263, 0.00194479, 2.8889,
  361.434, 131.434, 387.232, 0.0273761, 1.0168, 0.1, 0.1, 0.1,
  0.946972, 0.0628295, 5001, 19.7664, 42.7474, 0.363645, 0.0000706968}
```

```
(NewKern) In[16]:= pars[[adIndex]]
```


```
(NewKern) Out[16]=
  {2.78687, 1.23172, 0.645974, 54.8715, 0.808874, 1.98871,
  288.917, 2.74103, 0.140093, 0.00710473, 4.2343, 0.1, 0.1, 0.1,
  0.136876, 0.411586, 1516, 0.673766, 0.0509843, 0.00948727, 0.0507143}
```

```

(NewKern) In[44]:= init = {totK, totP, totS, 0, 0, 0, totT, 0, 0, 1. * 10^-4};
maxAndIndex[a_] :=
  {#, First@SparseArray[UnitStep[a - #]]["AdjacencyLists"]} &@Max@a
usIndex = maxAndIndex[transPars[[15]]] // Last;
adIndex = maxAndIndex[transPars[[16]]] // Last;
stepNum = 5;
maxPars = Solve[Array[k, 10] == pars[[usIndex]][[Range[10]]]];
totT = pars[[usIndex]][[11]];
Block[{tPer, step},
  step = 0;
  tPer = {};
  ssthreshold = 1.*^-5;
  (* Print[des]; *)
  {sol} = NDSolve[{Through[dvars[t]] == des, Through[vars[0]] == init,
    With[{df = Through[dvars[t]]},
      WhenEvent[(Norm[df] < ssthreshold), {AppendTo[tPer, t], step = step + 1,
        If[step > stepNum, "StopIntegration"], k11[t] → 10 * k11[t]}]]} /.
    maxPars, vars, {t, 0, 200 000}, MaxSteps → 10 000];
  ts = tPer;
  x4 = Evaluate[x[4][ts - 0.001] /. sol] / totS;
  k11t = Evaluate[(k11[ts - 0.001]) /. sol];
];
fittedHill = FindFit[Transpose[{k11t, x4},
  a + (b - a) * hillK / (hillK + x^(-n)), {a, b, hillK, n}, x]
Show[LogLinearPlot[a + (b - a) * hillK / (hillK + x^(-n)) /. fittedHill,
  {x, 10^-4, 10}, (*Ticks→{Automatic, {0, 0.5, 1}}, *)
  PlotRange → {-0.05, 1.05}, AxesLabel → {"[T]", "[Sp] / [Stot]"},
  PlotTheme → "Monochrome", PlotStyle → {Thickness[0.01]}],
  ListLogLinearPlot[Transpose[{k11t, x4}, PlotTheme → "Monochrome",
  PlotMarkers → {Automatic, 24}], PlotLabel → None,
  LabelStyle → {24, GrayLevel[0]}, ImageSize → Large]
(NewKern) Out[51]:=
  {a → 0.000051636, b → 0.993402, hillK → 279 809., n → 4.47787}


```

(NewKern) Out[52]=



```
(NewKern) In[53]:= init = {totK, totP, totS, 0, 0, 0, totT, 0, 0, 1. * 10^-4};
maxPars = Solve[Array[k, 10] == pars[[adIndex]][[Range[10]]]];
totT = pars[[adIndex]][[11]];
Block[{tPer, step},
  step = 0;
  tPer = {};
  ssthreshold = 1.*^-5;
  (* Print[des]; *)
  {sol} = NDSolve[{Through[dvars[t]] == des, Through[vars[0]] == init,
    With[{df = Through[dvars[t]]},
      WhenEvent[Norm[df] < ssthreshold, {AppendTo[tPer, t], step = step + 1,
        If[step > stepNum, "StopIntegration", k11[t] → 10 * k11[t]}]}] /.
    maxPars, vars, {t, 0, 200 000}, MaxSteps → 10 000];
  ts = tPer;
  x4 = Evaluate[x[4][ts - 0.001] /. sol];
  k11t = Evaluate[(k11[ts - 0.001]) /. sol];
];
Plot[{x[4][t] / totS /. sol}, {t, 0, ts[[stepNum]] - 0.01},
  PlotLegends → Placed[{"[Sp]/[Stot"]}, {0.85, 0.85}], PlotRange → {0, 1.01},
  AxesLabel → {"t"}, PlotTheme → "Monochrome", PlotStyle → {Thickness[0.01]},
  PlotLabel → None, LabelStyle → {24, GrayLevel[0]}, ImageSize → Large]
```

(NewKern) Out[56]=



(NewKern) In[141]:=

```


init = {totK, totP, totS, 0, 0, 0, totT, 0, 0, 0.1};
stepNum = 3;
maxPars = Solve[Array[k, 10] == pars[[adIndex]][[Range[10]]]];
totT = pars[[adIndex]][[11]]
Block[{tPer, step},
  step = 0;
  tPer = {};
  ssthreshold = 1.*^-5;
  (* Print[des]; *)
  {sol} = NDSolve[{Through[dvars[t]] == des, Through[vars[0]] == init,
    With[{df = Through[dvars[t]]},
      WhenEvent[Norm[df] < ssthreshold, {AppendTo[tPer, t], step = step + 1,
        If[step > stepNum, "StopIntegration"], k11[t] → 5 * k11[t]}]]} /.
    maxPars, vars, {t, 0, 200 000}, MaxSteps → 10 000];
  ts = tPer;
  x4 = Evaluate[x[4][ts - 0.001] /. sol];
  k11t = Evaluate[k11[ts - 0.001] /. sol];
];
Show[Plot[{x[4][t] / totS} /. sol, {t, 10, ts[[stepNum + 1]] - 0.01},
  PlotLegends → Placed[{"[Sp]/[Stot]", {0.25, 0.95}}, PlotRange → {0, 1.01},
  AxesLabel → {"t"}, PlotTheme → "Monochrome", PlotStyle → {Thickness[0.01]},
  PlotLabel → None, LabelStyle → {24, GrayLevel[0]}, ImageSize → Large],
Plot[{k11[t] /. sol}, {t, 10, ts[[stepNum + 1]] - 0.01},
  PlotLegends → Placed[{"[K]", {0.55, 0.95}},
  PlotRange → {0, 1.01}, AxesLabel → {"t"}, PlotTheme → "Monochrome",
  PlotStyle → {Dashed, Thickness[0.007]}, PlotLabel → None,
  LabelStyle → {24, GrayLevel[0]}, ImageSize → Large]]

```

(NewKern) Out[143]=

4.2343

(NewKern) Out[145]=




(NewKern) In[146]:=

```

input = LogPlot[{{k11[t]} /. sol}, {t, 10, ts[[stepNum + 1]] - 0.01},
  PlotLegends → Placed[{"[K]"}, {0.15, 0.9}], PlotTheme → "Monochrome",
  PlotStyle → {Blue, Dashed, Thickness[0.007]}, Ticks → {},
  LabelStyle → {18, GrayLevel[0]}, ImageSize → Large,
  ImagePadding → 50, Frame → {True, True, False, False},
  FrameStyle → {Automatic, Blue, Automatic, Automatic}]

```

(NewKern) Out[146]=




(NewKern) In[149]:=

```

actualInput = LogPlot[{x[1][t]} /. sol, {t, 10, ts[[stepNum + 1]] - 0.01},
  PlotLegends → Placed[{"[K]"}, {0.65, 0.15}], PlotTheme → "Monochrome",
  PlotStyle → {Blue, Dashed, Thickness[0.007]}, Ticks → {},
  LabelStyle → {18, GrayLevel[0]}, ImageSize → Large,
  ImagePadding → 50, Frame → {True, True, False, False},
  FrameStyle → {Automatic, Blue, Automatic, Automatic}]

```

(NewKern) Out[149]=




(NewKern) In[135]:=

```

output = Plot[{x[4][t] / totS} /. sol, {t, 10, ts[[stepNum + 1]] - 0.01},
  PlotLegends → Placed[{"[Sp]/[Stot]", {0.4, 0.9}}, PlotRange → {0, 1},
  PlotStyle → {Darker[Green], Thickness[0.01]}, Ticks → {0, 0.5, 1},
  LabelStyle → {18, GrayLevel[0]}, ImageSize → Large, ImagePadding → 50,
  (*Axes→False,*) Frame → {False, False, False, True},
  FrameTicks → {None, None, None, {0, 0.5, 1}},
  FrameStyle → {Automatic, Automatic, Automatic, Darker[Green]}]

```

(NewKern) Out[135]=



(NewKern) In[136]:=

```

adPlot = Overlay[{output, input}]
Export["scaffoldTitrationUnsaturatedVaringKAd.eps", adPlot];
Export["scaffoldTitrationUnsaturatedVaringKAd.pdf", adPlot];

```

(NewKern) Out[136]=

