SN54ALS374A, SN54AS374, SN74ALS374A, SN74AS374
OCTAL D-TYPE EDGE-TRIGGERED FLIP-FLOPS
WITH 3-STATE OUTPUTS

SDAS167C – APRIL 1982 – REVISED NOVEMBER 1999

- **D-Type Flip-Flops in a Single Package With 3-State Bus Driving True Outputs**
- **Full Parallel Access for Loading**
- **Buffered Control Inputs**
- **Package Options Include Plastic Small-Outline (DW) Packages, Ceramic Chip Carriers (FK), and Standard Plastic (N) and Ceramic (J) DIPs**

SN54ALS374A, SN54AS374 . . . J PACKAGE
SN74ALS374A, SN74AS374 . . . DW OR N PACKAGE
(TOP VIEW)

```
         _____
$\overline{OE}$ [ 1      20 ] V_CC
   1Q [ 2      19 ] 8Q
   1D [ 3      18 ] 8D
   2D [ 4      17 ] 7D
   2Q [ 5      16 ] 7Q
   3Q [ 6      15 ] 6Q
   3D [ 7      14 ] 6D
   4D [ 8      13 ] 5D
   4Q [ 9      12 ] 5Q
  GND [ 10     11 ] CLK
```

SN54ALS374A, SN54AS374 . . . FK PACKAGE
(TOP VIEW)

```
        1D  1Q  OE  VCC  8Q
         3   2   1  20  19
   2D [ 4            18 ] 8D
   2Q [ 5            17 ] 7D
   3Q [ 6            16 ] 7Q
   3D [ 7            15 ] 6Q
   4D [ 8            14 ] 6D
         9  10  11  12  13
        4Q  GND CLK 5Q  5D
```

description

These octal D-type edge-triggered flip-flops feature 3-state outputs designed specifically for driving highly capacitive or relatively low-impedance loads. They are particularly suitable for implementing buffer registers, I/O ports, bidirectional bus drivers, and working registers.

On the positive transition of the clock (CLK) input, the Q outputs are set to the logic levels set up at the data (D) inputs.

A buffered output-enable ($\overline{OE}$) input places the eight outputs in either a normal logic state (high or low logic levels) or the high-impedance state. In the high-impedance state, the outputs neither load nor drive the bus lines significantly. The high-impedance state and the increased drive provide the capability to drive bus lines without interface or pullup components.

$\overline{OE}$ does not affect internal operations of the flip-flops. Old data can be retained or new data can be entered while the outputs are in the high-impedance state.

The SN54ALS374A and SN54AS374 are characterized for operation over the full military temperature range of –55°C to 125°C. The SN74ALS374A and SN74AS374 are characterized for operation from 0°C to 70°C.

FUNCTION TABLE
(each flip-flop)

INPUTS			OUTPUT
$\overline{OE}$	CLK	D	Q
L	↑	H	H
L	↑	L	L
L	H or L	X	Q_0
H	X	X	Z

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

TEXAS INSTRUMENTS

POST OFFICE BOX 655303 • DALLAS, TEXAS 75265

logic symbol†

logic diagram (positive logic)

To Seven Other Channels

† This symbol is in accordance with ANSI/IEEE Std 91-1984 and
  IEC Publication 617-12.

absolute maximum ratings over operating free-air temperature range (unless otherwise noted)‡

Supply voltage range, V_{CC} .... –0.5 V to 7 V
Input voltage range, V_I .... –0.5 V to 7 V
Voltage applied to a disabled 3-state output .... –0.5 V to 5.5 V
Package thermal impedance, θ_{JA} (see Note 1): DW package .... 58°C/W
                                            N package .... 69°C/W
Storage temperature range, T_{stg} .... –65°C to 150°C

‡ Stresses beyond those listed under "absolute maximum ratings" may cause permanent damage to the device. These are stress ratings only, and
  functional operation of the device at these or any other conditions beyond those indicated under "recommended operating conditions" is not
  implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.
NOTE 1:   The package thermal impedance is calculated in accordance with JESD 51.

recommended operating conditions

		SN54ALS374A			SN74ALS374A			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.7			0.8	V
I_{OH}	High-level output current			–1			–2.6	mA
I_{OL}	Low-level output current			12			24	mA
T_A	Operating free-air temperature	–55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER	TEST CONDITIONS		SN54ALS374A			SN74ALS374A			UNIT
			MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}	$V_{CC} = 4.5$ V,	$I_I = -18$ mA			−1.5			−1.5	V
V_{OH}	$V_{CC} = 4.5$ V to 5.5 V,	$I_{OH} = -0.4$ mA	V_{CC}−2			V_{CC}−2			V
	$V_{CC} = 4.5$ V	$I_{OH} = -1$ mA	2.4	3.3					
		$I_{OH} = -2.6$ mA				2.4	3.2		
V_{OL}	$V_{CC} = 4.5$ V	$I_{OL} = 12$ mA		0.25	0.4		0.25	0.4	V
		$I_{OL} = 24$ mA					0.35	0.5	
I_{OZH}	$V_{CC} = 5.5$ V,	$V_O = 2.7$ V			20			20	µA
I_{OZL}	$V_{CC} = 5.5$ V,	$V_O = 0.4$ V			−20			−20	µA
I_I	$V_{CC} = 5.5$ V,	$V_I = 7$ V			0.1			0.1	mA
I_{IH}	$V_{CC} = 5.5$ V,	$V_I = 2.7$ V			20			20	µA
I_{IL}	$V_{CC} = 5.5$ V,	$V_I = 0.4$ V			−0.2			−0.2	mA
I_O‡	$V_{CC} = 5.5$ V,	$V_O = 2.25$ V	−20		−112	−30		−112	mA
I_{CC}	$V_{CC} = 5.5$ V	Outputs high		11	20		11	19	mA
		Outputs low		19	28		19	28	
		Outputs disabled		20	31		20	31	

† All typical values are at $V_{CC} = 5$ V, $T_A = 25°C$.
‡ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

timing requirements over recommended operating free-air temperature range (unless otherwise noted)

			SN54ALS374A		SN74ALS374A		UNIT
			MIN	MAX	MIN	MAX	
f_{clock}	Clock frequency			30		35	MHz
t_w	Pulse duration	CLK high or low	16.5		14		ns
t_{su}	Setup time	Data before CLK↑	10		10		ns
t_h	Hold time	Data after CLK↑	4		0		ns

switching characteristics over recommended operating conditions (unless otherwise noted (see Figure 3)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	SN54ALS374A		SN74ALS374A		UNIT
			MIN	MAX	MIN	MAX	
f_{max}			30		35		MHz
t_{PLH}	CLK	Q	3	14	3	12	ns
t_{PHL}			5	17	5	16	
t_{PZH}	$\overline{OE}$	Q	3	18	3	17	ns
t_{PZL}			5	21	5	18	
t_{PHZ}	$\overline{OE}$	Q	1	11	1	10	ns
t_{PLZ}			2	19	2	18	

recommended operating conditions

		SN54AS374			SN74AS374			UNIT
		MIN	NOM	MAX	MIN	NOM	MAX	
V_{CC}	Supply voltage	4.5	5	5.5	4.5	5	5.5	V
V_{IH}	High-level input voltage	2			2			V
V_{IL}	Low-level input voltage			0.7			0.8	V
I_{OH}	High-level output current			−12			−15	mA
I_{OL}	Low-level output current			32			48	mA
T_A	Operating free-air temperature	−55		125	0		70	°C

electrical characteristics over recommended operating free-air temperature range (unless otherwise noted)

PARAMETER		TEST CONDITIONS		SN54AS374			SN74AS374			UNIT
				MIN	TYP†	MAX	MIN	TYP†	MAX	
V_{IK}		V_{CC} = 4.5 V,	I_I = −18 mA			−1.2			−1.2	V
V_{OH}		V_{CC} = 4.5 V to 5.5 V,	I_{OH} = −2 mA	V_{CC}−2			V_{CC}−2			V
		V_{CC} = 4.5 V	I_{OH} = −12 mA	2.4	3.2					
			I_{OH} = −15 mA				2.4	3.3		
V_{OL}		V_{CC} = 4.5 V	I_{OL} = 32 mA		0.29	0.5				V
			I_{OL} = 48 mA					0.34	0.5	
I_{OZH}		V_{CC} = 5.5 V,	V_O = 2.7 V			50			50	µA
I_{OZL}		V_{CC} = 5.5 V,	V_O = 0.4 V			−50			−50	µA
I_I		V_{CC} = 5.5 V,	V_I = 7 V			0.1			0.1	mA
I_{IH}		V_{CC} = 5.5 V,	V_I = 2.7 V			20			20	µA
I_{IL}	$\overline{OE}$, CLK	V_{CC} = 5.5 V,	V_I = 0.4 V			−0.5			−0.5	mA
	Data					−3			−2	
I_O‡		V_{CC} = 5.5 V,	V_O = 2.25 V	−30		−112	−30		−112	mA
I_{CC}		V_{CC} = 5.5 V	Outputs high		77	120		77	120	mA
			Outputs low		84	128		84	128	
			Outputs disabled		84	128		84	128	

† All typical values are at V_{CC} = 5 V, T_A = 25°C.

‡ The output conditions have been chosen to produce a current that closely approximates one half of the true short-circuit output current, I_{OS}.

timing requirements over recommended operating free-air temperature range (unless otherwise noted)

			SN54AS374		SN74AS374		UNIT
			MIN	MAX	MIN	MAX	
f_{clock}	Clock frequency			100*		125	MHz
t_w	Pulse duration	CLK high	5.5*		4		ns
		CLK low	3*		3		
t_{su}	Setup time	Data before CLK↑	3*		2		ns
t_h	Hold time	Data after CLK↑	3*		2		ns

* On products compliant to MIL-PRF-38535, this parameter is not production tested.

SN54ALS374A, SN54AS374, SN74ALS374A, SN74AS374
OCTAL D-TYPE EDGE-TRIGGERED FLIP-FLOPS
WITH 3-STATE OUTPUTS
SDAS167C – APRIL 1982 – REVISED NOVEMBER 1999

switching characteristics over recommended operating conditions (unless otherwise noted) (see Figure 3)

PARAMETER	FROM (INPUT)	TO (OUTPUT)	SN54AS374		SN74AS374		UNIT
			MIN	MAX	MIN	MAX	
f_{max}			100*		125		MHz
t_{PLH}	CLK	Q	3	11	3	8	ns
t_{PHL}			4	11.5	4	9	
t_{PZH}	$\overline{OE}$	Q	2	7	2	6	ns
t_{PZL}			3	11	3	10	
t_{PHZ}	$\overline{OE}$	Q	2	10	2	6	ns
t_{PLZ}			2	7	2	6	

* On products compliant to MIL-PRF-38535, this parameter is not production tested.

SN54ALS374A, SN54AS374, SN74ALS374A, SN74AS374
OCTAL D-TYPE EDGE-TRIGGERED FLIP-FLOPS
WITH 3-STATE OUTPUTS
SDAS167C – APRIL 1982 – REVISED NOVEMBER 1999

APPLICATION INFORMATION

Figure 1. Expandable 4-Word by 8-Bit General File Register

APPLICATION INFORMATION

SN54ALS374A,
SN74ALS374A,
or 'AS374

Output Enable 1 — EN

Clock 1 — C1

1D

Bidirectional
Data Bus 1

Bidirectional
Data Bus 2

SN54ALS374A,
SN74ALS374A,
or 'AS374

Output Enable 2 — EN

Clock 2 — C1

1D

Clock 1   H

Bus-Exchange
Clock

Clock 2   H

Clock Circuit for Bus Exchange

Figure 2. Bidirectional Bus Driver

PARAMETER MEASUREMENT INFORMATION
SERIES 54ALS/74ALS AND 54AS/74AS DEVICES

**LOAD CIRCUIT FOR
BI-STATE TOTEM-POLE OUTPUTS**

**LOAD CIRCUIT FOR
OPEN-COLLECTOR OUTPUTS**

**LOAD CIRCUIT FOR
3-STATE OUTPUTS**

**VOLTAGE WAVEFORMS
SETUP AND HOLD TIMES**

**VOLTAGE WAVEFORMS
PULSE DURATIONS**

**VOLTAGE WAVEFORMS
ENABLE AND DISABLE TIMES, 3-STATE OUTPUTS**

**VOLTAGE WAVEFORMS
PROPAGATION DELAY TIMES**

NOTES: A. C_L includes probe and jig capacitance.
B. Waveform 1 is for an output with internal conditions such that the output is low except when disabled by the output control.
Waveform 2 is for an output with internal conditions such that the output is high except when disabled by the output control.
C. When measuring propagation delay items of 3-state outputs, switch S1 is open.
D. All input pulses have the following characteristics: PRR ≤ 1 MHz, $t_r = t_f = 2$ ns, duty cycle = 50%.
E. The outputs are measured one at a time with one transition per measurement.

Figure 3. Load Circuits and Voltage Waveforms

TEXAS
INSTRUMENTS

IMPORTANT NOTICE

Texas Instruments and its subsidiaries (TI) reserve the right to make changes to their products or to discontinue any product or service without notice, and advise customers to obtain the latest version of relevant information to verify, before placing orders, that information being relied on is current and complete. All products are sold subject to the terms and conditions of sale supplied at the time of order acknowledgement, including those pertaining to warranty, patent infringement, and limitation of liability.

TI warrants performance of its semiconductor products to the specifications applicable at the time of sale in accordance with TI's standard warranty. Testing and other quality control techniques are utilized to the extent TI deems necessary to support this warranty. Specific testing of all parameters of each device is not necessarily performed, except those mandated by government requirements.

CERTAIN APPLICATIONS USING SEMICONDUCTOR PRODUCTS MAY INVOLVE POTENTIAL RISKS OF DEATH, PERSONAL INJURY, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE ("CRITICAL APPLICATIONS"). TI SEMICONDUCTOR PRODUCTS ARE NOT DESIGNED, AUTHORIZED, OR WARRANTED TO BE SUITABLE FOR USE IN LIFE-SUPPORT DEVICES OR SYSTEMS OR OTHER CRITICAL APPLICATIONS. INCLUSION OF TI PRODUCTS IN SUCH APPLICATIONS IS UNDERSTOOD TO BE FULLY AT THE CUSTOMER'S RISK.

In order to minimize risks associated with the customer's applications, adequate design and operating safeguards must be provided by the customer to minimize inherent or procedural hazards.

TI assumes no liability for applications assistance or customer product design. TI does not warrant or represent that any license, either express or implied, is granted under any patent right, copyright, mask work right, or other intellectual property right of TI covering or relating to any combination, machine, or process in which such semiconductor products or services might be or are used. TI's publication of information regarding any third party's products or services does not constitute TI's approval, warranty or endorsement thereof.