OSURC Rover 2015 Electrical Box Connector Wiring

Nick Ames

Revision 3, 2015-03-17

1 Connector Pinouts

1.1 Drive Motors, E-Stop, and Lights

Jack, Solder Side

Cable, Solder Side

Pin #	Wire Color	Name	Description
1	⬛	-	Negative or Motor Black
2	🟥	+	Positive or Motor Red

Figure 1: Drive Motors, E-Stop, and Lights

1.2 Main Power Input

Jack, Solder Side

Cable, Solder Side

Pin #	Wire Color	Name	Description
1	⬛	-	Gnd
2	⬛	-	Gnd
3	🟥	+	24V In
4	🟥	+	24V In

Figure 2: Gimbal Sensor

1.3 Gimbal Sensor

Jack, Solder Side

Cable, Solder Side

Pin #	Wire Color	Name	Description
1	⬛	Gnd	Gnd
2	🟥	5V	5V
3		SCL	I2C Clock
4	🟨	SDA	I2C Data

Figure 3: Gimbal Sensor

1.4 Arm Force Sensors

Jack, Solder Side

Cable, Solder Side

Pin #	Wire Color	Name	Description
1		F1	Force Ch. 1
2		F2	Force Ch. 2
3		F3	Force Ch. 3
4		F4	Force Ch. 4
5		Gnd	Gnd
Note: Use 6-conductor cable.			

Figure 4: Arm Force Sensors

1.5 Arm Stepper Motors

Jack, Solder Side

Cable, Solder Side

Pin #	Wire Color	Name	Description
1		A1	Coil A-1
2		A2	Coil A-2
3		Gnd	Gnd
4		B2	Coil B-2
5		B1	Coil B-1
6		Limit	Limit Switch
Note: The limit connection is to the NC pin.			
Match stepper wire colors to cable wire colors.			

Figure 5: Arm Stepper Motors

1.6 Gimbal Motors

Jack, Solder Side

Cable, Solder Side

Pin #	Wire Color	Name	Description
1		P1	Pitch 1
2		P2	Pitch 2
3		P3	Pitch 3
4		Y3	Yaw 3
5		R3	Roll 3
6		R2	Roll 2
7		R1	Roll 1
8		Y2	Yaw 2
9		Y1	Yaw 1

Figure 6: Gimbal Motors