OTP and AES: A Historical Transition Between two Systems of Cryptography

Valdemar Thanner Supervised by Mr. Bernhard Keller Linguistic supervision by Ms. Margrit Oetiker


Kantonsschule Zug


06.03.2017


OTP: The One Time Pad


AES: The Advanced Encryption Standard


AES: High-Level Structure











AES: SubBytes

AES: ShiftRows

$$\begin{pmatrix} a_{0,0} & a_{0,1} & a_{0,2} & a_{0,3} \\ a_{1,0} & a_{1,1} & a_{1,2} & a_{1,3} \\ a_{2,0} & a_{2,1} & a_{2,2} & a_{2,3} \\ a_{3,0} & a_{3,1} & a_{3,2} & a_{3,3} \end{pmatrix} \xrightarrow{\text{ShiftRows}} \begin{pmatrix} a_{0,0} & a_{0,1} & a_{0,2} & a_{0,3} \\ a_{1,1} & a_{1,2} & a_{1,3} & a_{1,0} \\ a_{2,2} & a_{2,3} & a_{2,0} & a_{2,1} \\ a_{3,3} & a_{3,0} & a_{3,1} & a_{3,2} \end{pmatrix}$$

AES: MixColumns

$$\begin{pmatrix} 02 & 03 & 01 & 01 \\ 01 & 02 & 03 & 01 \\ 01 & 01 & 02 & 03 \\ 03 & 01 & 01 & 02 \end{pmatrix} \cdot \begin{pmatrix} a_0 \\ a_1 \\ a_2 \\ a_3 \end{pmatrix} = \begin{pmatrix} s_0 \\ s_1 \\ s_2 \\ s_3 \end{pmatrix}$$

AES: MixColumns

$$\begin{pmatrix} 02 & 03 & 01 & 01 \\ 01 & 02 & 03 & 01 \\ 01 & 01 & 02 & 03 \\ 03 & 01 & 01 & 02 \end{pmatrix} \cdot \begin{pmatrix} a_0 \\ a_1 \\ a_2 \\ a_3 \end{pmatrix} = \begin{pmatrix} s_0 \\ s_1 \\ s_2 \\ s_3 \end{pmatrix}$$

$$s_0 = 02a_0 + 03a_1 + 01a_2 + 01a_3$$

 $s_1 = 01a_0 + 02a_1 + 03a_2 + 01a_3$
 $s_2 = 01a_0 + 01a_1 + 02a_2 + 03a_3$
 $s_3 = 03a_0 + 01a_1 + 01a_2 + 02a_3$

AES: AddRoundKey