

Torus amplitudes and modular invariance

Otto T.P. Schmidt

Seminar on Theoretical Physics



Outline

1. Motivation
2. The moduli space of tori
 - One-loop open strings
 - Rectangular tori
 - General tori
3. Torus partition function
4. Modular invariance
5. URLs and links

Outline

1. Motivation

2. The moduli space of tori

One-loop open strings

Rectangular tori

General tori

3. Torus partition function

4. Modular invariance

5. URLs and links

Interactions and observables

In the study of string interactions, the ultimate goal will be the assignment of a probability for a certain process and the prediction of a physical cross section.


As outlined in Section 22, the computation of an observable cross section involves a series of steps:

1. Canonical representation of string diagram through moduli space
2. Compute scattering amplitude by means of conformal field theory
3. Convert scattering amplitude into a cross section

Loop amplitudes in string theory

In order to obtain accurate scattering amplitudes of processes, one needs to include contributions from loops in string diagrams.

These loops can be seen as contributions from the next higher order perturbation. Graphically we consider the following processes:



Ultraviolet divergence

Amplitudes from virtual processes as depicted before can lead to ultraviolet (UV) divergences in quantum field theory (QFT).

Whereas QFT must employ complex renormalizations to deal with these UV divergences, we do not encounter these problems in string theory.

Outline

1. Motivation

2. The moduli space of tori

One-loop open strings

Rectangular tori

General tori

3. Torus partition function


4. Modular invariance

5. URLs and links

One-loop open strings

Before approaching the moduli space of tori, let's consider a one-loop open string with light-cone momentum p^+ . This will serve as an intuitive analogon.

The light-cone diagram is:






For fixed external momentum p^+ we find the two parameters: $\Delta T \in (0, \infty)$ and $p_1^+ \in (0, p^+)$.
→ The class of Riemann surfaces of this process has two moduli.

Canonical annulus

Use $w = \tau + i\sigma$ and apply conformal transformations:

1. Exponential map: $z = \exp\left[\frac{w}{2\alpha' p^+}\right]$
2. Linear fractional transformation: $\eta = \frac{1+iz}{1-iz}$
3. Canonical annulus: *A region in \mathbb{C} that is topologically an annulus can be mapped conformally to a canonical annulus*






Rectangular tori

In order to apply the concept of moduli spaces to a torus, we need to assure that a torus is indeed a Riemann surface.

Consider a rectangular region of \mathbb{C} . By applying the analytic identifications $z \sim z + L_1$ and $z \sim z + iL_2$ we obtain a torus. This shows that the region remains a Riemann surface.

Graphically:



Parametrisation

We have:

Rectangular torus

$$z \sim z + L_1 \text{ and } z \sim z + iL_2$$

By applying $z' = \frac{z}{L_1}$ the identifications become:


Torus parameter T

$$z' \sim z' + 1 \text{ and } z' \sim z' + iT \text{ with } T = \frac{L_2}{L_1}$$

Ultraviolet divergence

T is a parameter of the torus but does not yet define the moduli space, i.e. tori with different T can be conformally equivalent.

Consider the following series of conformal maps to a rectangular torus with $T < 1$:



Rectangular torus

Tori with T and $\frac{1}{T}$ are conformally equivalent

→ The moduli space can be chosen to be $T \in (0, 1]$ or $T \in [1, \infty)$

General tori

Rectangular tori represent only a subset off all conformally inequivalent tori. Let's construct a more general class of tori:


General construction of a torus Riemann surface

Choose $\omega_1, \omega_2 \in \mathbb{C}$ with $\Im(\frac{\omega_1}{\omega_2})$.

A torus is obtained by the indentifications $z \sim z + \omega_1$ and $z \sim z + \omega_2$.

By scaling we obtain $z \sim z + 1$ and $z \sim z + \tau$ with $\tau = \frac{\omega_2}{\omega_1}$, $\Im(\tau) > 0$.

→ Note that for $\tau = iT$ ($\Leftrightarrow \Re(\tau) = 0$) we consider the rectangular torus.




Twisting the torus

Intuitively, if a cylinder is twisted and the end surfaces are connected, we expect a different torus.

Formally: Consider $\Re(\tau) \neq 0$ and a point $P = 0 = \tau$. We can reconstruct the rectangular *fundamental domain* by using the identification $z \sim z + 1$.

Graphically:



Twisting parameter

The point P is no longer identified with a point on the perpendicular. Indeed the degree of twisting is parametrised by $\theta = 2\pi\Re(\tau)$. How does θ affect the torus parameter τ ?

Consider the map $\tau \rightarrow \tau + 1$

Colors

You need to pick these colors

- `titlefgcolor` (the box on the title page)
- `titlebgcolor` (the background on the title page, in case you don't use an image)
- `accentcolor` (alert text, blocks)

Use these commands at the beginning of the document

```
\colorlet{titlefgcolor}{ETHblue}  
\colorlet{titlebgcolor}{ETHblue!60!black} % Use only multiples of 20%  
\colorlet{accentcolor}{ETHred}
```



Old ETH colors (ETH1, ..., ETH9) are deprecated and should not be used.
They are available as `oldETH1`, ..., `oldETH9` for backward compatibility.

Title

Subtitle

Text and some **alert text**

$$m_a^\top h(\cdot)$$

- list one
- list another one
 - test 1
 - test 2

Outline

1. Motivation
2. The moduli space of tori
 - One-loop open strings
 - Rectangular tori
 - General tori
3. Torus partition function
4. Modular invariance
5. URLs and links

Title with no subtitle

Large box

Notice that blocks are a bit larger than the text, that's intended.

Column environments also eat some margins. Use the option `[onlytextwidth]` if you want to align columns to the wide blocks.

Small box




With some more text

Think outside the box!

Outline

1. Motivation
2. The moduli space of tori
 - One-loop open strings
 - Rectangular tori
 - General tori
3. Torus partition function
4. Modular invariance
5. URLs and links

And, of course, figures!



Free overlay

The package `textpos` is also enabled in case you want to overlay content freely in the slide.

This text is located at position (1,3):

```
\begin{textblock}{3}(1,3) ... \end{textblock}
```

(1 unit equals to the left text margin)



The upper left corner of this image is at the slide center point:

```
\begin{textblock*}{40mm}(0.5\paperwidth,0.5\paperheight)
```

```
\includegraphics[width=20mm]{example-image-a}
```

```
\end{textblock*}
```

Tables

Don't use vanilla L^AT_EX tables please

Item		
Animal	Description	Price (\$)
Gnat	per gram	13.65
	each	0.01
Gnu	stuffed	92.50
Emu	stuffed	33.33
Armadillo	frozen	8.99

Outline

1. Motivation
2. The moduli space of tori
 - One-loop open strings
 - Rectangular tori
 - General tori
3. Torus partition function
4. Modular invariance
5. URLs and links

Clickable links

Lorem ipsum dolor sit amet, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation...

<http://control.ee.ethz.ch>

Automatic Control Laboratory 
name@ethz.ch

Professor John Doe

Role of person giving presentation

beat.muster@abcd.ethz.ch

ETH Zurich

Organisational unit

Building Room

Street House number

0000 Town, Country

<http://www.abcd.ethz.ch>

You can edit the content of the `closingframe` environment to design your own closing frame. Example:



Author name
name@ethz.ch