Лабораторная работа №9

Задание 1

```
A = [-7 0 0 0;
0 3 0 0;
0 0 2 7;
0 0 -7 2]
```

```
B = [0; 7; 0; 6]
```

```
B = 4×1
0
7
0
6
```

Определяем собственные числа

eig(A)

```
ans = 4×1 complex

2.0000 + 7.0000i

2.0000 - 7.0000i

-7.0000 + 0.0000i

3.0000 + 0.0000i
```

Выберем различные значения желаемой степени устойчивости α

```
a_1 = 7
```

 $a_1 = 7$

 $a_2 = 2$

 $a_3 = 0.0500$

Далее решаем неравенства Ляпунова

```
x_0 = [1; 1; 1; 1]
```

```
x_0 = 4×1
1
1
1
```

```
%m = 2500

cvx_begin sdp
```

```
variable Q(4, 4)
variable Y(4, 2)
variable P(4, 4)
variable Y1(1, 4)
%variable m
%minimize m
%Q > 0.00001*eye(4);
P > 0.00001*eye(4);
Warning: The use of strict inequalities in CVX is strongly discouraged,
   because solvers treat them as non-strict inequalities. Please
    consider using ">=" instead.
Warning: This linear matrix inequality appears to be unsymmetric. This is
very likely an error that will produce unexpected results. Please check
the LMI; and, if necessary, re-enter the model.
%A'*Q + Q*A + 2*a 3*Q + C'*Y'+Y*C <= 0;
P*A' + A*P + 2*a_1*P + Y1'*B' + B*Y1 <= 0;
Warning: This linear matrix inequality appears to be unsymmetric. This is
very likely an error that will produce unexpected results. Please check
the LMI; and, if necessary, re-enter the model.
%[P x_0;
    \times 0' 1] > 0;
%[P Y';
     Y m] > 0;
cvx_end
Calling SDPT3 4.0: 44 variables, 8 equality constraints
 num. of constraints = 8
 dim. of sdp var = 8, num. of sdp blk = 2
 dim. of free var = 24 *** convert ublk to lblk
 number of nearly dependent constraints = 1
 To remove these constraints, re-run sqlp.m with OPTIONS.rmdepconstr = 1.
  SDPT3: Infeasible path-following algorithms
**************
 version predcorr gam expon scale_data
  HKM 1 0.000 1 0
it pstep dstep pinfeas dinfeas gap
                                      prim-obj
                                                  dual-obj cputime
 0|0.000|0.000|3.9e+02|3.4e+02|1.1e+05| 0.000000e+00 0.000000e+00| 0:0:00| chol 1 1
 1|0.953|0.933|1.9e+01|2.3e+01|1.6e+03| 0.000000e+00 6.696852e-04| 0:0:00| chol 1 1
 2|0.934|0.753|1.2e+00|5.7e+00|1.3e+02| 0.000000e+00 6.873988e-04| 0:0:00| chol 1 1
 3|0.976|0.963|3.0e-02|2.1e-01|2.1e+00| 0.000000e+00 3.519687e-05| 0:0:00| chol 1 1
 4|0.988|0.989|3.4e-04|2.4e-03|1.8e-02| 0.000000e+00 4.100499e-07| 0:0:00| chol 1 1
 5|0.989|0.993|3.0e-06|2.9e-05|2.6e-04| 0.000000e+00 4.851690e-09| 0:0:00| chol 1 1
 6|0.989|1.000|1.9e-08|1.6e-05|1.2e-05| 0.000000e+00 1.802595e-10| 0:0:00| chol 1 1
 7|1.000|0.988|5.1e-10|7.3e-07|1.6e-07| 0.000000e+00 2.237131e-12| 0:0:00| chol 1 1
 8|1.000|0.988|3.8e-12|9.8e-09|2.1e-09| 0.000000e+00 2.830639e-14| 0:0:00|
 stop: max(relative gap, infeasibilities) < 1.49e-08</pre>
 number of iterations = 8
 primal objective value = 0.00000000e+00
 dual objective value = 2.83063876e-14
gap := trace(XZ) = 2.05e-09
relative gap = 2.05e-09
```

```
actual relative gap = -2.83e-14
rel. primal infeas (scaled problem) = 3.84e-12
rel. dual
                                   = 9.78e-09
rel. primal infeas (unscaled problem) = 0.00e+00
                   " = 0.00e+00
rel. dual
norm(X), norm(y), norm(Z) = 4.2e+01, 2.8e+01, 2.8e+01
norm(A), norm(b), norm(C) = 5.0e+01, 1.0e+00, 1.0e+00
Total CPU time (secs) = 0.25
CPU time per iteration = 0.03
termination code = 0
DIMACS: 3.8e-12 0.0e+00 9.8e-09 0.0e+00 -2.8e-14 2.1e-09
Status: Solved
Optimal value (cvx_optval): +0
%m
```

И находим матриу реглятора К:

```
K = Y1*inv(P)

K = 1×4
    0.0000 -17.7356 -16.0240 14.3722

%L = inv(Q)*Y
```

Далее определим корни матрицы А+ВК:

```
%LC = eig(A+L*C)
BK = eig(A+B*K)
```

BK = 4×1 complex -11.4979 +18.9272i -11.4979 -18.9272i -7.9204 + 0.0000i -7.0000 + 0.0000i