Задание

Лаб 3. Вы синтезировали регулятор контура тока. Как изменится настройка системы управления, если датчик тока тоже будет измерять ток в мА. Привести формулы для вычисления новых коэффициентов регулятора и графики переходных процессов

Определяем вариант задания:

```
ob.R = 10+unifrnd(-1,1);
ob.L = 0.02+unifrnd(-0.01,0.01);
ob.J = 100+unifrnd(-10,10);
ob.Ce = 2;
ob.Cm = ob.Ce;
save('data.mat', 'ob');
```

```
syms Tu L R s
```

Передаточная функция электрической части привода постоянного тока

```
crl.Wob = (1/(L*s+R))/1000;
```

Передаточная функция разомкнутой системы, настроенной на технический оптиум

```
Tu = L/R;
crl.Wol = 1/(2*Tu*s*(Tu*s+1))

crl = struct with fields:
    Wob: 1/(1000*(R + L*s))
    Wol: R/(2*L*s*((L*s)/R + 1))
        Tu: 0.0033
    Kia: 1.4541e+06
    Kid: 1.4541e+06
    Tz: 0.0011
```

передаточная функция регулятора

```
Wreg = crl.Wol/(crl.Wob);
disp(collect(Wreg, s))
```

```
\frac{500 R^2}{L s}
```

```
crl.Tu = ob.L/ob.R;
crl.Kia = 500*ob.R/(crl.Tu);
crl.Kid = crl.Kia;
Tmdl = 0.04;
To=0.1*crl.Tu;
```

Аппроксимация

```
for i = 1:10
```

```
crl.Tz=i/10*To;
Tzap(i) = crl.Tz;
warning off
warning off
Simnew = sim('lab3_3_extra.slx','ReturnWorkspaceOutputs', 'on');
warning on


t = Simnew.ia(:,1);
ia = Simnew.ia(:,3);
id = Simnew.ia(:,4);
f(i)=trapz(t,abs(id-ia));
end
```

```
Found algebraic loop containing:
lab3_3_extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL_KEY/RESHAPE
lab3_3_extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3 3 extra/Gain2
lab3 3 extra/Gain4
lab3 3 extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3 3 extra/ob1/DC motor/PS-Simulink Converter/EVAL KEY/RESHAPE
lab3_3_extra/ADC
lab3 3 extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3_3_extra/Gain2
lab3 3 extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL_KEY/RESHAPE
lab3_3_extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3 3 extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL_KEY/RESHAPE
lab3_3_extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3_3_extra/Gain2
lab3_3_extra/Gain4
```

```
lab3_3_extra/I tr/Gain6
lab3 3 extra/I tr/Sum2
lab3 3 extra/I tr/Gain5
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL KEY/INPUT 1 1 1
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL KEY/OUTPUT 1 0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL_KEY/RESHAPE
lab3 3 extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3_3_extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3 3 extra/I tr/Gain5
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3 3 extra/ob1/DC motor/PS-Simulink Converter/EVAL KEY/RESHAPE
lab3 3 extra/ADC
lab3 3 extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3_3_extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL KEY/INPUT 1 1 1
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL KEY/OUTPUT 1 0
lab3 3 extra/ob1/DC motor/PS-Simulink Converter/EVAL KEY/RESHAPE
lab3 3 extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3 3 extra/Gain2
lab3_3_extra/Gain4
lab3 3 extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3 3 extra/ob1/DC motor/PS-Simulink Converter/EVAL KEY/RESHAPE
lab3 3 extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3_3_extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
lab3_3_extra/I tr/Gain5
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL KEY/OUTPUT 1 0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL KEY/RESHAPE
lab3_3_extra/ADC
lab3 3 extra/Sum1 (algebraic variable)
Found algebraic loop containing:
lab3 3 extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3 3 extra/I tr/Sum2
lab3 3 extra/I tr/Gain5
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL KEY/INPUT 1 1 1
lab3 3 extra/ob1/DC motor/Solver Configuration/EVAL KEY/OUTPUT 1 0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL_KEY/RESHAPE
lab3 3 extra/ADC
lab3_3_extra/Sum1 (algebraic variable)
```

```
h=figure;
set(h,'DefaultAxesFontSize', 12, 'DefaultAxesFontName','Times New Roman');

plot(Tzap/To,f,'Linewidth', 1)
hold on
grid on
xlabel('\it T_{zap}/T_o')
ylabel('\it f')
```



Перенастройка с помощью метода переоборудования

```
Tmdl = 0.05;
To=1*ob.L/ob.R;
crl.Tz = 0.5*To;
crl.Tu = ob.L/ob.R + crl.Tz

crl = struct with fields:
    Wob: 1/(1000*(R + L*s))
    Wol: R/(2*L*s*((L*s)/R + 1))
    Tu: 0.0018
    Kia: 4.5414e+06
    Kid: 4.5414e+06
    Tz: 6.0167e-04
```

```
crl.Kia = 500*ob.R/(crl.Tu);
```

```
crl.Kid = crl.Kia;
warning off
simNew = sim('lab3_3_extra.slx', 'ReturnWorkspaceOutputs','on');


Found algebraic loop containing:
lab3_3_extra/Gain2
lab3_3_extra/Gain4
lab3_3_extra/I tr/Gain6
lab3_3_extra/I tr/Sum2
```

lab3_3_extra/I tr/Gain5

lab3 3 extra/ADC

lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/INPUT_1_1_1
lab3_3_extra/ob1/DC motor/Solver Configuration/EVAL_KEY/OUTPUT_1_0
lab3_3_extra/ob1/DC motor/PS-Simulink Converter/EVAL_KEY/RESHAPE

```
lab3_3_extra/Sum1 (algebraic variable)
warning on
t = simNew.ia(:,1);
iref = simNew.ia(:,2);
ia = simNew.ia(:,3);
id = simNew.ia(:,4);
h=figure;
set(h, 'DefaultAxesFontSize', 12, 'DefaultAxesFontName', 'Times New Roman');
plot(t,iref,'Linewidth', 1)
hold on
grid on
plot(t,ia,'Linewidth', 1)
plot(t,id,'Linewidth', 1)
xlabel('\it t,\rm \it s')
ylabel('\it i \rm, \it A')
legend('\it i_{ref}', '\it i_a', '\it i_d', 'Location', 'best')
```



Время переходного процесса для входа tp1 в 5% зону

```
t0 = t(1);
y = id;
y0 = id(1);
yss = id(end);
D5 = 0.05*abs(yss-y0);
ind = abs(y-yss)<D5;
tn = t(ind);
t_tr = tn(1)-t0;
fprintf('Время переходного процесса tp1 в 5%% зоны: %.1f*Tu \n', t_tr/crl.Tu)
```

Время переходного процесса tp1 в 5% зоны: 3.4*Tu

Время переходного процесса для входа tp2 в 5% зону

```
t0 = t(1);
y = id;
y0 = id(1);
yss = id(end);

D5 = 0.05*abs(yss-y0);
ind = abs(y-yss)>D5;
tn = t(ind);
t_tr = tn(end)-t0;
```

```
fprintf('Время переходного процесса tp2 в 5%% зоны: %.1f*Tu \n', t_tr/crl.Tu)
```

Время переходного процесса tp2 в 5% зоны: 5.7*Ти

Перерегулирование:

```
dy = abs(max(y)-yss)/abs(y0-yss);
fprintf('Перерегулирование: %.1f*Tu \n', dy*100)
```

Перерегулирование: 5.6*Ти