THE CUBING OF GULLIES USING 'GIS' METHODOLOGY, APPLIED TO A BADLAND IN SOUTH-EAST SPAIN.

C. CONESA-GARCÍA & F. LÓPEZ-BERMÚDEZ, MURCIA/SPAIN

SUMMARY

The analysis of three-dimensional forms constitutes one of the most simple and important techniques within the raster systems of geographical information in present use. In this way operations can be carried out relating to the calculation of volumes, which are very useful in geomorphology: the definition of polygons of different elevations to estimate their volumetric relationships, the determination of the volume included between the surfaces of two DTMs of identical references x, y, operations with the field factor (exploration law) and interpolation of topographical profiles. In the case of gullied areas or badlands, they offer a methodological solution suitable to the problem of quantifying the amount of material lost through hydric erosion, since the high concentration of sediment and the frequent mudslides make it difficult to obtain this data by the classic procedures (samplers of sediments in suspension, and bed material load, sediments boxes, erosion pins, metal rods, etc.). In this work a methodology is put forward, using the IDRISI software, for the cubing of gullies in a south-eastern Spain). Over the present DTM of this area a second one which has been deduced from the former is superimposed, representing the morphology previous to the start of gullying. With the resulting meshes and by means of "overlay" and "scalar" modules, maps of isodepths and degrees of excavation are drawn, at the same time as files of values of partial cubing are created. Finally, the geometry of the forms of incision is analysed, trying to establish correspondences between the types of profile and the geomorphic processes.

Key words: badlands, gully, semiarid, GIS, ephemeral channel.

ZUSAMMENFASSUNG

Die Analyse dreidimensionaler Oberflächenformen stellt eine der einfachsten, zugleich aber auch eine der wichtigsten Techniken dar, die im Rahmen systematischer, rasterbasierter Systeme geographischer Informationsgewinnung derzeit genutzt wird. Damit können für die Geomorphologie sehr nützliche Operationen zur Erfassung von Volumina durchgeführt werden. Dazu gehört die Bestimmung von Polygonen unterschiedlicher Höhenlagen zur Abschätzung ihrer Volumina, die Erfassung des Rauminhalts zwischen den Oberflächen von zwei DTM's mit identischen x,y-Werten, Operationen mit dem Feldfaktor (exploration-law) und die Interpolation topographischer Profile. In gullydurchsetzten Oberflächen oder Badlands eröffnen diese Methoden Lösungen zur Bilanzierung von Materialverlusten

CONCLUSIONS

Without being a GIS 3D, IDRISI, like the majority of the raster-based microcomputer GIS, which allow the analysis of DTM images, provides a very useful tool for the calculation of volumes, by means of its *analytical ring modules*. Its application to strongly eroded areas like badlands, to find the degree of excavation and cube the total soil loss corresponding to its gullies, constitutes a satisfactory solution in the morphological study of these areas of high erodibility where it might be complicated to carry out an experimental evaluation.

Again, the great detail found in DTM obtained from the digitalized cartographical basis (scale 1/100) allows a correct estimation of the volume of terrain dismantled, in each gully, from the beginning of the incision phase to be made, to know precisely the distribution of the excavation depths and to establish possible conjectures about the geometry of the badlands.

ACKNOWLEDGEMENTS

The authors are grateful for funding received enabling this work to be carried out, under the auspices of the National Plan of Research and Technical Development, the National Programme on Conservation of the Natural Heritage and Processes of Environmental Damage. Project AMB93-0844-C06-03.

REFERENCES

- BELCHER, R. C. & PARADIS, A. R. (1991): A mapping approach to three-dimensional modeling. In Turner, A.K. (ed.) *Three-Dimensional Modeling With Geo-Scientific Information Systems*, NATO ASI Series C: Mathematical and Physical Sciences, Vol. 354, Dordrecht: Kluwer Academic Publishers.
- CLARKE, K. C. (1986): Advances in Geographic information System. Computers, Environment and Urban Systems, 10: 175-184.
- CONESA GARCÍA, LÓPEZ BERMÚDEZ, F. & ALONSO SARRIA, F. (1994. Morfometría de grietas de retracción en un badland del sureste semiárido peninsular. In: Arnáez, J., García Ruiz, J.M. & Gómez Villar, A. (Eds), *Geomorfología en España*, Sociedad Española de Geomorfología, Zaragoza, pp. 41-54.
- COWEN, D. J. (1988): GIS versus CAD versus DBMS: What are the Differences?. Photogrametric Engineering & Remote Sensing, 54, 11: 1551-1555.
- EASTMAN, J. R. (1992): IDRISI (v.4.0), User's Guide. Clark University, Graduate School of Geography, Massachusetts, 178 p.
- FISHER, T. R. & WALLES, R. Q. (1991): Three-dimensional solid modelling of geo-objects using non-uniform rational B-splines. In Turner, A. K. (ed.) *Three-Dimensional Modelling With Geo-Scientific Information Systems*, NATO ASI Series C: Mathematical and Physical Sciences, Vol. 354, Dordrecht: Kluwer Academic Publishers.
- FISHER, T. R. (1993): Use of 3D Geographic Information Systems in Hazardous Waste Site Investigations. In Goodchild, M.F., Parks, B.O. & Steyaert, L.T. (eds.) *Environmental Modelling with GIS*, Oxford University Press, Oxford, pp. 238-247.
- FRIED, D. C. & LEONARD, J. E. (1990): Petroleum 3-D models come in many flavors. *Geobyte* 5(1): 27-30
- GARCIA, J P. & DE LA CRUZ, A.(1992): GIS tridimensional. La solución innovadora para las ciencias de la tierra. Los Sistemas de Información Geográfica en la Gestión Territorial, AESIGIT, Madrid, pp. 55-67.

- HARVEY, A. M. (1984): Aggradation and dissection sequences on Spanish alluvial fans: influence on morphological development. *Catena*,11: 289-304.
- KAVOURAS, M. (1987): A spatial information system for the geosciences. *PhD Dissertation*, Frederiction: University of New Brunswick.
- LÓPEZ BERMÚDEZ, F., ALONSO SARRIA, F., ROMERO DIAZ, M. A., CONESA GARCÍA, C., MARTÍNEZ FERNÁNDEZ, JOSÉ, MARTÍNEZ FERNÁNDEZ, JULIA, (1992): Caracterización y diseño del campo experimental de Los Guillermos (Murcia) para el estudio de los procesos de erosión y desertificación en litologías blandas. In: López Bermúdez, F., Conesa García, C. & Romero Díaz, M.A. (Eds) Estudios de Geomorfología en España, T.1, Sociedad Española de Geomorfología, Murcia, pp. 151-160.
- MALLET, J-L. (1991): Gocad: a computer aided design program for geological applications. In TURNER, A. K. (ed.) *Three-Dimensional Modeling With Geo-Scientific Information Systems*, NATO ASI Series C: Mathematical and Physical Sciences, Vol. 354, Dordrecht: Kluwer Academic Publishers.
- PURCELL, J. & VARBERG, D. (1987): Calculus with-Analytic Geometry, Prentice Hall, Mexico, pp. 683-704.
- SAMET, H. (1990): Applications of Spatial Data Structures, New York, Addison-Wesley.
- SMITH, D. R. & PARADIS, A. R. (1990): Three-Dimensional GIS for the Earth Sciences. GIL/LIS, pp. 324-335.

Eingang des Manuskripts: 11. 2. 2000 Annahme des Manuskripts: 15. 4. 2000

Adress of the authors:

C. Conesa-García, F. López-Bermúdez, Department of Physical Geography. University of Murcia, E-30001 Murcia, Spain