



OUTLIERS

FleetView: Every Agent Session, Live, on a Single Screen

A browser page showing every Claude Code session on your computer, grouped by your own folders, with the ones that asked you something named first

FOR MAC

PIECE 2 OF 4 • THE AGENT WORKSPACE

DOWNLOAD

<https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac>

EST. MMXXVI • OUTLIERS ACCELERATOR

What it is


FleetView is a single browser page that shows every Claude Code session running on your computer today, and tells you which of them have asked you something and are waiting on your answer.

Each of your folders is a small dot, called a hub: your second brain, your CRM, the folder where you write your posts (if you have one), and any other folder you name when you install. Every session hangs off the folder it runs in. A folder appears once it has a session today. Sessions from folders you did not name hang off a hub called **Other**.

This is piece 2 of 4 in the agent workspace. Install them in order: 1 agent-flow, 2 FleetView, 3 ProjectForge, 4 Jeeves. Each one also works on its own.

WORDS USED IN THIS GUIDE

WORD	WHAT IT MEANS HERE
Session	1 conversation with Claude Code, running in 1 terminal window.
Terminal	The text window where you type commands. On a Mac the app is called Terminal: press Command and Space, type <code>Terminal</code> , press Enter.
Token	The unit Claude's usage is counted in. 1 token is roughly 3 quarters of a word.
M, B	Million and billion. 41.3M tokens means 41.3 million tokens.
Context window	How much text a session can keep in view at once: 200,000 tokens usually, 1,000,000 on some models.
Model	Which Claude model answers: Opus, Sonnet, Fable, Mythos or Haiku. All 5 are Claude models made by Anthropic.
Subagent (helper agent)	A second Claude that your session starts to do 1 job and report back, such as finding notes. FleetView's page calls them helpers.
Hook	A command Claude Code runs by itself every time a given event happens, such as a tool about to run. Hooks are listed in <code>settings.json</code> , Claude Code's settings file. FleetView uses none.
Log file	The file where Claude Code writes down every message of a session as it happens. FleetView reads these.
127.0.0.1 and localhost	2 ways of writing "this computer". An address that starts with either of them opens only on your own computer.
Port	The number after the colon in an address such as http://localhost:3010 . It picks out which program on your computer answers. In this set of 4: agent-flow 3001, FleetView 3010, ProjectForge 3020, Jeeves 4040.
~	Short for your home folder. <code>~/claude/projects</code> is the folder <code>.claude/projects</code> inside it.
Node.js and npm	Node.js is free software that runs FleetView's server. npm is the tool that comes with it and downloads code packages.
GitHub, repo, stars	GitHub is the website where the code is kept. A repo is a project's folder of code, kept on GitHub; <code>git clone</code> copies it to your computer. Stars are GitHub's count of people who bookmarked a project.
Git branch	The named version of the code a session is working on. It only shows for folders that use Git.




FLEETVIEW WITH 9 MADE-UP SESSIONS IN 4 FOLDERS: 2 ASKED YOU SOMETHING (AMBER), 1 IS WAITING ON A TOOL (VIOLET), 2 ARE WORKING (GREEN), THE REST HAVE ANSWERED OR ARE IDLE (BLUE-GREY). THE KEY ALONG THE BOTTOM EDGE EXPLAINS EVERY MARK.

What each part of the picture means:

- **The circle's colour** is what the session is doing:
 - **Green: working.** Claude is doing something right now.
 - **Amber: it asked you something.** Claude's last message ends in a question (a question mark at the end of any of its last 3 lines) and nobody has answered it. This is the one colour that means "go and type".
 - **Darker amber: it asked you over 30 minutes ago.** Still a question for you, but an older one, so it is dimmer than the question you were asked 2 minutes ago.
 - **Violet: it may need your approval.** Claude asked to run a tool and nothing has come back for over 30 seconds. That is either Claude Code asking your permission in that terminal, or a long command such as `npm install`. It is counted on its own, not as "need you".
 - **Blue-grey: nothing for you to do.** Either idle, or Claude answered and asked nothing. The line under the circle says which.
 - **Grey with a white tick: you pressed Mark as done.**
- **"2 need you"** at the top left counts only the amber sessions: the ones that asked you something. A session that answered and asked nothing is never counted, which is why the number stays small enough to act on. A question stops counting after the number of hours set by `waiting_hours` in FleetView's settings file `config.json` (1 hour unless you change it), and the session goes blue-grey.
- The **Needs you** strip under it names those sessions, **newest question first**, with how long each has waited. Click a name to open that session. The strip wraps onto more rows as it needs them and never takes more than about 15% of the screen height.

- **The letter inside** is the Claude model the session uses. Anthropic names its models Opus, Sonnet, Fable, Mythos and Haiku: O Opus, S Sonnet, F Fable, M Mythos, H Haiku, and ? for any other model.
- **The ring round the circle** shows how full the session's context window is. The ring is always the same light grey. Over 85% full, a small red ! appears beside the circle. Colour is kept for what the session is doing, so a full context window and a waiting question never show as the same colour. A small **1M** tag means the session has a 1,000,000-token window instead of the usual 200,000.
- **Under the circle** is the session's title (Claude Code gives every session a title), then 1 line saying where it stands: "asked you 4 min ago", "may need approval · 3 min", "answered 12 min ago · \$0.09", or its cost and number of turns. A turn is 1 reply from the model.
- **Small dots beside a circle** are helper agents (subagents) the session started in the last 30 minutes. Hover a dot to read what that helper is doing.
- **The top bar** adds up every session today, whether or not it is drawn: how many need you, how many are working, how many may need approval, sessions, helpers, tokens and cost. Then your **5-hour window**: a Claude subscription limits how much you can use in each 5-hour period, and this shows the tokens used so far in the current period, where you will end up at this rate, and the minutes until it resets. Then your **7-day total**: tokens used in the last 7 days, which Claude also limits. When idle sessions are left off the drawing, the top bar says how many and offers **show all**.
- **The key** along the bottom explains every colour, letter and mark.

Hover over any circle and a label says, in words, what it is doing.




HOVERING OVER THE CRM SESSION THAT ASKED A QUESTION: WHAT IT IS DOING IN WORDS, HOW LONG AGO IT ASKED, ITS MODEL, ITS COST AND HOW FULL ITS CONTEXT WINDOW IS. MADE-UP DATA.

Click any circle and a side panel opens with the full detail and the last 10 entries in the session's log. Each entry is labelled **you typed** (your message), **Claude thinking** (the start of what Claude wrote back) or **Claude used** (a file it read or a command it ran). For a session that asked you something, the panel has a **Mark as done** button: press it when you have dealt with that question another way, so it stops counting. Press Escape to close the panel.

NOTE

The dollar figures are what those tokens would cost if you paid per token. They are not money taken from your subscription. If you are on a Claude subscription (Pro or Max) you do not pay them. The page says this once, in its key.

There is also a card view at `http://localhost:3010/cards.html` (3010 is the port), with the same sessions, the same totals and the same colours as cards. It works with no internet.



THE CARD VIEW OF THE SAME MADE-UP SESSIONS: THE ONES THAT ASKED YOU SOMETHING FIRST, NEWEST FIRST, EACH SAYING WHEN IT ASKED. EACH CARD NAMES ITS FOLDER ONCE, WITH THE GIT BRANCH. TAKEN A FEW MINUTES AFTER THE GRAPH PICTURE, SO THE TOTALS HAVE MOVED ON.

PIECE 2 · FLEETVIEW

Why you would want it

Once you run agents, you run several at once. You might have a second brain session tidying notes, a CRM session working out who to follow up and a session drafting posts, each in its own terminal window.

Without FleetView you find out what each is doing by clicking from 1 Terminal to the next. You miss the session that finished 20 minutes ago and has been waiting for your answer since. You do not see that a session's context window is 90% full and about to lose track of the start of the conversation. And on a subscription you need to know how close you are to your 5-hour limit, which Claude Code does not show you in a single place.



LEFT: 4 TERMINALS, 2 OF THEM QUIETLY WAITING FOR AN ANSWER. RIGHT: THE SAME 4 SESSIONS ON FLEETVIEW, WITH THE 2 WAITING ONES COUNTED AND NAMED AT THE TOP. MADE-UP EXAMPLE.

FleetView answers 3 questions:

1. Which session is waiting for me, and for how long?
2. What is running right now, and in which folder?
3. How much of my 5-hour usage window have I used, and where will I end up?

It only reads the log files Claude Code already writes for every session, in the folder `~/ .claude/projects` (the folder `.claude/projects` inside your home folder). It adds no hooks and changes no settings.

WHAT IT IS FOR

Seeing every Claude Code session on your computer today on 1 screen, which of them asked you a question, and how much of your 5-hour usage allowance is gone.

WORKS WELL WHEN

- **You run 3 or more sessions at once**, each in its own terminal window, and you keep losing track of which one is waiting for you.
- **You are on a Claude subscription** and want to know how close you are to the 5-hour limit before you start a long job.
- **You want to catch a full context window early**. A red ! beside a session means its context window, the text it can keep in view at once, is over 85% full: your cue to finish or restart it before it starts forgetting the beginning of the conversation.
- You came back after an hour away and want to know what moved, in which folder, without clicking through 6 terminals.

DOES NOT WORK WELL WHEN

- **You read the dollar figures as money**. They are the pay-per-token prices for the tokens used. On a Claude subscription no such money leaves your account. Read them as a rough measure of how much work a session did, not as money.
- **You use a model FleetView does not price**. It carries Anthropic's own published price list only. A model with no line of its own in FleetView's price table is flagged on screen rather than guessed, and you add its prices yourself in the file `lib/prices.json`.
- **You expect "needs you" to mean "finished"**. It means Claude's last message ended in a question. A session grinding through a 40-minute job in silence is not counted at all, so a long quiet job looks the same as a job that finished and asked nothing.
- FleetView cannot tell you whether the work is any good. It reports who is running and who is waiting: it checks whether Claude's last message ends in a question, never whether the answer is right.
- **You are screen-sharing**. The side panel shows folder paths, file names and the start of what you typed. Set `hide_paths` to `true` in FleetView's settings file `config.json`, then run `python3 install.py --stop` and `python3 install.py --start`, before you share: the change only takes effect after that restart.

PIECE 2 • FLEETVIEW

How we built it

Everything below comes from Ashley's own records. The times on 2026-06-12 are the times of the screenshots saved that day.

2026-06-12, AFTERNOON: THE SINGLE-TAB TOOL THAT COULD NOT MERGE

That day Ashley installed agent-flow (piece 1 of 4), an open-source tool that draws a live picture of 1 Claude Code session per browser tab, at <http://localhost:3001>. He wanted all his sessions in a single tab. Claude wrote a change to merge them. The data came through correctly, but agent-flow's drawing code can only put 1 session at the centre of each picture, so the merged sessions piled on top of each other. The change was taken back out. Ashley's verdict: *"that hasn't worked - It's not working at all."*

THE SEARCH FOR A SINGLE-SCREEN TOOL


Claude then tried the other open-source dashboards for Claude Code:

- **Claude-Code-Agent-Monitor** (456 stars at the time) was ruled out first. On its first start it rewrote the hooks in Claude Code's own settings file, `~/.claude/settings.json`, without asking. Then it tried to import Ashley's entire session history, the log files Claude Code had written, 9.4 gigabytes of them across 3,842 files. That used about 10 processor cores and crashed its own web server. It was stopped and its hooks were removed.
- **claude-view** was ruled out because it runs on macOS only, and Ashley works on a PC. 2 other tools were ruled out because they needed Docker (a tool for running programs in a sealed box) or Bash (the Mac and Linux command line), which are awkward on his PC.
- **claude-code-dashboard**, by the GitHub user Stargx, was picked because it needs no hooks. It reads the log files in `~/.claude/projects` directly, so every folder on the computer is covered with no set-up. Its card view, unchanged, was running by 16:56.

What was kept from it: the code that watches the log files and reads new lines as they arrive, the first version of the working, waiting and idle rules, and the card page. Its port was changed from 3001 to 3010, because agent-flow already used 3001. (Its instructions file said you could choose the port with a setting called `PORT`; the code ignored that setting.)

2026-06-12, EVENING: THE GRAPH

A second search of GitHub found nothing that draws all live sessions as a single graph on his PC. The nearest tools either looked back at sessions after the fact or showed 1 project only. So Claude added a new address on the server, `/api/graph`, that hands the page its data, and a new page, `graph.html`, written from scratch with no borrowed code. It shows today's sessions, helper agents active in the last 30 minutes and each session's last 10 log lines, and trims idle sessions to the 3 most recent per folder. The first version was on screen at 18:55.



ASHLEY'S FIRST FLEETVIEW GRAPH, 2026-06-12 18:55. HIS REAL FOLDERS, HIS CRM (A FOLDER NAMED NEXUS) AND HIS SECOND BRAIN, WITH 9 SESSIONS. THIS FIRST VERSION NAMED EACH SESSION AFTER ITS GIT BRANCH, THE NAMED VERSION OF THE CODE IT WAS WORKING ON, WHICH IS WHY MOST OF THEM READ "MASTER"; THE FIGURES BESIDE EACH ONE ARE THE COST IF PAID PER TOKEN, THEN THE NUMBER OF TURNS (426T MEANS 426 TURNS). "SUBAGENTS LIVE 2" MEANS 2 HELPER AGENTS WERE RUNNING. THE TOP BAR HAD NO TOKEN COUNTS YET. (ASHLEY'S OWN PC, NOT A MAC)

Later that evening:

- **The price table was corrected.** The original table priced Opus 4.6 at \$15 per million tokens sent to the model (input) and \$75 per million tokens it wrote back (output), and priced text saved for Claude to re-read later at a quarter of the price of text sent to the model. The Opus prices and the price for saved text were both wrong. The table also had no rows for Fable or Opus 4.8, so it priced them at Sonnet rates, below their real rates. The fix that evening added prices for both.
- **22:25, token counts.** Ashley is on a subscription, so tokens matter more than dollars. The top bar gained a total token count and an output token count.
- **22:34, the 5-hour window.** Ashley asked for his usage limit to be shown: *"fix it"*. A new address on the server, `/api/usage`, runs ccusage, a free open-source tool that works out Claude's 5-hour usage periods from the same log files. It shows the tokens used so far in the current 5-hour period, the tokens you are on course to use by the end of it, and the minutes until the period resets.

tokens 139.75M output 681.1k cost \$115.97 5h window 170.87M used → 189.08M proj · 26m left

THE FIRST 5-HOUR WINDOW GAUGE, 2026-06-12 22:34. READING ALONG THE ROW: 139.75M TOKENS IN TOTAL, 681.1K OF THEM WRITTEN BACK BY CLAUDE, \$115.97 IF THOSE TOKENS WERE PAID FOR ONE BY ONE, THEN THE 5-HOUR WINDOW AT 170.87M TOKENS USED, 189.08M PROJECTED BY THE END OF THE PERIOD, 26 MINUTES UNTIL IT RESETS. K MEANS THOUSAND, M MEANS MILLION. (ASHLEY'S OWN PC, NOT A MAC)

- **22:45 to 23:06, budgets and alarms.** Ashley asked for all of it to be built: *"make all this so"*. A 7-day total was added. You could now click either gauge and type your own budget into it: green while the projected total is under 70% of your budget, amber from 70% to 90%, red at 90% and over. Your

browser shows 1 notice when the 5-hour window is on course to pass the budget you typed in. Anthropic does not publish the exact token limit for each plan, so FleetView does not guess one; Ashley typed in his own figure.

cost \$162.38 5h window 197.65M / 200.00M used → 209.28M proj · 15m left 7d 976.71M / 1.50B


BUDGETS SET, 2026-06-12 22:45: THE 5-HOUR WINDOW IN RED AT 197.65M TOKENS USED OF THE 200.00M BUDGET ASHLEY TYPED IN, 209.28M PROJECTED BY THE END, 15 MINUTES UNTIL IT RESETS; THEN THE 7-DAY TOTAL, 976.71M TOKENS OF A 1.50B BUDGET. M MEANS MILLION, B MEANS BILLION. (ASHLEY'S OWN PC, NOT A MAC)

THE SAME EVENING: THE OTHER VIEWS ON THE SAME SERVER


The same evening Claude also added a map of all 73 of Ashley's agents, called FleetMap, and a view of agents passing work between his apps, called Comms Mesh. A small file on his PC started the server by itself, with no window, each time Ashley switched on his computer and signed in. On 2026-07-02 a 3D video view, Fleet Cinema, was added to the same server; its Vault Galaxy view draws every note in his second brain as a star. None of these are in your download: they were built around Ashley's own agents and apps. They are shown here as Ashley built them.



ASHLEY'S REAL FLEETMAP ON 2026-06-12: 73 AGENTS IN COLOURED TEAMS, WITH ASHLEY IN THE CENTRE AND A KEY AT THE BOTTOM LEFT. (ASHLEY'S OWN PC, NOT A MAC)



ASHLEY'S REAL COMMS MESH, 2026-06-12: AGENTS IN HIS WORK BOARD (ORANGE) AND HIS LINKEDIN APP (PINK), WITH EACH HAND-OFF BETWEEN THEM LISTED ALONG THE BOTTOM. (ASHLEY'S OWN PC, NOT A MAC)




VAULT GALAXY FROM ASHLEY'S FLEET CINEMA, CAPTURED 2026-09-22: 835 NOTES AND 1,619 LINKS DRAWN AS A STAR FIELD, WITH THE PANEL THAT TURNS IT INTO A VIDEO. (ASHLEY'S OWN PC, NOT A MAC)

2026-06-21: THE RULING AGAINST SEPARATE DASHBOARDS

9 days later Ashley ruled against building any more separate dashboards. On a page that streamed events as they happened: *"I hate seeing a stream of info - It just means nothing."* On a second standalone dashboard: *"I'd rather have this as part of Project Forge frankly."* ProjectForge is his work board. He ruled that views of the agents belong as a tab inside the work board, never as another program on another port.

2026-07-27 TO 2026-09-22: IT STOPPED RUNNING

- **2026-07-27:** Ashley's list of outside tools he tracks moved the Stargx dashboard from "give to members" to "keep an eye on": 10 stars, no change since 2026-03-09, "fine for us because we can fix it", but too thin to put in front of the 6 people paying for his Outliers programme at the time.
- **2026-08-12:** the last day Ashley's own notes show FleetView running.
- **2026-09-22:** nothing answered on port 3010, although the file that started it with the computer was still there. Why it stopped starting by itself when the computer started is not recorded. A copy started by hand from a temporary folder came up in about 2 seconds.



ASHLEY'S REAL FLEETVIEW ON 2026-09-22, FROM THAT COPY: 7 SESSIONS ROUND 4 OF HIS FOLDERS: NEXUS (HIS CRM), THE OBSERVATORY (A RESEARCH FOLDER), SB AND SECOND BRAIN (2 SECOND-BRAIN FOLDERS); THE 5-HOUR WINDOW AT 340.84M TOKENS USED, 374.00M PROJECTED BY THE END, 26 MINUTES UNTIL IT RESETS; 3.44B TOKENS (3.44 BILLION) OVER THE LAST 7 DAYS. IN THIS OLD COPY THE RING AROUND EACH CIRCLE USED BLUE, AMBER AND RED, THE SAME COLOURS THE CIRCLE ITSELF USES FOR WHAT THE SESSION IS DOING, SO THE 2 RAN TOGETHER. YOUR COPY USES A PLAIN GREY RING. (ASHLEY'S OWN PC, NOT A MAC)

2026-09-22: MAKING IT FIT FOR YOU

For this download we took Stargx's dashboard plus 3 of Ashley's additions (the graph page, the 5-hour and 7-day panel, and the corrected prices), and fixed what we found wrong on the day. It was checked 3 ways before you got it: a run-through of this guide by a tester who had never seen it, following only the words on the page, a usability review of the pages, and a security review of the code. What they found is fixed:

- **Amber vanished after 15 seconds, and the first fix then left 18 of 30 sessions amber.** The original kept a session amber for 15 seconds after Claude answered, then turned it blue, so a session that asked you a question 4 minutes ago looked the same as a session nobody had touched since breakfast. (Claude Code writes a few bookkeeping lines to its log after each reply, and those were resetting the colour.) The first fix went the other way: every finished reply counted, so on a 30-session day 18 circles were amber and the colour told you nothing. The rule you have is the narrow

one: a session is amber only when Claude's last message asked you something. "Done, saved." is not a question, so that session sits quietly in blue-grey and says "answered 12 min ago".

- **The 7-day figure counted other AI tools.** ccusage adds up every AI coding tool it finds on your computer unless it is asked for Claude only. Yours asks for Claude Code only (`ccusage claude` , checked with `ccusage 20.0.24` on 2026-09-22).
- **The totals disagreed.** The graph added up only the sessions it drew, and the card page hid others. Both pages now show the same totals for every session today, and say when some are not drawn.
- **A stopped FleetView still looked alive.** If FleetView stopped, the page froze and kept a session pulsing green. Yours shows a red **FleetView stopped** banner within 5 seconds, and every "12 min ago" on the page stops counting up with it.
- **The original showed nothing if you installed it before you had ever used Claude Code, and only woke up when you restarted it.** Yours starts reading the log folder as soon as Claude Code creates it.
- Ashley's copy grouped sessions by the folder name after the Documents folder in its path, which only fits his habits. Yours groups by the folders you name when you install.
- His copy had no price for Opus 5, the model every session used that day, so it priced them at Sonnet 4.6 rates. Prices now come from a table checked on 2026-09-22 against Anthropic's pricing page, and a model with no price row shows "no price" instead of a guess.
- His copy assumed every session had a 200,000-token context window. A session on a 1,000,000-token window showed 100% full. FleetView now switches to 1,000,000 when the model name ends in `[1m]` (the label Claude Code adds to a model running with the 1,000,000-token window) or a single turn uses more than 200,000 tokens.
- A Haiku helper agent inside an Opus session was priced as Opus, and the helper's replies were counted into the main session's ring, so the ring read wrong. Each reply is now priced with its own model, and the ring counts only the main conversation.
- The original let any computer on your network open the page, so anyone on the same wifi could read your session titles and folder paths. Yours only answers on this computer, and it checks the address each request was sent to, refusing any request not sent to `localhost` or `127.0.0.1` . That stops a website you visit from pointing its own name at your computer to read your session titles, folder paths and what you typed.
- His copy ran ccusage every 60 seconds all day. Yours runs it only while a FleetView page is open.
- The card page loaded its drawing library, React, from the internet. Yours carries a copy, so it works offline.

Pros and cons

	PROS	CONS
Set-up	Reads files Claude Code already writes. It adds no hooks (commands Claude Code would run by itself), changes no settings and keeps no database. Deleting the folder removes it completely.	Needs Node.js (free software that runs FleetView's server) version 22 or newer, and Python 3.11 or newer, which you may not have.
Cost in tokens	Uses 0 Claude tokens. It is plain code reading files.	None.
Cost in time	About 5 minutes to install. Starts in seconds: Ashley's log files, 3.2 gigabytes of them when we checked on 2026-09-22, were read and drawn in about 2 seconds.	The first read of a very large history takes longer and uses some processor time.
What it shows	Every session in a single tab, including sessions started before FleetView, with the waiting ones first. The 5-hour gauge shows how much of your 5-hour allowance you have used and where you will end up at this rate.	On 2026-06-21 Ashley ruled against a page that listed every agent event in a long running list as it happened: "I hate seeing a stream of info - It just means nothing."
Waiting	Amber stays until you answer, and the Needs you strip says how long each has waited.	A session counts as waiting whenever Claude's last message ends in a question, including questions you have already dealt with another way. Press Mark as done on those.
Accuracy	Prices checked on 2026-09-22; unknown models are flagged, not guessed.	Prices go out of date with every new model, and you must add each new model's prices to <code>lib/prices.json</code> yourself. The context window is a best estimate (see When it goes wrong).
Upkeep	Small: 1 server file and 2 pages. Your own Claude can change it in minutes.	The free project it is built on, Stargx's claude-code-dashboard, is barely maintained: 13 people have bookmarked it on GitHub and nobody has changed the code since 2026-03-09 (checked 2026-09-22). If it breaks, you and your own Claude fix it.
Privacy	Only reachable from your own computer.	The side panel shows folder paths, file names and the start of what you typed. Careful when screen-sharing: set <code>hide_paths</code> to <code>true</code> in <code>config.json</code> (see Every command and setting).



WHAT FLEETVIEW READS AND WHAT IT NEVER TOUCHES.

THE FREE READY-MADE ALTERNATIVE

If you would rather have a bigger, polished tool that someone else maintains, look at **Claude-Code-Agent-Monitor** (<https://github.com/hoangsonww/Claude-Code-Agent-Monitor>, MIT licence: free to use and change, as long as the credit stays). On 2026-09-22 it had 1,012 stars and a change the day before. It is a full app you open at <http://localhost:4820>, with a database, charts of how your agents work, a desktop app for PCs and Macs that sits beside the clock, and an interface you can read in 5 languages.

WARNING

Its set-up (`npm run setup` , then `npm run install-hooks`) adds its own hooks to `~/.claude/settings.json` , and its desktop app installs those hooks on first start. It also imports your whole session history when it first starts. On Ashley's computer on 2026-06-12 that import used about 10 processor cores and crashed it. Before you try it, copy `~/.claude/settings.json` somewhere safe, and expect 1 extra program to start every time Claude Code reaches one of its hooks, which is on every tool it uses and every reply it writes.

PIECE 2 • FLEETVIEW

Before you start

BEFORE YOU START ON A MAC

Python. Install Python from <https://www.python.org/downloads/macos/> (the macOS installer; we tested 3.14.7). When it finishes, double-click **Install Certificates.command** and **Update Shell Profile.command** in the Python folder inside Applications, then open a new Terminal window. Check with `python3 -c "import sys; print(sys.prefix)"` : it must print a line starting `/Library/Frameworks/Python.framework` . If it starts `/opt/homebrew` or `/usr/local/Cellar` , your Terminal uses Homebrew's Python: every command here still works, and the self-checks below use a private Python folder, which works with either.

Node.js. Install the LTS version from <https://nodejs.org> (we tested v24.21.0), open a new Terminal window, and check with `node --version` : `v22` or higher.

The first `git` . Your Mac may show a box asking to install the command line developer tools. Press Install, wait until it has finished, then type the `git` line again (not tested on a real Mac).

If Terminal says `claude` is not found, type


`echo 'export PATH="$HOME/.local/bin:$PATH"' >> ~/.zshrc` , open a new Terminal window, and check with `claude --version` .

Your second brain is at `~/Second Brain` on a Mac (a folder in your home folder), not in Documents, because macOS can refuse a program that starts by itself access to Documents (not tested on a real Mac). If a page says "macOS refused access to" a folder, move that folder into your home folder and run `python3 install.py` again (not tested on a real Mac).

Apple Silicon or Intel: the steps are the same on both, and both were tested.

The table below says how to check each of these, and what else FleetView needs.

YOU NEED	HOW TO CHECK	HOW TO GET IT
Node.js 22 or newer	Open Terminal and type <code>node --version</code> . You should see v22 or higher. Node 18 stopped getting security fixes on 2025-04-30 and Node 20 on 2026-04-30, so the installer refuses anything older.	The LTS installer (LTS means long-term support, the version that goes on getting security fixes longest) from https://nodejs.org . Then open a new Terminal window.
Python 3.11 or newer	<code>python3 --version</code> . Python 3.10 gets security fixes only until 2026-10-31 and older versions get none, so the installer refuses 3.10 and older.	https://www.python.org/downloads/macos/ (see Python above).
Git (the tool that copies the code from GitHub to your computer)	<code>git --version</code>	It comes with your Mac's command line developer tools (see The first <code>git</code> above).
Claude Code, used at least once	Type <code>ls ~/.claude/projects</code> : it lists 1 folder per project once you have used Claude Code	You have this from the earlier sessions. If not, FleetView still installs and starts reading the folder as soon as it appears.
Internet	Open any web page in your browser. If it loads, you have what FleetView needs	Needed for the install and for the first run of the 5-hour gauge (it downloads ccusage). The pages themselves need nothing from the internet.

A terminal window titled 'zsh' with a dark background and light green text. It shows the following commands and their outputs:

```
~ % node --version
v24.21.0
~ % python3 --version
Python 3.14.7
~ % git --version
git version 2.39.5 (Apple Git-154)
~ % python3 -c "import sys; print(sys.prefix)"
/Library/Frameworks/Python.framework/Versions/3.14
```

THE CHECKS IN TERMINAL ON A TEST MAC, WITH WHAT A GOOD ANSWER LOOKS LIKE. THE VERSION NUMBERS ARE THE ONES THE TEST MAC PRINTED ON 2026-09-25.

PIECE 2 • FLEETVIEW

Install it


1. Open Terminal: press Command and Space, type `Terminal`, press Enter. It opens in your home folder, which is where all 4 downloads in this set go.
2. Copy the program to your computer and start the installer, typing 1 line at a time:

```
git clone https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac
cd outliers-ws-02-fleetview-mac
python3 install.py
```

3. The installer checks Python and Node.js. If Python is older than 3.11, or Node.js is missing or older than 22, it tells you how to get it and stops without changing anything.
4. It downloads 2 small add-on code packages FleetView needs, using npm (the download tool that comes with Node.js). This needs internet and takes under a minute.
5. It asks where your **second brain folder** is, then your **CRM folder**. (If you keep them in Obsidian, the note-taking app, these are what Obsidian calls vaults.) It looks in your home folder, then your Documents folder and suggests the likeliest folder in brackets. Press Enter to accept, type a different path, or type `-` to skip.
6. It asks for **any other project folders**, 1 at a time. If you keep a folder where you write your posts, add it here and give it a short name such as `Content Engine`. Press Enter on an empty line to finish.
7. It asks for the **port**: the number at the end of the page's address (3010 gives <http://localhost:3010>). Press Enter for 3010, unless something else on your computer already uses 3010.
8. It asks whether to switch on the **5-hour and 7-day token panel**. Say yes unless you have no internet.
9. It asks whether FleetView should **start by itself, with no window, each time you log in to your Mac**. No account is involved: this is your Mac's own log-in. Saying yes writes a LaunchAgent: a small file, `~/Library/LaunchAgents/com.outliers.fleetview.plist`, that tells your Mac to start FleetView each time you log in. It takes effect from your next log-in; the installer also prints the

`launchctl load -w` line that would switch it on straight away, which you do not need, because the next question starts FleetView now.

10. It asks whether to **start FleetView now**, with no window. Say yes.
11. Open <http://localhost:3010/graph.html> in your browser. (`http://localhost:3010/` takes you there too.)

A screenshot of a terminal window titled "outliers-ws-02-fleetview-mac - zsh". The terminal shows the output of running "python3 install.py". The output is a multi-step installer script for FleetView. It explains that FleetView shows every Claude Code session on the computer on one page, reads log files, and changes nothing in Claude Code. It checks for Node.js v24.21.0 and notes that the directory /Users/<you>/.claude/projects does not exist yet. It downloads 2 code packages with npm. It asks for folder paths for sessions and prompts. It asks for a port (3010) and whether to switch on the 5-hour and 7-day token panel. It creates a config.json file. It asks to start FleetView by itself, with no window, each time you switch on the computer and sign in. It provides instructions to start it now with "launchctl load -w" and shows the path to the plist file. It asks to start FleetView now, with no window. It shows the command to stop it: "python3 install.py --stop". It mentions that dollar figures on the page are what the tokens would cost if you paid per token.

```
outliers-ws-02-fleetview-mac % python3 install.py
FleetView installer

FleetView shows every Claude Code session on this computer on 1 page.
It only reads the log files Claude Code already writes. It changes nothing
in Claude Code.

Node.js v24.21.0 found.
Note: /Users/<you>/.claude/projects does not exist yet. That is normal if
you have not used Claude Code on this
computer. FleetView starts reading it by itself as soon as your first
session creates it.
Downloading 2 code packages with npm (needs internet, about 20 seconds)...
Code packages downloaded.

FleetView groups your sessions by the folder they ran in. Tell it your
folders.
Press Enter to accept the suggestion in brackets, or type '-' to skip one.

Where is your second brain vault?
[/Users/<you>/Second Brain] >
Where is your CRM vault?
[/Users/<you>/CRM] >
Any other project folders? For example the folder where you write your
posts. One at a time; Enter on its own to finish.

Folder path (Enter to finish):
>
Which port should the page use?
[3010] >
The token panel uses ccusage, a free open-source tool, run through npx.
The first run
downloads it (needs internet). It runs only while a FleetView page is
open.

Switch on the 5-hour and 7-day token panel? (Y/n)
>
config.json created.

Start FleetView by itself, with no window, each time you switch on this
computer and sign in? (Y/n)
> To start it now, without logging out of your Mac and back in, run:
launchctl load -w
"/Users/<you>/Library/LaunchAgents/com.outliers.fleetview.plist"
Starts with the computer: a small file called com.outliers.fleetview.plist
was written into your LaunchAgents folder (Mac)
(/Users/<you>/Library/LaunchAgents/com.outliers.fleetview.plist).

Start FleetView now, with no window? (Y/n)
> FleetView started in the background.

Done. Open http://localhost:3010/graph.html in your browser.
To stop it: python3 install.py --stop
Dollar figures on the page are what the tokens would cost if you paid per
```

WHAT THE INSTALLER PRINTS ON A TEST MAC WHEN YOU PRESS ENTER AT EVERY QUESTION. THE HOME FOLDER IS SHOWN AS `/Users/<you>`. (Y/N) MEANS PRESSING ENTER GIVES YES.

When it has worked you see your folders as hubs with today's sessions hanging off them, like the picture at the start of this guide. If you have no Claude Code session today, the page says so; start a session and it appears within 2 seconds.

NOTE

The 5-hour gauge says "first check" for up to a minute the first time, while your computer downloads ccusage. After that it updates about once a minute while the page is open, and the 7-day total about every 5 minutes.

Running the installer again with the same answers changes nothing, and if FleetView is running it says so. If you change an answer, it saves your old settings as `config.json.bak-<date and time>` first (for example `config.json.bak-20260924-110312`), stops the running FleetView and starts it again on the new settings, so there is never more than 1 copy running.

These commands run inside the FleetView folder. In a new terminal, type

```
cd outliers-ws-02-fleetview-mac first.
```

- To stop FleetView: `python3 install.py --stop`. This finds it however it was started, including when it started by itself with the computer.
- To start it again: `python3 install.py --start`. This only starts it, with your saved answers. It asks no questions.
- To stop it starting by itself when the computer starts: `python3 install.py --uninstall`. This stops FleetView and removes the LaunchAgent file it made.
- To remove it completely: uninstall, then delete the folder.


TIP

Want to see FleetView working before your own sessions exist? In a new terminal, type `cd outliers-ws-02-fleetview-mac`, then `npm run demo`, then open <http://localhost:3011/graph.html>. It draws 8 made-up sessions in 4 folders (1 of them the Other hub) on port 3011, so it never clashes with your own copy on 3010. Press Ctrl+C to stop it.

PIECE 2 • FLEETVIEW


Using it day to day

- **Leave the tab open.** Pin `http://localhost:3010/graph.html` in your browser. It refreshes itself every 2 seconds, and "updated 0s ago" at the top tells you it is alive.
- **Look at the Needs you strip first.** It names every session that asked you something, newest question first, and wraps onto more rows when there are more of them. Click a name to open it, then switch to that terminal and answer.



THE TOP OF THE PAGE: "2 NEED YOU", AND THE NEEDS YOU STRIP NAMING EACH SESSION THAT ASKED A QUESTION, NEWEST FIRST, WITH HOW LONG AGO IT ASKED. MADE-UP DATA.

- **Dealt with a question another way? Press Mark as done.** Open the session and press **Mark as done**; the circle turns grey, gets a white tick and its line reads "done · was waiting 12 min", so you can see you dealt with it rather than never opened it. The choice is kept in this browser. If Claude writes again in that session, it comes back.
- **"May need approval" is its own colour.** If a session asked to run a tool and nothing has come back for 30 seconds, it turns violet and is counted under **may need approval** in the top bar, not under "need you". Claude Code may be asking your permission in that terminal, or a long command such as `npm install` is running. Check the terminal.
- **Watch for the red !** beside a circle. It means that session's context window is over 85% full. Start a fresh session for the next task, or ask it to summarise and carry on.
- **Set your budgets once.** Click **5-hour window** in the top bar and type a token number, such as `100M` (100 million). Do the same for **7 days**. Allow browser notifications when asked. With no budget the gauge stays grey; with a budget it turns amber at 70% and red at 90% of the projected total, and you get 1 notice when the projection passes your budget. The budgets are saved in this browser only. If FleetView cannot read what you typed, it says so and keeps your old budget.
- **See everything.** The graph draws every working and waiting session, plus the 3 most recent idle ones per folder. When some idle sessions are left out, the top bar says how many and offers **show all**, and each folder hub says "+2 idle not drawn". You can also open <http://localhost:3010/graph.html?all=1> to draw every session.
- **Busy days.** As soon as any 1 folder has more than 4 sessions, or you have more than 12 in total, the graph switches to 1 column per folder, with the sessions that asked you something at the top. 30 sessions stay readable on a laptop screen: we checked it in a browser window 1366 pixels wide and 768 pixels tall, and all 58 pieces of writing on the page, the session titles and the lines under them, stayed clear of each other. Each column heading says how many sessions it has and how many need you.



30 MADE-UP SESSIONS: 1 COLUMN PER FOLDER, THE ONES THAT ASKED YOU SOMETHING AT THE TOP. OF THE 30, 5 ASKED A QUESTION, 3 ARE WAITING ON A TOOL, 5 ARE WORKING AND THE REST HAVE ANSWERED OR ARE IDLE.

- **2 different totals.** The top-bar tokens and cost add up every session today on this computer. The 5-hour gauge counts your account's current 5-hour window, which can start yesterday evening and includes sessions no longer on screen. When they differ, the 5-hour gauge is the one that matches your usage limit.
- **Tokens that are mostly re-reads.** Most of the token total is usually "re-read context": Claude re-reading text it was already sent, the cheapest kind. Hover over **tokens** to see the share.
- **New model released?** Open `lib/prices.json`, add a row with the rates from <https://platform.claude.com/docs/en/about-claude/pricing>, then restart FleetView (`python3 install.py --stop`, then `python3 install.py --start`). Until you do, that model shows "no price" and its tokens appear in grey as "tokens with no price", left out of the dollar total. The table you have was read off that page on 2026-09-22, the day Claude Opus 5.5 came out, and it carries Opus 5.5 at \$4 per million tokens sent to the model and \$20 per million tokens it writes back. `npm test` reads your own logs from the last 7 days and fails if a model in them has no row, so a new model cannot go unpriced without you being told.

PIECE 2 • FLEETVIEW

Fit it to your own AI system

The safe way. Try every change on a copy of FleetView first, so the FleetView you use every day keeps running while you experiment. 5 steps:

1. Make the copy. In Finder, open your home folder, click the `outliers-ws-02-fleetview-mac` folder, choose File, then Duplicate, and rename the copy `fleetview-test`.

2. Give the copy its own port. In `fleetview-test`, open `config.json` in a text editor such as TextEdit, change `"port": 3010` to `"port": 3012` and save. Never use 3001, 3020 or 4040: the other 3 pieces in this set use them.
3. In `fleetview-test`, delete the file `fleetview.pid` if it is there. It is the record of your everyday FleetView, copied across with the folder. (If you forget, the installer sees that the record belongs to another folder and leaves your everyday FleetView alone.)
4. Start the copy. Open a new terminal (it opens in your home folder), type `cd fleetview-test`, then `python3 install.py --start`, and open <http://localhost:3012/graph.html>. In that folder, `python3 install.py --stop` stops the copy only. You do not need to run `python3 install.py` on its own in the copy: it would only ask the install questions again.
5. When a change works, make the same change in your everyday `outliers-ws-02-fleetview-mac` folder and restart FleetView there: in the terminal, type `cd ../outliers-ws-02-fleetview-mac`, then `python3 install.py --stop`, then `python3 install.py --start`.

The copy reads the same Claude Code log files as your everyday FleetView. Both only read them, so neither gets in the other's way.

FleetView has 2 sets of checks, and a change should pass both. `npm test` runs FleetView's own 60 checks; near the end, look for `pass 60` and `fail 0`. The installer's 30 checks run with `pytest`, a free Python testing tool, from a private Python folder: a folder in your home folder with its own copy of Python's add-ons, so the checks work whichever Python your Mac uses. Make that folder and install `pytest` into it once, from any folder:

```
python3 -m venv ~/outliers-checks
source ~/outliers-checks/bin/activate && python -m pip install pytest
```

Then run both sets of checks in the copy:

```
npm test
source ~/outliers-checks/bin/activate && python -m pytest -q
```

The second should end with "27 passed, 3 skipped": the 3 skipped check the file that starts FleetView with the computer on a PC, which a Mac does not use. If a check fails and its message says a model name is in your logs with no row in `lib/prices.json`, Claude has released a model FleetView has no price for: add it to `lib/prices.json` (see Using it day to day). Any other failure means the change broke something, so put it back before you go on.

Read "Every command and setting" near the end of this guide before you ask Claude for a change, because much of what you want is already a setting in `config.json`. The setting to leave alone is `host : 127.0.0.1` means only this computer can open the page. Put your computer's network address there instead and every other computer on the same wifi can open the page and read your sessions, what you typed and your usage.

Change it until it matches how you work. FleetView did not start as Ashley's: it started as somebody else's free dashboard, published with its code open to read, that showed 1 card per session and nothing more. Ashley moved it off port 3001 so it would stop clashing with agent-flow, replaced its price table after finding 2 models charged at Sonnet's cheaper rates instead of their own, and then had Claude write

the graph page you are looking at from scratch, in plain code with no libraries. That same evening he had Claude add the 5-hour and 7-day usage gauges, budget alarms you set by clicking a gauge (green under 70%, amber to 90%, red above, with a browser alert when the projection passes what you set), and a second page that drew all 73 of his agents as a map.

Each change below is a prompt you can paste into Claude Code, opened in your copy, the `fleetview-test` folder: in a new terminal, type `cd fleetview-test`, then `claude`. Claude reads the code and makes the change. Then run both sets of checks in the copy, as in The safe way above; every check should pass. To see the change, run `python3 install.py --stop` and then `python3 install.py --start` in the copy, and reload <http://localhost:3012/graph.html>. When you are happy, paste the same prompt into Claude Code opened in your everyday `outliers-ws-02-fleetview-mac` folder, run both sets of checks there, and restart it with `python3 install.py --stop`, then `python3 install.py --start`.

Which file each paste-in prompt below changes

config.json your folders, port, settings prompts 1, 3 and 6	watcher.js the server: reads the session logs and sends the pages their data prompts 1, 3, 4	lib/sessions.js turns log lines into sessions and status prompt 2
public/graph.html the page you look at prompts 1, 2, 4, 5, 6, 7, 8	public/cards.html the card view prompt 7	tests/ run <code>npm test</code> and the pytest checks (see The safe way) after every change every prompt

Paste a prompt into Claude Code opened in your copy, the `fleetview-test` folder (port 3012). Claude changes these files; you run both sets of checks (see The safe way), then `python3 install.py --stop` and `python3 install.py --start` in the copy to see the change. When it works, make the same change in your everyday `outliers-ws-02-fleetview-mac` folder.

WHICH FILE EACH PASTE-IN PROMPT BELOW CHANGES.

1. PUT YOUR CRM'S TODAY LIST BESIDE THE GRAPH

If your CRM vault writes a daily list of who to contact (in Ashley's it is a page called `Today.md`), this puts it beside your sessions, so you can see whether your CRM agent has made today's list yet.

In this FleetView folder, add a collapsible panel on the left of `public/graph.html` that shows my CRM's `Today.md` page. Add a `"crm_today"` path to `config.json` and `config.example.json`, add a `GET /api/crm-today` route in `watcher.js` that reads that file (read-only, never write to my CRM) and returns its text, and show the first 15 lines in the panel with the file's last-changed time. If the file is missing, show "No Today page yet". Add a test in `tests/` using a made-up `Today.md`.

2. A PLAIN LINE PER SESSION: WHAT DID I ASK IT?

This adds, under each circle, the last message you typed in that session.

In this FleetView folder, change lib/sessions.js to keep the most recent message I typed in each session (type "user", not a subagent), cut to 60 characters, and send it in the /api/graph data as "lastAsk". In public/graph.html, draw it in small grey text under each session's title, and add it to the hover label. Keep the tests passing and add a test for lastAsk.

3. AN ALARM THAT REACHES YOU WITH THE BROWSER CLOSED

Today the budget alarm and the waiting list only work while the page is open.

In this FleetView folder, add a server-side check to watcher.js: read "budget_5h_tokens" and "notify_waiting_minutes" from config.json. When the ccusage 5-hour projection passes the budget, or a session has been waiting for longer than notify_waiting_minutes, show a macOS notification once. Only check while the server is running, never on a separate timer or scheduled task. Add the settings to config.example.json and explain them in README.md.

4. COST PER FOLDER PER WEEK

Where did this week's usage go, folder by folder? The download cannot tell you. The top bar adds up 1 total for the day, and nothing on the page breaks that total down by folder. This prompt adds it, so you can see which of your folders uses the most: second brain, CRM or any other folder you named.

In this FleetView folder, add a GET /api/by-folder route to watcher.js that adds up tokens and cost per folder group for the last 7 days, using the sessions already read and lib/groups.js. Add a small table at the bottom of public/graph.html, opened by clicking "by folder" in the key. Label the dollar column "\$ if paid per token". Add a test with the made-up sessions from tools/make-demo.js.

5. COLOUR HELPER AGENTS BY WHAT YOUR AGENTS DO

Your agents live in `~/.claude/agents` and in your vault's `.claude/agents`. Each file has a description.

In this FleetView folder, read every agent file in `~/.claude/agents` and in the `.claude/agents` folder of each folder listed in config.json (read-only). Sort them into up to 6 colour groups using simple keywords from each agent's description (for example: research, writing, CRM, vault upkeep, content, other). Colour each helper-agent dot on public/graph.html by its group and add the groups to the key along the bottom. Do not hard-code any agent names.

6. FLAG SESSIONS THAT WRITE INTO A DRAFTS FOLDER

When a session is writing post drafts into a folder you review, you usually want to read them straight after.

In this FleetView folder, add a "watch_folders" list to config.json, for example the folder where my post drafts are saved. When a session in /api/graph has touched a file inside one of those folders in the last 30 minutes, add "touchedWatched": true, and draw a small star next to that session on public/graph.html. When the session is then waiting for me, put it first in the Needs you strip with the words "drafts ready". Add a test with made-up sessions.

7. HIDE PATHS WITH 1 CLICK FOR SCREEN-SHARING

The `hide_paths` setting hides folder paths, file names and what you typed, but you have to edit a file and restart. This puts it on a button.

In this FleetView folder, add a "hide details" button to the key of public/graph.html and public/cards.html. When pressed, the pages hide full folder paths, file names and the text of the recent steps, and show only the folder group name. Remember the choice in the browser's localStorage, wrapped in try/catch. The existing hide_paths setting in config.json should still work and should win when it is true.

8. PUT IT WHERE YOU ALREADY LOOK

Ashley's own ruling was that views like this belong inside the page you already work from, not in yet another tab.

In this FleetView folder, make public/graph.html work when shown inside another page: add a "compact=1" address option that hides the key, shrinks the top bar to "need you", working, 5h window and 7 days, and fits the graph to a small area. Then tell me the exact address to use, and how to add it to my second brain's home note or my work board as an embedded web page.

Every command and setting

COMMANDS

COMMAND	WHAT IT DOES
<code>python3 install.py</code>	Checks Node.js, downloads 2 code packages, asks for your folders, writes the settings file <code>config.json</code> , offers to make FleetView start by itself, with no window, when the computer starts, then starts FleetView
<code>python3 install.py --start</code>	Starts FleetView in the background with your saved answers. No questions. Says so if it is already running
<code>python3 install.py --stop</code>	Stops FleetView, however it was started. It checks it is really FleetView first, so it never ends another program
<code>python3 install.py --uninstall</code>	Stops FleetView and removes the LaunchAgent file it made, so it no longer starts by itself when the computer starts. Leaves your settings and this folder
<code>python3 install.py --yes</code>	Installs with no questions, using the options below (the words starting with <code>--</code>) and the defaults it finds. It does not start FleetView or make it start with the computer unless you add <code>--start</code> and <code>--launcher</code>
<code>--second-brain PATH, --crm PATH, --folder "NAME=PATH"</code>	Give your folders on the command line (<code>--folder</code> can be repeated)
<code>--port 3010, --projects-dir PATH, --no-ccusage</code>	Choose the port, a different Claude Code log folder, or switch the token panel off
<code>--launcher / --no-launcher, --no-start</code>	Make FleetView start by itself when the computer starts, or not; do not start FleetView now
<code>node watcher.js</code> or <code>npm start</code>	Start FleetView in this terminal, showing any error it hits. Ctrl+C stops it
<code>npm run demo</code>	Made-up sessions on port 3011 (see the tip in Install it)

COMMAND	WHAT IT DOES
<code>node tools/make-demo.js <folder> --sessions 30</code>	Writes a made-up busy day of 30 sessions into a folder you name, to see what a full screen looks like
<code>npm test</code>	Runs FleetView's own 60 checks against made-up sessions and prints a line per check saying whether it passed
<code>source ~/outliers-checks/bin/activate && python -m pytest -q</code>	Runs the installer's own 30 checks in a temporary folder, using pytest from your private Python folder (see Fit it to your own AI system). On a Mac 27 pass and 3 are skipped. 90 checks in total with <code>npm test</code>

SETTINGS IN `config.json`

SETTING	WHAT IT DOES
<code>port</code>	The page's port, 3010 by default
<code>host</code>	<code>127.0.0.1</code> : only this computer can open the page. Leave it
<code>folders</code>	Your folders: <code>[{ "name": "CRM", "path": "..."}]</code> . A session belongs to the folder whose path matches most closely, so a sub-folder you name wins over its parent
<code>idle_per_folder</code>	How many idle sessions to draw per folder. It is 3 unless you change it. The totals always count every session, drawn or not
<code>waiting_hours</code>	How many hours an unanswered question stays amber (1). After that the session turns blue-grey and leaves the Needs you list. Raise it if you want yesterday evening's question still showing this morning
<code>fresh_minutes</code>	A question asked less than this many minutes ago is drawn in the bright amber; older ones get the darker amber. It is 30 minutes unless you change it
<code>hide_paths</code>	<code>true</code> hides folder paths, file names and the text of the recent steps, for screen-sharing
<code>usage.enabled</code>	<code>false</code> switches the 5-hour and 7-day panel off
<code>usage.package</code>	The ccusage version FleetView runs (<code>ccusage@20.0.24</code> , checked 2026-09-22). Only change this if you mean to
<code>projects_dir</code>	The folder Claude Code writes its session logs into. Leave it out unless Claude Code keeps its logs somewhere other than <code>~/ .claude/projects</code>

After any change, restart FleetView: `python3 install.py --stop` , then `python3 install.py --start` . `config.example.json` shows every setting with an example.

FILES FLEETVIEW MAKES

- `fleetview.pid` : the running FleetView's process number and port, so `--stop` can find it. Removed when it stops.
- `fleetview.log` : what FleetView printed when it was started in the background. If it will not start, the reason is at the end of this file.
- `config.json.bak-<date and time>`, for example `config.json.bak-20260924-110312` : your old settings, saved whenever the installer changed them.

ADVANCED: SETTINGS FROM THE TERMINAL

`PORT` overrides the port, `FLEETVIEW_CONFIG` points at a different settings file, `CLAUDE_CONFIG_DIR` points at a different Claude Code folder, and `FLEETVIEW_NO_CCUSAGE=1` switches the token panel off. These are environment variables: set a variable for 1 start by typing it before the command, such as `PORT=3012 npm start`. (Do not pick 3020: ProjectForge, piece 3 of 4, uses it.) To see the raw data the pages read, open <http://localhost:3010/api/graph> (and `/api/usage`, `/api/meta`) in your browser.

When it goes wrong

WHAT YOU SEE	WHY	THE FIX
A red FleetView stopped banner	The FleetView program is no longer running, so the page is not getting updates. On Ashley's computer on 2026-09-22 FleetView had stopped starting by itself when the computer started; the reason was never recorded.	Run <code>python3 install.py --start</code> in the FleetView folder. The page picks up by itself. If it will not start, read the end of <code>fleetview.log</code> , or run <code>node watcher.js</code> to see the error.
"Port 3010 is already in use"	Another program is using that port. On 2026-06-12 another tool, agent-flow (piece 1 of 4), was already on 3001, which is why FleetView moved to 3010.	Open http://localhost:3010/graph.html ; if FleetView is there, it is already running. If not, run <code>python3 install.py</code> again and choose another port.
FleetView is set to start by itself, but the page does not open after you restart the computer	The LaunchAgent file names the exact folder Node.js was in when you installed FleetView. If you reinstalled Node.js somewhere else, the file still names the old folder.	Run <code>python3 install.py</code> again and press Enter at each question; it writes the LaunchAgent file again.
Terminal says "command not found" after you typed a Python command	A Mac has no Python command without the 3 on the end.	Type <code>python3</code> , as every command in this guide does.
The installer says Node.js is too old	FleetView needs Node.js 22 or newer.	Install the LTS version from https://nodejs.org , open a new Terminal window, run <code>python3 install.py</code> again.
The installer says Python is too old	FleetView needs Python 3.11 or newer.	Install it from https://www.python.org/downloads/macos/ (see Before you start on a Mac), open a new Terminal window, run <code>python3 install.py</code> again.
Nothing is amber, but you know a session is waiting	Amber means Claude's last message asked you something. A session that stopped on a statement ("Done, saved.") is blue-grey and reads "answered 12 min ago". A question older than <code>waiting_hours</code> (1 hour) has also stopped counting.	Nothing to fix: open the session from its folder column. To keep older questions counting, raise <code>waiting_hours</code> in <code>config.json</code> .

WHAT YOU SEE	WHY	THE FIX
A session sits on "may need approval" for a long time	Claude asked to run a tool and nothing has come back. Either Claude Code is asking your permission in that terminal, or the command really is that long.	Look at that terminal and answer the permission question, or leave it: the violet circle is not counted in "need you".
A wide amber banner: "Your settings file could not be read"	<code>config.json</code> is damaged. Some text editors add an invisible mark at the start of the file when they save it; a comma after the last item, a <code>//</code> comment, or a half-saved file do the same. FleetView keeps the port it last ran on, so the page you already have open still works, but none of your folder names are in use until you fix the file.	The banner names the fault, and the line number when there is one. Fix it, or run <code>python3 install.py</code> to write the file again. Your file is never changed for you.
FleetView will not start, and says "FleetView was NOT started"	<code>config.json</code> is damaged and FleetView has no record of the port it last ran on, so it will not guess one. All 4 ways of starting it refuse the same way: <code>python3 install.py --start</code> , <code>npm start</code> , <code>node watcher.js</code> and the LaunchAgent that starts it when you log in. Your settings are never quietly thrown away.	Read the 4 lines it prints: they name the fault and the line it is on. Fix that line, or run <code>python3 install.py</code> to write the file again. When it was started by that LaunchAgent, those 4 lines are at the end of <code>fleetview.log</code> in the FleetView folder.
A session shows "no price"	Its model has no row in <code>lib/prices.json</code> . Ashley's June copy had no Opus 5 row and silently used Sonnet 4.6 rates, which made every cost wrong.	Add the model's row from https://platform.claude.com/docs/en/about-claude/pricing and restart.
A red ! beside a circle	That session's context window is over 85% full.	Start a fresh session for the next task, or ask this one to summarise and carry on.
A ring sits at 100% on a long session	The session has a 1,000,000-token window, but FleetView has not yet seen either sign of it: a model name ending in <code>[1m]</code> , or a single turn over 200,000 tokens. Ashley's copy always assumed 200,000.	FleetView switches to a 1,000,000-token window when the model name ends in <code>[1m]</code> or a single turn uses more than 200,000 tokens. The side panel says which of those 2 reasons it went on. Until then, a ring on a session with the 1,000,000-token window reads too full.
5-hour gauge shows "not available"	ccusage could not run: no internet on the first run, or npx (the tool that downloads and runs ccusage) is blocked by your computer's security settings.	Hover over the gauge to see the reason. Check your internet, or switch the panel off in <code>config.json</code> (<code>"usage": {"enabled": false}</code>).

WHAT YOU SEE	WHY	THE FIX
A session you just started does not appear	Before your first Claude Code session the log folder does not exist.	Wait a few seconds: FleetView looks for the folder every 3 seconds and starts reading as soon as it appears. The empty page tells you which folder it is waiting for.
Top-bar cost and the 5-hour gauge disagree	They count different sessions: the top bar every session today, the gauge your account's current 5-hour window.	Trust the 5-hour gauge for your limit. The top bar is today's total on this computer, which is a different number.
Another dashboard filled your settings.json with hooks	That was Claude-Code-Agent-Monitor on 2026-06-12, not FleetView. FleetView never touches settings.json.	Restore the copy of settings.json you made before installing it.

PIECE 2 • FLEETVIEW

Download

The code, this guide's source and the tests:

<https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac>

```
git clone https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac
cd outliers-ws-02-fleetview-mac
python3 install.py
```

```
outliers-ws-02-fleetview-mac/
install.py          asks your folders, installs, starts and stops FleetView
watcher.js         the server (reads the logs, serves the pages)
lib/               sessions, folders, prices (prices.json), token panel
public/graph.html  the graph page
public/cards.html  the card page
public/vendor/     React, somebody else's code kept inside the download, so the card page needs no internet
tools/make-demo.js made-up sessions: npm run demo
tests/            npm test and the pytest checks
config.example.json every setting, with an example
guide/GUIDE.md     this guide
README.md         short instructions
LICENSE           your right to use and change it
UPSTREAM-LICENSE  the licence of the Stargx dashboard it is built on
WHAT-I-STOLE.md   which parts came from other projects
```

WHAT IS IN THE DOWNLOAD.

FleetView is built on Stargx/claude-code-dashboard (MIT licence, Copyright (c) 2025 Cold Beam Games), uses ccusage (MIT licence) for the 5-hour and 7-day gauges, and carries React 18.3.1 (MIT licence) for the card page. Prices were checked on 2026-09-22.

What was run on a Mac

Run <https://github.com/OUTLIERS-ai/outliers-mac-test/actions/runs/36136617939> on 2026-09-25. Every command below was typed exactly as this guide prints it, each in a new Terminal window, from a fresh download of this repo.

7 runs on GitHub's test Macs. 3 set up like a new member's Mac (Python from python.org, Node.js from nodejs.org, no Homebrew): macOS 15.7.9 on Apple Silicon, macOS 15.7.9 on Intel, macOS 26.6.2 on Apple Silicon. And 2 with Homebrew installed as well, each run twice, once with Homebrew added before Python and once after: macOS 15.7.9 on Apple Silicon and macOS 15.7.9 on Intel.

COMMAND	RESULT
<code>git --version</code>	run on all test Macs
<code>git clone https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac</code>	run on all test Macs
<code>cd outliers-ws-02-fleetview-mac</code>	run on all test Macs
<code>python3 install.py</code>	run on all test Macs
<code>python3 install.py --stop</code>	run on all test Macs
<code>python3 install.py --start</code>	run on all test Macs
<code>node watcher.js</code>	run on all test Macs
<code>npm start</code>	run on all test Macs
<code>npm run demo</code>	run on all test Macs
<code>node tools/make-demo.js <folder> --sessions 30</code>	read, not run: a pattern, not a line to type as printed: you put your own folder name where <folder> is
<code>npm test</code>	run on all test Macs
<code>python3 -m venv ~/outliers-checks</code>	run on all test Macs
<code>source ~/outliers-checks/bin/activate && python -m pip install pytest</code>	run on all test Macs
<code>source ~/outliers-checks/bin/activate && python -m pytest -q</code>	run on all test Macs
<code>python3 install.py --yes</code>	run on all test Macs
<code>python3 install.py --uninstall</code>	run on all test Macs

The LaunchAgent the installer writes was loaded and started on every test Mac, as your Mac does when you log in, and the page answered.

`source ~/outliers-checks/bin/activate && python -m pytest -q` printed 27 passed, 3 skipped on every test Mac.

NOT TESTED ON A REAL MAC

GitHub's test Macs are not a member's Mac, and 2 steps were **not tested on a real Mac**:

- **A real restart.** The test Macs cannot be switched off and on again, so it was not tested that FleetView starts by itself after you restart your Mac. The file that starts it when you log in was loaded and checked on the test Macs; the restart itself was not.
- **macOS's question "Allow Node.js to find devices on local networks?"** The test Macs never show it. If it appears the first time the page opens, press Allow. This advice is not tested on a real Mac.

DOWNLOAD THIS PIECE

<https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac>

```
git clone https://github.com/OUTLIERS-ai/outliers-ws-02-fleetview-mac
cd outliers-ws-02-fleetview-mac
python3 install.py
```