

OVP Guide to Using Processor Models

Model specific information for ARM_Cortex-M55

X-2025.12 December,2025



Copyright and Proprietary Information Notice

© 2025 Synopsys, Inc. This Synopsys software and all associated documentation are proprietary to Synopsys, Inc. and may only be used pursuant to the terms and conditions of a written license agreement with Synopsys, Inc. All other use, reproduction, modification, or distribution of the Synopsys software or the associated documentation is strictly prohibited.

Destination Control Statement

All technical data contained in this publication is subject to the export control laws of the United States of America. Disclosure to nationals of other countries contrary to United States law is prohibited. It is the reader's responsibility to determine the applicable regulations and to comply with them.

Disclaimer

SYNOPSYS, INC., AND ITS LICENSORS MAKE NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARD TO THIS MATERIAL, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE.

Trademarks

Synopsys and certain Synopsys product names are trademarks of Synopsys, as set forth at <https://www.synopsys.com/company/legal/trademarks-brands.html>. All other product or company names may be trademarks of their respective owners.

Free and Open-Source Licensing Notices

If applicable, Free and Open-Source Software (FOSS) licensing notices are available in the product installation.

Third-Party Links

Any links to third-party websites included in this document are for your convenience only. Synopsys does not endorse and is not responsible for such websites and their practices, including privacy practices, availability, and content.

www.synopsys.com

Document Status

Author	Synopsys Inc
Version	X-2025.12
Filename	OVP_Model_Specific_Information_armm_Cortex-M55.pdf
Created	10 December 2025
Status	OVP Standard Release

Model Release Status

This model is included in all general releases.

Contents

1	Overview	1
1.1	Description	1
1.2	Licensing	1
1.3	Limitations	2
1.4	Verification	2
1.5	Features	3
1.6	Unpredictable Behavior	4
1.6.1	Equal Target Registers	4
1.6.2	Floating Point Load/Store Multiple Lists	4
1.6.3	If-Then (IT) Block Constraints	4
1.6.4	Use of R13	4
1.6.5	Use of R15	4
1.7	Integration Support	5
1.7.1	Memory Transaction Query	5
1.7.2	Halt Reason Introspection	5
1.7.3	Automatic WFI Wake Up	5
2	Configuration	6
2.1	Location	6
2.2	GDB Path	6
2.3	Semi-Host Library	6
2.4	Processor Endian-ness	6
2.5	QuantumLeap Support	6
2.6	Processor ELF code	6
3	All Variants in this model	7
4	Bus Master Ports	8
5	Bus Slave Ports	9
6	Net Ports	10
7	FIFO Ports	12
8	Formal Parameters	13
8.1	Parameter values and limits	15

9 Execution Modes	18
10 Exceptions	19
11 Hierarchy of the model	20
11.1 Level 1	20
12 Model Commands	21
12.1 Level 1	21
12.1.1 debugflags	21
12.1.2 isync	21
12.1.3 itrace	21
13 Registers	23
13.1 Level 1	23
13.1.1 Core	23
13.1.2 Control	23
13.1.3 System	24
13.1.4 System_secure	27
13.1.5 System_non_secure	28
13.1.6 Integration_support	28

Chapter 1

Overview

This document provides the details of an OVP Fast Processor Model variant.

OVP Fast Processor Models are written in C and provide a C API for use in C based platforms. The models also provide a native interface for use in SystemC TLM2 platforms.

The models are written using the OVP VMI API that provides a Virtual Machine Interface that defines the behavior of the processor. The VMI API makes a clear line between model and simulator allowing very good optimization and world class high speed performance. Most models are provided as a binary shared object and also as source. This allows the download and use of the model binary or the use of the source to explore and modify the model.

The models are run through an extensive QA and regression testing process and most model families are validated using technology provided by the processor IP owners. There is a companion document (OVP Guide to Using Processor Models) which explains the general concepts of OVP Fast Processor Models and their use. It is downloadable from the OVPworld website documentation pages.

1.1 Description

ARMM Processor Model

1.2 Licensing

Usage of binary model under license governing simulator usage.

Note that for models of ARM CPUs the license includes the following terms:

Licensee is granted a non-exclusive, worldwide, non-transferable, revocable licence to:

If no source is being provided to the Licensee: use and copy only (no modifications rights are granted) the model for the sole purpose of designing, developing, analyzing, debugging, testing, verifying, validating and optimizing software which: (a) (i) is for ARM based systems; and (ii) does not incorporate the ARM Models or any part thereof; and (b) such ARM Models may not be used

to emulate an ARM based system to run application software in a production or live environment.

If source code is being provided to the Licensee: use, copy and modify the model for the sole purpose of designing, developing, analyzing, debugging, testing, verifying, validating and optimizing software which: (a) (i) is for ARM based systems; and (ii) does not incorporate the ARM Models or any part thereof; and (b) such ARM Models may not be used to emulate an ARM based system to run application software in a production or live environment.

In the case of any Licensee who is either or both an academic or educational institution the purposes shall be limited to internal use.

Except to the extent that such activity is permitted by applicable law, Licensee shall not reverse engineer, decompile, or disassemble this model. If this model was provided to Licensee in Europe, Licensee shall not reverse engineer, decompile or disassemble the Model for the purposes of error correction.

The License agreement does not entitle Licensee to manufacture in silicon any product based on this model.

The License agreement does not entitle Licensee to use this model for evaluating the validity of any ARM patent.

The License agreement does not entitle Licensee to use the model to emulate an ARM based system to run application software in a production or live environment.

Source of model available under separate Imperas Software License Agreement.

1.3 Limitations

Performance Monitors are not implemented.

Debug Extension and related blocks are not implemented.

MVE instruction subset (Helium) is not implemented.

LOB extension instructions are implemented without optimisation of branches.

MSCR, PFCR, CPDLPSTATE and DPDLPSTATE are implemented but have no effect in the model.

EWIC interrupt status access registers are not implemented.

1.4 Verification

Models have been extensively tested by Imperas. ARM Cortex-M models have been successfully used by customers to simulate the Micrium uC/OS-II kernel and FreeRTOS.

1.5 Features

The model is configured with 16 interrupts and 3 priority bits (use `override_numInterrupts` and `override_priorityBits` parameters to change these).

Thumb-2 instructions are supported.

MPU is present. Use parameter `override_MPU_TYPE` to disable it or change the number of MPU regions if required.

SysTick timer is present. Use parameter `SysTickPresent` to disable it if required.

FPU extension is not present. Use parameter `override_MVFR0` to enable it if required.

DSP extension is present. Use parameter `override_InstructionAttributes3` to disable it if required.

Bit-band region is not present. Use parameter `BitBandPresent` to enable it if required.

SAU is present. Use parameter `override_SAU_TYPE` to disable it or change the number of SAU regions if required.

SIE-200 IDAU not is present. Use parameter `SIE200IDAUPresent` to enable it if required.

TCMs are present (ITCM is 16777216 bytes, DTCM is 16777216 bytes). Use parameters `override_ITCMSize` and `override_DTCMSize` to set TCM sizes if required (note that these parameters specify size codes in `CFGITCMSIZE/CFGDTCMSIZE` format, not byte sizes).

When TCMs are present, bus ports called ITCM and DTCM are created so that TCM contents may be viewed or modified externally by connecting to these ports. Parameter `useInternalTCMs` specifies whether TCM memory is modeled internally or externally. If modeled externally, the TCMs must be implemented on a bus which is then connected to the TCM bus ports listed above.

Memory alias regions are present when configured by the `CFGMEMALIAS` input signal. When alias regions are enabled and the security extension is present, TGU system registers allow fine-grained access control to ITCM and DTCM blocks. Parameters `override_ITGU_CFG` and `override_DTGU_CFG` allow block sizes and numbers to be configured for ITGU and DTGU, respectively.

A 20-bit PPB bus port can be connected. If it is, then any loads or stores to address range `0xE0040000:0xE00FFFFF` will be visible on this bus at address range `0x00040000:0x000FFFFF`.

An AHB peripheral interface port is present. If this port is unconnected, all AHB region accesses are routed via the data bus. If the port is connected, then all data accesses to the System region `0xE0100000:0xFFFFFFFF` will be routed to that port. Additionally data accesses to addresses in the Peripheral region starting at address `0x40000000` will be routed to that port if enabled by `CM7_AHBPCR`.

An AHB region of size 536870912 bytes is present. Use parameter `override_AHBPSize` set a different size if required, or to disable the region if required using size zero. Note that this parameter specifies size codes in `CM7_AHBPCR` format, not byte size.

If the AHB region is present, use parameter `override_AHBPEnable` or configuration net `initahbp` to specify whether the AHB region should be enabled or disabled at reset.

1.6 Unpredictable Behavior

Many instruction behaviors are described in the ARM ARM as CONSTRAINED UNPREDICTABLE. This section describes how such situations are handled by this model.

1.6.1 Equal Target Registers

Some instructions allow the specification of two target registers (for example, double-width SMULL, or some VMOV variants), and such instructions are CONSTRAINED UNPREDICTABLE if the same target register is specified in both positions. In this model, such instructions are treated as UNDEFINED.

1.6.2 Floating Point Load/Store Multiple Lists

Instructions that load or store a list of floating point registers (e.g. VSTM, VLDM, VPUSH, VPOP) are CONSTRAINED UNPREDICTABLE if either the uppermost register in the specified range is greater than 32 or (for 64-bit registers) if more than 16 registers are specified. In this model, such instructions are treated as UNDEFINED.

1.6.3 If-Then (IT) Block Constraints

Where the behavior of an instruction in an if-then (IT) block is described as CONSTRAINED UNPREDICTABLE, this model treats that instruction as UNDEFINED.

1.6.4 Use of R13

Use of R13 is described as CONSTRAINED UNPREDICTABLE in many circumstances. This model allows R13 to be used like any other GPR.

1.6.5 Use of R15

Use of R15 is described as CONSTRAINED UNPREDICTABLE in many circumstances. This model allows such use to be configured using the parameter “unpredictableR15” as follows:

Value “undefined”: any reference to R15 in such a situation is treated as UNDEFINED;

Value “nop”: any reference to R15 in such a situation causes the instruction to be treated as a NOP;

Value “raz_wi”: any reference to R15 in such a situation causes the instruction to be treated as a RAZ/WI (that is, R15 is read as zero and write-ignored);

Value “execute”: any reference to R15 in such a situation is executed using the current value of R15 on read, and writes to R15 are allowed.

Value “assert”: any reference to R15 in such a situation causes the simulation to halt with an assertion message (allowing any such unpredictable uses to be easily identified).

In this variant, the default value of “unpredictableR15” is “execute”.

1.7 Integration Support

This model implements a number of non-architectural pseudo-registers and other features to facilitate integration.

1.7.1 Memory Transaction Query

Two registers are intended for use within memory callback functions to provide additional information about the current memory access. Register `executionPri` indicates the current processor execution priority. Register `atomicType` indicates whether the current instruction has any special atomic constraints (0 indicates no constraint, 1 indicates atomic, 2 indicates exclusive access).

1.7.2 Halt Reason Introspection

An artifact register `HaltReason` can be read to determine the reason or reasons that a processor is halted. This register is a bitfield, with the following encoding: bit 0 indicates the processor has executed a wait-for-event (WFE) instruction; bit 1 indicates the processor has executed a wait-for-interrupt (WFI) instruction; bit 2 indicates the processor has entered lockup state; and bit 3 indicates the processor is held in reset.

1.7.3 Automatic WFI Wake Up

A simulation environment can cause a core to wake up from the WFI state by writing to the artifact register `WakeWFINow`.

Chapter 2

Configuration

2.1 Location

This model's VLVN is `arm.ovpworld.org/processor/armmm/1.0`.

The model source is usually at:

`$IMPERAS_HOME/ImperasLib/source/arm.ovpworld.org/processor/armmm/1.0`

The model binary is usually at:

`$IMPERAS_HOME/lib/$IMPERAS_ARCH/ImperasLib/arm.ovpworld.org/processor/armmm/1.0`

2.2 GDB Path

The default GDB for this model is: `$IMPERAS_HOME/lib/$IMPERAS_ARCH/gdb/arm-none-eabi-gdb`.

2.3 Semi-Host Library

The default semi-host library file is `arm.ovpworld.org/semihosting/armNewlib/1.0`

2.4 Processor Endian-ness

This is a LITTLE endian model.

2.5 QuantumLeap Support

This processor is qualified to run in a QuantumLeap enabled simulator.

2.6 Processor ELF code

The ELF code supported by this model is: `0x28`.

Chapter 3

All Variants in this model

This model has these variants

Variant	Description
ARMv6-M	
ARMv7-M	
Cortex-M0	
Cortex-M0plus	
Cortex-M1	
Cortex-M3	
Cortex-M4	
Cortex-M4F	
Cortex-M7	
Cortex-M7F	
Cortex-M23	
Cortex-M33	
Cortex-M33F	
Cortex-M55	(described in this document)
Cortex-M55F	

Table 3.1: All Variants in this model

Chapter 4

Bus Master Ports

This model has these bus master ports.

Name	min	max	Connect?	Description
INSTRUCTION	32	33	mandatory	
DATA	32	33	optional	
PPB	20	20	optional	PPB interface
AHB	32	33	optional	AHB interface
ITCM	24	24	optional	instruction TCM interface
DTCM	24	24	optional	data TCM interface

Table 4.1: Bus Master Ports

Chapter 5

Bus Slave Ports

This model has no bus slave ports.

Chapter 6

Net Ports

This model has these net ports.

Name	Type	Connect?	Description
sysResetReq	output	optional	Indicates that a reset is required
intISS	output	optional	Indicates that an interrupt service has started
eventOut	output	optional	EVENTO output signal (SEV)
lockup	output	optional	Indicates fatal lockup state entered
haltReason	output	optional	Indicates why core is halted
currPri	output	optional	Current execution priority
currNS	output	optional	Current security state
intnum	output	optional	Exception number of current execution context
int	input	optional	Raise or lower interrupt by index
reset	input	optional	RESET (active high)
cpuWait	input	optional	CPUWAIT (active high at reset only)
nmi	input	optional	NMI (posedge-triggered)
eventIn	input	optional	EVENTI input (posedge-triggered)
initnsvtor	input	optional	Non-secure VTOR reset configuration
initsvtor	input	optional	Secure VTOR reset configuration
CFGMEMALIAS	input	optional	Memory alias enable
inititem	input	optional	Enable ITCM at reset (if high)
initdtcm	input	optional	Enable DTCM at reset (if high)
initahbp	input	optional	Enable AHBP at reset (if high)
LOCKSVTAIRCR	input	optional	LOCKSVTAIRCR system register lock
LOCKNSVTOR	input	optional	LOCKNSVTOR system register lock
LOCKSMPU	input	optional	LOCKSMPU system register lock
LOCKNSMPU	input	optional	LOCKNSMPU system register lock
LOCKSAU	input	optional	LOCKSAU system register lock
LOCKTCM	input	optional	LOCKTCM system register lock
LOCKITGU	input	optional	LOCKITGU system register lock
LOCKDTGU	input	optional	LOCKDTGU system register lock
int0	input	optional	Scalar interrupt input 0

int1	input	optional	Scalar interrupt input 1
int2	input	optional	Scalar interrupt input 2
int3	input	optional	Scalar interrupt input 3
int4	input	optional	Scalar interrupt input 4
int5	input	optional	Scalar interrupt input 5
int6	input	optional	Scalar interrupt input 6
int7	input	optional	Scalar interrupt input 7
int8	input	optional	Scalar interrupt input 8
int9	input	optional	Scalar interrupt input 9
int10	input	optional	Scalar interrupt input 10
int11	input	optional	Scalar interrupt input 11
int12	input	optional	Scalar interrupt input 12
int13	input	optional	Scalar interrupt input 13
int14	input	optional	Scalar interrupt input 14
int15	input	optional	Scalar interrupt input 15

Table 6.1: Net Ports

Chapter 7

FIFO Ports

This model has no FIFO ports.

Chapter 8

Formal Parameters

Name	Type	Description
verbose	Boolean	Specify verbosity of output
showHiddenRegs	Boolean	Show hidden registers during register tracing
UAL	Boolean	Disassemble using UAL syntax
enableVFPAAtReset	Boolean	Enable vector floating point (SIMD and VFP) instructions at reset. (Enables cp10/11 in CPACR and sets FPEXC.EN)
compatibility	Enumeration	Specify compatibility mode
	ISA	
	gdb	
	nopBKPT	
unpredictableR15	Enumeration	Specify behavior for UNPREDICTABLE uses of R15
	undefined	
	nop	
	raz_wi	
	execute	
	assert	
override_debugMask	Uns32	Specifies debug mask, enabling debug output for model components
enableHostAtomics	Boolean	Enable use of host atomic instructions to emulate load/store exclusive operations (not architecturally accurate, accelerates parallel simulation)
enableWFEHostAtomics	Boolean	Enable WFE and SEV instructions when using host atomics (does nothing otherwise)
instructionEndian	Endian	The architecture specifies that instruction fetch is always little endian; this attribute allows the defined instruction endianness to be overridden if required
resetAtTime0	Boolean	Reset the model at time=0 (default=1)
SysTickPresent	Uns32	Specify number of SysTick timers present
BitBandPresent	Boolean	Specify presence of bit-band region
SIE200IDAUPresent	Boolean	Specify presence of SIE-200 Implementation-Defined Attribution Unit
useInternalTCMs	Boolean	Specify that configured TCMs should be modeled internally
override_PFR0	Uns32	Override ID_PFR0 register
override_PFR1	Uns32	Override ID_PFR1 register
override_DFR0	Uns32	Override ID_DFR0 register
override_AFR0	Uns32	Override ID_AFR0 register
override_MMFR0	Uns32	Override ID_MMFR0 register
override_MMFR1	Uns32	Override ID_MMFR1 register
override_MMFR2	Uns32	Override ID_MMFR2 register
override_MMFR3	Uns32	Override ID_MMFR3 register

override_ISAR0	Uns32	Override ID_ISAR0 register
override_ISAR1	Uns32	Override ID_ISAR1 register
override_ISAR2	Uns32	Override ID_ISAR2 register
override_ISAR3	Uns32	Override ID_ISAR3 register
override_ISAR4	Uns32	Override ID_ISAR4 register
override_ISAR5	Uns32	Override ID_ISAR5 register
override_MVFR0	Uns32	Override ID_MVFR0 register
override_MVFR1	Uns32	Override ID_MVFR1 register
override_MVFR2	Uns32	Override ID_MVFR2 register
override_ACTLR	Uns32	Override system ACTLR register
override_CPUID	Uns32	Override system CPUID register
override_MPU_TYPE	Uns32	Override system MPU_TYPE register
override_SMPU_TYPE	Uns32	Override system Secure MPU_TYPE register
override_SAU_TYPE	Uns32	Override system SAU_TYPE register
override_VTOR	Uns32	Override VTOR register reset value
override_SVTOR	Uns32	Override Secure VTOR register reset value
override_CCSIDR_1I	Uns32	Override CCSIDR (level 1 instruction)
override_CCSIDR_1D	Uns32	Override CCSIDR (level 1 data)
override_CCSIDR_2I	Uns32	Override CCSIDR (level 2 instruction)
override_CCSIDR_2D	Uns32	Override CCSIDR (level 2 data)
override_CCSIDR_3I	Uns32	Override CCSIDR (level 3 instruction)
override_CCSIDR_3D	Uns32	Override CCSIDR (level 3 data)
override_CCSIDR_4I	Uns32	Override CCSIDR (level 4 instruction)
override_CCSIDR_4D	Uns32	Override CCSIDR (level 4 data)
override_CCSIDR_5I	Uns32	Override CCSIDR (level 5 instruction)
override_CCSIDR_5D	Uns32	Override CCSIDR (level 5 data)
override_CCSIDR_6I	Uns32	Override CCSIDR (level 6 instruction)
override_CCSIDR_6D	Uns32	Override CCSIDR (level 6 data)
override_CCSIDR_7I	Uns32	Override CCSIDR (level 7 instruction)
override_CCSIDR_7D	Uns32	Override CCSIDR (level 7 data)
override_ITGU_CFG	Uns32	Override system ITGU_CFG register BLKSIZE and PRESENT fields
override_DTGU_CFG	Uns32	Override system DTGU_CFG register BLKSIZE and PRESENT fields
override_CFGMEMALIAS	Uns32	Specifies initial CFGMEMALIAS state
override_deviceStrongAligned	Boolean	Force accesses to Device and Strongly Ordered regions to be aligned
override_STRoffsetPC12	Uns32	Specifies that STR/STR of PC should do so with 12:byte offset from the current instruction (if 1), otherwise an 8:byte offset is used
override_ERG	Uns32	Specifies exclusive reservation granule
override_priorityBits	Uns32	Specifies number of priority bits in BASEPRI etc (1-8, default is 3)
override_numInterrupts	Uns32	Specifies number of external interrupt lines
override_ITCMSIZE	Uns32	Specifies ITCM size from 0KB to 16MB (CFGITCMSIZE value format)
override_DTCMSIZE	Uns32	Specifies DTCM size from 0KB to 16MB (CFGDTCMSIZE value format)
override_AHBPSIZE	Uns32	Specifies AHBP size from 0MB to 512MB (CM7_AHBPCR value format)
override_ITCMEnable	Boolean	Specifies initial ITCM enabled state
override_DTCMEnable	Boolean	Specifies initial DTCM enabled state
override_AHBPEnable	Boolean	Specifies initial AHBP enabled state
override_InstructionAttributes0	Uns32	Override ID_ISAR0 register (deprecated, use override_ISAR0)

override_InstructionAttributes1	Uns32	Override ID_ISAR1 register (deprecated, use override_ISAR1)
override_InstructionAttributes2	Uns32	Override ID_ISAR2 register (deprecated, use override_ISAR2)
override_InstructionAttributes3	Uns32	Override ID_ISAR3 register (deprecated, use override_ISAR3)
override_InstructionAttributes4	Uns32	Override ID_ISAR4 register (deprecated, use override_ISAR4)
override_InstructionAttributes5	Uns32	Override ID_ISAR5 register (deprecated, use override_ISAR5)

Table 8.1: Parameters

8.1 Parameter values and limits

These are the formal parameter limits and actual parameter values

Name	Min	Max	Default	Actual
(Others)				
variant				Cortex-M55
verbose			t	t
showHiddenRegs			f	f
UAL			t	t
enableVFPAAtReset			f	f
compatibility			ISA	ISA
unpredictableR15			execute	execute
override_debugMask	0	0xffffffff	0	0
enableHostAtomics			f	f
enableWFEHostAtomics			f	f
endian			none	none
instructionEndian			none	none
resetAtTime0			t	t
SysTickPresent	1	2	1	1
BitBandPresent			f	f
SIE200IDAUPresent			f	f
useInternalTCMs			f	f
override_PFR0	0	0xffffffff	0x20000030	0x20000030
override_PFR1	0	0xffffffff	0x230	0x230
override_DFR0	0	0xffffffff	0	0
override_AFR0	0	0xffffffff	0	0
override_MMFR0	0	0xffffffff	0x101040	0x101040
override_MMFR1	0	0xffffffff	0	0
override_MMFR2	0	0xffffffff	0x1000000	0x1000000
override_MMFR3	0	0xffffffff	0	0
override_ISAR0	0	0xffffffff	0x1103110	0x1103110
override_ISAR1	0	0xffffffff	0x2212000	0x2212000
override_ISAR2	0	0xffffffff	0x20232232	0x20232232

override.ISAR3	0	0xffffffff	0x11111131	0x11111131
override.ISAR4	0	0xffffffff	0x1310132	0x1310132
override.ISAR5	0	0xffffffff	0	0
override.MVFR0	0	0xffffffff	0	0
override.MVFR1	0	0xffffffff	0	0
override.MVFR2	0	0xffffffff	0	0
override.ACTLR	0	0xffffffff	0	0
override.CPUID	0	0xffffffff	0x410fd222	0x410fd222
override.MPU_TYPE	0	0xffffffff	0x800	0x800
override.S_MPU_TYPE	0	0xffffffff	0x800	0x800
override.SAU_TYPE	0	0xffffffff	4	4
override.VTOR	0	0xffffffff	0	0
override.SVTOR	0	0xffffffff	0	0
override.CCSIDR_1I	0	0xffffffff	0xf03fe019	0xf03fe019
override.CCSIDR_1D	0	0xffffffff	0xf03fe019	0xf03fe019
override.CCSIDR_2I	0	0xffffffff	0	0
override.CCSIDR_2D	0	0xffffffff	0	0
override.CCSIDR_3I	0	0xffffffff	0	0
override.CCSIDR_3D	0	0xffffffff	0	0
override.CCSIDR_4I	0	0xffffffff	0	0
override.CCSIDR_4D	0	0xffffffff	0	0
override.CCSIDR_5I	0	0xffffffff	0	0
override.CCSIDR_5D	0	0xffffffff	0	0
override.CCSIDR_6I	0	0xffffffff	0	0
override.CCSIDR_6D	0	0xffffffff	0	0
override.CCSIDR_7I	0	0xffffffff	0	0
override.CCSIDR_7D	0	0xffffffff	0	0
override.ITGU_CFG	0	0xffffffff	0x8000000a	0x8000000a
override.DTGU_CFG	0	0xffffffff	0x8000000a	0x8000000a
override.CFGMEMALIAS	0	16	0	0
override.deviceStrongAligned			t	t
override.STRoffsetPC12	0	1	0	0
override.ERG	0	0x400	0	0
override.priorityBits	1	8	3	3
override.numInterrupts	0	0x1f0	16	16
override.ITCMSize	0	15	15	15
override.DTCMSize	0	15	15	15
override.AHBPSize	0	4	4	4
override.ITCMEnable			f	f
override.DTCMEnable			f	f
override.AHBPEnable			f	f
override.InstructionAttributes0	0	0xffffffff	0x1103110	0x1103110
override.InstructionAttributes1	0	0xffffffff	0x2212000	0x2212000
override.InstructionAttributes2	0	0xffffffff	0x20232232	0x20232232
override.InstructionAttributes3	0	0xffffffff	0x11111131	0x11111131

override_InstructionAttributes4	0	0xffffffff	0x1310132	0x1310132
override_InstructionAttributes5	0	0xffffffff	0	0

Table 8.2: Parameter values and limits

Chapter 9

Execution Modes

Mode	Code
Thread_NS	0
Handler_NS	1
Thread_S	2
Handler_S	3

Table 9.1: Modes implemented in this processor

Chapter 10

Exceptions

Exception	Code
None	0
Reset	1
NMI	2
HardFault	3
MemManage	4
BusFault	5
UsageFault	6
SecureFault	7
SVCall	11
DebugMonitor	12
PendSV	14
SysTick	15
ExternalInt000	16
ExternalInt001	17
ExternalInt002	18
ExternalInt003	19
ExternalInt004	20
ExternalInt005	21
ExternalInt006	22
ExternalInt007	23
ExternalInt008	24
ExternalInt009	25
ExternalInt00a	26
ExternalInt00b	27
ExternalInt00c	28
ExternalInt00d	29
ExternalInt00e	30
ExternalInt00f	31

Table 10.1: Exceptions implemented by this processor

Chapter 11

Hierarchy of the model

A CPU core may be configured to instance many processors of a Symmetrical Multi Processor (SMP). A CPU core may also have sub elements within a processor, for example hardware threading blocks.

OVP processor models can be written to include SMP blocks and to have many levels of hierarchy. Some OVP CPU models may have a fixed hierarchy, and some may be configured by settings in a configuration register. Please see the register definitions of this model.

This model documentation shows the settings and hierarchy of the default settings for this model variant.

11.1 Level 1

This level in the model hierarchy has 3 commands.

This level in the model hierarchy has 6 register groups:

Group name	Registers
Core	16
Control	25
System	156
System_secure	33
System_non_secure	33
Integration_support	6

Table 11.1: Register groups

This level in the model hierarchy has no children.

Chapter 12

Model Commands

A Processor model can implement one or more **Model Commands** available to be invoked from the simulator command line, from the OP API or from the Imperas Multiprocessor Debugger.

12.1 Level 1

12.1.1 debugflags

show or modify the processor debug flags

Argument	Type	Description
-get	Boolean	print current processor flags value
-mask	Boolean	print valid debug flag bits
-set	Int32	new processor flags (only flags 0x0000008c can be modified)

Table 12.1: debugflags command arguments

12.1.2 isync

specify instruction address range for synchronous execution

Argument	Type	Description
-addresshi	Uns64	end address of synchronous execution range
-addresslo	Uns64	start address of synchronous execution range

Table 12.2: isync command arguments

12.1.3 itrace

enable or disable instruction tracing

Argument	Type	Description
-access	String	show memory accesses by this instruction. Argument can be any combination of X (execute), A (load or store access) and S (system)

-after	Uns64	apply after this many instructions
-enable	Boolean	enable instruction tracing
-full	Boolean	turn on all trace features
-instructioncount	Boolean	include the instruction number in each trace
-memory	String	(Alias for access). show memory accesses by this instruction. Argument can be any combination of X (execute), A (load or store access) and S (system)
-mode	Boolean	show processor mode changes
-off	Boolean	disable instruction tracing
-on	Boolean	enable instruction tracing
-processorname	Boolean	Include processor name in all trace lines
-registerchange	Boolean	show registers changed by this instruction
-registers	Boolean	show registers after each trace

Table 12.3: itrace command arguments

Chapter 13

Registers

13.1 Level 1

13.1.1 Core

Registers at level:1, group:Core

Name	Bits	Initial-Hex	RW	Description
r0	32	0	rw	
r1	32	0	rw	
r2	32	0	rw	
r3	32	0	rw	
r4	32	0	rw	
r5	32	0	rw	
r6	32	0	rw	
r7	32	0	rw	
r8	32	0	rw	
r9	32	0	rw	
r10	32	0	rw	
r11	32	0	rw	frame pointer
r12	32	0	rw	
sp	32	0	rw	stack pointer
lr	32	0	rw	
pc	32	0	rw	program counter

Table 13.1: Registers at level 1, group:Core

13.1.2 Control

Registers at level:1, group:Control

Name	Bits	Initial-Hex	RW	Description
cpsr	32	0	rw	xPSR register. Includes APSR, IPSR and EPSR
control	32	0	rw	
primask	32	0	rw	
faultmask	32	0	rw	
basepri	32	0	rw	
control_S	32	0	rw	
primask_S	32	0	rw	
faultmask_S	32	0	rw	
basepri_S	32	0	rw	

control_NS	32	0	rw	
primask_NS	32	0	rw	
faultmask_NS	32	0	rw	
basepri_NS	32	0	rw	
sp_process	32	0	rw	stack pointer
sp_process_S	32	0	rw	stack pointer
sp_process_NS	32	0	rw	stack pointer
msplim	32	0	rw	
msplim_S	32	0	rw	
msplim_NS	32	0	rw	
psplim	32	0	rw	
psplim_S	32	0	rw	
psplim_NS	32	0	rw	
sp_main	32	0	rw	stack pointer
sp_main_S	32	0	rw	stack pointer
sp_main_NS	32	0	rw	stack pointer

Table 13.2: Registers at level 1, group:Control

13.1.3 System

Registers at level:1, group:System

Name	Bits	Initial-Hex	RW	Description
ERRFR0	32	-	rw	0xe0005000: RAS Error Record Feature
ERRCTRL0	32	-	rw	0xe0005008: RAS Error Record Control
ERRSTATUS0	32	-	rw	0xe0005010: RAS Error Record Primary Status
ERRADDR0	32	-	rw	0xe0005018: RAS Error Record Address 0
ERRADDR20	32	-	rw	0xe000501c: RAS Error Record Address 20
ERRMISC00	32	-	rw	0xe0005020: RAS Error Record Miscellaneous 00
ERRMISC10	32	-	rw	0xe0005024: RAS Error Record Miscellaneous 10
ERRMISC20	32	-	rw	0xe0005028: RAS Error Record Miscellaneous 20
ERRMISC30	32	-	rw	0xe000502c: RAS Error Record Miscellaneous 30
ERRMISC40	32	-	rw	0xe0005030: RAS Error Record Miscellaneous 40
ERRMISC50	32	-	rw	0xe0005034: RAS Error Record Miscellaneous 50
ERRMISC60	32	-	rw	0xe0005038: RAS Error Record Miscellaneous 60
ERRMISC70	32	-	rw	0xe000503c: RAS Error Record Miscellaneous 70
ERRGSR0	32	-	rw	0xe0005e00: RAS Fault Group Status
ERRDEVID	32	-	rw	0xe0005fc8: RAS Error Record Device ID
ICTR	32	0	rw	0xe000e004: Interrupt Controller Type
ACTLR	32	0	rw	0xe000e008: Auxiliary Control
CPPWR	32	0	rw	0xe000e00c: Coprocessor Power Control
SYST_CSR	32	4	rw	0xe000e010: SysTick Control and Status
SYST_RVR	32	0	rw	0xe000e014: SysTick Reload Value
SYST_CVR	32	0	rw	0xe000e018: SysTick Current Value
SYST_CALIB	32	0	rw	0xe000e01c: SysTick Calibration Value
NVIC_ISER0	32	0	rw	0xe000e100: Interrupt Set Enable 0
NVIC_ICER0	32	0	rw	0xe000e180: Interrupt Clear Enable 0
NVIC_ISPR0	32	0	rw	0xe000e200: Interrupt Set Pending 0
NVIC_ICPR0	32	0	rw	0xe000e280: Interrupt Clear Pending 0
NVIC_IABR0	32	0	r-	0xe000e300: Interrupt Active Bit 0
NVIC_ITNS0	32	0	rw	0xe000e380: Interrupt Target Non-Secure 0
NVIC_IPR0	32	0	rw	0xe000e400: Interrupt Priority 0
NVIC_IPR1	32	0	rw	0xe000e404: Interrupt Priority 1
NVIC_IPR2	32	0	rw	0xe000e408: Interrupt Priority 2

NVIC_IPR3	32	0	rw	0xe000e40c: Interrupt Priority 3
REVIDR	32	-	rw	0xe000ecfc: Revision ID
CPUID	32	410fd222	r-	0xe000ed00: CPUID Base
ICSR	32	1000	rw	0xe000ed04: Interrupt Control and State
VTOR	32	0	rw	0xe000ed08: Vector Table Offset
AIRCR	32	fa050000	rw	0xe000ed0c: Application Interrupt and Reset Control
SCR	32	0	rw	0xe000ed10: System Control
CCR	32	201	rw	0xe000ed14: Configuration and Control
SHPR1	32	0	rw	0xe000ed18: System Handler Priority 1
SHPR2	32	0	rw	0xe000ed1c: System Handler Priority 2
SHPR3	32	0	rw	0xe000ed20: System Handler Priority 3
SHCSR	32	0	rw	0xe000ed24: System Handler Control and State
CFSR	32	0	rw	0xe000ed28: Configurable Fault Status
HFSR	32	0	rw	0xe000ed2c: HardFault Status
DFSR	32	0	rw	0xe000ed30: Debug Fault Status Register
MMAR	32	0	rw	0xe000ed34: MemManage Fault Address
BFAR	32	0	rw	0xe000ed38: BusFault Address
AFSR	32	0	rw	0xe000ed3c: Auxiliary Fault Status
ID_PFR0	32	20000030	rw	0xe000ed40: Processor Feature 0
ID_PFR1	32	230	rw	0xe000ed44: Processor Feature 1
ID_DFR0	32	0	rw	0xe000ed48: Debug Feature 0
ID_AFR0	32	0	rw	0xe000ed4c: Auxiliary Feature 0
ID_MMFR0	32	111040	rw	0xe000ed50: Memory Model Feature 0
ID_MMFR1	32	0	rw	0xe000ed54: Memory Model Feature 1
ID_MMFR2	32	1000000	rw	0xe000ed58: Memory Model Feature 2
ID_MMFR3	32	0	rw	0xe000ed5c: Memory Model Feature 3
ID_ISAR0	32	1103110	rw	0xe000ed60: Instruction Set Attributes 0
ID_ISAR1	32	2212000	rw	0xe000ed64: Instruction Set Attributes 1
ID_ISAR2	32	20232232	rw	0xe000ed68: Instruction Set Attributes 2
ID_ISAR3	32	1111131	rw	0xe000ed6c: Instruction Set Attributes 3
ID_ISAR4	32	1310132	rw	0xe000ed70: Instruction Set Attributes 4
ID_ISAR5	32	0	rw	0xe000ed74: Instruction Set Attributes 5
CLIDR	32	9000003	r-	0xe000ed78: Cache Level ID
CTR	32	8303c003	r-	0xe000ed7c: Cache Type
CCSIDR	32	f03fe019	r-	0xe000ed80: Cache Size ID
CSSELR	32	0	rw	0xe000ed84: Cache Size Selection
CPACR	32	0	rw	0xe000ed88: Coprocessor Access Control
NSACR	32	0	rw	0xe000ed8c: Non-Secure Access Control Register
MPU_TYPE	32	800	rw	0xe000ed90: MPU Type
MPU_CONTROL	32	0	rw	0xe000ed94: MPU Control
MPU_RNR	32	0	rw	0xe000ed98: MPU Region Number
MPU_RBAR	32	0	rw	0xe000ed9c: MPU Region Base Address
MPU_RLAR	32	0	rw	0xe000eda0: MPU Region Limit Address Register
MPU_RBAR_A1	32	0	rw	0xe000eda4: MPU Region Base Address Alias 1
MPU_RLAR_A1	32	0	rw	0xe000eda8: MPU Region Limit Address Register Alias 1
MPU_RBAR_A2	32	0	rw	0xe000edac: MPU Region Base Address Alias 2
MPU_RLAR_A2	32	0	rw	0xe000edb0: MPU Region Limit Address Register Alias 2
MPU_RBAR_A3	32	0	rw	0xe000edb4: MPU Region Base Address Alias 3
MPU_RLAR_A3	32	0	rw	0xe000edb8: MPU Region Limit Address Register Alias 3
MPU_MAIR0	32	0	rw	0xe000edc0: MPU Memory Attribute Indirection Register 0
MPU_MAIR1	32	0	rw	0xe000edc4: MPU Memory Attribute Indirection Register 1
SAU_CTRL	32	0	rw	0xe000edd0: SAU Control Register
SAU_TYPE	32	4	rw	0xe000edd4: SAU Type Register
SAU_RNR	32	0	rw	0xe000edd8: SAU Region Number Register
SAU_RBAR	32	0	rw	0xe000eddc: SAU Region Base Address Register
SAU_RLAR	32	0	rw	0xe000ede0: SAU Region Limit Address Register

SFSR	32	0	rw	0xe000ede4: Secure Fault Status Register
SFAR	32	0	rw	0xe000ede8: Secure Fault Address Register
DEMCR	32	100000	rw	0xe000edfc: Debug Exception and Monitor Control
STIR	32	-	-w	0xe000ef00: Software Triggered Interrupt
RFSR	32	-	rw	0xe000ef04: RAS Fault Status
ICIALLU	32	-	-w	0xe000ef50: Instruction Cache Invalidate All to PoU
ICIMVAU	32	-	-w	0xe000ef58: Instruction Cache Invalidate by Address to PoU
DCIMVAC	32	-	-w	0xe000ef5c: Data Cache Invalidate by Address to PoC
DCISW	32	-	-w	0xe000ef60: Data Cache Invalidate by Set/Way
DCCMVAU	32	-	-w	0xe000ef64: Data Cache Invalidate by Address to PoU
DCCMVAC	32	-	-w	0xe000ef68: Data Cache Clean by Address to PoC
DCCSW	32	-	-w	0xe000ef6c: Data Cache Clean by Set/Way
DCCIMVAC	32	-	-w	0xe000ef70: Data Cache Clean and Invalidate by Address to PoC
DCCISW	32	-	-w	0xe000ef74: Data Cache Clean and Invalidate by Set/Way
MSCR	32	300a	rw	0xe001e000: Memory System Control (register interface only)
PFCR	32	165	rw	0xe001e004: Prefetcher Control (register interface only)
ITCMCR	32	78	rw	0xe001e010: Instruction Tightly-Coupled Memory Control
DTCMCR	32	78	rw	0xe001e014: Data Tightly-Coupled Memory Control
PAHBCR	32	8	rw	0xe001e018: P-AHB Control
IEBR0	32	-	rw	0xe001e100: Instruction Error Bank 0 (register interface only)
IEBR1	32	-	rw	0xe001e104: Instruction Error Bank 1 (register interface only)
DEBR0	32	-	rw	0xe001e110: Data Error Bank 0 (register interface only)
DEBR1	32	-	rw	0xe001e114: Data Error Bank 1 (register interface only)
TEBR0	32	-	rw	0xe001e120: TCM Error Bank 0 (register interface only)
TEBRDATA0	32	-	rw	0xe001e124: TCU Error Bank 0 (register interface only)
TEBR1	32	-	rw	0xe001e128: TCM Error Bank 1 (register interface only)
TEBRDATA1	32	-	rw	0xe001e12c: TCU Error Bank 1 (register interface only)
DCADCRR	32	-	rw	0xe001e200: Direct D-Cache Access Read (register interface only)
DCAICRR	32	-	rw	0xe001e204: Direct I-Cache Access Read (register interface only)
DCADCLR	32	-	rw	0xe001e210: Direct D-Cache Access Location (register interface only)
DCAICLR	32	-	rw	0xe001e214: Direct I-Cache Access Location (register interface only)
CPDLPSTATE	32	333	rw	0xe001e300: Core Power Domain Low Power State (register interface only)
DPDLPSTATE	32	3	rw	0xe001e304: Debug Power Domain Low Power State (register interface only)
ITGU_CTRL	32	0	rw	0xe001e500: ITGU Control
ITGU_CFG	32	0	rw	0xe001e504: ITGU Configuration
ITGU_LUT0	32	0	rw	0xe001e510: ITGU Look Up Table 0
ITGU_LUT1	32	0	rw	0xe001e514: ITGU Look Up Table 1
ITGU_LUT2	32	0	rw	0xe001e518: ITGU Look Up Table 2
ITGU_LUT3	32	0	rw	0xe001e51c: ITGU Look Up Table 3
ITGU_LUT4	32	0	rw	0xe001e520: ITGU Look Up Table 4
ITGU_LUT5	32	0	rw	0xe001e524: ITGU Look Up Table 5
ITGU_LUT6	32	0	rw	0xe001e528: ITGU Look Up Table 6
ITGU_LUT7	32	0	rw	0xe001e52c: ITGU Look Up Table 7
ITGU_LUT8	32	0	rw	0xe001e530: ITGU Look Up Table 8
ITGU_LUT9	32	0	rw	0xe001e534: ITGU Look Up Table 9
ITGU_LUT10	32	0	rw	0xe001e538: ITGU Look Up Table 10
ITGU_LUT11	32	0	rw	0xe001e53c: ITGU Look Up Table 11
ITGU_LUT12	32	0	rw	0xe001e540: ITGU Look Up Table 12
ITGU_LUT13	32	0	rw	0xe001e544: ITGU Look Up Table 13
ITGU_LUT14	32	0	rw	0xe001e548: ITGU Look Up Table 14
ITGU_LUT15	32	0	rw	0xe001e54c: ITGU Look Up Table 15
DTGU_CTRL	32	0	rw	0xe001e600: DTGU Control

DTGU_CFG	32	0	rw	0xe001e604: DTGU Configuration
DTGU_LUT0	32	0	rw	0xe001e610: DTGU Look Up Table 0
DTGU_LUT1	32	0	rw	0xe001e614: DTGU Look Up Table 1
DTGU_LUT2	32	0	rw	0xe001e618: DTGU Look Up Table 2
DTGU_LUT3	32	0	rw	0xe001e61c: DTGU Look Up Table 3
DTGU_LUT4	32	0	rw	0xe001e620: DTGU Look Up Table 4
DTGU_LUT5	32	0	rw	0xe001e624: DTGU Look Up Table 5
DTGU_LUT6	32	0	rw	0xe001e628: DTGU Look Up Table 6
DTGU_LUT7	32	0	rw	0xe001e62c: DTGU Look Up Table 7
DTGU_LUT8	32	0	rw	0xe001e630: DTGU Look Up Table 8
DTGU_LUT9	32	0	rw	0xe001e634: DTGU Look Up Table 9
DTGU_LUT10	32	0	rw	0xe001e638: DTGU Look Up Table 10
DTGU_LUT11	32	0	rw	0xe001e63c: DTGU Look Up Table 11
DTGU_LUT12	32	0	rw	0xe001e640: DTGU Look Up Table 12
DTGU_LUT13	32	0	rw	0xe001e644: DTGU Look Up Table 13
DTGU_LUT14	32	0	rw	0xe001e648: DTGU Look Up Table 14
DTGU_LUT15	32	0	rw	0xe001e64c: DTGU Look Up Table 15

Table 13.3: Registers at level 1, group:System

13.1.4 System_secure

Registers at level:1, group:System_secure

Name	Bits	Initial-Hex	RW	Description
ACTLR_S	32	0	rw	0xe000e008: Auxiliary Control
SYST_CSR_S	32	4	rw	0xe000e010: SysTick Control and Status
SYST_RVR_S	32	0	rw	0xe000e014: SysTick Reload Value
SYST_CVR_S	32	0	rw	0xe000e018: SysTick Current Value
SYST_CALIB_S	32	0	rw	0xe000e01c: SysTick Calibration Value
ICSR_S	32	1000	rw	0xe000ed04: Interrupt Control and State
VTOR_S	32	0	rw	0xe000ed08: Vector Table Offset
AIRCR_S	32	fa050000	rw	0xe000ed0c: Application Interrupt and Reset Control
SCR_S	32	0	rw	0xe000ed10: System Control
CCR_S	32	201	rw	0xe000ed14: Configuration and Control
SHPR1_S	32	0	rw	0xe000ed18: System Handler Priority 1
SHPR2_S	32	0	rw	0xe000ed1c: System Handler Priority 2
SHPR3_S	32	0	rw	0xe000ed20: System Handler Priority 3
SHCSR_S	32	0	rw	0xe000ed24: System Handler Control and State
CFSR_S	32	0	rw	0xe000ed28: Configurable Fault Status
MMAR_S	32	0	rw	0xe000ed34: MemManage Fault Address
CTR_S	32	8303c003	r-	0xe000ed7c: Cache Type
CCSIDR_S	32	f03fe019	r-	0xe000ed80: Cache Size ID
CSSELR_S	32	0	rw	0xe000ed84: Cache Size Selection
CPACR_S	32	0	rw	0xe000ed88: Coprocessor Access Control
MPU_TYPE_S	32	800	rw	0xe000ed90: MPU Type
MPU_CONTROLS_S	32	0	rw	0xe000ed94: MPU Control
MPU_RNR_S	32	0	rw	0xe000ed98: MPU Region Number
MPU_RBAR_S	32	0	rw	0xe000ed9c: MPU Region Base Address
MPU_RLAR_S	32	0	rw	0xe000eda0: MPU Region Limit Address Register
MPU_RBAR_A1_S	32	0	rw	0xe000eda4: MPU Region Base Address Alias 1
MPU_RLAR_A1_S	32	0	rw	0xe000eda8: MPU Region Limit Address Register Alias 1
MPU_RBAR_A2_S	32	0	rw	0xe000edac: MPU Region Base Address Alias 2
MPU_RLAR_A2_S	32	0	rw	0xe000edb0: MPU Region Limit Address Register Alias 2
MPU_RBAR_A3_S	32	0	rw	0xe000edb4: MPU Region Base Address Alias 3

MPU_RLAR_A3_S	32	0	rw	0xe000edb8: MPU Region Limit Address Register Alias 3
MPU_MAIR0_S	32	0	rw	0xe000edc0: MPU Memory Attribute Indirection Register 0
MPU_MAIR1_S	32	0	rw	0xe000edc4: MPU Memory Attribute Indirection Register 1

Table 13.4: Registers at level 1, group:System_secure

13.1.5 System_non_secure

Registers at level:1, group:System_non_secure

Name	Bits	Initial-Hex	RW	Description
ACTLR_NS	32	0	rw	0xe000e008: Auxiliary Control
SYST_CSR_NS	32	4	rw	0xe000e010: SysTick Control and Status
SYST_RVR_NS	32	0	rw	0xe000e014: SysTick Reload Value
SYST_CVR_NS	32	0	rw	0xe000e018: SysTick Current Value
SYST_CALIB_NS	32	0	rw	0xe000e01c: SysTick Calibration Value
ICSR_NS	32	1000	rw	0xe000ed04: Interrupt Control and State
VTOR_NS	32	0	rw	0xe000ed08: Vector Table Offset
AIRCR_NS	32	fa050000	rw	0xe000ed0c: Application Interrupt and Reset Control
SCR_NS	32	0	rw	0xe000ed10: System Control
CCR_NS	32	201	rw	0xe000ed14: Configuration and Control
SHPR1_NS	32	0	rw	0xe000ed18: System Handler Priority 1
SHPR2_NS	32	0	rw	0xe000ed1c: System Handler Priority 2
SHPR3_NS	32	0	rw	0xe000ed20: System Handler Priority 3
SHCSR_NS	32	0	rw	0xe000ed24: System Handler Control and State
CFSR_NS	32	0	rw	0xe000ed28: Configurable Fault Status
MMAR_NS	32	0	rw	0xe000ed34: MemManage Fault Address
CTR_NS	32	8303c003	r-	0xe000ed7c: Cache Type
CCSIDR_NS	32	f03fe019	r-	0xe000ed80: Cache Size ID
CSSELR_NS	32	0	rw	0xe000ed84: Cache Size Selection
CPACR_NS	32	0	rw	0xe000ed88: Coprocessor Access Control
MPU_TYPE_NS	32	800	rw	0xe000ed90: MPU Type
MPU_CONTROL_NS	32	0	rw	0xe000ed94: MPU Control
MPU_RNR_NS	32	0	rw	0xe000ed98: MPU Region Number
MPU_RBAR_NS	32	0	rw	0xe000ed9c: MPU Region Base Address
MPU_RLAR_NS	32	0	rw	0xe000eda0: MPU Region Limit Address Register
MPU_RBAR_A1_NS	32	0	rw	0xe000eda4: MPU Region Base Address Alias 1
MPU_RLAR_A1_NS	32	0	rw	0xe000eda8: MPU Region Limit Address Register Alias 1
MPU_RBAR_A2_NS	32	0	rw	0xe000edac: MPU Region Base Address Alias 2
MPU_RLAR_A2_NS	32	0	rw	0xe000edb0: MPU Region Limit Address Register Alias 2
MPU_RBAR_A3_NS	32	0	rw	0xe000edb4: MPU Region Base Address Alias 3
MPU_RLAR_A3_NS	32	0	rw	0xe000edb8: MPU Region Limit Address Register Alias 3
MPU_MAIR0_NS	32	0	rw	0xe000edc0: MPU Memory Attribute Indirection Register 0
MPU_MAIR1_NS	32	0	rw	0xe000edc4: MPU Memory Attribute Indirection Register 1

Table 13.5: Registers at level 1, group:System_non_secure

13.1.6 Integration_support

Registers at level:1, group:Integration_support

Name	Bits	Initial-Hex	RW	Description
executionPri	32	7fffffff	r-	current execution priority level
stackDomain	64	7ff ecc8fc10	r-	stack domain for current execution level
HaltReason	8	0	r-	bit field indicating halt reason

atomicType	8	0	r-	current atomic instruction type (1:atomic, 2:exclusive)
WakeWFINow	8	0	-w	wake up core from WFI state
ambaResponse	32	0	rw	external AMBA-PV response

Table 13.6: Registers at level 1, group:Integration_support